Supplementary governance note for the trimming and client-size weighting study

Sheryar Kiani
2504142@students.au.edu.pk

Revised 12 October 2026

Abstract

This note records study identifiers, approval dates, checksums, and the deferred FedNova stop for the accompanying article. It is not a journal article, not an approval signature, and not a statement that the article has been submitted or accepted. The scientific decisions are in the article. ORCID identifiers, funding sources, and conflict-of-interest statements were not supplied.

1 People and scope

The article author is Sheryar Kiani, an M.S. student in the Department of Cyber Security, Air University, Islamabad. He is the corresponding author. The experimental amendments name Dr Hussain Kazmi as approver. He is not an author of the article. This note does not add a signature from him.

The article was revised on 11 October 2026 for an SJR-Q1, IEEE Access-style submission. This note was revised on 12 October 2026 to correct the archive file count, to label the archive sizes in binary mebibytes, to keep the repository address inside the page, after the upload, to record that `main` is published, and to list Sheryar Kiani as the sole author. No new model was trained for that revision. The parent preregistration, the training engine, the partition code, the sealed result packets, the IEEE class file, and the legacy template `access.tex` were not edited. No new version of the May 2026 Zenodo snapshot was minted.

2 Identifier map

The article uses plain names. The laboratory record uses the identifiers below.

- Three-seed CIC-IoT2023 confirmatory grid: 48 cells, Dirichlet $\alpha \in \{0.5, 0.1\}$, seeds $\{42, 123, 7\}$. Descriptive directional rules only.
- Three-seed N-BaIoT device block: 24 cells on the nine source-device clients. Descriptive directional rules only.
- Seven-seed family, recorded as Q1-E4 and closed on 5 October 2026: 112 cells on blocks T1, T2, T5, and T6. The seeds are 127, 131, 137, 139, 149, 151, and 157. The preregistered paired-t Holm decision supports only T2, size-weighted FedAvg minus unweighted FedAvg. The other 15 comparisons are inconclusive. Neither complete hypothesis is supported.

- Coordinate-wise median comparison, recorded as Q1-E5. An eight-test plan was accepted on 6 October 2026 at 0 decision cells. On 7 October 2026 the accepted continuation was the 28-cell coordinate-wise median comparison alone. That comparison was closed on 10 October 2026. All four Holm tests are inconclusive. No equivalence procedure was applied.
- Per-class display, recorded as Q1-E7: 24 descriptive CIC cells at $\alpha = 0.1$, seeds $\{42, 123, 7\}$. It is not a rare-class claim.
- Conceptual bridge, recorded as Q1-E6: not a theorem and not an attack result.
- Still deferred: FedNova, a further CIC wave, and an adversarial-client study recorded as Q1-E8. Reopening any of them requires a dated amendment. SCAFFOLD is not an arm.

3 FedNova stop

The 6 October 2026 plan included a FedNova comparison against a matched momentum-SGD FedAvg control. During the T1 learning-rate search, the CIC-IoT2023 multilayer perceptron, FedNova, momentum SGD, learning rate 0.1, seed 10007, produced a non-finite client update. A recovery run approved on 7 October 2026 reproduced that non-finite update. The prespecified rule stopped the search and did not allow a rate to be chosen from the cells that finished. No FedNova decision cell was run. The informational stop record was not signed. The continuation that was accepted is the 28-cell median comparison. FedNova remains deferred, so its accuracy on these blocks is unmeasured.

The incident note was not edited for this submission. Its SHA-256, verified again for this note, is

`17a7b49d1db8efef8263d2e46ae012a21ad39b84ad63cc8dda3460423272534a`

4 Checksums verified on 11 October 2026

The preregistration file `q1_e5_results/Q1_E5_PREREG_DRAFT.md` was hashed again and still matches the accepted SHA-256 below. The presented-before-acceptance hash is a different historical value and is not the current file hash.

`cd20c7a61b3a41ad214cc51bf4221f7837604fd1236f75282fd07be346ec6517`

The processed feature matrices used by the leakage audit and the partition check are:

- `cic_27bfed227ef77fab.npz`, 170,407,946 bytes.
  `8f032df1760a895b2358b8ff2da71491b09820c7af8c097dd00465fd7b981b38`
  Metadata SHA-256 `e5e0ef795fff100af24f6813ca3a2a61442e386aa01bf92878a9cfc0b03cb3b4`.
- `nbaiot_4ddb8b93b8821650.npz`, 243,513,210 bytes.
  `c0a1e21cd6336d3a090e5feb9411758abbf8669dcca01bd476defdbcf8380854`
  Metadata SHA-256 `0124ac4c793417d53bd062f4694e72ba903ed42beee8873d578adf57a3686b23`.

Each matrix exceeds the 100 MB git file limit, so neither file is stored as a git blob. The per-seed partition files in the archive are smaller and are included.

5 Two different time quantities

The article reports 171.954 hours of stored training time across the 112 seven-seed cells, from the `train_s` field. It also reports 42.066 hours of elapsed wall-clock time for the 28 median cells, from each cell's stored start to its stored finish.

The sealed planning figure for the median comparison is a different quantity: exact mean 42.988554875486145 hours, reported as 42.99, and exact maximum 45.850877955749894 hours, reported as 45.85. That planning figure is not the 42.066-hour elapsed sum, and the elapsed sum does not replace it.

6 Exact sign-flip sensitivity

For each of the 16 seven-seed contrasts, the statistic is the absolute sum of the seven paired Final macro-F1 differences. All 128 sign assignments are treated as equally likely. The two-sided p-value is the fraction of assignments whose absolute sum is at least as large as the observed absolute sum. Holm adjustment across the 16 exact p-values supports no comparison. With seven nonzero differences the smallest such p-value is $2/128$, and $16 \times 2/128 = 0.25$, so this exact family cannot reach a 0.05 Holm threshold. The preregistered paired-t Holm decision remains the official result.

7 Public archive and data acquisition

The public repository is published. Its full address is printed on its own line below. It contains this note, the manuscript, the result tables, the cell records, the manifests, and the partition files: 855 files, 379.63 MiB in total, and a largest file of 36.82 MiB. Those sizes use binary units, so the same totals are 398.07 MB and 38.61 MB in decimal units. The two processed matrices named above are not stored as git blobs, because each exceeds GitHub's 100 MB file limit. The raw corpora and the tuning matrices are not in the repository either.

`https://github.com/sheryar827/fl-iot-trimming-weighting-archive`

CIC-IoT2023 is the public corpus introduced by Neto *et al.*, *Sensors*, 2023. N-BaIoT is the public corpus introduced by Meidan *et al.*, *IEEE Pervasive Computing*, 2018. The processed caches cap each source file at 20,000 rows, use a stratified split with seed 42, and fit a standard scaler on the pooled training matrix only.

The earlier three-arm lineage remains at the address below. The concept DOI 10.5281/zenodo.20456827 resolves to the immutable v1.0.0 record 10.5281/zenodo.20456828, published on 30 May 2026. That record was not versioned again for this article.

`https://github.com/sheryar827/fl-iot-botnet-nbaiot-cic-iot2023`

8 Items still to supply before upload

ORCID identifiers were not supplied. No funding source was supplied. No conflict-of-interest statement was supplied. IEEE assigns the history line, the DOI, the volume, and the year after acceptance. None of those values is invented in the article. The article has not been submitted and has not been accepted.