

Script-Controlled ACL – Restrict Record Access Based on Field Value

Phase 6: Project Testing

6.1 Test Approach

Testing is performed by impersonating users from the ServiceNow user menu and opening the Institution Details list (u_institution_details.list). Each ACL is tested immediately after creation, then a combined test is run with all roles.

6.2 Test Cases

TC	User / Roles	Action	Expected Result	Actual	Status
TC-1	EEE User with bb1	Open list	Only EEE records (INS0001007, INS0001004) shown	As expected	Pass
TC-2	User without bb1	Open list	"No records to display"	As expected	Pass
TC-3	Admin	Open list	All 6 records (ECE, CSE, EEE) shown	As expected	Pass
TC-4	bb1 + bb2	Open list	Only EEE records; New button visible	As expected	Pass
TC-5	bb1 + bb2 + bb3	Edit Description inline	Edit saved ("ACL Is Executed")	As expected	Pass
TC-6	bb1 + bb2 + bb3 + bb4	Select record, Actions > Delete, confirm	Selected EEE record deleted	As expected	Pass

[Screenshot placeholder]

Impersonation result screens for TC-1 through TC-6 (one per test case is ideal).

Insert screenshot from your ServiceNow instance (or a frame from your demo recording) here.

6.3 Observations

- ACLs are cumulative in the lab: each additional role unlocks one more capability (view, create, edit, delete).
- The Branch restriction is enforced by the data condition of the read ACL, so non-EEE records never appear for bb1 users.
- A user holding only bb2, bb3 or bb4 (without bb1) cannot see records, so read access is the prerequisite for other operations.

6.4 Suggested Improvements

- Make the script itself branch-aware (for example, compare `current.branch` with the user's own branch/department) so that the rule does not depend solely on the data condition.
- Use groups or a department field to map users to branches instead of one role per capability.
- Add field-level ACLs for sensitive fields such as Email and Phone Number.