

# Script-Controlled ACL – Restrict Record Access Based on Field Value

Phase 7: Project Documentation

## 7.1 Project Artifacts

| Artifact          | Name / Value                                                                                            |
|-------------------|---------------------------------------------------------------------------------------------------------|
| Custom table      | Institution Details - u_institution_details                                                             |
| Test user         | EEE User (User ID: EEEUser)                                                                             |
| Custom roles      | bb1 (read), bb2 (create), bb3 (write), bb4 (delete)                                                     |
| ACLs              | 4 record ACLs on u_institution_details: read (advanced, script + data condition), create, write, delete |
| Application scope | Global                                                                                                  |

## 7.2 User Guide

- Viewing records: requires bb1; only EEE records are visible.
- Creating records: requires bb2 (in addition to bb1 to see the list).
- Editing records: requires bb3.
- Deleting records: requires bb4.
- Administrators: see all records regardless of branch.

## 7.3 Maintenance Notes

- Only users with the elevated security\_admin role can modify ACLs.
- Assign or remove roles on the user record to grant or revoke capabilities.
- Test any ACL change through impersonation before releasing it to users.

## 7.4 Learning Outcomes

The project shows how script-controlled READ, WRITE, CREATE and DELETE ACLs enforce record-level security, how roles and field values are evaluated together for access decisions, and how ACLs protect sensitive data across forms, lists and Service Portal interfaces.

## 7.5 References

- ServiceNow Product Documentation - Access Control Rules (ACLs)
- ServiceNow Product Documentation - Scripting in ACLs (gs.hasRole)
- Lab guide: Script-Controlled ACL - Restrict Record Access Based on Field Value