



TECHNICAL SPECIFICATIONS		
Aggregate	Details	6010 2WD
Engine	Туре	FPT S8000, Direct Injection, Turbocharged, Liquid Cooled with no loss tank
	Engine HP	60
	Rated Engine Speed	2300 RPM
	Air Cleaner	8" Dry type with dual element
Fuel System	Fuel Injection Pump	Rotary type
	Fuel filters	Spin-On with Water seperator
	Fuel tank capacity	60 / 100 L*
Transmission	Clutch	Double Clutch with Independent PTO Lever
	Gearbox	12F + 12R / 20F + 20R* / 24F + 24R*
	Gearbox type	Fully Synchromesh with Mechanical Shuttle / Power Shuttle*
Hydraulics	Lift Capacity	2000 Kg / 2500 Kg with Assist Ram*
	Controls	Sensomatic ²⁴ with 24 sensing points Lift-O-Matic with Height Limiter DRC valve & Isolator valve
	Remote Valve	Single / Double Acting (As Standard)
Brakes	Туре	Mechanically Actuated Oil Immeresed Multi disc brakes / Hydraulically Actuated Oil Immeresed Multi disc brakes*
Steering	Туре	Power Steering
РТО	Туре	Independent, 6 Splines
	RPM	540 @ 2198 ERPM 540E @ 1715 ERPM & RPTO / GSPTO*
Tyres	Front	7.50x16 inch*
	Rear	16.9x28 inch*
Additional Features		Optional Features
Sky Watch Cat Eye styling Flat deck platform Floor Mat Super Deluxe seat Adjustable front axle		ROPS & Canopy Front & Rear Weights Upto 3 Remote Valves 1000 PTO Option Hydraulic pump 54 & 60 L/min Swinging Drawbar 110 Ah battery & 90 Amp alternator

*Optional

Authorized Dealer









CNH Industrial (India) Private Limited: Plot No. 03, Udyog Kendra, Greater Noida, Gautam Budh Nagar District, Uttar Pradesh

Note: Since product information is a continuous process, specifications and details may change without any prior information. The accessories / tools shown here are not parts of the original device and New Holland does not promote or take responsibility of the tools not manufactured by the company.