

- All
- Q 1
- Q 2

Q2. Christmas Trees

Solved



Stuck somewhere?

Ask for help from a TA and get it resolved.

Get help from TA.

Problem Description

You are given an array **A** consisting of heights of Christmas trees and an array **B** of the same size consisting of the cost of each of the trees (B_i is the cost of tree A_i , where $1 \leq i \leq \text{size}(A)$), and you are supposed to choose 3 trees (let's say, indices p , q , and r), such that $A_p < A_q < A_r$, where $p < q < r$.

The cost of these trees is $B_p + B_q + B_r$.

You are to choose 3 trees such that their total cost is minimum. Return that cost.

If it is not possible to choose 3 such trees return -1.

Problem Constraints

$1 \leq A[i], B[i] \leq 10^9$
 $3 \leq \text{size}(A) = \text{size}(B) \leq 3000$

Input Format

First argument is an integer array A.
Second argument is an integer array B.

Output Format

Return an integer denoting the minimum cost of choosing 3 trees whose heights are strictly in increasing order, if not possible, -1.

Example Input

Input 1:

A = [1, 3, 5]
B = [1, 2, 3]

Input 2:

A = [1, 6, 4, 2, 6, 9]
B = [2, 5, 7, 3, 2, 7]

Example Output

Output 1:

6

Output 2:

7

Example Explanation

Explanation 1:

We can choose the trees with indices 1, 2 and 3, and the cost is $1 + 2 + 3 = 6$.

See Expected Output

```
Java 8 (Array Support)
/2
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
{
    minimumRightCost = Math.min(minimumRightCost, B[i]);
}
if(leftFlag && rightFlag)
{
    ans = Math.min(ans, (minimumRightCost + B[i]));
    mainFlag = true;
}
}
if(!mainFlag)//if ans is not found[there]
{
    return -1;
}
return ans;
```

Test Output Code's All Neat!

Compiling your Code...> Success!

Running Test Cases...> TestCase - Easy Success> TestCase - Hard Success

Final Verdict

Test Test With Custom Input

Submit