

CS 772/872: Advanced Computer and Network Security Fall 2025

Course Link:

<https://shhaos.github.io/courses/CS872/netsec-fall25.html>

Instructor: Shuai Hao

shao@odu.edu

www.cs.odu.edu/~haos



OLD DOMINION
UNIVERSITY

CS 772/872: Advanced Computer and Network Security

- **Network Security** (including Crypto foundations and applications)
- **Web and Browser Security**
- **Cloud Security**
- **System/Software Security**
- **AI/LLM Security** (by papers)



Network Security

- TCP/IP
- DNS
- BGP
- (D)DoS Attacks
- CDN
- Applied Cryptography
- PKI
- SSL/TLS and HTTPS
- DNSSEC/RPKI



Network Security

- **Confidentiality**: only sender, intended receiver should “understand” message contents
 - sender encrypts message
 - receiver decrypts message
- **Integrity**: sender, receiver want to ensure message not altered (in transit, or afterwards)
- **Authentication**: sender, receiver want to confirm identity of each other




Network Security

- **Confidentiality**: only sender, intended receiver should “understand” message contents
 - sender encrypts message
 - receiver decrypts message
- **Integrity**: sender, receiver want to ensure message not altered (in transit, or afterwards)
- **Authentication**: sender, receiver want to confirm identity of each other
- **Accessibility and Availability**: services must be accessible and available to users




Network Security




Network Security

- **Eavesdrop**: Intercept messages
- **Impersonation**: fake/spoof source address of packets
- **Hijacking**: “take over” ongoing connection by inserting himself in place
- **Denial of service**: prevent service from being used by others



Network Security

- Internet: a Network of Network




Autonomous system (AS) is a collection of IP networks under control of a single administrator (e.g., ISP)




Network Security

- OSI Protocol Stack




Network Security

- Encapsulation: end-to-end connectivity




Network Security

- **Narrow Waist**




IP – Internet Protocol

- **Connectionless**
 - Unreliable, “best-effort” protocol
- **Packet switching**
 - No states established ahead of time
 - Destination-based Routing
 - Shared resources




TCP – Transmission Control Protocol

- **Sender: break data into segments**
 - Sequence number is assigned to every segment
- **Receiver: reassemble segments in correct order**
 - Acknowledge receipt; lost segments will be re-sent
- **Connection state maintained on both sides**



TCP – Transmission Control Protocol


- TCP Handshake: Connection establishment



TCP – Transmission Control Protocol

- **SYN Flooding Attack**

- Attacker sends many connection requests with spoofed source address
- Victim allocates resources for each request
 - New thread
 - “half-open” connections
- Once resources exhausted, legitimate requests are dropped
- **Classic (Distributed-)Denial-of-Service (DDoS) pattern**




TCP – Transmission Control Protocol

- **Preventing Denial of Service**
 - DoS is caused by asymmetric state allocation
 - If a victim server opens new state for each connection attempt, attacker can initiate thousands of connections from bogus or forged IP addresses
 - **Cookies** ensure that the responder (victim) is stateless until initiator produced at least one acknowledgment
 - Responder's state (IP addresses and ports of the connection) is stored in a cookie and sent to initiator
 - After initiator responds, cookie is regenerated and compared with the cookie returned by the initiator



TCP – Transmission Control Protocol

- Preventing Denial of Service



TCP – Transmission Control Protocol


- **Denial of Service by Connection Reset**
 - If attacker can guess/predict/monitor the current sequence number for an existing connection, can send RESET packet to close it
 - Especially effective against long-lived connection
 - Widely used in Internet Censorship



UDP – User Datagram Protocol


- **Connectionless protocol**
 - Simply send datagram to application process at the specified port of the IP address
 - Source port number provides return address
 - Applications: media streaming, broadcast
- **No acknowledgement, no flow control, no message continuation**

TCP vs UDP Communication



UDP – User Datagram Protocol

- NTP Amplification Attack
 - “Reflection-and-Amplification” attack



- Dec. 2013 – Feb. 2014: 400Gbps DDoS attacks involving 4,500+ NTP servers targeting Cloudflare's data center



Network Defenses


- **Rate-limiting**
 - Straightforward but cannot differentiate legitimate traffic from malicious traffic
- **Egress Filtering against IP spoofing**
 - ISPs are lack of motivation to deploy
- **DDoS Protection Service offered by Content Delivery Networks (CDNs)**
 - Re-route the traffic to CDN's highly distributed network infrastructures
 - Must hide the the origin IP address



DNS – Domain Name System


- **Internet Dictionary**

- Maps symbolic names to numeric IP addresses
- UDP-based protocol



DNS – Domain Name System

- **Hierarchical System Design**
 - Root nameservers for top-level domains (.com, .edu, .uk, etc.)
 - 13 root server systems (A - M)
 - Top-level domain (TLD) nameservers indicate authoritative nameservers
 - Authoritative nameservers (ADNS) resolve subdomains
 - Local resolvers contact authoritative servers for requested domains



K-root servers



DNS – Domain Name System


- **DNS Caching**

- DNS responses can be cached (on local resolvers)
 - Quick response for repeated translations
 - Other queries may reuse some parts of lookup
 - NS records identify name servers responsible for a domain
- DNS negative queries can be cached
 - Don't have to repeat past mistakes (failed domains, misspellings, etc.)
- Cached data will periodically time out
 - Lifetime (TTL) of data controlled by owner of data, passed with every record




DNS – Domain Name System

- DNS Caching




DNS – Domain Name System

- DNS Caching



DNS – Domain Name System

- DNS Cache Poisoning




- Several opportunities to win the race.
- Here attacker attempts to pollute individual A records



DNS – Domain Name System

- DNS Cache Poisoning – Kaminsky attack



- If win the race, any request for `<XXX>.foo.com` will go to 6.6.6.6. The NS record is poisoned for a very long time
- If lose, try again with `<ANYTHING>.foo.com`




DNS – Domain Name System

- **Defending the DNS Cache Poisoning Problem**
 - Long TTL for legitimate responses?
 - Does it really help?
 - Randomized Transaction ID (TXID – 16 bits)
 - Randomize port in addition to TXID
 - 32 bits of randomness, makes it harder for attacker to guess TXID+port
- **DNSSEC**
 - **Cryptographic authentication of host-address mappings**



DNS – Domain Name System

- Other DNS-related Security Issues
 - Fast flux in DNS mapping
 - DNS-based C&C
- DNS squatting
 - typo-squatting,



DNS – Domain Name System

- **Other DNS-related Security Issues**
 - Fast flux in DNS mappings
 - DNS-based C&C (Control and Coordination)
 - DNS squatting
 - typo-squatting, combinatorics

Browser Security Indicators

Convey information about the security of a page

Locks, shields, keys, green bars...

"This page was fetched using SSL"

 Secure | <https://>

Page content was not viewed or altered by a network adversary
Certificate is valid (e.g. not expired), issued by a CA trusted by the browser, and the subject name matches the URL's domain

"This page uses an invalid certificate"

 Not secure | <https://>

"Parts of the page are not encrypted"

 <https://>

"The legal entity operating this web site is known"

Extended Validation (EV) certificates

 Square, Inc. [US] | <https://square.com>




DNS – Domain Name System

- **Other DNS-related Security Issues**
 - Fast flux in DNS mappings
 - DNS-based C&C (Control-and-command) in botnets
 - DNS squatting
 - typo-squatting, combo-squatting
 - Domain/subdomain hijacking
 - Dangling DNS records, domain shadowing
 - DNS Amplification



IP Routing – BGP (Border Gateway Protocol)

- Internet: a Network of Network




Autonomous system (AS) is a collection of IP networks under control of a single administrator (e.g., ISP)




IP Routing – BGP (Border Gateway Protocol)

- Internet: a Network of Network




IP Routing – BGP (Border Gateway Protocol)

- Internet: a Network of Network




IP Routing – BGP (Border Gateway Protocol)

- Internet: a Network of Network




IP Routing – BGP (Border Gateway Protocol)

- Internet: a Network of Network



BGP (In)Security

- BGP update messages contain no authentication or integrity protection
- Attacker (malicious ASes or misconfiguration) may falsify the advertised routes (BGP Hijacking)



BGP (In)Security

- BGP update messages contain no authentication or integrity protection
- Attacker (malicious ASes or misconfiguration) may falsify the advertised routes (BGP Hijacking)
 - Modify the IP prefixes associated with a route
 - Can blackhole traffic to certain IP prefixes
 - Change the AS path
 - Either attract traffic to attacker's AS, or divert traffic away
 - Economic incentive: an ISP wants to dump its traffic on other ISPs without routing their traffic in exchange



BGP (In)Security

- BGP Hijacking – **(Sub-)Prefix Hijacking**
 - Routers perform routing by the manner of the most specific prefix matching (i.e., longest-matching)
 - Adversaries may intentionally announce a prefix “smaller” than originally advertised one
 - A fraction of Internet traffic destined to the prefix to be captured by the adversary
 - Captured traffic is blackholed



BGP (In)Security


- **BGP Hijacking – Path Hijacking (Interception attack)**
 - ASes selectively/incidentally put themselves on the path
 - Adversaries may announce reachability of a prefix to attract traffic to be routed through the AS
 - The interception attack allows the malicious AS to become an intermediate AS in the path
 - Traffic can be routed back – keep the connection alive



BGP (In)Security

- **BGP Incident**

- Domain advertises good routes to adcs
- Result: packets go into a network ‘
- April 25, 1997: “The day the Internet
- AS7007 (Florida Internet Exchange) re-advertised all prefixes as if it owned the Internet
- In effect, AS7007 was advertising the Internet
- Huge network instability as incorrect routing data propagated and routers crashed under traffic



BGP (In)Security

- **BGP Incident**

- Domain advertises good routes to addresses it does not know how to reach
 - Result: packets go into a network “blackhole”
 - April 25, 1997: “The day the Internet died”
 - AS7007 (Florida Internet Exchange) de-aggregated the BGP route table and re-advertised all prefixes as if it originated paths to them
 - In effect, AS7007 was advertising that it has the best route to every host on the Internet
 - Huge network instability as incorrect routing data propagated and routers crashed under traffic

Figure 10-5 R10 Labs



BGP (In)Security

- **BGP Incident**

- Domain advertises good routes to addresses it does not know how to reach
 - Result: packets go into a network “blackhole”
 - April 25, 1997: “The day the Internet died”
 - AS7007 (Florida Internet Exchange) de-aggregated the BGP route table and re-advertised all prefixes as if it originated paths to them
 - In effect, AS7007 was advertising that it has the best route to every host on the Internet
 - Huge network instability as incorrect routing data propagated and routers crashed under traffic



BGP (In)Security


- **BGP Incident:** Pakistan Telecom hijacks YouTube (February 2008)
 - Pakistan government wants to block YouTube
 - AS17557 (Pakistan Telecom) advertises 208.65.153.0/24
 - All YouTube traffic worldwide directed to AS17557



BGP (In)Security


- **BGP Incident:** Pakistan Telecom hijacks YouTube (February 2008)

What should have happened




BGP (In)Security

- **BGP Incident:** Pakistan Telecom hijacks YouTube (February 2008)




BGP (In)Security

- BGP Incident



BGP (In)Security


- BGP Incident



BGP (In)Security

- **BGP Incident**


- Bitcoin Hijack (February 2014)
 - Hijacked users got directed to a mining server that was under the control of hijacker and redirects them to a malicious mining pool
 - Miners continues to receive mining tasks but don't get compensated



BGP (In)Security

- **BGP Incident**


- Bitcoin Hijack (February 2014)
 - Hijacked users got directed to a mining server that was under the control of hijacker and redirects them to a malicious mining pool
 - Miners continues to receive mining tasks but don't get compensated



BGP (In)Security

- **BGP Incident**

- Bitcoin Hijack (February 2014)
 - Hijacked users got directed to a mining server that was under the control of hijacker and redirects them to a malicious mining pool
 - Miners continues to receive mining tasks but don't get compensated



BGP (In)Security

- **Secure BGP is extremely hard**
 - The victim AS doesn't see the problem
 - Picks its own route
 - May not cause entire loss of connectivity
 - Partial damage
 - Performance degradation
 - Diagnosing prefix hijacking
 - Analyzing updates from many vantage points



BGP (In)Security

- **Secure BGP is extremely hard**
 - Complex System
 - Around 100K Autonomous Systems
 - Decentralized Control among ASes
 - Hard to reach agreement on the solution
 - Hard to deploy the solution even standardized
 - Low incentive: many solutions benefit others rather than the deployer itself, e.g., ingress filter to defend IP spoofing



BGP (In)Security

- **Secure BGP is extremely hard**
 - RPKI – Resource Public Key Infrastructure
 - Against prefix hijacking
 - Secure BGP/BGPsec
 - Against path hijacking




Content Delivery Network (CDN)

- **Content Delivery Network**
 - Deploy a large number of **edge servers** proximal to clients
 - Emerging in late 90s



Content Delivery Network (CDN)

- Content Delivery Network
 - Deploy a large number of **edge servers**
 - Emerging in late 90s



The legacy of Danny Lewin, the first man to die on 9/11

By Todd Leopold, CNN

Updated 7:24 AM ET, Wed September 11, 2013



MORE FROM CNN BUSINESS

Handshake aims to help students launch their career

Dow plunges after Trump tweets about China

Recommended by Outbrain

HISTORY

The First Victim of Sept. 11

He was likely the first person killed, but his influence was felt that entire terrible day—online.

By MOLLY KNIGHT RASKIN

SEPT 11, 2015 • 7:34 AM




Content Delivery Network (CDN)

- **Content Delivery Network**
 - Deploy a large number of **edge servers** proximal to clients
 - Emerging in late 90s
 - Delivery significant port of Internet traffic
 - All top Internet services leverage CDNs
 - DNS-based CDNs vs. Anycast-based CDNs



Content Delivery Network (CDN)

- Content Delivery Network




DNS-based CDNs



Content Delivery Network (CDN)

- Content Delivery Network




DNS-based CDNs



Content Delivery Network (CDN)

- Content Delivery Network




DNS-based CDNs



Content Delivery Network (CDN)

- Content Delivery Network



Anycast-based CDNs



Content Delivery Network (CDN)

- **Instinct Security Provided by CDNs**
 - Additional layer of proxy
 - Hide the actual origin source of web services
 - Highly distributed, scalable platforms
 - Absorb malicious traffic (blackholing/scrubbing traffic)
 - Redundancy of service instance
 - Provision of integrity/authentication (TLS/SSL)



Network Security

- TCP/IP
- DNS
- BGP
- (D)DoS Attacks
- CDN
- Applied Cryptography
- PKI
- SSL/TLS and HTTPS
- DNSSEC
- RPKI



CS 772/872: Advanced Computer and Network Security

Fall 2025

Course Link:

<https://shhaos.github.io/courses/CS872/netsec-fall25.html>

