



Pure Borrow

Linear Haskell Meets Rust-Style Borrowing

Yusuke Matsushita Kyoto University & MPI-SWS

Sept 18, 2026 @ Cambridge Logic & Semantics Seminar

About Me

- ◆ **Yusuke Matsushita 松下 祐介**
 - ▶ July 15, 1996, Osaka
- ◆ **'15–'24 Bachelor, Master, Ph.D. at UTokyo**
 - ▶ **Computer science — Programming languages**
 - Supervised by Prof. Naoki Kobayashi
- ◆ **'25– Assist. Prof. at Hakubi, KyotoU**
 - ▶ Focus on Rust 
 - ▶ '26– Visiting scientist at MPI-SWS
 - Germany, Prof. Derek Dreyer



15th / Graduate School of Informatics
Yusuke MATSUSHITA
Assistant Professor

Pioneering the next
generation of software
development technology with
the power of logic

— Exploring a New Age of
Software Development Springing
from Rust



About Me

Google Scholar

SIGN IN



Yusuke Matsushita

FOLLOW

GET MY OWN PROFILE

Kyoto University

Verified email at fos.kuis.kyoto-u.ac.jp - [Homepage](#)

Computer Science

Programming Languages

Machine Learning

TITLE	CITED BY	YEAR
RustHorn: CHC-based Verification for Rust Programs Y Matsushita, T Tsukada, N Kobayashi ACM Transactions on Programming Languages and Systems (TOPLAS) 43 (4), 1-54 109 2021		
RustHornBelt: A Semantic Foundation for Functional Verification of Rust Programs with Unsafe Code Y Matsushita, X Denis, JH Jourdan, D Dreyer Proceedings of the 43rd ACM SIGPLAN Conference on Programming Language ... 95 2022		
RustHorn: CHC-Based Verification for Rust Programs Y Matsushita, T Tsukada, N Kobayashi European Symposium on Programming (ESOP), 484-514 65 2020		
Nola: Later-Free Ghost State for Verifying Termination in Iris Y Matsushita, T Tsukada Proceedings of the ACM on Programming Languages 9 (PLDI) 8 2025		
Borrowable Fractional Ownership Types for Verification T Nakayama, Y Matsushita, K Sakayori, R Sato, N Kobayashi International Conference on Verification, Model Checking, and Abstract ... 7 2024		

Cited by

	All	Since 2021
Citations	301	294
h-index	5	5
i10-index	3	3

70

35

0

2020

2021

2022

2023

2024

2025

2026

Public access

VIEW ALL

0 articles

6 articles

not available

available

3

About Me



PLDI Review Committee PLDI Research Papers



Benjamin Mariano
The University of Texas at Austin, Texas, USA
United States



Guido Martínez
Microsoft Research
United States



Yusuke Matsushita
Kyoto University
Japan



Jedidiah McClurg
Cornell University
United States




Roland Meyer
TU Braunschweig
Germany




Mae Milano
Princeton University
United States



Program Committee POPL



Yannick Zakowski
Inria
France



Yingfei Xiong
Peking University
China



Youyou Cong
Institute of Science Tokyo
Japan



Yu Feng
University of California at Santa Barbara
United States



Yu-Fang Chen
Academia Sinica
Taiwan



Yusuke Matsushita
Kyoto University
Japan

Up to Now

High Schooler


Undergrad

Grad


Now

 **Haskell**

λ -calculus Monad




Type theory



Category theory



PL

 **Rust**

*Fast like C/C++,
Safe like Haskell?*



Study PL!



RustHorn

ESOP '20 & TOPLAS '21


Rust $\rightarrow$ Functional



RustHornBelt

PLDI '22


Logic for RustHorn



Pure Borrow

PLDI '26

Haskell Meets Rust!

Pure Borrow 

***Rust-Style Borrowing in
Linear Haskell with Purity***

Ad Denotational Semantic Typing


Matsushita, ongoing

**Denotational
Semantics**

Observational behavior

This work

Soundness



**Operational
Semantics**

Imperative impl


**Semantic typing
a.k.a. Logical relation**

Extensible proof!

*Termination-sensitive +
Step-indexed*

Purity of *lazy thunks*, *ST monad*, *Linear Haskell*, ...

Ad Rust Workshop? @ Kyoto, March 727



Rust Workshop

*Semantics for Rust
Verification for Rust
Bug finding for Rust*

第29回プログラミングおよびプログラミング 言語ワークショップ PPL 2027

日程 2027年3月8日（月）～ 3月11日（木）
会場 船井哲良記念講堂（京都大学 桂キャンパス）
主催 日本ソフトウェア科学会 プログラミング論研究会

TFP (and TFPiE) 2027

28th International Symposium on Trends in Functional
Programming
12th to 15th March 2027, Kyoto, Japan




Introduction


Software



Software



Software embodies *human ideals*
on *finite physical machines*



Two Major Paradigms of Programming




Functional


High-level abstraction

Well-behaved

Safe & Predictable



Imperative





Low-level control

Well-tuned

Performative

Unifying the Two Paradigms




Functional

High-level abstraction

Well-behaved

Safe & Predictable

Imperative




Low-level control

Well-tuned

Performative

Functional, with Purity




 **Haskell** '90



λ -calculus '36

Purity

***Same result
regardless of timing***



Well-behaved, esp. *parallelism*

Purity = Referential Transparency

Super Well-behaved!



Deterministic

*Same result
across executions*

$(t, t) \equiv \text{let } x = t \text{ in } (x, x)$

✓ **Predictable**

✓ **Equations**

Order-insensitive

*Commutates with
other computations*

$(t, u) \equiv \text{let } x = u \text{ in } (t, x)$

Parallelism, Lazy evaluation, ...

Reasoning & Optimization


e.g. $\text{map } (g \circ f) \equiv \text{map } g \circ \text{map } f$

Functional, More Imperative



Linear Haskell *Bernardy+ '18*

◀ ⚡ **Mutate!** **Linear Types** '90–



⋈ **Haskell** '90




λ-calculus '36

Performance?

Purity

**Same result
regardless of timing**



Well-behaved, esp. *parallelism*

- Original Haskell **Persistent** data $\rightarrow$ **Copy**

$$\text{Vec } a \xrightarrow{\quad} \text{Int} \rightarrow (a \rightarrow a) \rightarrow \text{Vec } a$$

$$[0, 1, 2, \dots, 999] \quad 0 \quad (+\ 7) \quad [7, 1, 2, \dots, 999] \quad \text{Pure!}$$

$$\quad \quad \quad \quad \quad \quad \quad \quad \quad \quad \quad \quad \quad \quad \quad [0, 1, 2, \dots, 999]$$

- Linear Haskell **Linear** $\rightarrow$ **Mutate** in place!

Linear arrow $\multimap$ Argument is used exactly **once**

$$\text{Vec } a \multimap \text{Int} \rightarrow (a \multimap a) \multimap \text{Vec } a$$


$$\underline{[0, 1, 2, \dots, 999]} \quad 0 \quad (+\ 7) \quad [7, 1, 2, \dots, 999] \quad \text{Pure!}$$

$$\text{No aliases!} \quad \quad \quad \quad \quad \quad \quad \quad \quad \quad \quad \quad \quad \quad \quad \text{Direct ownership passing}$$



Challenge

Separate mutations to disjoint subregions

E.g., **Parallel quicksort**



Unifying the Two Paradigms




Functional

High-level abstraction

Well-behaved

Safe & Predictable

Imperative






Low-level control

Well-tuned

Performative


Imperative, More Functional




Ownership & Region Types '94–



Memory corruption, Race condition, ...





'72



'85


Ownership

Separate **Mutable** State



XOR





Aliasing



→ ***No dangerous interference between computations***

Imperative, More Functional with Borrows


Borrow ↻ **Non-local!** ✈️
Separate ownership by **time**
Mutation w/o ownership passing



Ownership & Region Types '94—



Memory corruption, Race condition, ...




'72



'85


Rust-style Borrow



Borrowing Solved! But, ...





✓ **Borrow** *Separate mutations to disjoint subregions*

E.g., **Parallel** quicksort




Purity?

Challenge




Purity

*Same result
regardless of timing*





Borrow ↻ **Non-local!** ✈️
Separate ownership by time
Mutation w/o ownership passing

 **Linear Haskell**


 **Rust**



Pure Borrow 



***Rust-Style **Borrowing** in
Linear Haskell with **Purity*****




High-Level Comparison

	Pure 	Mutate  Borrow 	Parallel	Leak-free
Pure Only	●	○	●	
ST Monad	●	●	○	○
Rust	○	●	●	○
Basic Linear Haskell	●	●	●	●
Pure Borrow	●	●	●	●



Pure Borrow

*Rust-Style **Borrowing** in
Linear Haskell with **Purity***



- ✦ **Pure & Mutate & Parallelize** *Parallel quicksort*
- ✦ **Just APIs** *Rich features of Haskell*
- ✦ **Metatheory: Why Pure** WIP *Histories for borrows*

Overview

Preliminary Unrestricted vs Linearity

data Ur a **where**

$Ur :: a \rightarrow Ur\ a$

Unrestricted ω

Arbitrarily many times

Even infinitely

E.g., $inf :: a \rightarrow [a]$
 $\boxed{a} \rightarrow inf\ a = a :: inf\ a$

Linear 1

Exactly once

E.g., $pair :: a \multimap b \multimap (a, b)$
 $pair\ a\ b = (a, b)$

Preliminary Linearity Witness

data Ur a where

$$Ur :: a \rightarrow Ur\ a$$

Unrestricted ω

Linear 1

$$\text{lin} :: (\text{Lin} \Rightarrow \text{Ur } a) \multimap \text{Ur } a$$
$$\text{cf. runST} :: (\forall s. \text{ST}^s a) \rightarrow a$$

class Lin *Linearity witness* Spiwack+ '22

Used arbitrarily finite times But never in Ur

Preliminary **Mutable State** in Linear Haskell

Vector **data** Vec a

$\text{newVec} :: \text{Lin} \Rightarrow [a] \multimap \text{Vec } a$  **Linear!**

$\text{freeVec} :: \text{Vec } a \multimap [a]$

Preliminary Mutable State in Linear Haskell

Vector **data** Vec a

newVec :: Lin $\Rightarrow$ [a] $\multimap$ Vec a



Linear!

freeVec :: Vec a $\multimap$ [a]

class Movable a **where**

move :: a $\multimap$ Ur a

Before Pure Borrow

modifyAt' :: Vec a $\multimap$
Int $\rightarrow$ (a $\multimap$ a) $\multimap$ Vec a

readAt' :: Movable a $\Rightarrow$
Vec a $\multimap$ Int $\rightarrow$ (Ur a, Vec a)

Direct ownership passing!

Preliminary Example of Basic Linear Haskell

example :: **Ur** [Int]

example = **lin do**^o

$v \leftarrow \text{newVec } [0,1,2]$

v $\leftarrow \text{modifyAt}' \text{ } \underline{v} \ 0 \ (+ \ 3)$

v $\leftarrow \text{modifyAt}' \text{ } \underline{v} \ 2 \ (+ \ 5)$

v $\leftarrow \text{modifyAt}' \text{ } \underline{v} \ 0 \ (\times \ 4)$

move (freeVec v)

do^o $p \leftarrow t; c \equiv$

let ! $p = t$ **in do**^o c

$[[3, 1, 2]]$

$[[3, 1, 7]]$

$[[12, 1, 7]]$


Ur $[12, 1, 7]$

*Direct ownership
passing!*


Recap Challenge


Separate mutations to disjoint subregions

E.g., **Parallel quicksort**







Pure Borrow 



*Rust-Style **Borrowing** in
Linear Haskell with **Purity***




Recap Rust-Style Borrow



Core APIs


Borrow **Mutable borrower** **Lender**
 $\text{borrow} :: \text{Lin} \Rightarrow a \multimap (\text{Mut}^\alpha a, \text{Lend}^\alpha a)$
newtype of a



Mutate $\text{modifyAt} :: \text{Mut}^\alpha (\text{Vec } a) \multimap$
 $\text{Int} \rightarrow (a \multimap a) \multimap \text{BO}^\alpha (\text{Mut}^\alpha (\text{Vec } a))$
Monad



Split $\text{splitAt} :: \text{Mut}^\alpha (\text{Vec } a) \multimap$
 $\text{Int} \rightarrow (\text{Mut}^\alpha (\text{Vec } a), \text{Mut}^\alpha (\text{Vec } a))$



Reclaim $\text{reclaim} :: \text{End}^\alpha \xRightarrow{\alpha \text{ has ended}} \text{Lend}^\alpha a \multimap a$



BO Monad

BO^α a **Computation permitted only before α ends**

Borrower accesses BO^α $< \alpha \text{ ends} \leq$ **Lender reclaim** End^α

Pure $\text{runBO} :: \text{Lin} \Rightarrow (\forall \alpha. \text{BO}^\alpha (\text{End}^\alpha \Rightarrow a)) \multimap a$
Rank-2 poly cf. $\text{runST} :: (\forall s. \text{ST}^s a) \rightarrow a$



Linearity ensures commutativity

Parallel $\text{parBO} :: \text{BO}^\alpha a \multimap \text{BO}^\alpha b \multimap \text{BO}^\alpha (a, b)$

cf. *ST is not parallelizable*

Example

```
example :: Ur [Int]
example = lin doo
  v ← newVec [0, 1, 2]
  runBO do
    let !(mv, lv) = borrow v
    mut_example mv
    pure $ move $
      freeVec $ reclaim lv    Ur [12, 1, 7]
```

Example


```
example :: Ur [Int]
example = lin do°
  v ← newVec [0, 1, 2]
  runBO do
    let !(mv, lv) = borrow v
    mut_example mv
    pure $ move $
      freeVec $ reclaim lv
    Ur [12, 1, 7]
```

```
mut_example ::
  Mutα (Vec Int) → BOα ()
mut_example mv = do
  mv ← modifyAt mv 0 (+ 3)
  mv ← modifyAt mv 2 (+ 5)
  mv ← modifyAt mv 0 (× 4)
  pure $ consume mv

class Consumable a where
  consume :: a → ()
```

Example with Parallelization

```
example :: Ur [Int]
example = lin do°
  v ← newVec [0, 1, 2]
  runBO do
    let !(mv, lv) = borrow v
    mut_example mv
    pure $ move $
      freeVec $ reclaim lv
    Ur [12, 1, 7]
```




Parallelize!

```
mut_example mv =
  let !(mv0, mv1) = splitAt mv 1 in
  consume <$> parBO
    (do mv0 ← modifyAt mv0 0 (+ 3)
     modifyAt mv0 0 (× 4))
    (modifyAt mv1 1 (+ 5))
```


Share

Shared borrower

Share $\text{share} :: \text{Mut}^{\alpha} a \multimap \text{Ur} (\text{Share}^{\alpha} a)$




Read $\text{copyAt} :: \text{Copyable } a \Rightarrow$
 $\text{Share}^{\alpha} (\text{Vec } a) \rightarrow \text{Int} \rightarrow \text{BO}^{\alpha} (\text{Ur } a)$



class Copyable a **where**
 $\text{copy} :: \text{Share}^{\alpha} a \rightarrow a$

Split $\text{splitAt} :: \text{Share}^{\alpha} (\text{Vec } a) \multimap$
 $\text{Int} \rightarrow (\text{Share}^{\alpha} (\text{Vec } a), \text{Share}^{\alpha} (\text{Vec } a))$



Remark Internal Implementation

Just unsafe coercions → Efficient

borrow = unsafeCoerce $\lambda a \rightarrow (a, a)$

reclaim = unsafeCoerce $\lambda a \rightarrow a$

share = unsafeCoerce $\lambda a \rightarrow \text{Ur } a$


Reborrow

Reborrow

reborrowing $:: \text{Mut}^\alpha a \multimap$

$(\forall \beta. \text{Mut}^{\beta \wedge \alpha} a \multimap \text{BO}^{\beta \wedge \alpha'} r) \multimap$


$\text{BO}^{\alpha'} (r, \underline{\text{Mut}^\alpha a})$ **Lifetime intersection**



Temporary Sharing

Temporarily share

$\text{sharing} :: \text{Mut}^\alpha a \multimap$
 $(\forall \beta. \text{Share}^{\beta \wedge \alpha} a \rightarrow \text{BO}^{\beta \wedge \alpha'} r) \multimap$
 $\text{BO}^{\alpha'} (r, \text{Mut}^\alpha a)$



$\text{sharing } m \ k =$
 $\text{reborrowing } m \ \lambda m \rightarrow$
 $\text{let } !(Ur \ s) = \text{share } m \text{ in } k \ s$

Read from Mut

$\text{copyAtMut} :: \text{Copyable } a \Rightarrow$
 $\text{Mut}^\alpha (\text{Vector } a) \rightarrow \text{Int} \rightarrow$
 $\text{BO}^\alpha (Ur \ a, \text{Mut}^\alpha (\text{Vector } a))$

$\text{copyAtMut } i \ mv =$
 $\text{sharing } mv \ \$ \ \text{copyAt } i$

Lifetime Primitives

Atomic lifetime



data Lifetime = $Al\ \iota \mid \alpha \wedge \beta \mid Static$ $\alpha, \beta :: Lifetime$



Lifetime intersection

newLifetime :: **Lin** $\Rightarrow \exists\ \iota. Now^{Al\ \iota}$

endLifetime :: $Now^{Al\ \iota} \multimap Ur\ End^{Al\ \iota}$

$Now^{\alpha \wedge \beta} \approx (Now^{\alpha}, Now^{\beta})$

$End^{\alpha \wedge \beta} \approx End^{\alpha} + End^{\beta}$

BO Primitives

$\text{newLifetime} :: \text{Lin} \Rightarrow \exists \iota. \text{Now}^{\text{Al } \iota}$
 $\text{endLifetime} :: \text{Now}^{\text{Al } \iota} \multimap \text{Ur End}^{\text{Al } \iota}$

Pure $\text{execBO} :: \text{Now}^{\alpha} \multimap \text{BO}^{\alpha} a \multimap (\text{Now}^{\alpha}, a)$

$\text{runBO} :: \text{Lin} \Rightarrow (\forall \alpha. \text{BO}^{\alpha} (\text{End}^{\alpha} \Rightarrow a)) \multimap a$

Scope $\text{sexecBO} :: \text{Now}^{\beta} \multimap \text{BO}^{\beta \wedge \alpha} a \multimap \text{BO}^{\alpha} (\text{Now}^{\beta}, a)$

$\text{srunBO} :: (\forall \beta. \text{BO}^{\beta \wedge \alpha} (\text{End}^{\beta} \Rightarrow a)) \multimap \text{BO}^{\alpha} a$

reborrowing $\text{joinMut} :: \text{Mut}^{\beta} (\text{Mut}^{\alpha} a) \multimap \text{Mut}^{\beta \wedge \alpha} a$

Case Study

Pure Borrow is Already There!

SoftwareFoundationGroupAtKyotoU / pure-borrow

Public

Notifications

Fork 0

Star 61

<> Code

Issues

Pull requests 1

Actions

Projects

Security and quality

Insights

main

Go to file

<> Code

konn

Merge pull request #41 from SoftwareFoundat...

24fabd7 · last month

.agents/hooks	chore(agents): share Claude Cod...	2 months ago
.claude	chore(agents): share Claude Cod...	2 months ago
.codex	refactor(concurrent): rewrite qso...	last month
.github/workflows	ci: upgrade run-fourmolu to v13 a...	last month
.vscode	Suppressing further	9 months ago
app	chore(bench): omit missing case...	last month
bench	review: document the delimiter o...	last month
ci	Convinced GHC 9.10	5 months ago
doctests	fourmolized	5 months ago
internal-src	perf(worklist): add checked-surf...	last month
scripts	Auto-plot	5 months ago

About

Pure Borrow: Linear Haskell Meets Rust-Style Borrowing

Readme

BSD-3-Clause license

Activity

Custom properties

61 stars

11 watching

0 forks

Report repository

Releases 1

Release 0.0.0.0 Latest 4 months ago

Contributors 4

konn

Hiromi Ishii

shiatsumat

Yusuke Matsu...

Hackage :: [Package]

Search

Browse

What's new

Upload

User

pure-borrow: Rust-style borrowing in Linear Haskell with purity

[[bsd3](#), [library](#), [linear-haskell](#), [program](#)] [[Propose Tags](#)] [[Report a vulnerability](#)]

This package realizes rust-style borrowing in Linear Haskell with purity and concurrency support. See [Control.Monad.Borrow.Pure](#) for the main API documentation, and see our paper *Pure Borrowing: Linear Haskell Meets Rust-Style Borrowing* by Y. Matsushita and H. Ishii for the details.

[\[Skip to Readme\]](#)

Build

BuildFailed

Documentation

Available

Modules

[\[Index\]](#) [\[Quick Jump\]](#)

Control
Concurrent
DivideConquer
Control.Concurrent.DivideConquer.Linear
STM
Control.Concurrent.STM.TMDeque
Control.Concurrent.STM.TMDequeRingBuffer
Monad
Borrow

Versions [\[RSS\]](#)

0.0.0.0

Change log
[CHANGELOG.md](#)

Dependencies

[array](#), [base](#) ([>=4.17](#) & [<5](#)), [bytestring](#), [cassava](#), [containers](#), [deepseq](#), [directory](#), [file-embed](#), [hybrid-vectors](#), [linear-base](#) ([>=0.7](#)), [linear-generics](#), [monoidal-containers](#), [optparse-applicative](#), [process](#), [pure-borrow](#), [random](#), [stm](#), [tasty](#), [tasty-bench](#), [template-haskell](#), [temporary](#), [text](#), [transformers](#), [unordered-containers](#), [vector](#), [vector-algorithms](#) [\[details\]](#)

Tested with

ghc ==9.10.2 || ==9.12.4 || ==9.14.1

License

[BSD-3-Clause](#)

Copyright

Copyright (c) 2025-present, Yusuke Matsushita and Hiromi Ishii

Author


Yusuke Matsushita and Hiromi Ishii

Pure Borrow works on stable GHC


Parallel Quicksort

Pure + *Mutate* + *Parallel*

```
qsort :: Mutα (Vec Int) → BOα ()  
qsort v = let (Ur n, v) = size v in  
  if n ≤ 1 then pure (consume v) else do  
    (Ur a, v) ← copyAt v (n // 2)  
    (i, v) ← pivotSwap v a  
    let (lo, hi) = splitAt v i  
    consume <$> parBO (qsort lo) (qsort hi)
```



Advanced: Work-Stealing Scheduler




data DivideConquer ^{α} a = DivideConquer
($\forall \beta. \beta \leq \alpha \Rightarrow \text{Mut}^\beta \text{ a} \multimap \text{BO}^\beta (\text{Res}^\beta \text{ a})$)

data Res ^{β} a = Done | Cont [$\text{Mut}^\beta \text{ a}$]

divideAndConquer :: $\beta \leq \alpha \Rightarrow$
Int $\rightarrow$ DivideConquer ^{α} a $\rightarrow$
 $\text{Mut}^\alpha \text{ a} \multimap \text{BO}^\beta (\text{Mut}^\alpha \text{ a})$

Parallel Quicksort by Work Stealing



data DivideConquer^α a = DivideConquer
 (∀ β. β ≤ α ⇒ Mut^β a ⇝ BO^β (Res^β a))

data Res^β a = Done | Cont [Mut^β a]

divideAndConquer :: β ≤ α ⇒
 Int → DivideConquer^α a →
 Mut^α a ⇝ BO^β (Mut^α a)

qsortDC :: β ≤ α ⇒ Int →

Mut^α (Vec Int) ⇝ BO^β (Mut^α (Vector Int))

qsortDC nwork = divideAndConquer nwork \$

DivideConquer λv → **case** size v **of**

(Ur n, v)

| n ≤ 1 → **let** () = consume v **in** pure Done



| otherwise →

(Ur a, v) ← copyAtMut v (n // 2)

(lo, hi) ← pivotSwap v a; pure \$ Cont [lo; hi]

No thread joining needed → **Efficient**


Benchmark Results



Successfully *parallelized*

Metatheory

Challenge: Purity of Borrowing



Challenge: Purity of Borrowing

Borrow $\text{borrow} :: \text{Lin} \Rightarrow a \multimap (\text{Mut}^\alpha a, \text{Lend}^\alpha a)$

Mutate $\text{modifyAt} :: \text{Mut}^\alpha (\text{Vec } a) \multimap$
 $\text{Int} \rightarrow (a \multimap a) \multimap \text{BO}^\alpha (\text{Mut}^\alpha (\text{Vec } a))$

Split $\text{splitAt} :: \text{Mut}^\alpha (\text{Vec } a) \multimap$
 $\text{Int} \rightarrow (\text{Mut}^\alpha (\text{Vec } a), \text{Mut}^\alpha (\text{Vec } a))$

Reclaim $\text{reclaim} :: \text{End}^\alpha \Rightarrow \text{Lend}^\alpha a \multimap a$

Purity?



Insight **Purity** of the *ST* Monad

- ✦ ST monad has **mutations** but is **pure**!
- ✦ **Denotation**: **Store**-passing **state** monad
- ✦ But **no** parallelism

What about **borrowing**?

Idea: Histories

- ✦ Manage the global **history** of **mutations** to **borrow**s
- ✦ **BO** monad: **State** monad of the **mutation history**
 - ▶ **Mutations** are separable → **Parallelism** works!
- ✦ **Lifetime end** class: Owns the frozen **history**
- ✦ **reclaim**: Restore the **updated** value from the **history**

Our Formalization & Metatheory

- ✦ Core calculus + Linear type system for Pure Borrow
- ✦ Two operational semantics
 - ▶ Mutative, with memories & Denotational, based on histories
- ✦ Theorem: Denotational op sem is confluent
 - ▶ Full purity: Future work, due to fresh borrow id generation
- ✦ WIP: Mutative & denotational op sems bisimulate?
 - ▶ For well-typed programs & configurations

Reference Core Calculus Syntax

Variable	$Var \ni x, y, z$	Data constructor	C
Operator	$op ::= (+) \ 2 \mid \cdots \mid (\leq) \ 2 \mid \cdots$ $\mid \text{par} \ 2 \mid \text{consume} \ 1 \mid \text{move} \ 1$ $\mid \text{lin} \ 1 \mid \text{withLin} \ 1 \mid \text{newRef} \ 2 \mid \text{freeRef} \ 1$ $\mid \text{newLifetime} \ 2 \mid \text{endLifetime} \ 1 \mid \text{execBO} \ 2$ $\mid \text{borrow} \ 2 \mid \text{share} \ 1 \mid \text{copy} \ 1 \mid \text{joinMut} \ 1 \mid \text{reclaim} \ 2$		
Monad constructor	$mo ::= \text{pure} \ 1 \mid (\gg=) \ 2 \mid \text{sexecBO} \ 2$ $\mid \text{parBO} \ 2 \mid \text{deref} \ 1 \mid \text{updateRef} \ 2$		
Term	$Term \ni t, u ::= x \mid \text{let } \overline{x = t} \text{ in } u \mid \lambda x \rightarrow t \mid t \ u \mid \text{seq} \ x \ t \mid n$ $\mid C \ \bar{t} \mid \text{case } t \text{ of } \{ \overline{C \ \bar{x} \rightarrow u} \} \mid op \ \bar{t} \mid mo \ \bar{t}$		

Reference Core Calculus Type Syntax

Lifetime variable α, β Lifetime id ι

Lifetime $\alpha, \beta ::= \text{al } \iota \mid \text{static} \mid \alpha \wedge \beta \mid \alpha$

Multiplicity variable π, μ Multiplicity $\pi, \mu ::= 1 \mid \omega \mid \prod \bar{\pi}$

Type variable X, Y Variable $x ::= \alpha \mid \iota \mid \pi \mid X$

Type constructor F Borrower constructor $B ::= \text{Mut} \mid \text{Share}$

Type $Type \ni T, U ::= \forall x. T \mid X \mid T \rightarrow_{\pi} U \mid F \bar{T} \mid \text{Int} \mid \text{Lin}$
 $\mid \text{Ref } T \mid \text{Now}^{\alpha} \mid \text{End}^{\alpha} \mid B^{\alpha} T \mid \text{Lend}^{\alpha} T \mid \text{BO}^{\alpha} T$


$T \multimap U \triangleq T \rightarrow_1 U$ $T \rightarrow U \triangleq T \rightarrow_{\omega} U$

Data type declaration **data** $F \bar{X}$ **where** $\overline{C :: T \rightarrow_{\pi} F \bar{X}}$

Typing context $\Gamma, \Delta ::= \overline{x ::_{\pi} T}$

Related Work


Recap High-Level Comparison

	Pure 	Mutate ⚡ Borrow ↻	Parallel	Leak-free
Pure Only	●	○	●	
ST Monad	●	●	○	○
Rust	○	●	●	○
Basic Linear Haskell	●	●	●	●
Pure Borrow	●	●	●	●

Comparison with Monads


	Pure	Mutate	Borrow	Scope	Parallel	Leak-free
IO Monad <i>Peyton Jones+ '93</i>						
ST Monad <i>Launchbury+ '94</i>						
Monadic Regions <i>Fluet+ '04</i>						
RIO Monad <i>Bernardy+ '18</i>						
Pure Borrow						

- ✦ **O**Caml + **Safe low-level** control
 - ▶ **Ownership**, **memory-usage**, **thread safety**, ...
- ✦ **Lightweight mode** annotation
 - ▶ Easy to add to legacy OCaml code
 - ▶ Coarse **lifetime** modes: **global** vs **local**
- ✦ **No** strict **purity**



Linearity vs Uniqueness

Marshall+ '22



Linearity

Uniqueness

Comonad

many

$\leq$

once

unique

$\leq$

aliased
Monad



Non-linearity Ur

Comonad

$Ur\ a \multimap a$

$Ur\ a \multimap Ur\ (Ur\ a)$

Time-delimited aliasing Mut^α & $Lend^\alpha$

Monad-like

$a \multimap (Mut^\alpha\ a, Lend^\alpha\ a)$


$Mut^\alpha\ (Mut^\beta\ a) \multimap Mut^{\alpha \wedge \beta}\ a$

✦ Verify Rust programs as **functional** code

✦ Model **borrow**s by **prophecy** 


► Prophecy [Abadi+ '88]: Fetches **info** about the **future**

*Final result of
borrower's update*



Example of RustHorn's Translation

Rust



Functional



```
fn take_max< $\alpha$ >
  (ma: & $\alpha$  mut i32, mb: & $\alpha$  mut i32)
  -> & $\alpha$  mut i32 {
    if *ma >= *mb { ma } else { mb }
  }
```

```
fn test(mut a: i32, mut b: i32) {
  *take_max(&mut a, &mut b) += 7;
  assert!((a - b).abs() >= 7);
}
```

```
let take_max (a, a') (b, b') = 
  if a >= b then
    (assume(b' = b); (a, a'))
  else (assume(a' = a); (b, b'))
```

```
let test a b =
  let a' = rand() in let b' = rand() in
  let (r, r') =
    take_max (a, a') (b, b') in
  assume(r' = r + 7);
  assert(abs (a' - b') >= 7);
```

Prophecies vs Histories

Prophecies

- ◆ Concise & Local
 - ▶ Ideal for verification
- ◆ Non-determinism
- ◆ Precise resolution needed
 - ▶ Otherwise over-approximate

Histories

- ◆ Bulky & Global
- ◆ Deterministic
- ◆ Automatic & Robust
 - ▶ Ideal for the purity proof

Conclusion

Summary: Pure Borrow



- ✦ **Linear Haskell + Rust-style borrowing**
 - ▶ **Pure** & **Mutate** w/o ownership passing & **Parallelize**
 - ▶ **BO** monad for **lifetime** constraints
- ✦ Case study: **Parallel** quicksort
- ✦ **Metatheory**: **Purity** by **history**-based model



Future Work

- ✦ More **automation** for **borrowing**?
- ✦ **Logical relations** like RustBelt [Jung+ '18] ?
 - ▶ In **separation logic** [O'Hearn+ '01], e.g., Iris [Jung+ '15] ?
- ✦ **Denotational semantics**?
 - ▶ Fresh **borrow** id generation, as in ν -calculus [Pitts+ '93]
 - ▶ **Purity** & **Equational theory**? Soundness by logical relations?

Unifying the Two Paradigms




Functional

High-level abstraction

Well-behaved

Safe & Predictable

Imperative



Low-level control

Well-tuned

Performative

Thank you!

