



IdentityIQ[®] Release Notes

Version: 8.5

Revised: July 2025

This document and the information contained herein is SailPoint Confidential Information

Copyright and Trademark Notices

Copyright © 2025 SailPoint Technologies, Inc. All Rights Reserved.

All logos, text, content, including underlying HTML code, designs, and graphics used and/or depicted on these written materials or in this Internet website are protected under United States and international copyright and trademark laws and treaties, and may not be used or reproduced without the prior express written permission of SailPoint Technologies, Inc.

"SailPoint Technologies" (design and word mark), "SailPoint" (design and word mark), "Identity IQ," "IdentityNow," "Identity AI," "Identity Cube," and "SailPoint Predictive Identity" are registered trademarks of SailPoint Technologies, Inc. "Identity is Everything," "The Power of Identity," "Navigate," and "Identity University" are trademarks of SailPoint Technologies, Inc. None of the foregoing marks may be used without the prior express written permission of SailPoint Technologies, Inc.

All other trademarks shown herein are owned by the respective companies or persons indicated.

SailPoint Technologies, Inc. makes no warranty of any kind regarding these materials or the information included therein, including, but not limited to, the implied warranties of merchantability and fitness for a particular purpose. SailPoint Technologies shall not be liable for errors contained herein or direct, indirect, special, incidental or consequential damages in connection with the furnishing, performance, or use of this material.

Patents Notice: <https://www.sailpoint.com/legal/patents>

Restricted Rights Legend. All rights are reserved. No part of this document may be published, distributed, reproduced, publicly displayed, used to create derivative works, or translated to another language, without the prior written consent of SailPoint Technologies. The information contained in this document is subject to change without notice.

Use, duplication or disclosure by the U.S. Government is subject to restrictions as set forth in subparagraph (c) (1) (ii) of the Rights in Technical Data and Computer Software clause at DFARS 252.227-7013 for DOD agencies, and subparagraphs (c)(1) and (c)(2) of the Commercial Computer Software Restricted Rights clause at FAR 52.227-19 for other agencies.

Regulatory/Export Compliance. The export and re-export of this software is controlled for export purposes by the U.S. Government. By accepting this software and/or documentation, licensee agrees to comply with all U.S. and foreign export laws and regulations as they relate to software and related documentation. Licensee will not export or re-export outside the United States software or documentation, whether directly or indirectly, to any Prohibited Party and will not cause, approve or otherwise intentionally facilitate others in so doing. A Prohibited Party includes: a party in a U.S. embargoed country or country the United States has named as a supporter of international terrorism; a party involved in proliferation; a party identified by the U.S. Government as a Denied Party; a party named on the U.S. Department of Commerce's Entity List in Supplement No. 4 to 15 C.F.R. § 744; a party prohibited from participation in export or re-export transactions by a U.S. Government General Order; a party listed by the U.S. Government's Office of Foreign Assets Control as ineligible to participate in transactions subject to U.S. jurisdiction; or any party that licensee knows or has reason to know has violated or plans to violate U.S. or foreign export laws or regulations. Licensee shall ensure that each of its software users complies with U.S. and foreign export laws and regulations as they relate to software and related documentation.

Contents

IdentityIQ Release Notes	1
IdentityIQ 8.5 Updates and Enhancements	1
IdentityIQ 8.5 Feature Updates	1
Important Upgrade Considerations for IdentityIQ	5
Important Upgrade Considerations for Connectors	11
Supported Platforms	15
Connectors and Integration Modules Enhancements	18
Connectivity Supported Platform and Language Updates	30
Connectivity Dropped Platform Support	31
Dropped Connector Support	31
Known Issues - IdentityIQ	32
Resolved Issues - IdentityIQ	32
Resolved Issues - Connectivity	51

IdentityIQ Release Notes

These are the release notes for SailPoint IdentityIQ 8.5

SailPoint IdentityIQ is a complete identity and access management solution that integrates governance and provisioning into a single solution leveraging a common identity repository and governance platform. Because of this approach, IdentityIQ consistently applies business and security policy and role and risk models across all identity and access-related activities - from access requests to access certifications and policy enforcement, to account provisioning and user lifecycle management. Through the use of patent-pending technologies and analytics, IdentityIQ improves security, lowers the cost of operations, and improves an organization's ability to meet compliance and provisioning demands.

This release note contains the following information:

- IdentityIQ Feature Updates
- Connectors and Integration Modules Enhancements
- Dropped Connector Support
- Important Upgrade Considerations
- Supported Platforms
- Resolved issues

IdentityIQ 8.5 Updates and Enhancements

IdentityIQ 8.5 provides new features and capabilities across the product, including Compliance Manager, Lifecycle Manager, the Governance Platform, and Connectivity. Key enhancements in the release include:

IdentityIQ 8.5 Feature Updates

IdentityIQ 8.5 introduces the following new features or enhancements.

Feature/Enhancement	Description
Access Request Approvals in Microsoft Teams	IdentityIQ customers will be able to take decisions on access request approval work items directly within Microsoft Teams – Meeting users where they are. Key Takeaways: • Approvers can make informed decisions on the go, without navigating to the Iden-

Feature/Enhancement	Description
	IdentityIQ platform—reducing the approval turnaround time. • Empower approvers to act faster by managing IdentityIQ access request approvals directly within Microsoft Teams, eliminating the need for VPN access or navigating to the IdentityIQ interface. • This unified experience is accessible on both Desktop and Mobile Microsoft Teams app and browser to significantly enhance user productivity.
Restricting View of Sensitive Identity Attributes	Restricting the display of Sensitive Attributes plays a critical role in protecting sensitive data within IdentityIQ (IIQ). With multiple users interacting with the platform, the volume of sensitive data stored in IdentityIQ continues to grow. To minimize organizational risk, access to sensitive data can be restricted in the IdentityIQ UI. Through the Identity Mappings page in Global Settings, administrators can define which user(s) can and cannot view extended attributes in the UI. This can be implemented through Match Lists, Populations, Rules, Scripts, and Filters. Implementing role-based access controls in conjunction with RSA ensures that users can perform their job functions without exposing or compromising sensitive data. Customers should note that this is applicable only to Identity extended attributes. It does not apply to standard or system-type Identity Attributes.
GenAI Descriptions for Entitlements	The GenAI Descriptions for Entitlement feature is designed to support IdentityIQ environments with large entitlement catalogs. Keeping descriptions accurate, up to date, and consistent at this scale can take a lot of time and resources. This feature is designed to make that process easier and more efficient. By leveraging GenAI, this feature helps automate the generation of meaningful entitlement descriptions, significantly reducing manual effort and improving overall data quality, system maintainability, and administrative support for managing entitlements more efficiently. This feature: • Enables users to request AI-generated entitlement description recommendations directly from within the IdentityIQ entitlement catalog, • Allows users to review AI-generated entitlement description suggestions and submit for approval or reject the suggestion.

Feature/Enhancement	Description
	Seamlessly integrates with existing customer workflows for approval of entitlement description changes.
Access Request Entitlement Recommendations	Access Request Recommendations have been expanded to include entitlements, enhancing the self-service experience with intelligent, data-driven recommendations. This improvement helps users request appropriate access more efficiently and reduces the burden on approvers by minimizing unnecessary or inappropriate requests. This feature closes the gap between role and entitlement recommendations by offering both options for self-service access requests. Recommendations eliminate guesswork by suggesting the entitlements users need to perform their job and consolidating all required access into a single request.
UI/UX enhancements	IdentityIQ 8.5 includes a range of UI/UX enhancements designed to improve usability and modernize the user experience. Key enhancements include: Improved Sunrise/Sunset Experience: Enhanced the Manage User Access page with updates designed to make navigation clearer and user experience smoother. The terms Sunrise/Sunset Dates have been renamed to Start/End dates for better clarity. Additionally, the messaging has been updated from “Remove Access” to “Remove or Change Access”, making it more intuitive for users navigating the interface when needing to change the access. Additional Filters in Manage Access Requests: Introduced the following filters: Role Owner and Access Type. Enhancements on Access Reviews: Sorting Indicators: Table columns that support sorting now display sorting indicators, helping reviewers quickly organize and prioritize information. Due Date: The access review due date is now prominently displayed at the top right, keeping reviewers aware of deadlines and supporting timely, informed decisions. Configure Classifications for Entitlement Owner Certification: Users can now configure the "Show Classifications" setting for Entitlement Owner Certifications. This added flexibility helps reviewers make more informed decisions by providing better visibility into entitlement access classifications.

Feature/Enhancement	Description
	• Modernized UI : Some of the key features in IdentityIQ have been modernized using the latest Angular 18 framework to enhance user experience and ensure compliance with accessibility standards: ◦ Access Review ◦ Application: Rapid Setup ◦ Login Page ◦ Admin Preferences ◦ API Authentication ◦ Access History
Access Review and Rapid Setup pages in Angular 18 technology	Access Review: Several functionalities have been upgraded, along with additional enhancements, including: • Column Chooser: Updated with new behavior to allow repositioning of columns in the table. • Identity Filters: Now display only the “Display Name” and “Email Address.” • Items Per Page Component: Enhanced with the following behavior: Main Page: Dropdown options include 10, 25, 50, and 100, with the default set to 25 and in Dialogs/Pop-ups: The dropdown will display the values 5, 10, 25, 50, and 100, with the default set to 5. Rapid Setup: Improved form validations, including: • Snack Bars: Display all errors across Rapid Setup pages. • Red Exclamation in a Triangle: Indicates errors within the respective tab.
Security Upgrades and Library Updates	In version 8.5, new libraries have been added, and some existing libraries have been upgraded or removed. When you upgrade, be sure to test any custom forms in your implementation, to ensure compatibility with the updated libraries. A complete list of libraries is provided in the Important Upgrade Considerations for IdentityIQ

Feature/Enhancement	Description
	IdentityIQ section below.

Important Upgrade Considerations for IdentityIQ

IdentityIQ 8.5 is a major release that contains numerous new features and capabilities across all areas of the product. A comprehensive plan should be created when upgrading that includes becoming familiar with the new features and changes, identifying use cases and how they are affected by the changes, creating a detailed strategy for migration of configuration and customizations, testing the upgrade process using data and system resources that are as close to the production environment as possible, and performing a complete deployment test cycle.

Security Upgrades

With this release, new libraries have been added, and some existing libraries have been upgraded, or removed.

Due to an increased overall industry focus on supply chain attacks and product security, SailPoint has become more aggressive in updating third party libraries contained in IdentityIQ. SailPoint has always aggressively monitored the security of all components of our products regardless of the source of the component and will continue to do so, and SailPoint has always treated security issues found in all components of our products the same following our Product Vulnerability Management Policy which defines remediation and/or mitigation timelines based on the severity of a vulnerability. It is important to note that the severity of a vulnerability in a standalone library encompasses every possible use of the library. The severity of a finding or vulnerability in IdentityIQ due to a vulnerability in a library may be different due to the use of the library in IdentityIQ.

Many updates to third party libraries are not backward compatible, both at the API and functional level. Because of this, the changes required are often not simple a replacement of the library, but also changes to the component in the product that is a consumer of the library. Sometimes, a change to IdentityIQ behavior and/or APIs to accommodate these changes is required. Given that IdentityIQ is a platform that many of our customers and deployment partners use to build identity management solutions, the impact of these types of changes can be very high and our preference based on customer demand and feedback remains to introduce library changes in releases and not in patches unless remediation for a security vulnerability is required in which case updates can be introduced in patches.

A list of libraries that have been added or upgraded in this release is provided below. These are separated into the libraries in the IdentityIQ server layer and those in the IdentityIQ connector layer. Some libraries in the connector layer are bundled into larger packages and therefore the changes are not as visible when inspecting product file names.

For connector library upgrades, see [Important Upgrade Considerations for Connectors](#).

Starting in recent IdentityIQ releases and patches, a list of the libraries embedded in a connector bundle are contained in a file named SBOM.txt at the root of the bundle jar file.

IdentityIQ should not be thought of as a collection of independently upgradeable components, but instead a complete solution supported by SailPoint as it is delivered. Customers and deployment partners should not remove, modify, or update components of IdentityIQ outside of official releases by SailPoint.

Important: When upgrading, be sure to test any custom forms in your implementation, to ensure compatibility with the updated libraries.

The 3rd-party libraries listed below are updated to newer versions as part of an ongoing commitment to improve the quality and security of the product. The impact on custom connectors, rules, or other customizations which directly or indirectly use these libraries must be validated to ensure compatibility.

The following libraries in the IdentityIQ Server layer located in WEB-INF/lib are updated:

- aspectjrt-1.9.6.jar to aspectjrt-1.9.20.1.jar
- bcel-6.5.0.jar to bcel-6.7.0.jar
- bcpg-jdk18on-172.jar to bcpg-jdk18on-1.78.1.jar
- bcpkix-jdk15on-1.70.jar to bcpkix-jdk18on-1.78.1.jar
- bcprov-jdk15on-1.70.jar to bcprov-jdk18on-1.78.1.jar
- bcutil-jdk15on-1.70.jar to bcutil-jdk18on-1.78.1.jar
- commons-fileupload-1.4.jar to commons-fileupload-1.5.jar
- ecj-3.22.0.jar to ecj-3.29.0.jar
- ehcache-3.10.0.jar to ehcache-3.10.8.jar
- guava-30.1-jre.jar to guava-32.1.2-jre.jar
- hibernate-core-5.4.27.Final.jar to hibernate-core-5.5.9.Final.jar
- hibernate-jcache-5.4.27.Final.jar to hibernate-jcache-5.6.15.Final.jar
- jackson-annotations-2.13.2.jar to jackson-annotations-2.16.0.jar
- jackson-core-2.13.2.jar to jackson-core-2.16.0.jar
- jackson-databind-2.13.2.jar to jackson-databind-2.16.0.jar

- jackson-datatype-jsr310-2.13.2.jar to jackson-datatype-jsr310-2.16.0.jar
- jackson-dataformat-yaml-2.13.2.jar to jackson-dataformat-yaml-2.16.0.jar
- jboss-logging-3.4.1.Final.jar to jboss-logging-3.5.3.Final.jar
- jakarta.json-api-2.1.0.jar to jakarta.json-api-2.1.3.jar
- java-jwt-3.19.1.jar to java-jwt-4.4.0.jar
- jaxb-impl-2.3.3.jar to jaxb-impl-4.0.4.jar
- jersey-media-multipart-2.35.jar to jersey-media-multipart-2.41.jar
- jline-3.21.0.jar to jline-3.25.0.jar
- joda-time-2.10.14.jar to joda-time-2.12.5.jar
- json-smart-2.4.8.jar to json-smart-2.4.10.jar
- jwks-rsa-0.21.1.jar to jwks-rsa-0.22.1.jar
- kotlin-stdlib-1.6.21.jar to kotlin-stdlib-1.9.23.jar
- lucene-analysis-common-8.8.2.jar to lucene-analysis-common-9.8.0.jar
- lucene-core-8.8.2.jar to lucene-core-9.8.0.jar
- lucene-queryparser-8.8.2.jar to lucene-queryparser-9.8.0.jar
- metrics-core-4.2.9.jar to metrics-core-4.2.25.jar
- mimepull-1.9.15.jar to mimepull-1.10.0.jar
- mysql-connector-java-8.0.33.jar to mysql-connector-java-8.0.40.jar
- net.tascalate.javaflow.api-2.7.1.jar to net.tascalate.javaflow.api-2.7.5.jar
- okhttp-4.9.3.jar to okhttp-4.11.0.jar
- okio-2.8.0.jar to okio-3.6.0.jar

- owasp-java-html-sanitizer-20211018.2.jar to owasp-java-html-sanitizer-20220608.1.jar
- primefaces-8.0.12.jar to primefaces-8.0.25.jar
- reactive-streams-1.0.3.jar to reactive-streams-1.0.4.jar
- rhino-runtime-1.7.12.jar to rhino-runtime-1.7.14.jar
- snakeyaml-1.30.jar to snakeyaml-2.2.jar
- spring-aop-5.2.24.RELEASE.jar to spring-aop-5.3.39.jar
- spring-beans-5.2.24.RELEASE.jar to spring-beans-5.3.39.jar
- spring-context-5.2.24.RELEASE.jar to spring-context-5.3.39.jar
- spring-context-support-5.2.24.RELEASE.jar to spring-context-support-5.3.39.jar
- spring-core-5.2.24.RELEASE.jar to spring-core-5.3.39.jar
- spring-expression-5.2.24.RELEASE.jar to spring-expression-5.3.39.jar
- spring-jdbc-5.2.24.RELEASE.jar to spring-jdbc-5.3.39.jar
- spring-jms-5.2.24.RELEASE.jar to spring-jms-5.3.39.jar
- spring-messaging-5.2.24.RELEASE.jar to spring-messaging-5.3.39.jar
- spring-orm-5.2.24.RELEASE.jar to spring-orm-5.3.39.jar
- spring-tx-5.2.24.RELEASE.jar to spring-tx-5.3.39.jar
- spring-web-5.2.24.RELEASE.jar to spring-web-5.3.39.jar
- sshj-0.31.0.jar to sshj-0.38.0.jar
- twilio-8.14.0.jar to twilio-10.1.2.jar
- xmlsec-2.3.0.jar to xmlsec-2.3.4.jar

The following JavaScript libraries in the IdentityIQ Server layer are updated:

- AngularJS updated from 1.8.0 to 1.9.9
- codemirror-4.3 updated to codemirror-5.65.16
- jQuery UI updated from 1.12.1 to 1.13.2
- moment.js updated from 2.29.1 to 2.30.1
- moment-timezone-with-data.js updated from 0.5.32 to 0.5.45

Authorization of QuickLink Target Identities Vulnerability

[SECURITY] This release contains a fix for an important security vulnerability that was previously announced. This vulnerability allows an authenticated user to perform a Lifecycle Manager flow or other QuickLink for a target user outside of the defined QuickLink Population. This vulnerability in IdentityIQ is assigned CVE-2024-2228.

As with all software vulnerabilities, we recommend that all customers apply this upgrade or the e-fix for IIQSR-867 available in the Product Download Center on Compass as soon as possible.

JavaServer Faces File Path Traversal Vulnerability

[SECURITY] This release contains a fix for an important security vulnerability that was previously announced. This vulnerability allows access to arbitrary files in the application server file system due to a path traversal vulnerability in JavaServer. Faces (JSF) 2.2.20 documented in CVE-2020-6950. The remediation for this vulnerability contained in this security fix provides additional changes to the remediation announced in May 2021 tracked by ETN IIQSAW-3585 and in January 2023 tracked by IIQFW-336. This vulnerability in IdentityIQ is assigned CVE-2024-2227, which supersedes CVE-2022-46835.

As with all software vulnerabilities, we recommend that all customers apply this upgrade or the e-fix for IIQSR-868 available in the Product Download Center on Compass as soon as possible.

Access Request for Entitlement Values with Leading/Trailing Whitespace

[SECURITY] This release contains a fix for an important security vulnerability that was previously announced. An issue exists in all supported versions of IdentityIQ Lifecycle Manager that can result if an entitlement with a value containing leading or trailing whitespace is requested by an authenticated user in an access request. This vulnerability in IdentityIQ is assigned CVE-2024-1714.

As with all software vulnerabilities, we recommend that all customers apply this upgrade or the e-fix for IIQSR-869 available in the Product Download Center on Compass as soon as possible.

Improper Access Control Vulnerability

[SECURITY] This release contains a fix for an important security vulnerability that was previously announced. This vulnerability impacts all versions of IdentityIQ and allows HTTP access to static content in the IdentityIQ application directory that should be protected. This security fix is independent of previously announced path traversal vulnerabilities for IIQSR-868, IIQFW-336, and IIQSAW-3585. This vulnerability in IdentityIQ is assigned CVE-2024-10905.

As with all software vulnerabilities, we recommend that all customers apply this upgrade or the e-fix for IIQSR-906 available in the Product Download Center on Compass as soon as possible.

Enhancements to the File Access Manager (FAM) Classification Task

The File Access Manager Classifications Aggregation task now has a new "Query Type" Argument that provides a choice between the FAM SCIM service that is used to aggregate classifications:

1. The legacy API that aggregates classifications via FAM Permissions
2. A new, more efficient API that aggregates classifications via FAM Groups

NOTE: Requires these FAM Service Packs or later: 8.4 SP3, 8.3 SP7

A new **Query Type** field in the File Access Manager Classification task allows you to select which File Access Manager SCIM service to use to aggregate classifications. The Query Type options are:

- **Permissions:** uses the legacy API that aggregates classifications via File Access Manager Permissions.
- **Groups:** uses a new, more efficient API that aggregates classifications via File Access Manager Groups

Refer to [File Access Manager Classification](#) for more information.

Remove ActiveMQ dependency

Access History and Data Extract are no longer dependent on the ActiveMQ message broker. This applies to both embedded and external ActiveMQ configurations. Refer to this document on Compass for further details: [Removal of ActiveMQ dependency](#)

Support Hosted PostgreSQL - AWS RDS/AWS Aurora/Azure

PostgreSQL is now supported as a hosted database for IdentityIQ on the following cloud platforms: AWS RDS, AWS Aurora, Microsoft Azure.

Update UI for Identity Cube to include Trademark and show Trademark in PDF & CSV File downloads

The TM (trademark) symbol is now included for Identity Cube™ in the IdentityIQ product user interface and reports. This minor update currently only applies to the English language.

Rename AI Services

AI Services has been rebranded to AI-Driven Identity Security in the IdentityIQ user interface.

Support for RECYCLE_FACADES Setting in Tomcat

The Java system property `org.apache.catalina.connector.RECYCLE_FACADES` set to **true** is now supported to utilize enhanced security settings on Tomcat, preventing the UI errors generated in earlier IdentityIQ versions. This setting is not required but is the default in Tomcat 9.0.90 and later, and it may be optionally set for Tomcat 9.0.89 and earlier. Refer to Tomcat documentation for more information.

CLOB Data Fix for PostgreSQL Repositories

For installations which use a PostgreSQL database as the IdentityIQ repository, the dialect specified in `iiq.properties` must be updated to use the new SailPoint-specific PostgreSQL dialect to resolve a potential Character Large Object (CLOB) data corruption issue. This requires changing the dialect from `org.hibernate.dialect.PostgreSQL10Dialect` to `sailpoint.persistence.PostgreSQL10Dialect`.

The upgrade DDL script for PostgreSQL will copy and convert the CLOB data into the original text field that had previously held the OID value of the large object. If errors occur during this process, the queries can be modified to end with `LIKE <column_name>='1%'`; to filter out already-converted values that would prevent the update from completing. Once this is complete, it is safe to run the `vacuumlo` utility on the database to remove the no-longer needed CLOB data. Binary Large Object (BLOB) data remains unaffected.

Important Upgrade Considerations for Connectors

General Updates for Connectors

- The IQService version must match the IdentityIQ server version including the major release and patch versions. When one is upgraded, the other must be upgraded as well so that the version and patch levels match. For more information on upgrading the IQService, see the IdentityIQ Installation Guide's chapter on upgrading.
- If you are leveraging IQService before and after scripts, you must configure the TLS along with the client authentication for IQService to continue execution of these scripts. Before upgrading IQService in your environment, ensure you have completed the necessary prerequisites for TLS and client authentication

configuration.

- Atlassian Suite - Cloud connector
 - To leverage feature to be able to enable or disable accounts with applications created prior to this update -
 - Edit the application xml. Search for following text - featuresString="PROVISIONING, SYNC_PROVISIONING, SEARCH, DIRECT_PERMISSIONS"
 - Update this text to the below - featuresString="PROVISIONING, SYNC_PROVISIONING, SEARCH, DIRECT_PERMISSIONS, ENABLE"
 - Save the application.
- For Mainframe connectors, SailPoint no longer supports DES and 3DES encryption, so existing integrations using DES or 3DES will no longer function. Instead, SailPoint recommends using TLS encryption to secure communication between Mainframe integration components.
- The Oracle NetSuite connector will exclusively support WSDL v2023 with Token-Based Authentication (TBA) for any new application configured. Support for basic authentication and pass-through authentication will no longer be available for any new application configured after this release. For existing applications of the Oracle NetSuite connector configured using WSDL v2019, support will continue until the end of 2024. However, starting in 2025, only the latest version of WSDL (v2023) and TBA authentication will be supported.
- The 3rd-party libraries listed below are updated to newer versions as part of an ongoing commitment to improve the quality and security of the product. The impact on custom connectors, rules, or other customizations which directly or indirectly use these libraries must be validated to ensure compatibility.

Note: All Third party Jar upgrades files are available in SBOM.txt artifacts present in each FAT jars. SBOM.txt file contained information related to third party jars along with their dependencies.

Connector Security Upgrades

With this release, new libraries have been added, and some existing libraries have been upgraded, or removed. The following is a list of the current libraries:

- connector-bundle-collaboration-connectors
 - accessors-smart-1.2.jar to accessors-smart-2.4.8.jar

- commons-httpclient-3.1/commons-httpclient.jar (removed)
- json-20230227.jar to json-20231013.jar
- libcommons-codec-java-1.11 to libcommons-codec-java-1.17.1
- connector-bundle-common
 - aws-java-sdk-bom 1.12.22 to aws-java-sdk-bom 1.12.764
 - axis2-1.7.8/wstx-asl-3.2.9.jar to woodstox-core-7.1.0.jar
 - bcprov-jdk18on.1.77 to bcprov-jdk18on.1.78.1
 - com.hierynomus:sshj 0.37.0 to com.hierynomus:sshj 0.38.0
 - jose4j-0.9.3.jar to jose4j-0.9.6.jar
 - json-path-2.2.0.jar to json-path-2.9.0.jar
 - json-smart-2.4.7.jar to json-smart-2.4.10.jar
 - sshj-0.34.0.jar to sshj-0.38.0.jar
- connector-bundle-directories
 - joda-time-2.9.jar to joda-time-2.12.7.jar
 - accessors-smart-1.2.jar to accessors-smart-2.4.8.jar
- connector-bundle-filebased
 - accessors-smart-1.2.jar to accessors-smart-2.4.8.jar
 - bcprov-jdk18on.1.77 to bcprov-jdk18on.1.78.1
 - bcpkix-jdk18on-1.77.jar to bcpkix-jdk18on-1.78.1
 - libcommons-codec-java-1.11 to libcommons-codec-java-1.17.1
- connector-bundle-healthcare-epic
 - xmlsec.2.1.4 jar to xmlsec.2.3.4 jar

- connector-bundle-hrms-oraclefusionhcm
 - accessors-smart-1.2.jar to accessors-smart-2.4.8.jar
 - axis2-1.7.8 to axis2-1.8.2
- connector-bundle-jdbc
 - accessors-smart-1.2.jar to accessors-smart-2.4.8.jar
 - mysql-connector-j-8.0.33 to mysql-connector-j-9.0.0.jar
- connector-bundle-mainframe
 - accessors-smart-1.2.jar to accessors-smart-2.4.8.jar
- connector-bundle-misc
 - accessors-smart-1.2.jar to accessors-smart-2.4.8.jar
 - libcommons-codec-java-1.11 to libcommons-codec-java-1.17.1
 - JT400 library version 8.1 to JT400 library version 20.0.7
- connector-bundle-openconnector
 - bcprov-jdk18on-1.77 to bcprov-jdk18on-1.78.1
 - bcutil-jdk18on-1.77 to bcutil-jdk18on-1.78.1
 - bcpkix-jdk18on-1.77.jar to bcpkix-jdk18on-1.78.1
- connector-bundle-sap-on-prem
 - libcommons-codec-java-1.11 to libcommons-codec-java-1.17.1
- connector-bundle-webservices
 - accessors-smart-1.2.jar to accessors-smart-2.4.8.jar
 - kotlin-stdlib-1.4.10.jar to kotlin-stdlib-1.7.10.jar
 - libcommons-codec-java-1.11 to libcommons-codec-java-1.17.1

- okhttp-4.9.3.jar to okhttp-4.12.0.jar
- okio-2.8.0.jar to okio-3.7.0.jar
- spring-aop-5.2.24.RELEASE.jar to spring-aop-5.3.39.jar
- spring-beans-5.2.24.RELEASE.jar to spring-beans-5.3.39.jar
- spring-context-5.2.24.RELEASE.jar to spring-context-5.3.39.jar
- spring-context-support-5.2.24.RELEASE.jar to spring-context-support-5.3.39.jar
- spring-core-5.2.24.RELEASE.jar to spring-core-5.3.39.jar
- spring-expression-5.2.24.RELEASE.jar to spring-expression-5.3.39.jar
- spring-tx-5.2.24.RELEASE.jar to spring-tx-5.3.39.jar
- spring-web-5.2.24.RELEASE.jar to spring-web-5.3.39.jar
- connector-bundle-unix
 - accessors-smart-1.2.jar to accessors-smart-2.4.8.jar
 - sshj-0.34.0.jar updated to sshj-0.37.0.jar

Supported Platforms

IMPORTANT: SailPoint does not support anything beyond the compatibility of the platform vendors. Confirm the interoperability and support from those vendors when deciding on your platforms.

Operating Systems

- Windows Server 2025 and 2022
- Solaris 11.4 and 10
- IBM AIX 7.3 and 7.2

Note regarding **Linux Support:** The distributions and versions of Linux highlighted below have been verified by IdentityIQ Engineering, but any currently available and supported distributions

and versions of Linux will be supported by SailPoint. Implementers and customers should verify that the distribution and version of Linux of choice is compatible with the application server, database server, and JDK also being used.

- Red Hat Linux 9.5 and 8.10
- Oracle Linux 9.5 and 8.10
- SUSE Linux 15.6 and 12.5

Application Servers

- Apache Tomcat 9.0
- Oracle WebLogic 14c
- JBoss Enterprise 7.4
- IBM WebSphere Liberty 25.0 and 24.0

Databases (On Site)

- MySQL 8.4 and 8.0
- MS SQL Server 2022 and 2019
- Oracle 19c
- PostgreSQL 17 and 16

Cloud Platforms

- AWS EC2
- AWS Aurora
- AWS RDS (MySQL, MS SQL, Oracle)
- Azure (VM, Azure SQL)
- Google Cloud Platform – Google Compute Engine

Java Platform

- Oracle JDK 17
- OpenJDK 21 and 17 is now supported on all environments
- Eclipse Temurin JDK 17
- IBM Semeru 21 and 17

Browsers

- Google Chrome Latest Version
- Microsoft Edge Latest Version
- Safari Latest Version
- Firefox Latest Version

Mobile User Interface OS / Browser Support

- Android with Chrome latest version
- iOS with Safari latest version

Languages

- Brazilian Portuguese
- Chinese (Taiwan)
- Danish
- Dutch
- English
- Finnish
- French
- French Canadian

- German
- Hungarian
- Italian
- Japanese
- Korean
- Norwegian
- Polish
- Portuguese
- Simplified Chinese
- Spanish
- Swedish
- Traditional Chinese
- Turkish

Connectors and Integration Modules Enhancements

IdentityIQ 8.5 provides various enhancements in the following connectors and integration modules.

New Connectors

IdentityIQ 8.5 delivers new, out-of-the-box connectors for the following enterprise applications, which simplifies the connectivity of these systems.

New Connectors	Description
Atlassian Data Center Connector	SailPoint announces the SailPoint Atlassian Data Center connector, which securely connects to the Atlassian Data Center and provides governance capabilities for users and groups.
AWS IAM Identity Center	The SailPoint integration with AWS IAM Identity Center enables centralizes user access management for multiple AWS accounts. It integrates seamlessly with various AWS Identity Center, enabling streamlined provisioning and management of user accounts within the IAM Identity Center's identity store.

New Connectors	Description
HealthStream CredentialStream Connector	SailPoint announces the HealthStream CredentialStream connector, which connects to the HealthStream CredentialStream system and extends a deep level of management to provider data along with facilities, specialties, and credential/license information.
Microsoft Azure DevOps Connector	SailPoint is pleased to announce the availability of the new Azure DevOps connector. The SailPoint Azure DevOps connector securely connects with the Microsoft DevOps services and provides governance capabilities for the users and manages groups as entitlements. For more information, refer to the Integrating SailPoint with Azure DevOps connector guide.
Non-Employee Risk Management (NERM) Connector	SailPoint is pleased to announce the availability of the new Non-Employee Risk Management (NERM) connector. This connector facilitates the integration between Non-Employee Risk Management (NERM) and IdentityIQ (IdentityIQ) to effectively manage non-employee profiles and their associated assignments. It consolidates profiles, correlates accounts, and access, establishing NERM as the authoritative source of identity data within IdentityIQ.
SAP Commerce Cloud (Hybris) (IPS Proxy)	The SAP Commerce Cloud integration offers access management of SAP Commerce "Employees" type users, group entitlements, and rich attribute collection as supported by SAP.
SailPoint SAP Cloud Identity Access Governance (IAG)	The SailPoint SAP Cloud Identity Access Governance (IAG) integration enhances the management of user access and compliance within SAP systems. It allows customers to leverage SailPoint as a central hub for initiating access requests across their SAP landscape, including SAP IAG, ultimately streamlining the request process and strengthening governance.
SAP Integrated Business Planning (IBP)	SailPoint's integration with SAP Integrated Business Planning (IBP) enhances security and compliance for businesses using IBP by simplifying the management of user identities and entitlements, including roles, catalog IDs associated with roles, and groups. It also automates user onboarding, movement, and offboarding processes to ensure compliance with security requirements.
SAP Analytics Cloud Integration	SailPoint's SAP Analytics Cloud integration provides a comprehensive SAP Cloud integration that enables businesses to significantly improve security and compliance within SAP Analytics Cloud. This integration facilitates streamlined governance of user identities, entitlements such as roles and groups, and the automation of JML workflows and compliance requirements.
SAP Ariba Integration	SailPoint's SAP Ariba integration provides a comprehensive SAP Cloud integration that enables businesses to significantly improve security and compliance within SAP Ariba procurement and sourcing processes. This integration facilitates streamlined governance of user identities, entitlements such as roles and groups, and the automation of JML workflows for security and compliance requirements across Ariba Parent and Child Realms.
SAP BTP Cockpit Cloud Foundry Connector	The SailPoint SAP BTP Cockpit Cloud Foundry connector enhances security and compliance for SAP BTP applications and services by effectively managing user access and entitlements (role collections) across BTP Global Accounts, Directories, and Sub Accounts.

New Connectors	Description
SAP Identity Directory Connector	The SailPoint SAP Identity Directory connector aligns with SAP's reference architecture and empowers businesses to elevate security and compliance measures for applications integrated with SAP Cloud Identity Services (CIS). By leveraging centralized governance capabilities, this integration streamlines the management of user identities and entitlements (groups), ensuring that stringent security and compliance requirements are met across all SAP Cloud applications linked to SAP CIS.
SailPoint Guidewire BillingCenter Connector	SailPoint announces the SailPoint Guidewire BillingCenter connector, which provides governance capabilities for the Guidewire BillingCenter system users. Its capabilities include aggregation, provisioning users, and adding or removing entitlements at the account level.
SailPoint Guidewire ClaimCenter Connector	SailPoint announces the SailPoint Guidewire ClaimCenter connector, which provides governance capabilities for the Guidewire ClaimCenter system users. Its capabilities include aggregation, provisioning users, and adding or removing entitlements at the account level.
SailPoint Guidewire ContactManager Connector	SailPoint announces the SailPoint Guidewire ContactManager connector, which provides governance capabilities for the Guidewire ContactManager system users. Its capabilities include aggregation, provisioning users, and adding or removing entitlements at the account level.
SailPoint Guidewire PolicyCenter Connector	SailPoint announces the SailPoint Guidewire PolicyCenter connector, which provides governance capabilities for the Guidewire PolicyCenter system users. Its capabilities include aggregation, provisioning users, and adding or removing entitlements at the account level.
SuccessFactor LMS Connector	SuccessFactor LMS connector is released which can integrate SailPoint IdentityIQ with SAP SuccessFactors Learning Management Systems to aggregate and provision user training information for user access governance.
UKG Pro Core HCM Connector	UKG Pro Core HCM connector will provide the capability for seamless and secure connection to UKG Pro Core HCM Module which will be used as an authoritative source and act as a source of employee records. The UKG Pro Core HCM connector now supports update operations for employee records, and it can now aggregate employment detail attributes for employees.
Webex Control Hub Connector	SailPoint is pleased to announce the availability of the new WebEx Control Hub connector. The SailPoint Webex Control Hub connector provides governance capabilities for the users of the Webex Control Hub. Capabilities include aggregation, provisioning users, and adding or removing entitlements at the account level. For more information please refer to Integrating SailPoint with Webex Control Hub.

New Connectors	Description
Workday Students Connector	The SailPoint Workday Students connector is now available to help manage student identities by retrieving relevant data for identity governance and access management.
Workiva Connector	SailPoint announces the SailPoint Workiva connector, which securely connects with the Workiva system and provides governance capabilities for the Workiva users.

Atlassian Cloud Jira Service Management

- The Atlassian Cloud Jira Service Management now supports the Access Request comment on the Jira tickets.

Atlassian Data Center Connector

- The Atlassian Data Center connector now supports Personal Access Token (PAT) authentication for the service account configured on the application.
- In absence of Atlassian APIs to read all accounts, connector now supports reading accounts from file exported from the end system for Atlassian Data Center 10.x
- Atlassian Data Center connector now supports auto refresh of the tokens when PAT is set as the authentication type.

Atlassian Data Center for Service Desk Integration

- The Atlassian Data Center for Service Desk Integration now supports Personal Access Token as an authentication method.

Atlassian Server Jira Service Management

- The Atlassian Server Jira Service Management now supports the Access Request comment on the Jira tickets.

Atlassian Suite - Cloud Connector

- The SailPoint Connector for Atlassian Suite - Cloud now supports Enable and Disable account operations. Refer to the documentation for additional configurations required to use this feature. For leveraging this feature with already created applications, refer to Upgrade Consideration section.

AWS Connector

- The AWS Connector will now require IdentityIQ Cloud Governance license to enable cloud governance features. Refer to IdentityIQ documentation for more information.

Box Connector

- The Box connector can now aggregate and provision tracking codes as additional attributes in the account schema.

Cloud Gateway

- The Cloud Gateway is now shipped with secure tomcat release Apache Tomcat 9.0.104

Coupa Connector

- The Coupa connector now supports the invoicing-user attribute, which indicates whether a user has an invoicing license. For more information, refer to the connector guide.

Duo Connector

- The Duo connector can now aggregate more than 4 aliases of an account when an account aggregation is performed.
- The Duo Connector is now able to grant specific Administrative Units to Duo administrators.

Dynamic 365 Finance and Operation Connector

- Dynamic 365 Finance and operation connector now support creation of account

Epic SER Connector

- The Epic SER connector is enhanced to aggregate multi-valued attributes.

Google Workspace Connector

- The Google Workspace (formerly G Suite) connector can now aggregate tags and labels for configured projects.

Ivanti Cherwell Connector

- The IdentityIQ for Ivanti Cherwell Service Desk Integration now populates the Access Request comment in the Ticket.

IQService

- It is now mandatory to configure the TLS and client authentication in order to further enhance the security posture of IQService, especially If you are leveraging IQService before and after scripts.
- IQService now supports native PowerShell scripts with version 5.1 and later.
- IQService now supports -m parameter to store x509 subject and serial number to look for the best match in case of multiple certificates present in IQService personal certificate store.
- SailPoint Integration Service (IQService) now supports communicating over Internet Protocol version 6 (IPv6).

Linux Connector

- The Linux Connector Red Hat Enterprise Linux (RHEL) 9 deprecated SCP support.
- SailPoint recommends using sudo users to connect to your Linux systems.

Mainframe Connectors

- The Mainframe IBM RACF, Mainframe ACF2, and Mainframe Top Secret connectors are enhanced to read the 'prependBeforeVal' or 'appendAfterVal' attribute from the attributes map of AttributeRequest in the provisioning plan. It will then prefix/append it to the value of the attribute before passing it to the SailPoint connectors for Mainframe ACF2, RACF, and Top Secret. This allows the pre/post scripts to access meta data of the provisioning request for each attribute.

Microsoft Active Directory Connector

- The Microsoft Active Directory connector now supports gMSA as a Service Account using Simple Authentication and Security Layer (SASL) protocol.
- Exchange management operations with the Active Directory Connector will work with Exchange Server where certificate signing of PowerShell serialization payload is enabled. Please refer [Certificate signing of PowerShell serialization payload in Exchange Server - Microsoft Support](#) for more information about this feature by Microsoft.

Microsoft Entra ID Connector

- Microsoft Entra ID is the new name for the Azure Active Directory Connector. When configuring a new connector, it will still be displayed as Azure Active Directory in the application type list. This is a rebranding effort and Connector functionality will remain the same. For more information, refer to https://documentation.sailpoint.com/connectors/identityiq/microsoft/azure_ad/help/integrating_azure_active_directory/introduction.html.
- The Microsoft Entra ID Connector (Azure Active Directory Connector) has now improved the delta aggregation performance
- The Microsoft Entra ID (Formerly Azure Active Directory) connector now supports the management of Organizational Mail Contacts as accounts.
- The Microsoft Entra ID (Formerly Azure Active Directory) connector has been enhanced so that Azure Active Directory B2C tenants now support the Add, Set, and Remove operations for the userIdentities and signInNames attributes of social and local user accounts during the Modify and Update provisioning operations.
- The Microsoft Entra ID (Formerly Azure Active Directory) Connector now supports sending customized message in the Invitation Email for B2B Guest User.
- The Microsoft Entra ID connector ((formerly, Azure Active Directory) now supports Azure extension attributes and Directory (Entra ID) extension attributes, which store the custom attribute information coming through Active Directory (i.e. onPremisesExtensionAttribute). It also supports update operation for multivalued extension attribute.
- The Microsoft Entra ID connector now supports creation of Service Principals for already existing Applications (Local / Multi Tenant Type).
- The Microsoft Entra ID connector now supports creating SAML based application and corresponding Service Principal using the Gallery application templates.
- The Microsoft Entra ID connector now supports managing Administrative Units as entitlements. For more information, refer to Administrative Units section in [connector guide](#).
- The Microsoft Entra ID connector now supports managing custom security attributes for Microsoft Entra ID users. For more information, refer to [Custom Security Attributes](#).
- The Microsoft Entra ID connector now supports applying group membership filters during account aggregation for memberships belonging to the group object type. For more information, refer to [Aggregation, Filter, and Partitioning Settings](#).

- The Microsoft Entra ID connector now supports aggregating risk related information for Service Principals accounts.
- The Microsoft Entra ID connector now supports reading LastSuccessfulSignInDateTime sign in activity information for the users.

Microsoft SQL Server Connector

- The Microsoft SQL Server connector can now aggregate service accounts which are connected to login users when an aggregation is performed.
- MS SQL Server Connector is now certified to utilize Windows gMSA as the service account while configuring MS SQL applications.
- The MS SQL Server connector will be able to aggregate the Windows AD groups created on the MS SQL server.

Okta connector

- The SailPoint Okta Connector will no longer encode the special character "?", "=", and "&" in the API request

Oracle ERP Siebel Connector

- The Oracle ERP Siebel connector now supports aggregation of responsibilities, and assigns the Dummy Primary Position ID to the user (leaver use case).
- The Sailpoint Oracle ERP Siebel connector now supports Siebel CRM v24.x

Oracle HCM Cloud Connector

- Oracle HCM Cloud connector is now enhanced to support encrypted files along with existing encrypted and signed supported files.
- The Oracle HCM Cloud connector will no longer utilize Worker API during Delta aggregation.
- Oracle HCM Cloud Connector now supports update of username and work email.

Oracle HRMS Connector

- The Oracle HRMS connector now has the capability to aggregate inactive users when an account aggregation is performed.

Oracle PeopleSoft HCM Connector

- The Oracle PeopleSoft HCM connector now has the ability to exclude Inactive Users when an account aggregation is performed.

Oracle NetSuite ERP Connector

- The SailPoint Oracle NetSuite connector now enhanced to support WSDL v2023 with Token-Based Authentication (TBA). Please note that support for basic authentication and pass-through authentication will no longer be available for any new application configured after this release.
- The Oracle NetSuite ERP Connector now supports aggregation and provisioning of location attribute.

SAP Ariba Integration

- The SAP Ariba integration now supports SCIM-based aggregation for high data volumes and adds enhancements for supporting Purchasing Unit ID support.

SAP Concur Connector

- The SAP Concur connector has been enhanced to support "Test Employees" and "BI Managers" attributes.

SAP Direct Connector

- The SAP Direct connector has been enhanced to provide more efficient management of SAP Licenses by utilizing the License ID instead of relying solely on the description field. This enhancement is particularly advantageous for SAP systems that offer multiple client language support.
- The SAP Direct Connector has been improved to handle indirect roles by leveraging SAP HR Organization data. This upgraded connector is capable of consolidating Organization Data associated with SAP employees, such as their position, job, or organization unit.
- SAP Direct connector customers now have the ability to differentiate between TCodes added through menu, TCodes added directly, and other menu items. This enhancement is made possible by the introduction of three new attributes in the role schema, and provides users with greater flexibility and control over their SAP Direct connector experience.

SAP GRC Connector

- The SAP GRC connector has been enhanced to support user IDs with mixed-case and special characters, along with the support for custom delimiter characters, making it even more resilient and adaptable to a wide

range of customer use cases.

- The SAP GRC Connector is undergoing expansion to encompass non-ABAP SAP systems. In this latest release, we have achieved full compatibility between SAP GRC integration and SAP Enterprise Portal.
- The SAP GRC Connector has been enhanced and is fully compatible with another non-ABAP system - SAP Process Orchestration.
- The integration of SAP GRC now provides enhanced visibility by displaying the actual requester details for associated tickets. This valuable enhancement equips approvers with comprehensive context and specific information regarding the request's purpose and origin. Consequently, this improvement streamlines the approval process, empowering approvers to make more informed and efficient decisions.
- The SAP GRC connector now offers enhanced functionality for modifying attributes associated with a user during the disable operation. This critical enhancement allows Account Disable requests to be distinguished between inactive users (leavers) and active users (leave of absence). The upgrade also ensures a seamless clean exit process by facilitating the removal of:
 - User roles
 - Configuring specific user groups during the disable operation
 - Setting a user's end date
 - Selectively disabling the account on specified systems

In addition to streamlining the account management process, these advanced features provide greater flexibility and precision in handling different scenarios; ultimately enhancing the overall user experience and administrative control within the SAP GRC system.

- SailPoint's SAP GRC Integration now supports Access Management Requests that are configured for Auto-Approval in the SAP GRC system.
- As a result of the table and sync job changes in SAP GRC12 SP19 and above, the *Disable only master system* feature in the SAP GRC connector source configuration is being deprecated. It is recommended that customers utilize the *Disable All Systems Connected to SAP GRC* feature for account deprovisioning instead.
- The SAP GRC integration has been improved to exclude certain systems linked to GRC from user aggregation, provisioning, and attribute update operations.
- SailPoint's SAP GRC integration now includes seamless integration with SAP ARA Service, enabling robust SOD Checks and Risk Analysis through GRC. This enhancement allows managers in IdentityIQ to view and

address potential risks before submitting provisioning requests. Identified risks are displayed as Policy Violations, empowering managers to take proactive measures or engage with relevant stakeholders such as Requesters, Role Owners, and Risk Owners.

- The SailPoint SAP GRC integration for SAP GRC has been enhanced to integrate with SAP IAG. The configuration helps customers to request user and entitlement provisioning, remove user access, and perform risk analysis of user requests in IAG for connected SAP cloud systems using the SAP GRC system as a bridge.

SAP HANA Database Connector

- The SAP HANA Database Connector now supports multiple SAML (Security Assertion Markup Language) Providers for aggregation and provisioning operations.

SAP HR/HCM Connector

- SAP HR/HCM connector is now enhanced to configure with load balancer parameters when SAP system is configured with load balancer at customer end.

SAP S/4 HANA Public Cloud Connector

- The integration of S/4HANA Public Cloud has been enhanced to support the creation of business users, enable API-based aggregation of roles, and manage attributes for these users. This enhancement empowers our customers to fully leverage the integration for seamless user lifecycle management, entitlement management, and effective CRUD (Create, Read, Update, Delete) operations.

Salesforce Connector

- The Salesforce connector now supports "DelegateGroup" as a group object.
- The Salesforce connector now supports role hierarchy representation (parent and child) for the role entitlement object.

ServiceNow Identity Governance Connector

- The ServiceNow Identity Governance connector now supports OKTA OAuth 2.0 with the Client Credentials grant type, in addition to the Refresh Token grant type. For more information, refer to [OAuth 2.0 Authentication](#).

ServiceNow Service Desk Integration Module

- The ticket resolution comments (close_notes) from ServiceNow will now be provided on Identity Request.

SuccessFactors Connector

- The SuccessFactors connector is now enhanced with write-back abilities for SuccessFactor and ODATA attributes.
- SAP SuccessFactors connector now provides users with the option to configure a time zone for aggregation and provisioning operations.
- The SuccessFactors connector can now aggregate labels linked to codes for additional attributes. The codes used to aggregate the labels must be associated with picklists or foundation objects from the source which relate to the additional attributes. For more information, refer to [Advanced Settings](#).

UKG Pro Core HCM Connector

- The UKG Pro Core HCM connector can now aggregate Platform Config fields associated with various classes during full and delta aggregation.

Windows Local Connector

- The Windows Local Connector now supports adding and removing entitlements for Non-local (domain) users.

Workday Connector

- The Workday connector is now enhanced to support the Pre-Hire record
- The Workday Connector is now enhanced to fetch the latest terminated record in case of multiple terminated records associated with workers under Oauth2 mode.

Workday Accounts Connector

- The Workday Accounts Connector can now be configured to exclude inherited Organization roles associated with the accounts during account aggregation.
- The Workday Accounts connector supports implementer accounts.
- The Workday Accounts connector is now enhanced to aggregate integration user accounts.
- Workday Accounts connector is now enhanced to support the aggregation of extended enterprise learner accounts.
- The Workday Accounts connector will now support the aggregation of Organization Role as a group Object.

- The Workday accounts connector now aggregates the associated security groups with Workday account. It also aggregates the details as an entitlement object. For more information, refer to [OAuth 2.0 Authentication](#), [Account Attributes](#), and [Group Attributes](#).
- The Workday Accounts connector is now enhanced to support the aggregating custom fields for OrganizationRole Group. For more information, refer to [Configuration to Fetch the Custom Attributes for OrganizationRole Group](#).
- The Workday Accounts connector now supports managing Student Accounts.

Workiva Connector

- The Workiva connector now supports Group Filter which can be used to filter groups during Group aggregation.

Zendesk Connector

- The Zendesk connector now supports the “Bearer Token” authentication type.

Zendesk for Service Desk Integration

- The Zendesk for Service Desk Integration now supports the “Bearer” authentication type.

Connectivity Supported Platform and Language Updates

Connector/Component	New Platform Version
ACF2 Full Connector	The ACF2-Full connector now supports z/OS 3.1
IBMi Connector	The Sailpoint IBM i Connector is now certified with IBM i V7R5 system.
HCL Domino Connector	The HCL Domino connector now supports HCL Domino version 14.0.
Linux Connector	• The SailPoint Linux Connector is now certified with Red Hat Enterprise Linux 9.2 • The SailPoint Linux Connector is now certified with Ubuntu version 22.04.
RACF-Full Connector	RACF-Full connector now supports z/OS 3.1
RACF LDAP Connector	The RACF LDAP connector now supports z/OS 3.1.
Oracle Database Connector	The Oracle Database connector now offers support for version 23ai.
Oracle EBS Connector	SailPoint Oracle EBS connector now supports Oracle E-Business Suite (EBS) version 12.2.12.
Oracle PeopleSoft ERP Connector	The SailPoint's Oracle PeopleSoft ERP connector now supports PeopleSoft ERP version 8.61

Connector/Component	New Platform Version
SAP Direct Connector	- The SAP Direct connector is now tested and certified with the SAP ERP Enhancement Package 8 (EHP) for continuous support and seamless integration. - The SAP Direct connector now supports SAP S/4HANA 2022 On-Prem SP/FP Stack 04. - The SAP Direct connector now supports SAP S/4HANA 2023 On-Prem SP/FP Stack 02.
SAP GRC Connector	The SAP GRC connector now supports SAP GRC Access Control 12.0 SP26.
SAP Portal Connector	The SAP Portal Integration is certified with NetWeaver 7.5 SP 28 for maintaining SailPoint's commitment to business continuity and customer support.
SAP Hana DB Connector	Supports SAP HANA 2.0 SPS8 version
SAP HR/HCM Connector	- The SAP HR/HCM connector is now certified with SAP S4Hana 2022 version. - The SAP HR/HCM connector now supports the SAP S/4 HANA 2023 on-premise version. - The SAP HR/HCM connector now supports SAP Enterprise Central Component (ECC) 6.0 with Enhancement Package 8 (EHP8).
Salesforce Connector	Salesforce connector now supports salesforce API version 59.
Top Secret - Full Connector	The Top Secret connector now supports z/OS 3.1

Connectivity Dropped Platform Support

Connector/Integration Module	Dropped Platforms
Microsoft Active Directory Connector	- Microsoft Exchange Server 2013 - Microsoft Lync Server 2013
BMC Helix ITSM Service Desk Integration	BMC Helix ITSM 20.02

Dropped Connector Support

End of Life: The following connectors and connector components are no longer supported:

- Atlassian Suite - Server connector
 - Atlassian has announced the end of support for the Atlassian Server scheduled for February 15, 2024. For more information about the SailPoint deprecation policies and support for deprecated connectors, refer to [SailPoint Support Policy for Connectivity](#).

For more information about the Atlassian announcement, refer to [Atlassian End of Support Policy | Atlassian Support | Atlassian Documentation](#)
- The Atlassian Server Jira Service Desk Integration is now deprecated as Atlassian has announced the end of support for the Atlassian Server scheduled for February 15, 2024. For more information about the SailPoint deprecation policies and support for deprecated connectors, refer to [SailPoint Support Policy for Connectivity](#).
- The VMS Connector is now deprecated. For more information about the SailPoint deprecation policies and support for deprecated connectors, refer to [SailPoint Support Policy for Connectivity](#).

Known Issues - IdentityIQ

Issue ID	Description
IIQETN-11203	When an assigned role that has been added by an assignment rule is removed from an identity through a revoke or remove action, Access History will not recognize that there is a negative assignment. As a result, role removal events are not created consistently and some data and counts may be incorrect.
IIQETN-11209	In the Access History feature, if any of the roleAssignments for an identity capture are set to <code>negative="true"</code> , then the counts shown in the UI for Roles and Entitlements may be inaccurate.

Resolved Issues - IdentityIQ

Issue ID	Description
IIQCB-5673	The AccessHistory database configuration now supports specifying a JNDI datasource.
IIQCB-5709	Newly added advanced search filters in the Certification Campaign Results page now automatically gain focus, streamlining the filtering process by allowing users to press Enter to apply filters and display results.
IIQCB-5710	Enhanced the user interface of the Manage Accounts page. The footer, page size dropdown, and paging elements now appear in their intended positions, ensuring full functionality and improved usability.
IIQCB-5906	[SECURITY] The jQuery UI library is updated from version 1.12.1 to 1.13.2

Issue ID	Description
	to mitigate a Cross-site Scripting (XSS) vulnerability.
IIQCB-6066	[SECURITY] The PrimeFaces library used in the IdentityIQ user interface is updated from version 8.0.12 to 8.0.25. This update helps enhance the security by preventing potential Cross-site Scripting (XSS) attacks through the user interface.
IIQCB-6315	Resolved an Unauthorized Access exception that previously prompted users for login credentials when attempting to access dropdown menus on the Manage User Access page.
IIQCB-6794	[SECURITY] Resolved a cross-site scripting (XSS) vulnerability in the Setup > Groups > Workgroups tab, preventing malicious JavaScript code injection when creating or editing a Workgroup name.
IIQETN-9177	Backslash characters in passwords no longer cause authentication errors in JLine via the IIQ Console.
IIQFW-1514	The keyboard focus is now visible on the “Select Template” and “Select Application” fields in the Rapid Setup wizard, improving accessibility without changing functionality.
IIQFW-3243	In Rapid Setup, for an application which has more than one entitlement defined, an Entitlement Exception filter can now be added in the Leaver form for any or all entitlements.
IIQKAP-1124	Pager buttons now respond to both ENTER and SPACE keys during keyboard navigation, providing a more inclusive user experience in line with WCAG 2.1 requirements.
IIQKAP-1130	Improved screen reader and keyboard navigation for the Work Item Details page through the addition of ARIA attributes and heading roles to work item titles.
IIQKAP-1143	Access Request page now retains focus in the filter panel after filter removal.
IIQKAP-1181	The user name menu ARIA label has been enhanced to indicate it is a menu item with a submenu containing Logout and User Preferences options. The label now includes specific keyboard instructions to access and navigate the submenu, consistent with other top navigation menu items.
IIQMAG-4829	When refreshing the Data Extract configuration cache, only related tasks are scanned for updates instead of all tasks within the system.
IIQMAG-5069	In the Access History view profile, attribute changes for a single access

Issue ID	Description
	item are now consolidated into a single entry.
IIQMAG-5070	The Accounts, Entitlements, and Roles buttons on the Identity Details page are now correctly grouped in a list container for improved layout and accessibility.
IIQMAG-5079	Timeline date selection accessibility is improved with clearer labels for selected and unselected dates, and more user-friendly IDs.
IIQMAG-5112	Enhanced color contrast of UI elements on key pages to meet WCAG 2.0 Level AA standards, improving accessibility for users with visual impairments.
IIQMAG-5133	The revocation details section on the Revoke Entitlement page now uses a header element, improving accessibility for screen reader users.
IIQMAG-5134	The “Select Page” and “Select Everything” options now work correctly to select identities on the population summary screen without any errors.
IIQMAG-5135	The Choose Year and Month buttons in the Access History Date Picker have updated ARIA labels to improve accessibility for keyboard users.
IIQMAG-5160	On the Group Summary page, a relevant error message with the correct ID is now displayed when a user enters an invalid date format in the date field, helping all users identify and correct the input error.
IIQMAG-5161	On the Edit Identity Correlation Configuration page, the “Clear All Filters” button colors have been adjusted for better contrast and easier visibility for all users.
IIQMAG-5166	The Attribute Details modal now sets focus on the first input field when opened, instead of on the Close button
IIQMAG-5170	Accessibility is improved when using VoiceOver on Mac Safari. Users can now navigate between the fields using left and right arrow keys, without the page reloading unexpectedly. This can be achieved by using the Control+Option+Spacebar key combination.
IIQMAG-5172	In this release, the “no results” text in the Forwarding History, Comments, and Object Properties tabs of the details dialog was converted to a header. It’s now easily navigable via tabindex or ANDI, and read aloud for improved accessibility.
IIQMAG-5177	IdentityIQ buttons now provide a visual focus indicator when tabbed to using the keyboard.
IIQMAG-5192	Required validation messages now appear correctly for ObjectMultiSuggest fields on the Identity Attribute, Capability, Assigned

Issue ID	Description
	Roles, and Business Role pages. Removing all values will display “This field is required”.
IIQMAG-5281	The Access History identity filter panel UI is improved by removing empty heading space when no identities are selected.
IIQMAG-5285	The ARIA label for the date of birth month/day toggle in the Identity Attribute UI has been updated to clarify that users can switch options, improving accessibility.
IIQMAG-5289	The Accounts, Roles and Entitlements debug pages now include a Table Name parameter, which uses the aria-label attribute to provide context for data tables. This improves the experience for users with screen readers.
IIQMAG-5293	The Identity List View page now uses ARIA labels to distinguish the identity filter button’s state, for improved accessibility with screen readers.
IIQMAG-5297	Access History page Accounts, Entitlements, and Roles table headers now use heading tags instead of span tags to improve accessibility based on an audit by the Accessibility team.
IIQMAG-5434	The Identity Details tab now supports special characters in custom attributes within the Identity Details section. This update corrects previous encoding problems, improving the accuracy of displayed identity information.
IIQMAG-5435	The Task Result page has been updated to properly handle UTF-8 encoding for special characters in warning and error messages. Users will now see correctly displayed international characters and symbols, improving the overall readability and accuracy of task notifications.
IIQMAG-6140	If the "Require users to enter their current password when setting a new password" option is disabled in Global Settings, a user can now change their password in the Edit Preferences page, resolving an issue which previously disabled the Save button.
IIQMAG-6801	Scalability is now improved for role entitlement relationship processing for large sets of roles.
IIQMAG-6898	File Access Manager (FAM) alerts aggregation on FAM version 8.4 or later (ElasticSearch) now work with IdentityIQ.
IIQPB-1711	ARIA role="main" and aria-label were added to main content in Lifecycle Manager, Certification, Request, and Identity Certification for accessibility and 508 compliance.
IIQPB-1712	The Registration Authorization object details page now uses the strong tag

Issue ID	Description
	instead of the b tag to improve accessibility per 508 standards.
IIQPB-1720	The Role Revocation dialog in Manager Certifications is now WCAG 2.1 AA compliant, with improved screen reader compatibility for easier navigation.
IIQPB-1722	Focus indicators in the navigation, quicklinks, and tables now meet WCAG 2.1 non-text contrast requirements (1.4.11). This ensures a minimum 3:1 contrast ratio, improving accessibility and compliance with standards like Section 508.
IIQSAW-5254	The SPRights "ViewAccessConnectionsPage, FullAccessDebugPage" are granted for all the debug connections.
IIQSAW-5258	Audible announcements added for screen readers to improve accessibility when navigating the application. Screen readers now announce 'page is loading' and 'loading data completed' on most pages, except those using the ExtJS framework.
IIQSAW-5343	Introduced the Database name as part of upgrade error message, it will give the specific Database name in case of version upgrade needed.
IIQSAW-5409	The title and status fields on the Track my Requests page are now h3 and h4 headings to improve prominence and accessibility for screen reader users.
IIQSAW-5414	The Save, Cancel, and Next buttons on the Certificate, Policy Violation, and Manage User Access screens are now correctly announced by VoiceOver when revealed or enabled.
IIQSAW-5448	The Access History page now correctly displays reassigned accounts after aggregation. Previously, missing identityId in messages prevented proper updates, but this is now resolved.
IIQSR-741	Redundant Identity Snapshot creation is now prevented by distinguishing an intentional change of an editable attribute during the Identity Refresh task with the "Maintain identity histories" option.
IIQSR-783	Partitioned group aggregation no longer results in database deadlocks.
IIQSR-793	Aggregation tasks now continue if errors occur during partition creation, and applications with partition creation errors no longer have deletion checks performed if deletion checks are enabled.
IIQSR-803	[SECURITY] OAuth secrets are no longer fetched en-masse and will only be fetched with each individual request for the secret of each Oath client.
IIQSR-811	Correlation rules for SAML SSO receive all available XS Types from the

Issue ID	Description
	SAML response.
IIQSR-817	Effective Entitlements with Classifications are now correctly displayed.
IIQSR-820	The FAM Classifications Aggregation task now has a new "Query Type" argument that provides a choice between the FAM SCIM service that is used to aggregate classifications: 1. The legacy API that aggregates classifications via FAM Permissions 2. A new, more efficient API that aggregates classifications via FAM Groups(NOTE: Requires these FAM Service Packs or later: 8.4 SP3, 8.3 SP7) Refer to Upgrade Considerations section for more information.
IIQSR-822	The original role change event is now passed to the optional role change propagation workflow.
IIQSR-826	The expired password page is now executed after successfully completing the MFA workflow form.
IIQSR-830	When an identity refresh completes without having the identity locked, the identity will continue to be saved to persist further identity changes.
IIQSR-831	Identity refresh locks are no longer released prematurely, causing errors, when certain provisioning operations take place during the refresh.
IIQSR-832	Policy conflict detection now properly considers the requirements and permissions of inherited roles.
IIQSR-834	Partitioned aggregation of multiplex applications no longer results in a NullPointerException.
IIQSR-835	Report email templates are now evaluated so that template code is not sent in emails.
IIQSR-840	Eliminated the potential for an exception occurring when a Role Membership Certification rescinds a child Certification, which had resulted in the CertificationEntity and/or the related CertificationItems being orphaned from their respective parent objects.
IIQSR-841	Certification corruption due to runtime exceptions during critical certification processing is greatly reduced.
IIQSR-843	The Roles by Application Report no longer throws a LazyInitializationException when there are more than 1000 roles, with some roles having classifications.
IIQSR-845	LCM access requests no longer show as complete when request-related workitems are still open.
IIQSR-847	[SECURITY] Exported advanced analytic searches where no filters were

Issue ID	Description
	chosen no longer contain results that were not part of the executor's scope.
IIQSR-849	[SECURITY] Strict scope restrictions no longer result in excess results for advanced searches.
IIQSR-854	Added a second pool for Scripts which can be configured in <code>iiq.properties</code> using the property prefix <code>'scriptRunnerPoolConfig'</code> .
IIQSR-857	[SECURITY] Property values displayed in the header portion of Live Reports now have HTML characters escaped.
IIQSR-859	An <code>AccountRequest</code> without an explicit operation assigned is now assumed to have the <code>Modify</code> operation.
IIQSR-860	Improved performance when requesting access for Identities which already have extensive access.
IIQSR-862	Sequential and partitioned aggregation tasks now correctly follow "halt on error" settings for each individual partition.
IIQSR-863	Access Request items are no longer checked for completeness by the 'Perform Identity Request Maintenance' task prior to approval completions.
IIQSR-866	Server-side performance is now improved when searching for requestable entitlements during Request Access.
IIQSR-867	[SECURITY] Better evaluation of the QuickLink when determining if a requestee is valid.
IIQSR-868	[SECURITY] Sensitive files are no longer returned in a traversal attack against the JavaServer Faces library used by IdentityIQ.
IIQSR-869	[SECURITY] An issue exists in all supported versions of IdentityIQ Life-cycle Manager that can result if an entitlement with a value containing leading or trailing whitespace is requested by an authenticated user in an access request.
IIQSR-872	<code>QueryOptions.setCloneResults()</code> now supports an optional flag to call <code>SailPointContext.commitTransaction()</code> before cloning results.
IIQSR-873	[SECURITY] HTML EmailTemplates are accurately determined to be HTML when Velocity code precedes the HTML tag.
IIQSR-874	The attribute sync workflow was not running during Identity Refresh when it should have been.
IIQSR-876	Bulk request processing in the Request Access feature now includes enhanced detection of existing requests, eliminating the occurrence of duplicate access requests.

Issue ID	Description
IIQSR-879	Improved current page persistence with SAML SSO enabled and shorter-duration web server session life.
IIQSR-887	Errors containing 'Context already created for this thread' while running the BundleProfileRelationSynchronizer are prevented.
IIQSR-888	When a sequential task is marked as Completed, do not allow additional child tasks to be executed from it.
IIQSR-891	[SECURITY] Externally referenced HTML content is no longer allowed in emails.
IIQSR-893	Integration configurations set to send multiple ticket requests have retain operations properly set when roles have overlapping entitlement profiles.
IIQSR-894	[SECURITY] Corrected issue where proxy Application secrets were being decrypted.
IIQSR-895	Process events partitions now use unique names which prevents the issue that caused the Identity Refresh to be marked complete while partitions are still executing.
IIQSR-896	A Role Display Name is no longer decoded as if it was HTML text.
IIQSR-897	Better determination of default remediator when revoking roles for disconnected Applications.
IIQSR-898	Permitted roles are now correctly removed when not assigned by another role.
IIQSR-899	A LazyInitializationException no longer occurs when executing provisioning outside the scope of an IdentityIQ code path.
IIQSR-900	Identity request processing now leaves request items pending when a manual action is open and the identity request is still in a split provisioning state.
IIQSR-902	The Java system property org.apache.catalina.connector.RECYCLE_FACADES set to true is now supported to utilize enhanced security settings on Tomcat. Refer to the Upgrade Considerations section for more information.
IIQSR-904	IdentityIQ no longer uses PostgreSQL large objects for any Character Large Object (CLOB) data, resolving an issue in which the vacuumlo utility would corrupt the CLOB data. Refer to the Upgrade Considerations section for more information.
IIQSR-905	Certification archive generation no longer results in an error when duplicate "Perform Maintenance" tasks are launched simultaneously.

Issue ID	Description
IIQSR-906	[SECURITY] Request URLs are properly decoded when determining authorized access.
IIQSR-907	Approvals made quickly as part of a large work item are now serialized to prevent most 'click loss.'
IIQSR-908	Rapid target aggregations no longer result in error.
IIQSR-909	The Rapid Setup Leaver process no longer duplicates entitlement removal requests when a role is both assignable and detectable.
IIQSR-910	Configuring group membership scope on certain application definition pages now correctly persists changes.
IIQSR-913	[SECURITY] Removed the /faces prefix mapping in WEB-INF/web.xml in the IdentityIQ installation directory which avoids any access to content by prepending the URI with /faces.
IIQSR-915	When making a decision on a policy violation within a Targeted Certification, the Allow button is now consistently translated across the languages to mean "Allow" instead of "Allow until".
IIQSR-916	The Full Text Index Refresh task is now optimized correctly.
IIQSR-922	The AngularJS libraries are updated from version 1.8.0 to 1.9.9.
IIQSR-927	The BundleProfileRelation Service now supports an optional attribute "disableInitialDiff". When this attribute is set to "true", BundleProfileRelations will not be evaluated for all Roles in the environment on startup.
IIQSR-928	The BundleProfileRelation Service no longer creates overlapping work in clustered environments with more than one IdentityIQ instance.
IIQSR-929	The Refresh Role-Entitlement Associations task partitions no longer lock each other out, allowing the partitions to execute simultaneously.
IIQSR-930	Duplicate BundleProfileRelations are no longer created by the synchronization service.
IIQTC-411	A form validation error is now shown when submitting a form after clearing the value in a dynamically set required field via the keyboard.
IIQTC-414	When disabling Full Text Search in the Lifecycle Manager configuration page, clicking Save no longer toggles the "Filter searches by" field from "Starts With" to "Contains".
IIQTC-415	[SECURITY] The Apache Commons FileUpload library is updated from 1.4 to 1.5 to mitigate CVE-2023-24998.
IIQTC-416	[SECURITY] The Google Guava library is updated from 30.1 to 32.1.2 to mitigate a security vulnerability.

Issue ID	Description
IIQTC-418	Workgroup administration now considers inherited child scopes when a user is assigning an authorized/controlled scope to a workgroup or adding a member to a group.
IIQTC-419	In a certification campaign, the Certifier is no longer presented with the comments box twice when rejecting a revocation challenge.
IIQTC-421	When creating or updating an entitlement, the approval request workitem is now properly assigned to the Application owner.
IIQTC-423	Role change propagation no longer removes the end date from an identity's role assignment.
IIQTC-425	In Advanced Analytics, when configuring an Advanced Search of type "Account", the option to select "Entitlements" has been removed from the Field pull-down since this property was never intended to be used as a search filter. The "Entitlements" field is still available in the "Choose Fields To Display" for the search results.
IIQTC-428	Badly formatted encrypted strings are now returned as-is and logged with a warning instead of erroring out.
IIQTC-429	Further improvements in the Task Manager reduce the likelihood of a task result being saved with a non-unique name, leading to a constraint violation. This also includes enhanced accommodation for tasks initiated through a batch request.
IIQTC-433	When executing a saved "Advanced Analytics" report based on the "Entitlement" search type, the report now correctly displays the applicationName instead of the applicationId.
IIQTC-434	[SECURITY] HTML EmailTemplates are accurately determined to be HTML when Velocity code precedes the HTML tag.
IIQTC-440	Adding a scope when creating a new policy or editing an existing policy through the UI is now saved successfully.
IIQTC-441	In Manage User Access, when a user selects an Entitlement for which they're restricted to raise the access request, a warning message is displayed in a popup to warn they're not authorized.
IIQTC-444	Enabling the progressMode for the Impact Analysis task no longer causes errors when viewing its result.
IIQTC-445	Account credentials in which the password contains a colon will now authenticate successfully using the REST API.
IIQTC-446	When an Identity is locked, the message "Invalid Username or Password"

Issue ID	Description
	is now displayed at login instead of a System Exception error.
IIQTC-449	[SECURITY] Resolved a Cross Site Scripting (XSS) vulnerability in the account preview pop-up of the schema configuration section of application create/edit.
IIQTC-452	When a user has multiple eligible accounts on an application being requested, running the Identity Refresh task no longer causes manual workitems to be generated, thereby preventing automatic provisioning.
IIQTC-453	When a task is configured with "Allow Concurrency" unchecked and "Previous Result Action" set to "Rename New", if an attempt is made to launch the task concurrently with an instance of the same task, an error is now generated and viewable in the Task Results tab.
IIQTC-454	Bundles that have a displayName are now also searchable with the name attribute.
IIQTC-455	[SECURITY] The moment.js libraries are updated from 2.29.1 to 2.30.1 to mitigate the vulnerabilities documented in CVE-2022-31129 and CVE-2022-24785.
IIQTC-457	[SECURITY] The Apache XML Security for Java library (xmlsec) is updated from 2.3.0 to 2.3.4 to mitigate CVE-2023-44483.
IIQTC-458	Resolved an issue occurring when submitting an access request with attachments immediately after having built the same access request for the same identity and entitlement but not submitting it and navigating away from the page. This scenario previously resulted in an error preventing the new access request from being submitted.
IIQTC-461	The Propagate Role Changes task no longer generates a LazyInitializationException error when the "Check active policies" option is enabled.
IIQTC-463	[SECURITY] The JSON library is updated to 20231013 to mitigate CVE-2022-45688 and CVE-2023-5072.
IIQTC-465	Extended attributes on identity pages now accurately reflect mapping changes between applications, including scenarios where the newly mapped application contains no value for the attribute.
IIQTC-466	The Perform Maintenance task with the certification phase transition option enabled now shows a warning when the identity does not exist instead of generating a NullPointerException.
IIQTC-467	Failures during group hierarchy aggregation no longer result in orphaned

Issue ID	Description
	groups.
IIQTC-468	When an account aggregation task is not actually in the process of aggregating accounts, check deleted operations are now skipped if a partition throws an error.
IIQTC-469	A Batch Request now throws an error with case-sensitive database searches involving an identity which differs only in its casing from what is in the database.
IIQTC-470	The Encrypted Data Synchronization task no longer causes a NullPointerException on applications with no Attributes element.
IIQTC-471	Duplicate profiles are no longer created when importing a bundle with the "Allow propagation of role changes" setting enabled.
IIQTC-472	When the customer modifies the Identity Attribute value, the modified value is now correctly reflected.
IIQTC-475	Managers can now access details on special identities, such as service accounts, through a custom QuickLink with the "viewIdentity" action. Previously, incorrect rights checking prevented this access.
IIQTC-476	The Dispatch Access History task now prevents a StackOverflowError caused by a loop in a role hierarchy. In these situations the role is skipped, an error is logged in the console, and the other roles are successfully processed.
IIQTC-477	The Manager column is now included in the Entitlement Owner certification CSV export. This only affected 8.4 when upgrading from an earlier version.
IIQTC-479	The reconnection in the aggregator closed transactions no longer cause javax.persistence.TransactionRequiredException.
IIQTC-480	Batch requests are now created for each application where the target identity has an existing account and attributes.
IIQTC-481	Eliminated certification delays caused from duplicate entries in entitlements, ensuring faster and more accurate certification processing.
IIQTC-482	Changed the Role Details visibility to Assigned & Detected when a detected IT role is required by an assigned role.
IIQTC-483	Access to the SCIM API is no longer routed through Passthrough Authentication (if enabled) if the client is already authenticated with a valid OAuth2 bearer token.
IIQTC-485	[SECURITY] An end user request can no longer be intercepted and redir-

Issue ID	Description
	ected to some external/untrustworthy application.
IIQTC-486	The Sensitive Data Exposure widget on the IdentityIQ dashboard now rounds the score value to the nearest decimal place.
IIQTC-488	Attribute Sync can now allow Account Selection when an Identity has multiple accounts on an application and the target mapping does not have 'Provision to all accounts' selected.
IIQTC-489	Names for workflows used for tasks related to entitlement creation, update, and deletion can now be customized instead of being restricted to using the previously hardcoded workflow name of "Entitlement Update".
IIQTC-492	A successful SCIM API call using an OAuth2 bearer token no longer generates a loginFailure audit entry.
IIQTC-495	[SECURITY] The JSON Smart library is updated from version 2.4.8 to 2.4.10 to mitigate CVE-2023-1370.
IIQTC-497	The Access Request Status Report no longer fails with a "Key Pending Completion is duplicated in pie dataset" error.
IIQTC-499	When viewing an Identity in the Identity Warehouse, in the Events tab, the Summary under Identity Events now displays "Open Work Item" instead of "Provision to null" for manual provisioning applications.
IIQTC-503	A user with system admin capabilities in the workgroup can now correctly perform self-certification.
IIQTC-504	Field validation no longer occurs twice when a form is submitted, eliminating redundant operations and improving performance.
IIQTC-506	Access Requests no longer allow selecting a role that has already been requested by an identity.
IIQTC-510	The CheckedPolicyViolations API now returns an empty array instead of null when no violations or policies exist. This change improves consistency and prevents potential issues in integrations that expect an array response.
IIQTC-512	An entitlement search no longer throws an "index out of bounds" exception when encountering a '{' character in the string.
IIQTC-514	Performance of the BundleProfileRelation service event processing is now significantly improved, particularly in large-scale environments.
IIQTC-515	The Native Identity Change Detection feature for Active Directory has been improved to ensure accurate Distinguished Name (DN) assignment in provisioning plans, addressing a previous issue with outdated DNs.

Issue ID	Description
IIQTC-518	The Dispatch Access History task no longer fails when a ManagedAttribute has a display_name of more than 128 characters. The column sizes in the history-related tables have been increased wherever necessary.
IIQTC-522	[SECURITY] A multi-value field value in a Form is now checked for potentially harmful characters, preventing HTML injection through user input.
IIQTC-523	[SECURITY] The Bouncy Castle libraries are updated from 1.70 to 1.78.1 to mitigate CVE-2023-33201.
IIQTC-524	[SECURITY] The rule name field is now sanitized to prevent cross-site scripting (XSS) attacks, ensuring that malicious scripts cannot be executed through user input.
IIQTC-525	[SECURITY] Under Global Settings, the Scopes list now properly escapes HTML, preventing potential XSS vulnerabilities.
IIQTC-526	[SECURITY] The CodeMirror library is updated from 4.3.0 to 5.65.16 to mitigate CVE-2020-7760.
IIQTC-527	The Lifecycle Events Status Report no longer fails with a "Key Pending Completion is duplicated in pie dataset" error.
IIQTC-528	[SECURITY] Accessing the "Forgot Password" feature now requires users to successfully complete multi-factor authentication before they can use authentication questions for password recovery.
IIQTC-530	Task execution has been improved to handle sequential tasks with empty child tasks correctly. This prevents unexpected pauses during processing, resulting in more efficient and predictable task completion.
IIQTC-531	In the Workgroup edit page, the Capabilities list no longer shows inherited capabilities as selected.
IIQTC-532	[SECURITY] In Advanced Analytics, when performing an Identity Search by region, the "Show Entitlements" popup no longer displays identities outside of an identity's scope.
IIQTC-533	In the Role Editor under the Required Roles section, the popup window displayed when selecting Modify Required Roles now allows sorting by role name.
IIQTC-534	Manage User Access no longer combines all available populations of requestees, scoped or unscoped, in the event a requestor's SSO session expires, or their session or cookies are otherwise cleared. Such an event will now generate an error.

Issue ID	Description
IIQTC-535	In Lifecycle Manager, entitlements for complex role definitions are now displayed correctly.
IIQTC-538	Batch request status is now updated as per the batch request item result.
IIQTC-539	The description of a Role Composition certification is now displayed in the default locale if the user's locale is not available.
IIQTC-540	Filter labels in the "Manage Access" section are now displayed correctly by preventing unnecessary HTML escaping.
IIQTC-541	Executing a targeted aggregation against an Active Directory application no longer deletes all recycle bin accounts.
IIQTC-542	[SECURITY] The JSONPath library is updated from 2.7.0 to 2.9.0 to mitigate CVE-2023-51074.
IIQTC-544	In the certification page, in the Returned Delegations section of the Important tab, subsequent decisions by the certifier are now successfully applied, such as Approve and Revoke. Additionally, the Undo Decision action is now displayed consistently in the menu.
IIQTC-545	Fixed an error when viewing access history for Identities with over 1,000 accounts or entitlements.
IIQTC-546	Using an extended attribute to filter identities in a targeted certification now works correctly.
IIQTC-547	[SECURITY] Selecting a Form button which has the 'next' action and skipvalidation set to true now checks for potentially harmful characters entered in text fields, protecting against HTML injection through user input.
IIQTC-548	For an Identity with a capability that comes from a role, when assigning or removing another role with an attachment through Manage User Access, the task result no longer generates a ConstraintViolationException.
IIQTC-550	[SECURITY] The Spring Framework libraries are updated from version 5.3.31 to 5.3.39 to mitigate CVE-2024-38808, CVE-2024-38809, CVE-2024-22243, and CVE-2024-22262.
IIQTC-551	If a user attempts to save an Advanced Analytics report with a name that already exists, an error message is now displayed, preventing the existing report from being overwritten.
IIQTC-553	In Advanced Analytics, if an issue occurs when performing IAI Role Discovery, the error message is now displayed in the UI.
IIQTC-554	In the view Identity page, Entitlements tab, under Roles, clicking in the area next to the name of an IT Role now displays the expected Cer-

Issue ID	Description
	tification dropdown with the Last Certification Details.
IIQTC-556	Users can now run concurrent Impact Analysis tasks with different roles, resolving an issue that would previously result in an error.
IIQTC-557	[SECURITY] The SSHJ library is updated from 0.37.0 to 0.38.0 to mitigate CVE-2023-48795.
IIQTC-560	The Environment Information Report no longer fails with an NullPointerException when an IntegrationConfig object is missing an executor entry.
IIQTC-561	Certification descriptions now correctly display Identity names containing special characters.
IIQTC-562	The target column size and type for managed attributes is changed to accommodate target permissions with a full path whose length is greater than 255 characters.
IIQTC-564	When creating an entitlement request, attempting to select the same date for Start (Sunrise) and End (Sunset) is now prohibited by disabling the Save button.
IIQTC-567	SAML SSO no longer generates misleading errors on certain browsers.
IIQTC-568	For reassigned Access Reviews, the "Signed By" field is no longer blank if the person who performs the first sign-off is the same person as the final approver.
IIQTC-569	In Advanced Analytics, the Access Review search results now display the correct certificationName.
IIQTC-573	In Advanced Analytics, the Account search by Application now includes all Entitlement types for accounts.
IIQTC-574	The Advanced Access Review Live Report now correctly shows special characters when exported to CSV.
IIQTC-584	The Case Insensitive flag on an Application is now correctly applied to an Attribute Assignment removal, preventing an entitlement that was removed from being re-provisioned on the next Identity Refresh.
IIQTC-585	Classifications can no longer be removed until pending approvals are completed, and pending work items now correctly display the content of Role Modifications.
IIQTC-587	When using the Group By filter with the Changes Detected option in a certification, bulk approvals for selected certification items are saved successfully and a NoSuchMethodException error is no longer logged.

Issue ID	Description
IIQTC-589	In the Approval widget, the Approve button is now displayed only after the approval workitems are fully loaded, resolving an issue which allowed the Approve button to be selected prematurely causing a JavaScript error.
IIQTC-590	Sunset date are also called End date is now successfully cleared on the user entitlement and the corresponding scheduled request for removal is deleted when calling <code>attributeRequest.setRemoveDate(null)</code> .
IIQTC-591	Entitlements which are part of a non-provisioned permitted IT role can now be promoted to an Entitlement Group and show up in certifications to certify Additional Entitlements.
IIQTC-592	The Perform Maintenance task with the prune attachments option now completes successfully on MS SQL Server when the total number of attachments among the Identity Request items exceeds 2100.
IIQTC-593	Resolved a <code>NullPointerException</code> (NPE) triggered when making decisions on role membership certifications with an active revocation period and rule, preventing items from entering an invalid state.
IIQTC-594	Corrected a malformed error message to display proper exception details while running the Performance Identity Request Maintenance Task.
IIQTC-596	Multi-valued string entries on a provisioning form can now be cleared.
IIQTC-597	An Access Request with a multi-valued attribute added through a Role Provisioning Form is now correctly validated by the Perform Identity Request Maintenance task and marked as Complete.
IIQTC-599	Resolved <code>NullPointerException</code> in Advanced Policies with Entitlement filters when an Identity Link has no attributes.
IIQTC-600	Identity names and Role names containing special characters are now displayed correctly in the UI banner when created or updated.
IIQTC-602	The Perform Identity Request Maintenance task now correctly moves an Access Request to Completed by equating an Identity Request attribute value of empty string with a null identity-link attribute value.
IIQTC-603	Resolved a memory leak in the Access Request Status Report that caused report generation to fail with large data volumes.
IIQTC-606	IdentityAI recommendations are now displayed for all approval workitems generated in LCM Provisioning, resolving an issue which caused workitems generated after an <code>approvalSplitPoint</code> to be excluded.
IIQTC-607	In the Entitlement Catalog, selecting Import displays a pop-up with a list of supported Entitlement properties. This list no longer includes scope since

Issue ID	Description
	it is not supported for import.
IIQTC-608	File names for exported reports no longer have embedded spaces removed.
IIQTC-609	Optimized query execution and improved memory management during identity refresh.
IIQTC-611	In the Entitlement Catalog, long entitlement attribute display names are now truncated with an ellipsis and show the full text on mouse hover.
IIQTC-613	For Access Request notification emails, the Remove Action now populates the item.displayValue variable used by the Velocity template with the Display Value that is populated on the Group Standard Properties instead of using the Value which maps into the item.csv variable.
IIQTC-614	Within the same IdentityIQ deployment, termination of a sequential task can now be initiated from any server instance, removing a previous limitation which required the termination be initiated from the same instance where the task is executing.
IIQTC-615	The SCIM APIs now return a Date in correct date-time format instead of epoch format when inside a Map.
IIQTC-620	The Identity Refresh task with the "Synchronize attributes" option no longer triggers Attribute Sync for unchanged attribute values.
IIQTC-621	The Check Expired Mitigations task now completes successfully when the associated policy for a policy violation is deleted, instead of failing with a NullPointerException (NPE).
IIQTC-622	The "RapidSetup - Leaver" workflow no longer causes a "No serializer registered" error if a wait is added to a step near the end of the workflow.
IIQTC-623	[SECURITY] A user with SPRight "ViewQuickLinks" is now restricted from creating or editing a QuickLink Population.
IIQTC-624	[SECURITY] The /ui/rest/identities/<id> API now enforces scoping and sends a 401 Unauthorized error response if a user tries to view an identity which is outside of the managed scope.
IIQTC-625	When an Entitlement has an extended attribute of type Identity, its value is now properly returned via the SCIM API.
IIQTC-626	Running the Refresh Identity Cube task with only the "Refresh identity attributes" option no longer removes the value of an attribute if the identity does not have an application account for the associated application source mapping rule.

Issue ID	Description
IIQTC-628	Manually Assignable Permitted IT Roles are now accurately displayed based on what Role they are allowed by and how they are acquired.
IIQTC-629	The "My Access Reviews" page now correctly displays identity names with special characters.
IIQTC-630	Localized characters are no longer corrupted in emails sent via OAuth authentication. Emails now retain proper character encoding.
IIQTC-633	Performance is improved when running the Perform Maintenance task with the "Archive and prune certifications" option on a large certification archive containing objects that need pruning.
IIQTC-635	Fixed issue where multi-valued identity attributes were incorrectly cleared during refresh with provision assignments.
IIQTC-636	Running a rule with ruleRunner.maxPoolReuse=1 in iiq.properties no longer causes an exception.
IIQTC-637	NullPointerException is no longer thrown for accounts of type service account if correlateOnly flag is set on the account aggregation task.
IIQTC-639	In Advanced Analytics, saving the results of an Advanced Search as a report is now successful and no longer produces an error.
IIQTC-640	A JavaScript error no longer occurs when opening the Business Process Editor screen.
IIQTC-642	Provisioning with credential cycling now correctly fails when the credential store is unavailable, rather than generating a manual work item.
IIQTC-643	When viewing a manual work item and clicking the "View Details for <identity_name>" link, the Detailed Identity Information pop-up now correctly displays special characters in the Identity Attributes tab.
IIQTC-651	Special Characters are now correctly displayed in the Name column of the Lifecycle Events page, Name column of the populations tab in Group Configuration page, Conflict column in the Details tab of Policy Violations page, Application Account attributes in Identity Warehouse page, the Errors and Warnings tab of certification page, and in the UI banner when a population is created.
IIQTC-654	Identity attributes are no longer cleared when importing XML that contains leading or trailing spaces in the owner's name.

Resolved Issues - Connectivity

Issue ID	Description
CONBRUG31-2129	Upgraded the bouncy castle jars bcpkix, bcprov, and bcutil from jdk15on - 1.70 to jdk18on-1.77 in connector-bundle-openconnector.
CONBRUG31-2152	Upgraded the bouncy castle jars bcpkix, bcprov, and bcutil to jdk18on-1.77 in connector-bundle-common.
CONBRUG31-2442	Upgraded the Vulnerable Library com.hierynomus:sshj 0.37.0 in connector-bundle-common to com.hierynomus:sshj 0.38.0 to mitigate a security vulnerability.
CONBRUG31-2478	Upgraded the vulnerable library json-path-2.2.0.jar to version library json-path-2.9.0 to mitigate a security vulnerability.
CONBRUG31-2479	Upgraded the Vulnerable Library in connector-bundle-common jose4j jar from 0.9.3 to 0.9.6, json-path jar from 2.2.0 to 2.9.0, aws-java-sdk-bom from 1.12.22 to 1.12.764 in lib-s/aws/pom.xml to mitigate a security vulnerability.
CONBRUG31-2480	Upgraded the below Vulnerable Library versions to version 1.78.1 to mitigate a security vulnerability. org.bouncycastle:bcpkix-jdk18on-1.77.jar org.bouncycastle:bcprov-jdk18on-1.77.jar org.bouncycastle:bcutil-jdk18on-1.77.jar
CONBRUG31-2481	Upgraded the Vulnerable Library org.bouncycastle:bcprov-jdk18on from 1.77 to 1.78.1 in open connector and connector-common to mitigate a security vulnerability.
CONBRUG31-2608	Upgraded the Vulnerable Library commons-codec from 1.11 to 1.17.1 in connector-bundle-file-based, connector-bundle-collaboration, connector-bundle-webservices and connector-bundle-misc to mitigate a security vulnerability.
CONBRUG31-2651	1. Updated axis2-1.7.8/wstx-asl-3.2.9.jar to woodstox-core-7.1.0.jar. 2. Added new libs/stax2-api-4.2.2/stax2-api-4.2.2.jar.
CONCHENAB-4763	The child application account aggregation of Oracle Identity Manager is now successful.
CONCHENAB-5646	Below JAR is upgraded to a newer version due to vulnerabilities found in the older version. Please check the impact on custom connectors, rules or any other customization, which are directly or indirectly using this JAR file. okio-3.7.0/okio-3.7.0.jar okio-3.7.0/okio-jvm-3.7.0.jar okhttp-4.12.0/okhttp-4.12.0.jar
CONCHENAB-5830	The SailPoint Workday Accounts connector aggregation will no longer fail when iterating over large data sets.
CONCHENAB-6155	The SailPoint Tools Base64 implementation is deprecated, and is no longer available to use.
CONCHENAB-6388	The Okta connector now supports non-encoded characters in the URLs for multithreaded cache creation.

Issue ID	Description
CONCHENAB-6612	Axis2 libraries are upgraded to version: 1.8.2
CONCHORDS-2126	The ACF2 connector provides support for releases R16. The TSS connector provides support for releases R16.
CONCHORDS-2364	The Atlassian Suite Cloud connector has been updated to use the latest Atlassian API changes. With this change, users created by the connector would not have product access as per the Default Product Access defined in Atlassian. To give product access to newly created users, assign the appropriate group entitlements to the user.
CONCHORDS-2735	SailPoint's Atlassian Suite Cloud connector now successfully aggregates more than 9000 accounts even when the application is configured to manage only active users.
CONETN-4138	SCIM2.0 NON-Relaxed connector now supports provisioning of Multivalued Core attributes Patch operation.
CONETN-4168	The SAP HR Connector now has improved performance for delta aggregation.
CONETN-4199	SAP GRC Connector no longer fails with NullPointerException when correct permission are not given to service account
CONETN-4232	SAP Sybase Connector now shows detailed error message during failure.
CONETN-4259	The Cloud Gateway connector sync now correctly handles the proxy application if defined to itself.
CONETN-4268	Workday Connector now correctly updates work telephone of non US workers.
CONETN-4278	The Cloud Gateway no longer prints sensitive information in trace level logs when provisioning plans are pushed through Cloud Gateway via Password Interceptor.
CONETN-4287	The LDAP Connector no longer throws an error when the attribute's value is null or empty for SET and REMOVE operations.
CONETN-4290	The Azure Active Directory Connector now fetches all the cloud managed entities with permission type view, edit and delete.
CONETN-4302	The SCIM 2.0 Connector no longer skips attributes added in readOnly list during PUT operation in relax configuration mode.
CONETN-4303	The Azure Active Directory Connector now shows the correct displayName of custom AzureADActive and AzureADEligible roles assigned to the user after Account Aggregation.
CONETN-4304	The Workday Accounts Connector no longer displays duplicate entitlements when running account aggregation.
CONETN-4307	It is recommended to pass UserPrincipalName in plan (as exch_userPrincipalName) while shadowAccountDN creation name with space in CN to avoid LogonName creation with garbage.
CONETN-4308	The SuccessFactors Connector now provisions blank value for non-mandatory phone attrib-

Issue ID	Description
	utes.
CONETN-4309	The SAP SuccessFactors connector now correctly provisions groups for an account having different values for the Person ID external and Userid attributes.
CONETN-4313	The Azure Active Directory Connector does not loop the API requests in case of invalid Microsoft response or token when attribute 'continueOnError' is set to true during delta aggregation.
CONETN-4317	The SAP Concur Connector now de-provisions group aware entitlements for an account correctly.
CONETN-4318	The Azure Active Directory Connector now supports disabling the ServicePlan during account aggregation when fetchServicePlan is set to false.
CONETN-4336	The Azure Active Directory Connector now aggregates users only from B2C Tenant when Manage B2C Tenant is set to true.
CONETN-4337	Oracle HCM Accounts connector now supports provisioning of Person Number with multiple work relationships.
CONETN-4338	Workday Connector now skips record during delta aggregation when future hire date is corrected and record is outside offset.
CONETN-4351	The Cloud Gateway now sets retry status correctly when provisioning operation fails with 502 error and 502 error is configured as part of retryableErrors in application.
CONETN-4355	The SAP HR/HCM Connector no longer creates dump in SAP target system when an aggregation is performed.
CONETN-4362	The Oracle Fusion HCM connector aggregated the future data when a single account aggregation is performed.
CONETN-4375	single account aggregation is working with 2 '\$(identity)'
CONETN-4379	The Microsoft Entra ID Connector no longer fails with ClassCastException when Interrupted Exception occurs during account creation.
CONETN-4392	The Active Directory Connector will now successfully create a contact without displaying an error message in the UI when the setAttributeLevel flag is set to false.
CONETN-4396	The Azure Active Directory Connector now fetches the shared mailbox even if they have the same display name.
CONETN-4402	Single Account aggregation is now working after provisioning.
CONETN-4403	The Azure Active Directory Connector now fetches the description attribute of the Groups properly during all Group Operations.
CONETN-4410	Oracle EBS connector is now able to set Security group as per provisioning plan.
CONETN-4418	Workday Connector now aggregates correct manager data for future hires when past rescind hire is turned on.

Issue ID	Description
CONETN-4420	SCIM 2.0 Relax connector now supports provisioning of Multivalued Core and Extended attributes for PUT operation.
CONETN-4428	AIX Connector now gets flags info from AIX managed system to perform self change password operation.
CONETN-4433	Microsoft Entra ID Connector now sets null values for account attributes during SET operation while provisioning.
CONETN-4454	The Mainframe Connector provisioning operation no longer fails when attributes with null values are present.
CONETN-4462	SCIM 2.0 connector now supports provisioning of complex extended attributes using PATCH operation.
CONETN-4463	The Okta connector now correctly provisions simple attributes with null or empty values.
CONETN-4465	The SuccessFactors Connector now correctly aggregates the Manager ID for Future Rehires.
CONETN-4469	The Azure Active Directory Connector now shows proper Error message for Unsupported Get Object operations of AzureADActive and AzureADEligible Roles.
CONETN-4472	The Oracle PeopleSoft HCM Connector no longer fails when query has more than one input in the query.
CONETN-4476	SuccessFactors Connector no longer aggregates pre hire accounts from OnBoarding Module 2.0
CONETN-4478	During Add member provisioning operation IQService no longer removes existing members from group if current schema is not returned from the AD system.
CONETN-4495	SAP GRC Integration no longer updates Valid From value to default date when updating Valid To value for an account.
CONETN-4498	Oracle HRMS Connector now supports account creation with Full name passed as null.
CONETN-4502	The Azure Active Directory Connector now fetches Owners of Distribution Groups via IQService when the owner of Distribution Group is in another Group.
CONETN-4506	Oracle EPM cloud connector no longer fails while creating a user with a trailing space in user-login.
CONETN-4509	Microsoft Entra ID connector now no longer fails while using Advanced Filter options during delta aggregation.
CONETN-4530	Webservices Connector now sends cookie value in correct format in http request to endpoint.
CONETN-4539	SAP Concur Connector no longer generates multiple access tokens after access token is expired during account aggregation.
CONETN-4541	The Oracle HCM Cloud connector now display correct error logs when a test connection fails.
CONETN-4544	Microsoft Entra ID Connector now does not show users out of filter scope as deleted in account aggregation task during delta aggregation.

Issue ID	Description
CONETN-4546	SCIM connector now correctly reads and displays Privileged Data Properties.
CONETN-4547	Snowflake connector no longer fails with org.apache.http.NoHttpResponseException while aggregating huge data.
CONETN-4548	Oracle ERP Cloud Connector no longer fails with error "another user has changed the row with primary key" while creating new person.
CONETN-4549	The SuccessFactors Connector now correctly pulls future-dated attributes when running the delta aggregation.
CONETN-4552	The SAP GRC Integration now shows correct status of accounts when an account aggregation is performed.
CONETN-4554	SAP Direct connector now will populate the /SAILPOIN/CONF table with the latest ABAP report shared.
CONETN-4557	IBM Tivoli DS Connector will now fetch values changed on the managed system as part of the delta aggregation.
CONETN-4558	ADAM Connector account aggregation has been improvised in case where Group Member Search DN value is not specified .
CONETN-4559	Webservices after Operation Rule's restClient now has all the header values even if duplicate header keys are present.
CONETN-4562	SuccessFactors Connector now does not delete accounts reired using OnBoarding 2.0 Module.
CONETN-4564	The Microsoft Entra ID (Azure Active Directory) Connector now fetches appRoleAssignments for users during Account Aggregation.
CONETN-4565	The PeopleSoft Direct Connector can now aggregate roles including special characters in their name when a group aggregation is performed.
CONETN-4566	Workday Accounts now aggregates all the courses associated with an account.
CONETN-4567	SuccessFactors connector now supports FutureActions for LOA/RLOA for delta aggregation.
CONETN-4568	Snowflake Connector now supports use of cloud gateway.
CONETN-4570	IQService now respects subject Name in the certificate in spite of any language set on the Operating System.
CONETN-4574	Oracle Internet Directory entitlement aggregation now respects group.iterateSearchFilter value
CONETN-4577	IQService now performs change password on secure port 636 if TLS for domain settings is enabled.
CONETN-4579	Oracle HCM Cloud Connector now correctly logs an appropriate error message when an account aggregation fails to aggregate any accounts.
CONETN-4580	The SAP SuccessFactors Connector now respects the server time zone when fetchServer-Time attribute is set to true.

Issue ID	Description
CONETN-4581	Oracle HCM Cloud connector now correctly aggregates the additional attribute during get object.
CONETN-4583	Oracle HCM Cloud Connector now shows correct log statement.
CONETN-4584	WebService Connector now does not append header values with same keys, except for the header "Set-cookie"
CONETN-4588	SuccessFactors Connector no longer fails when performing get account operation
CONETN-4609	The SAP HR/HCM connector now correctly populates the values for communication data.
CONETN-4610	The Google Workspace Connector now leverages multithreading to aggregate the group membership during account aggregation.
CONETN-4611	The Microsoft Entra ID connector now throws an ERROR if account aggregation fails.
CONETN-4616	The SCIM 1.1 connector now shows an appropriate error message for an invalid apiToken when a test connection is performed.
CONETN-4618	The Microsoft Entra ID (formerly Azure Active Directory) Connector now saves the correct value of account delta token during Partitioned Delta aggregation
CONETN-4620	In LDAP account aggregation now we can skip DefaultGroupMembership after setting disableDefaultGroupClassFilter to true
CONETN-4621	The Oracle NetSuite connector now aggregates accounts using optimized aggregation API's when the optimisedAggregation flag is true.
CONETN-4622	The Okta connector now allows retries for provisioning operations.
CONETN-4627	The Microsoft Entra ID (formerly Azure Active Directory) Connector now aggregates the AppRoleAssignments membership details of the users without any errors.
CONETN-4631	The UKG Pro Core HCM connector no longer fails account aggregation when the terminated offset value is present.
CONETN-4632	The Active Directory connector account aggregation with partitioning now aggregates all accounts correctly.
CONETN-4635	LDAP Connector now supports Identity attribute other than DN in user-defined group schema if "useGroupSchemaIdentityAttribute" is enabled in application.
CONETN-4637	The Microsoft Entra ID connector now replaces the legacy attribute names with the new names in the userFilters and groupFilters during delta aggregation
CONETN-4638	The Cloud Gateway connector test connection will fail with a proper error message when the username or password is incorrect.
CONETN-4639	The Microsoft Entra ID connector's account aggregation no longer fails while fetching Exchange Online attributes.
CONETN-4645	Slack connector account aggregation does not fail with class cast exception while fetching users from workspace.

Issue ID	Description
CONETN-4646	The Oracle EPM Cloud connector now supports the retry mechanism for aggregating application roles.
CONETN-4648	The Microsoft Dynamics 365 for Finance and Operations connector no longer fails with 400 bad request error for bulk provisioning.
CONETN-4649	The Amazon Web Services (AWS) Connector now provisions roles that have white spaces in their names.
CONETN-4651	Microsoft Entra ID (Azure Active Directory) VA based connector now does not duplicate the "immutableID" attribute when the entry "skipProcessLegacyIdentifiers" is set to true in the Source xml
CONETN-4652	The SAP Direct connector now supports adding roles to an account that does not have previously assigned SAP roles to it.
CONETN-4653	The SAP Portal - (User Management Web Service) Integration Module no longer fails when aggregating accounts that have missing attributes.
CONETN-4655	The Entra ID Connector does not throw a PowerShell error while aggregating Shared Mailboxes.
CONETN-4656	SAP GRC Risk analysis no longer fails with requestStatus Map is empty error while provisioning.
CONETN-4657	Microsoft Entra ID Connector now supports configuring number of threads used for fetching MFA attributes with the use of entry "max-thread-mfa-attributes"
CONETN-4665	SAP GRC connector risk analysis no longer fails with a nullpointer exception when the request is rejected.
CONETN-4666	SailPoint's Mainframe connector now supports failWhenWarn for the delay delete operation on an Identity.
CONETN-4667	The Microsoft Entra ID connector performance has been improved while fetching Exchange Online attributes.
CONETN-4668	The ResourceGroup entitlement aggregation for the Microsoft Entra ID connector no longer fails when GOV-Cloud URIs are configured.
CONETN-4669	The Oracle HCM Cloud connector now correctly aggregates FUTURE_WORKRELATIONSHIP_START_DATE and FUTURE_ASSIGNMENT_ACTION for re-hire workers.
CONETN-4672	The Microsoft SQL Server connector no longer fails when aggregating from an application having the "is_disabled" attribute in its schema.
CONETN-4673	The SAP HR/HCM connector no longer fails during account aggregation when a build map rule is configured.
CONETN-4674	The issue with CLOSE_WAIT connections caused by third-party applications on the IQService

Issue ID	Description
	port has been resolved.
CONETN-4675	The SAP GRC integration now supports provisioning access requests that have special characters in the comments field.
CONETN-4682	The provisioning operation will now be completed successfully if there is a request to add "ProfileID" and remove "Role" in the same request.
CONETN-4685	Group Aggregation remainssuccessful even with over 100 workgroups.
CONETN-4701	The Salesforce Connector will correctly encode and process special characters (<, >, &, ', ") in the password string when utilizing the Password Grant Type for authentication.
CONETN-4710	SCIM 2.0 connector now supports adding groups during create user operation via users endpoint for relax configuration.
CONETN-4711	SAP Concur will no longer fail while provisioning core attributes.
CONETN-4715	The SAP GRC Integration now correctly sets the "Valid from" in the target system based on the configuration of the skipFromDate attribute in the application.
CONETN-4724	The SCIM 2.0 connector no longer fails with a "NullPointerException" when provisioning an account for a non compliant application.
CONETN-4725	SAP GRC connector will now aggregate all the roles with same name assigned to an account.
CONETN-4729	The PeopleSoft Direct connector correctly populates the description of entitlements when an entitlement aggregation is performed.
CONETN-4730	The Microsoft SharePoint server connector now aggregates correct group membership for an account even when a similar group with same name exists in two different sites collections.
CONETN-4735	The Delimited File Connector now executes the pre iterate rule consistently when a partitioned aggregation is performed.
CONETN-4737	The Delimited File connector now correctly populates the stats values for the post iterate rule when an aggregation is performed.
CONETN-4738	Microsoft Entra ID : excludeAttributesFromProvisioning now does not ignores the EXO_Attributes while provisioning of Accounts.
CONETN-4749	The Snowflake connector can now retry all types of errors as specified in the "retryableErrors" list when an aggregation is performed.
CONETN-4765	The Salesforce connector now shows the status as "Failed" for the failed provisioning operation.
CONETN-4774	The Workday Accounts connector now aggregates all the organization roles correctly when a group aggregation is performed.
CONETN-4775	Aggregation for the source connected via Cloud Gateway now works when the http proxy changes the header to small case.
CONETN-4781	The Entra ID connector now correctly initializes the cache only once during account aggreg-

Issue ID	Description
	ation.
CONETN-4786	The Microsoft Entra ID Connector does not cause memory leak issue in case of failed partitioned aggregation.
CONETN-4789	Microsoft Entra ID connector now no longer throws error during provisioning when the attribute value has two words.
CONETN-4790	The Microsoft Entra ID Connector now supports updating the External Email Address of the Mail Contact.
CONETN-4791	The Entra ID Connector no longer fails with error "no threadid found for teamid" while running channel aggregation.
CONETN-4795	SAP Concur connector now aggregates all the accounts correctly when account aggregation is performed.
CONETN-4805	ServiceDesk connector no longer hangs in case of no response from managed system and provisioning operation is timed out after 3 minutes.
CONETN-4809	The Workday connector no longer fails with the "Not supported: http://-javax.xml.XMLConstants/property/accessExternalDTD" error when an account aggregation is performed.
CONETN-4812	The Okta connector no longer fails with ObjectNotFoundException for bulk group provisioning operation.
CONETN-4813	The Cloud Gateway connector is now able to perform a retry operation after a specific delay when encountering the error "Content is not allowed in prolog" for Active Directory connector aggregation.
CONETN-4818	Snowflake connector no longer aggregate Roles with "" appended in the name .
CONETN-4830	The Client Authentication for IQService is now successful when MSA service account is used in application
CONETN-4833	The Workday connector displays an appropriate error message when a provisioning operation with unsupported operation or value is performed.
CONETN-4836	Now, during entitlement aggregation we can aggregate more than 1000 Shared Mailbox.
CONETN-4837	SharePoint account aggregation is successful even when LogiName starts with newline character
CONETN-4839	Microsoft Azure SQL Database connector now supports provisioning and de-provisioning database role when database name matches the server name.
CONETN-4842	The SCIM 2.0 connector no longer fails when the provisioning attributes with the "PUT" operation doesn't exist on the user.
CONETN-4843	The Microsoft Entra ID connector now parses the sharedMailbox membership details correctly.
CONETN-4848	The Microsoft SharePoint Online connector now filters the content storage sites and the per-

Issue ID	Description
	sonal sites (domain-my.sharepoint.com) during the aggregation operation.
CONETN-4850	The LDAP based connector now able to fetch attribute which have values more than 1500 .
CONETN-4852	The Microsoft Entra ID connector now fetches the owners data for all Distribution Groups properly.
CONETN-4858	IQService now supports execution of signed scripts as nativeRules when executionPolicy set to AllSigned.
CONETN-4865	CLOSE_WAIT issues due to connections caused by third-party applications on the IQService port has been addressed
CONETN-4869	The SAP Concur connector can correctly provision accounts that have the "active" attribute set to false.
CONETN-4872	Rest Webservices connector now supports getBaseURL() for requestEndpoint in before/after rule.
CONETN-4874	The Oracle HCM Cloud connector shows detailed error messages on failures when an aggregation is performed.
CONETN-4875	The Microsoft Entra ID Connector now supports removing attribute telephoneNumber.
CONETN-4888	Oracle NetSuite connector now supports provisioning of account schema attributes.
CONETN-4892	The Web Services connector can now parse Byte-Order-Mark (BOM) characters while utilizing XML parsing.
CONETN-4896	Delimited File Connector no longer throws NPE during aggregation with partitioning for csv with no data .
CONETN-4899	The SAP Direct connector no longer fails when connecting with an application whose service account has a username with length greater than 12 characters.
CONETN-4900	SAP Direct no longer fails with OPTION_NOT_VALID error when role name has a trailing white space.
CONETN-4901	The LDAP connector now handles the search filter with negation (!) appropriately.
CONETN-4907	Snowflake connector no longer aggregate duplicate role with "" is after entitlement aggregation.
CONETN-4911	Webservices Connector now doesn't suppress original http error message from managed system during Provisioning operation.
CONETN-4915	The Microsoft Entra ID Connector now works when both userPartitions and userFilters are configured.
CONETN-4917	The SAP Direct connector no longer fails when previewing or aggregating accounts from an application with no "contractualusertype" schema configured.
CONETN-4922	The SuccessFactors connector Single Account aggregation no longer throws a NullPointerException in case of missing picklist value.

Issue ID	Description
CONETN-4923	The Microsoft Dynamics 365 for Finance and Operations connector no longer fails with "Unable to parse additional config attributes to an integer value" when a test connection is performed.
CONETN-4927	The Cloud Gateway connector is now able to perform a successful test connection for applications with the name containing the '+' character.
CONETN-4928	The entitlement aggregation for object type "IAMRole" of the Google Workspace connector no longer fails due to projects that are in pending deletion state.
CONETN-4935	The Microsoft Entra ID connector now provisions the multiple single valued extension attributes (e.g. extension_appld_post) correctly.
CONETN-4936	The Microsoft Entra ID connector no longer fails with Null Pointer Exception while setting the single valued extension attributes (e.g. extension_appld_post).
CONETN-4939	SailPoint's Oracle HCM Cloud connector can now correctly aggregate accounts and groups containing Spanish characters.
CONETN-4940	The Microsoft Active Directory connector is now more resilient in handling the bulk user creation using group Managed Service Account (gMSA) when configured as service account in the application.
CONETN-4942	Microsoft Entra ID Connector is now able to Remove the manager of User when manager value is not sent in the Provisioning Value with Set Operation.
CONETN-4944	Microsoft Entra ID connector is now able to Add/Remove Roles when the Operation of the Account Request is Enable/Disable.
CONETN-4945	Delimited File connector now throws valid exception during test connection and aggregation .
CONETN-4946	IQService-Update Service now registers correct Service name in Windows event logs.
CONETN-4950	The Microsoft Entra ID Connector now supports configuring the number of retries for a PIM cache request under the Attribute maxRetryCount.
CONETN-4952	The entitlement aggregation of the iamResourcePermission object type to the Google Workspace connector no longer fails due to projects/serviceAccounts in a pending deletion state.
CONETN-4954	A Boolean key, "disableInitializeSession," has been introduced to determine whether or not the INITIALIZE_SESSION procedure call should be skipped.
CONETN-4955	The creation of the Stored Procedure call is updated to ensure the correct procedure is invoked, ensuring that the password_no_of_days updates correctly.
CONETN-4956	SAP HR aggregation will no longer fail with nullpointer exception.
CONETN-4960	SailPoint's Ivanti Cherwell Service Desk connector now processes the empty array in the request payload.
CONETN-4961	The Web Services connector now supports generating a new refresh token in cases where the oauth_token_info parameter stored in the application config is corrupted. This functionality also

Issue ID	Description
	extends to forced Test Connection operations that are initiated from the connector configuration interface.
CONETN-4962	The Microsoft Sharepoint Online connector no longer fails while running aggregations using authentication type JWT Certificate Credentials.
CONETN-4964	Active Directory aggregation via IdentityIQ Cloud Gateway now runs successfully without going into a loop when Promote Managed Attribute is set to the Task definition.
CONETN-4965	SailPoint's Oracle HCM Cloud connector no longer throws Null Pointer Exception when the lastAggregation date is in the DD/MM/YYYY format.
CONETN-4970	The SAP Direct Connector can now retry provisioning operations when retry parameters are configured.
CONETN-4971	SailPoint's Microsoft SQL Server connector now supports deleting an account when an application with the JTDS driver is configured.
CONETN-4974	Microsoft SharePoint Online Connector now bring the AdminOfSites during Account aggregation.
CONETN-4975	SCIM 2.0 connector no longer goes into loop in case of retryable Errors mentioned in application.
CONETN-4976	The Oracle ERP connector now supports custom path for role definition when aggregating data access objects.
CONETN-4977	SailPoint's Oracle EPM Cloud integration can now aggregate all accounts correctly with a configurable useApprolesExtension parameter.
CONETN-4978	SailPoint's SAP GRC connector now correctly bypasses the system configured in application when a provisioning operation is performed.
CONETN-4979	warn logger statement changed to debug level
CONETN-4980	SAP GRC no more throws Sleep interrupt while checking status.
CONETN-4981	Azure SQL Server Connector will no longer fail while aggregating server roles.
CONETN-4982	Workday connector now handles the corrected worker.
CONETN-4983	SailPoint's BMC Helix ITSM Service Desk integration now shows the proper error message when a request fails with authentication error code 401.
CONETN-4987	SAP Direct Connector Entitlement aggregation will not throw ArrayIndexOutOfBoundsException in case of bad data in AGR1251
CONETN-4989	SCIM 2.0 Connector no longer throws Class Cast Exception for Enable Disable operation when Provision Multivalued Compatibility flag is set to true.
CONETN-4990	The Microsoft Entra ID connector can now aggregate the sharedMailbox with readable DisplayName and GUID instead of only GUID when the attribute "useDisplayNameForSharedMailbox" is configured in the source/application.

Issue ID	Description
CONETN-4991	SAP GRC connector no longer stops aggregation if invalid data is encountered.
CONETN-4992	The Microsoft Entra ID VA Based Connector now properly shows the value of managedIdentity_tags attribute on ISC Identity.
CONETN-4993	IQService now releases memory during aggregation when exchange online is configured For Microsoft Entra ID connector.
CONETN-4994	SailPoint's Workday Accounts connector now correctly aggregates accounts, even when the Disable Optimization option is enabled.
CONETN-4995	The application xml file will now persist and will not modify randomly during multiple thread provisioning operations when the Active Directory connector is configured with Cloud Gateway.
CONETN-4996	Aggregation Should not fail when same person has two records with same START_DATE.
CONETN-4997	SuccessFactors connector now supports server side pagination by enabling flag CON_SUCCESSFACTORS_ADD_SERVER_SIDE_PAGING.
CONETN-4998	We are regenerating the access token explicitly during aggregation in case of expiration.
CONETN-5000	Active Directory provisioning errors are shown correctly on UI when setAttributeLevelResult is configured as true.
CONETN-5001	Oracle EBS connector now fetches PASSWORD_EXPR and PASSWORD_NO_OF_DAYS correctly during account aggregation.
CONETN-5003	The Microsoft Entra ID connector no longer fails with Null Pointer Exception when handling deleted channels.
CONETN-5006	The SAP GRC Integration now correctly sends the Requester information to target system as provided in the Before Provisioning rule.
CONETN-5007	SailPoint's JDBC connector now aggregates group hierarchical information correctly during a group aggregation with the merging option enabled.
CONETN-5009	Workday Connector now no longer shows IS_RESCINDED as true for Corrected Users who are outside of Effective offset
CONETN-5011	SailPoint's AWS Identity Center connector no longer throws a "Member must not be null" error when an account aggregation is performed.
CONETN-5012	SailPoint's SuccessFactors connector now aggregates the PersonID External value for external users when a targeted account aggregation is performed.
CONETN-5018	The specified directory service attribute or value already exists error will not get thrown while provisioning countryCode.
CONETN-5019	Provisioning of person number with multiple work relationship no longer fails.
CONETN-5020	The Oracle E-Business Integration now correctly provisions the PASSWORD_EXP attribute value between Days, Access and None.
CONETN-5022	The Active Directory connector will no longer print repetitive info level logs during partition

Issue ID	Description
	aggregation.
CONETN-5029	The SCIM 2.0 connector now updates the email.work.primary.value, familyName, and givenName without any errors.
CONETN-5030	Dynamics 365 FO connector no longer fails for bulk removal.
CONETN-5031	Oracle ERP Cloud connector now throws more readable and understandable exception during data access group aggregation failure.
CONETN-5032	The SuccessFactors connector now supports server-side pagination to support aggregation processes which handle a large number of employees
CONETN-5033	The Cloud Gateway connector now creates posixgroup and nisNetgroup for load balancing.
CONETN-5037	JDBC connector no longer dump the unwanted warning message after aggregation.
CONETN-5040	Dynamics 365 CRM connector now supports retry for Add entitlement operation.
CONETN-5047	Oracle EBS connector now fetch proper value for disableInitializeSession flag
CONETN-5048	SCIM 2.0 VA based Connector now no longer fails with Class Cast Exception when the user Id is of type Integer
CONETN-5050	SCIM 2.0 Connector now supports Simple Extended Multivalued attribute in Create Operation.
CONETN-5051	AWS IAM Identity center connector now able to provision entitlement passed as list.
CONETN-5057	JackHenry Connector now correctly handle the "errorCompareString" and Implementation for "Custom Soap Headers"
CONETN-5058	Oracle EPM Cloud Connector now no longer fails with ERROR "User with same name already exists" when create operation is triggered on module for existing IDCS user
CONETN-5059	Dynamics 365 FO use Account request native identity for provisioning operation.
CONETN-5061	The Workiva connector no longer fails with error ClassNotFoundException while running test connection and aggregations.
CONHOWRAH-4700	The Active Directory connector now has the TLS option enabled by default during creation of a new application to enforce a secure communication over the network.
CONHOWRAH-4901	The Active Directory connector now handles the resource leaks, specifically Connection Eviction threads, gracefully while fetching the appRoleAssignments memberships during account aggregation.
CONHOWRAH-4980	The Directories bundle has now been upgraded to the latest version of joda-time-2.12.7.jar.
CONHOWRAH-5371	The Google Workspace connector now prevents logging the sensitive information related to JWT token during connection.
CONHOWRAH-5508	The Microsoft Entra ID connector now handles the aggregation filter correctly during the partitioned account aggregation.

Issue ID	Description
CONJUBILEE-2065	A security vulnerability for default file within Tomcat has been fixed for the Cloud Gateway. It is recommended to update the Cloud gateway by performing steps mentioned in the documentation https://documentation.sailpoint.com/connectors/identityiq/cloud_gateway/help/cloud_gateway/security_vulnerability.html
CONJUBILEE-2066	A security vulnerability for HSTS header within tomcat has been fixed for Cloud Gateway. It is recommended to update the Cloud gateway by performing steps mentioned in the documentation https://documentation.sailpoint.com/connectors/identityiq/cloud_gateway/help/cloud_gateway/security_vulnerability.html
CONJUBILEE-2243	The Privileged Account Management (PAM) collector now displays single privilege data inside containers.
CONJUBILEE-2689	The SailPoint Tools Base64 implementation is deprecated and no longer available to use.
CONJUBILEE-3058	SailPoint's Jack Henry Symitar connector now supports custom SOAPAction headers in request execution.
CONJUBILEE-3127	The default version of Apache Tomcat in IdentityIQ Cloud Gateway is now 9.0.97.
CONJUBILEE-3369	The Cloud Gateway connector now includes Apache Tomcat 9.0.104.
CONNAMDANG-4930	Upgraded the Vulnerable Library MySQL jar to version mysql-connector-j-9.0.0 to mitigate a security vulnerability.
CONSEALINK-4067	EPIC SER Connector now honors the Update Contact Comment Checkbox.
CONSEALINK-5239	Removed commons-httpclient-3.1/commons-httpclient.jar from connector-bundle-collaboration-connectors.
CONSEALINK-5321	Upgraded org.bouncycastle:bcpkix-jdk18on from 1.77 to 1.78.1.
CONSEALINK-5322	Upgraded org.bouncycastle:bcprov-jdk18on from version 1.77 to 1.78.1.
CONSEALINK-5819	Upgraded the Vulnerable Library json-20230227.jar to json-20231013.jar to mitigate a security vulnerability.
CONSEALINK-6432	SailPoint's Cerner Healthcare connector no longer fails during aggregation if the phone number is set as Internal Secure.
CONUMSHIAN-5332	SailPoint has applied recent security updates to our SAP Portal integration by upgrading the gson jar in the SDA file. To protect your privacy, using the latest SDA file is highly advised.
CONUMSHIAN-8518	The SAP GRC connector now handles bad data for entitlement aggregation by avoiding the null pointer exception.