Status	Finished
Started	Sunday, 2 November 2025, 10:48 AM
Completed	Sunday, 2 November 2025, 11:34 AM
Duration	45 mins 20 secs

Question **1**	Write a program that prints a simple chessboard.
Correct	

Input format:

The first line contains the number of inputs T.
The lines after that contain a different values for size of the chessboard

Output format:

Print a chessboard of dimensions size * size. Print a Print W for white spaces and B for black spaces.

Input:

2
3
5

Output:

WBW
BWB
WBW
WBWBW
BWBWB
WBWBW
BWBWB
WBWBW

Answer: (penalty regime: 0 %)

```
1  #include<stdio.h>
2  int main()
3  {
4      int n;
5      int size,i,j,count;
6      char ch,first,second;
7      scanf("%d",&n);
8      while(n--){
9          scanf("%d",&size);
10         scanf("%c",&ch);
11         if(ch=='W'){
12             first='W';
13             second='B';
14         }
15         else{
16             first='B';
```

	Input	Expected	Got	
⊘	2 3 5	WBW BWB WBW WBWBW BWBWB WBWBW BWBWB WBWBW	WBW BWB WBW WBWBW BWBWB WBWBW BWBWB WBWBW	⊘

Passed all tests! ⊘

Question **2**

Correct

Let's print a chessboard!

Write a program that takes input:

The first line contains T, the number of test cases

Each test case contains an integer N and also the starting character of the chessboard

Output Format

Print the chessboard as per the given examples

Sample Input / Output

Input:

2
2 W
3 B

Output:

WB
BW
BWB
WBW
BWB

Answer: (penalty regime: 0 %)

```
 1  #include<stdio.h>
 2  int main(){
 3      int t;
 4      scanf("%d",&t);
 5      while(t--){
 6          int n,i,j;
 7          char other,start;
 8          scanf("%d %c",&n,&start);
 9          other=(start=='W')?'B':'W';
10          for(i=0;i<n;i++){
11              for(j=0;j<n;j++){
12                  if((i+j)%2==0)
13                      printf("%c",start);
14                  else
15                      printf("%c",other);
16              }
```

	Input	Expected	Got	
✓	2 2 W 3 B	WB BW BWB WBW BWB	WB BW BWB WBW BWB	✓

Passed all tests! ✓

Question **3**

Correct

Problem Statement:

In a small coding competition, participants are to be grouped into teams of three members, each membe
The rule of the competition states that no member can repeat within the same team.

Write a program to display all possible unique team combinations that can be formed using the membe

Sample Output:

1 2 3

1 3 2

2 1 3

2 3 1

3 1 2

3 2 1

Answer: (penalty regime: 0 %)

```c
#include<stdio.h>
int main(){
    int i, j, k;
    for(i=1;i<=3;i++){
        for(j=1;j<=3;j++){
            for(k=1;k<=3;k++){
                if(i !=j&&j !=k&&i !=k){
                    printf("%d %d %d\n",i,j,k);
                }
            }
        }
    }
    return 0;
}
```

	Expected	Got	
⊘	1 2 3 1 3 2 2 1 3	1 2 3 1 3 2 2 1 3	⊘

	Expected	Got	
	2 3 1	2 3 1	
	3 1 2	3 1 2	
	3 2 1	3 2 1	

Passed all tests! ⊘