Status	Finished
Started	Wednesday, 15 October 2025, 12:07 PM
Completed	Wednesday, 15 October 2025, 12:42 PM
Duration	35 mins 7 secs
Marks	3.00/3.00
Grade	**10.00** out of 10.00 (**100**%)

Question **1**

Correct

Mark 1.00 out of 1.00

Objective

This is a simple challenge to help you practice printing to stdout.|

We're starting out by printing the most famous computing phrase of all time! In the editor below, use eit ***World!*** to stdout.

Input Format

You do not need to read any input in this challenge.

Output Format

Print ***Hello, World!*** to stdout.

Sample Output

Hello, World!

Answer: (penalty regime: 0 %)

```
#include<stdio.h>
int main()
{
    printf("Hello, World!");
    return 0;
}
```

	Expected	Got	

	Expected	Got	
✓	`Hello, World!`	`Hello, World!`	✓

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.

Question **2**

Correct

Mark 1.00 out of 1.00

Objective

This challenge will help you to learn how to take a character, a string and a sentence as input in C.

To take a single character ***ch*** as input, you can use scanf("%c", &ch); and printf("%c", ch) writes a characte

char ch;

scanf("%c", &ch);

printf("%c", ch);

This piece of code prints the character ***ch***.

Task

You have to print the character, ***ch***.

Input Format

Take a character, ***ch*** as input.

Output Format

Print the character, ***ch***.

Answer: (penalty regime: 0 %)

```
#include<stdio.h>
int main ()
{
    char ch;
    scanf("%c",&ch);
    printf ("%c",ch);
    return 0 ;
}
```

	Input	Expected	Got	

	Input	Expected	Got	
✓	c	c	c	✓

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.

Question **3**

Correct

Mark 1.00 out of 1.00

Objective

The fundamental data types in c are int, float and char. Today, we're discussing int and float data types.

The printf() function prints the given statement to the console. The syntax is printf("format string",argum integer, character, string or float as argument, then in the format string we have to write %d (integer), %

The scanf() function reads the input data from the console. The syntax is scanf("format string",argument_ reads integer number from the console and stores the given value in variable ***number***.

To input two integers separated by a space on a single line, the command is scanf("%d %d", &n, &m), wh

Task

Your task is to take two numbers of int data type, two numbers of float data type as input and output the

1. Declare ***4*** variables: two of type int and two of type float.
2. Read ***2*** lines of input from stdin (according to the sequence given in the 'Input Format' section below)
3. Use the **+** and **-** operator to perform the following operations:
* Print the sum and difference of two int variable on a new line.
* Print the sum and difference of two float variable rounded to one decimal place on a new line.

Input Format

The first line contains two integers.

The second line contains two floating point numbers.

Constraints

· ***1 ≤ integer variables ≤ 10^4***
· ***1 ≤ float variables ≤ 10^4***

Output Format

Print the sum and difference of both integers separated by a space on the first line, and the sum and diff separated by a space on the second line.

Sample Input

10 4
4.0 2.0

Sample Output

14 6
6.0 2.0

Explanation

When we sum the integers ***10*** and ***4***, we get the integer ***14***. When we subtract the second number ***4*** fro
difference.

When we sum the floating-point numbers ***4.0*** and ***2.0***, we get ***6.0***. When we subtract the second numbe
their difference.

Answer: (penalty regime: 0 %)

```c
#include<stdio.h>
int main()
{
    int a,b;
    float x,y;
    scanf("%d %d \n", &a,&b);
    scanf(" %f %f ",&x,&y);
    printf("%d %d \n",a+b,a-b);
    printf("%.1f %.1f",x+y,x-y);
}
```

	Input	Expected	Got	
✓	10 4 4.0 2.0	14 6 6.0 2.0	14 6 6.0 2.0	✓
✓	20 8 8.0 4.0	28 12 12.0 4.0	28 12 12.0 4.0	✓

Passed all tests!

Correct

Marks for this submission: 1.00/1.00.