

Support — Error Playbook

Every error the Verify API returns, and what to do with it — meaning, action, the reply to send the customer, and whether to escalate.

Generated 2026-08-19

Every error looks like this

```
{
  "timestamp": "2026-08-19T10:45:31Z",
  "errorCode": 1302,
  "error": "UNPROCESSABLE_ENTITY",
  "message": "Fingerprint did not match the national ID",
  "requestId": "019fad7e-6726-7436-9b0a-64c2255a1477"
}
```

Three habits that resolve most tickets

1. Grab the requestId first — it's in the body and the X-Request-Id header. Nothing can be traced without it.
2. Read errorCode, not just the HTTP status — the code is precise; the status groups many causes.
3. Never accept a fingerprint image or PIN over chat/email — ask for the requestId and national number instead.

● Guide the customer — they can fix it ● Account / config — you or ops act ● Escalate — contact dev / ops

Request & Biometrics the data or the fingerprint

1002 Validation failed / Invalid biometrics

VALIDATION_FAILED

HTTP 400

Guide the customer

WHAT IT MEANS

A field failed validation, or — most often — the fingerprint image couldn't be read. The message shows “MOI 220 · Invalid biometrics” or “203 · Bad image format” for the biometric case.

WHAT TO DO

Ask the customer to recapture the fingerprint: clean the sensor, place the finger flat and firm, use the correct finger, and send a valid WSQ image. For a field error, point them to the field named in the message.

REPLY TO THE CUSTOMER

“The fingerprint couldn't be read clearly. Please clean the sensor, place the finger flat and firmly, and recapture the print, then try again. Make sure it's the correct finger for this person.”

ESCALATE? **Sometimes** — Only if good-quality captures keep failing — then send dev the requestId + a sample.

1302 Fingerprint did not match the ID

BIOMETRIC_NO_MATCH

HTTP 422

[Guide the customer](#)

WHAT IT MEANS

The national ID exists, but the fingerprint did not match that person. This is a correct, deliberate rejection — not a fault. No personal data is returned.

WHAT TO DO

Confirm the right person and finger are being used, then recapture and retry. Repeated no-match usually means the wrong person/finger or a poor capture.

REPLY TO THE CUSTOMER

“The fingerprint did not match this national ID. Please confirm you're verifying the correct person and finger, recapture the print, and try again.”

ESCALATE? **No** — No — this is a genuine result from Yemen ID. Do not override a no-match.

1301 National number not found

NOT_FOUND

HTTP 404

[Guide the customer](#)

WHAT IT MEANS

The national ID number was not found in the Yemen ID database.

WHAT TO DO

Check the number was entered correctly — 12 digits, format NNNN-NNNN-NNNN. A typo is the usual cause.

REPLY TO THE CUSTOMER

“This national ID number was not found. Please double-check the number (12 digits) and try again.”

ESCALATE? **No** — No — a real result from Yemen ID.

1001 Bad request

BAD_REQUEST

HTTP 400

[Guide the customer](#)

WHAT IT MEANS

The request wasn't formatted correctly — malformed JSON, a missing required field, or a wrong data type.

WHAT TO DO

Have the client check their request body against the API docs / Postman collection: valid JSON, required fields present, correct field names.

REPLY TO THE CUSTOMER

“The request wasn't formatted correctly. Please check it against the integration guide — valid JSON and all required fields — then try again.”

ESCALATE? **Sometimes** — Only if the request genuinely looks correct — send dev the requestId.

1101 Authentication required

UNAUTHENTICATED

HTTP 401

[Guide the customer](#)

WHAT IT MEANS

No credentials were sent, or the auth header was malformed. The client isn't sending their API key correctly.

WHAT TO DO

Confirm they use HTTP Basic auth — clientId as username, clientSecret as password — on every call.

REPLY TO THE CUSTOMER

“Your request is missing authentication. Please send your API key using HTTP Basic auth — client ID as the username and client secret as the password — on every request.”

ESCALATE? **No** — No.

1102 Invalid credentials

INVALID_CREDENTIALS

HTTP 401

[Account / config](#)

WHAT IT MEANS

The clientId/clientSecret is wrong, revoked, or expired. (Rarely, on verify, it means Yemen ID rejected our internal token — that's on us.)

WHAT TO DO

Confirm the client ID. If the secret was lost or the key revoked, arrange a re-issue. If the message references MOI / token, treat it as a backend issue and escalate.

REPLY TO THE CUSTOMER

“Your API credentials were not accepted. Please double-check your client ID and secret. If the secret was lost, we can issue you a new key — let us know.”

ESCALATE? **Sometimes** — Only if the credentials are confirmed correct — possible Yemen ID token issue → dev/ops.

1201 Access denied (IP allow-list)

FORBIDDEN

HTTP 403

[Account / config](#)

WHAT IT MEANS

The request was blocked — most commonly the caller's IP address isn't on the allow-list for their API key.

WHAT TO DO

Ask for the client's server (egress) IP and add it to their credential's allow-list, or confirm the existing entry.

REPLY TO THE CUSTOMER

“Access was denied — your server's IP address may not be on the approved list for your API key. Please share the IP address your requests come from and we'll allow it.”

ESCALATE? **Sometimes** — To ops — to update the allow-list (not a bug).

1202 Not entitled by plan

ENTITLEMENT_DENIED

HTTP 403

[Account / config](#)

WHAT IT MEANS

The client's subscription/plan doesn't include the operation they called (or the subscription is inactive/expired).

WHAT TO DO

Check their active subscription and plan in the admin portal. Route upgrades to sales/ops.

REPLY TO THE CUSTOMER

"Your current plan doesn't include this operation, or your subscription isn't active. Please contact us to enable it or upgrade your plan."

ESCALATE? **No** — No — sales / ops handle plan changes.

Client Portal — PIN only on the portal Transactions page

1203 PIN unlock required

PIN_UNLOCK_REQUIRED

HTTP 423

[Guide the customer](#)

WHAT IT MEANS

The portal's Transactions page is PIN-protected; the user must enter their PIN before it opens.

WHAT TO DO

Tell the portal user to enter their PIN when prompted.

REPLY TO THE CUSTOMER

"The Transactions page is protected by a PIN. Please enter your PIN when prompted to view it."

ESCALATE? **No** — No.

1204 Invalid PIN

INVALID_PIN

HTTP 401

[Guide the customer](#)

WHAT IT MEANS

The PIN entered for the portal Transactions page was incorrect.

WHAT TO DO

Ask them to re-enter carefully. If forgotten, an admin can reset the PIN from the portal.

REPLY TO THE CUSTOMER

"That PIN was incorrect. Please try again. If you've forgotten it, we can reset it for you."

ESCALATE? **No** — No — an admin resets the PIN if needed.

1403 Insufficient wallet balance

INSUFFICIENT_FUNDS

HTTP 402

[Account / config](#)

WHAT IT MEANS

The client is on prepaid billing and their wallet balance is too low to charge this transaction.

WHAT TO DO

Check their wallet in the admin portal. Process a top-up, or approve their pending top-up request. Loop in finance if payment is needed.

REPLY TO THE CUSTOMER

“Your wallet balance is too low to process this request. Please top up your wallet — or submit a top-up request from the portal — and we'll credit it.”

ESCALATE? **Sometimes** — To finance / ops — to credit the wallet (not a bug).

1402 Quota / rate limit exceeded

QUOTA_EXCEEDED

HTTP 429

[Account / config](#)

WHAT IT MEANS

The client hit a rate limit (too many requests too fast) or their plan's usage quota.

WHAT TO DO

Check their usage. Advise slowing the request rate and retrying shortly; route quota increases to sales/ops.

REPLY TO THE CUSTOMER

“You've reached your usage limit. Please slow your request rate and try again shortly. If you need a higher limit, contact us to raise your quota.”

ESCALATE? **No** — No — ops / sales adjust quotas.

1401 Conflict

CONFLICT

HTTP 409

[Account / config](#)

WHAT IT MEANS

The request conflicts with the current state — usually something that already exists (e.g. a duplicate). The message names the conflict.

WHAT TO DO

Read the message to see what conflicts, then advise accordingly (e.g. the record already exists — no need to re-create).

REPLY TO THE CUSTOMER

“This request conflicts with existing data — it looks like the item already exists. Please review and, if needed, use the existing record.”

ESCALATE? **Sometimes** — Only if the conflict makes no sense for what they sent — then dev with the requestId.

2103 Verification service unavailable

CONNECTOR_UNAVAILABLE

HTTP 503

Escalate

WHAT IT MEANS

The Yemen ID (MOI) backend is unreachable — the service is down or the VPN tunnel to it is down. This usually affects all customers at once.

WHAT TO DO

Escalate to ops immediately. Note it likely hits every client. Ops checks the VPN tunnel (moi-vpn.service) and MOI availability.

REPLY TO THE CUSTOMER

“The verification service is temporarily unavailable. Our team is already working to restore it. Please try again shortly — no action is needed on your side.”

ESCALATE? **Yes** — Yes — ops, urgent (VPN / MOI outage).

2102 Verification service timed out

CONNECTOR_TIMEOUT

HTTP 504

Escalate

WHAT IT MEANS

The Yemen ID (MOI) backend was too slow to respond within the timeout.

WHAT TO DO

Have them retry once. If it persists, escalate to ops to check the VPN tunnel and MOI latency.

REPLY TO THE CUSTOMER

“The verification service is responding slowly right now. Please try again in a moment. If it keeps happening, let us know — we're monitoring it.”

ESCALATE? **Yes** — Yes if it persists — ops (VPN / MOI latency).

2101 Verification service error

CONNECTOR_ERROR

HTTP 502

Escalate

WHAT IT MEANS

The Yemen ID (MOI) backend returned an error or an unexpected response we couldn't process.

WHAT TO DO

Escalate to dev/ops with the requestId and timestamp. Have the customer retry shortly.

REPLY TO THE CUSTOMER

“The verification service returned a temporary error. Please try again shortly. We've logged it and are looking into it.”

ESCALATE? **Yes** — Yes — dev / ops with the requestId.

2001 Internal server error

INTERNAL_ERROR

HTTP 500

Escalate

WHAT IT MEANS

An unexpected error inside our platform — a bug or a transient fault, not something the customer did.

WHAT TO DO

Capture the requestId + timestamp and escalate to dev. Ask the customer to retry.

REPLY TO THE CUSTOMER

“A temporary error occurred on our side — nothing to fix on yours. Please try again. We've already logged it and are investigating.”

ESCALATE? **Yes** — Yes — dev with the requestId (always).

When you escalate — hand this to dev/ops

Include every item — a ticket without a requestId can't be traced.

- requestId — from the response body / X-Request-Id
- Timestamp (UTC) of the failed call
- errorCode + the full message
- HTTP status returned
- Client — tenant name or client ID (never the secret)
- Endpoint called + national number tried
- Frequency — once, or ongoing since when
- Scope — one client or several

Privacy — non-negotiable. Never collect or forward fingerprint images or PINs. The requestId lets dev pull the full (redacted) trace safely — that's all they need.