Exp No:10

Internetworking With Router In Cisco Packet Tracer Simulator

Aim:

To design and configure different network using a router in Cisco packet tracer.

Procedure:

i) Open Cisco packet tracer and place one router, two switch and 4 PCs.

ii) Connect two PCs to each switch using ethernet cable.

iii) Connect both switchs to the router.

iv) Assign static IP address to all PCs and router interface.

Device	IP Address	Subet mask	Gateway
PC_0	192.168.1.2	255.255.255.0	192.168.1.1
PC_1	192.168.1.3	255.255.255.0	192.168.1.1
PC_2	192.168.2.2	255.255.255.0	192.168.2.1
PC_3	192.168.2.3	255.255.255.0	192.168.2.1

Router Configuration;

```
enable
configure terminal
interface gigabit Ethernet 0/0
IP Address 192.168.1.1. 255.255.0
no shut down
exit.
```

6) Design and configure an internetwork using a wireless router, DHCP Server, and internet cloud.

AIM: To configure a wireless network using a wireless router, DHCP and an internet cloud.

PROCEDURE:

* Place a wireless router, PCs or laptops, and an internet cloud in cisco packet tracer.
* Connect the internet cloud to the wireless routers internet port
* Enable DHCP on the wireless router.
* Configure the wireless SSID and password.
* Connect laptop to the wireless network.
* Test connectivity using the ping command.

RESULT: The wireless network is configured, and device receiv IP address automatically through DHCP.

c) Design and configure an internetwork in your Lab using a switch, router, and ethernet cables.

AIM: To establish communication between computer using a switch, router and ethernet cables.

PROCEDURE:

* Place a router, one switch, and 3-4 PCs in cisco packet tracer.
* Connect all PCs to the switch using ethernet cables.
* Assign IP address to the PCs in the same subnet.
* Enable the router interface using the no shutdown command.
* Test communication using the ping command.

RESULT: The internetwork is configured successfully and communication between connected device is verified using ping.