EXP. No: 11

ROUTING AT NETWORK LAYER

a)

AIM: To configure static routing between two network using cisco packet tracer.

PROCEDURE:

* Place two router, two switchs and 4 PCs.
* Connect PCs to switch and switchs to router.
* Connect the two router using an ethernet link.
* Assign IP address to all PCs and router interface.
* Configure static router on both router.

Router 1 Configuration:

```
enable
configure terminal
interface gigabit ethernet 0/0
IP address 192.168.1.1 255.255.255.0
no shutdown
exit
```

Router 2 Configuration:

```
enable
configure terminal
interface gigabit ethernet 0/0
IP address 192.168.2.1 255.255.255.0
no shutdown
exit
```

RESULT: Statics routing is configure successfully.

b) Simulate RIP using cisco packet tracer

AIM: To configure the routing information protocol (RIP) for communication between different network.

PROCEDURE:

* Create a topology with two router & two LANs.
* Assign IP Addresses to router interface and PCs.
* Enable RIP on both routers.
* Advertise the connected network.
* Test connectivity using the ping command.

Router 1 Configuration:

```
enable
configure terminal
router rip
version 2
no auto-summary.
network 192.168.1.0   10.0.0.0
end
```

Router 2 Configuration:

```
enable
Configure terminal
router rip
version 2
no auto-summary
network 192.168.1.0   10.0.0.0
end.
```

Testing: Show IP route
Ping 192.168.2.2

RESULT: RIP is configured successfully and the router exchange routing information to communicate between network.