


SMT & THROUGH-HOLE BOARD STACKERS

(2.00 mm) .0787" PITCH • TW SERIES

CLT or MMS	SQT
8	4
G b p s	G b p s



TW

Board Mates:

CLT, SQT, SQW, ESQT,
TLE, SMM, MMS

Cable Mates:

TCSD

SPECIFICATIONS

Insulator Material:

Black Liquid Crystal Polymer
Terminal Material:
Phosphor Bronze

Plating:

Sn or Au over
50 μ " (1.27 μ m) Ni

Current Rating:

TW-SM = 4.9 A per pin
(2 pins powered)
TW-TH = 5.2 A per pin
(2 pins powered)

Operating Temp Range:

-55 °C to +105 °C with Tin;
-55 °C to +125 °C with Gold






PROCESSING





Lead-Free Solderable:

Yes

SMT Lead Coplanarity:

(0.15 mm) .006" max*
*(.004" stencil solution
may be available; contact
ipg@samtec.com)

TW	NO. PINS PER ROW	LEAD STYLE	PLATING OPTION	ROW OPTION	STACKER HEIGHT	SM	OTHER OPTION																				
	02 thru 36	Specify LEAD STYLE from chart	-F = Gold flash on post, Matte Tin on tail -L = 10 μ" (0.25 μm) Gold on post, Matte Tin on tail -T = Matte Tin	-S = Single Row -D = Double Row	- "XXX" = Stacker Height in inches (0.13 mm) .005" increments Example: -250 = (6.35 mm) .250"		- "XXX" = Polarized Position -A = Alignment Pin (Metal or plastic at Samtec discretion) (4.83 mm) .190" min. board space (-D only) -P = Pick & Place Pad (1.91 mm) .075" min. post height (04-36 only) - "X"R Specify "T" for Tape & Reel Specify "F" for Full Reel Tape & Reel (must order max. quantity per reel; contact Samtec for quantity breaks) (-07 lead style N/A) (-06 lead style with -P option N/A as standard)																				
																											
		<table><tr><th>LEAD STYLE</th><th>OAL</th></tr><tr><td>-02</td><td>(7.85) .309</td></tr><tr><td>-03</td><td>(11.86) .467</td></tr><tr><td>-04</td><td>(12.37) .487</td></tr><tr><td>-06</td><td>(15.37) .605</td></tr><tr><td>-07</td><td>(17.35) .683</td></tr><tr><td>-09</td><td>(9.86) .388</td></tr></table>		LEAD STYLE	OAL	-02	(7.85) .309	-03	(11.86) .467	-04	(12.37) .487	-06	(15.37) .605	-07	(17.35) .683	-09	(9.86) .388	<table><tr><th>ROW OPTION</th><th>A</th></tr><tr><td>-S</td><td>(5.08) .200</td></tr><tr><td>-D</td><td>(6.35) .250</td></tr></table>		ROW OPTION	A	-S	(5.08) .200	-D	(6.35) .250		
LEAD STYLE	OAL																										
-02	(7.85) .309																										
-03	(11.86) .467																										
-04	(12.37) .487																										
-06	(15.37) .605																										
-07	(17.35) .683																										
-09	(9.86) .388																										
ROW OPTION	A																										
-S	(5.08) .200																										
-D	(6.35) .250																										

TW	NO. PINS PER ROW	LEAD STYLE	PLATING OPTION	ROW OPTION	STACKER HEIGHT	TAIL SPEC																																	
	02 thru 50	Specify LEAD STYLE from chart	-F = Gold flash on post, Matte Tin on tail -L = 10 μ" (0.25 μm) Gold on post, Matte Tin on tail -T = Matte Tin	-S = Single Row -D = Double Row -T = Triple Row -Q = Four Row -5 = Five Row -6 = Six Row	- "XXX" = Stacker Height in inches (0.13 mm) .005" increments Example: -250 = (6.35 mm) .250"	- "XXX" = Tail Length in inches (0.13 mm) .005" increments Example: -150 = (3.81 mm) .150" - "XXX" = Polarized Position (Specify position to be removed)																																	
																																							
-S, -D*, -Q		-T, -5, -6																																					
																																							
-S, -D*, -Q		-T, -5, -6																																					
		<table><tr><th>LEAD STYLE</th><th>OAL</th></tr><tr><td>-01</td><td>(8.20) .323</td></tr><tr><td>-02</td><td>(9.60) .377</td></tr><tr><td>-03</td><td>(13.60) .535</td></tr><tr><td>-04</td><td>(14.10) .555</td></tr><tr><td>-05</td><td>(15.10) .594</td></tr><tr><td>-06</td><td>(17.10) .673</td></tr><tr><td>-07</td><td>(19.10) .751</td></tr><tr><td>-08*</td><td>(21.10) .830</td></tr><tr><td>-09</td><td>(11.60) .456</td></tr><tr><td>-10</td><td>(15.60) .614</td></tr><tr><td>-11</td><td>(10.08) .397</td></tr><tr><td>-12*</td><td>(28.19) 1.110</td></tr></table>		LEAD STYLE	OAL	-01	(8.20) .323	-02	(9.60) .377	-03	(13.60) .535	-04	(14.10) .555	-05	(15.10) .594	-06	(17.10) .673	-07	(19.10) .751	-08*	(21.10) .830	-09	(11.60) .456	-10	(15.60) .614	-11	(10.08) .397	-12*	(28.19) 1.110	<table><tr><th>ROW OPTION</th><th>STACKER HEIGHT</th></tr><tr><td>-S, -D*, -Q</td><td>(3.05) .120 MIN</td></tr><tr><td>-T, -5, -6</td><td>(4.06) .160 MIN</td></tr></table>		ROW OPTION	STACKER HEIGHT	-S, -D*, -Q	(3.05) .120 MIN	-T, -5, -6	(4.06) .160 MIN	*-D with stacker height greater than (4.06 mm) .160" will not have standoffs.	
LEAD STYLE	OAL																																						
-01	(8.20) .323																																						
-02	(9.60) .377																																						
-03	(13.60) .535																																						
-04	(14.10) .555																																						
-05	(15.10) .594																																						
-06	(17.10) .673																																						
-07	(19.10) .751																																						
-08*	(21.10) .830																																						
-09	(11.60) .456																																						
-10	(15.60) .614																																						
-11	(10.08) .397																																						
-12*	(28.19) 1.110																																						
ROW OPTION	STACKER HEIGHT																																						
-S, -D*, -Q	(3.05) .120 MIN																																						
-T, -5, -6	(4.06) .160 MIN																																						
				*Style -08 & -12 = S & D only																																			

Notes:

For added mechanical stability, Samtec recommends mechanical board spacers be used in applications with gold or selective gold plated connectors. Contact ipg@samtec.com for more information.

This Series is non-standard, non-returnable.

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Samtec:](#)

[TW-11-12-G-D-660-150](#) [TW-27-07-G-D-415-165](#) [TW-06-09-G-T-220-100](#) [TW-20-05-G-D-160-090](#) [TW-40-10-L-D-374-102](#) [TW-10-03-S-S-230-110](#) [TW-30-03-G-Q-165-100](#) [TW-10-03-S-Q-255-150](#) [TW-13-07-G-D-450-125](#) [TW-06-12-G-D-475-220](#) [TW-08-08-G-D-370-195](#) [TW-04-06-G-D-395-120](#) [TW-03-03-G-D-120-100](#) [TW-02-06-G-D-395-120](#) [TW-03-07-G-D-390-110](#) [TW-04-03-G-S-250-090](#) [TW-02-03-T-D-185-075](#) [TW-02-09-T-S-215-121](#) [TW-02-03-T-S-315-075](#) [TW-03-05-L-D-315-090](#) [TW-04-02-G-D-180-100](#) [TW-05-02-G-S-125-050](#) [TW-04-07-G-D-520-080](#) [TW-03-02-T-S-120-125](#) [TW-03-09-G-D-155-115](#) [TW-05-05-L-D-335-100](#) [TW-05-06-S-T-452-080](#) [TW-05-09-T-S-255-100](#) [TW-05-12-G-D-670-190](#) [TW-08-09-L-D-200-090](#) [TW-08-10-L-D-338-105](#) [TW-09-06-G-D-260-205](#) [TW-06-06-T-S-455-109](#) [TW-06-09-T-D-204-109](#) [TW-05-03-L-D-300-090](#) [TW-06-05-L-D-435-100](#) [TW-07-07-G-D-461-090](#) [TW-10-07-G-D-375-188](#) [TW-10-05-T-D-365-105](#) [TW-08-03-L-D-220-120](#) [TW-08-02-T-D-185-115-016](#) [TW-08-03-L-S-265-090](#) [TW-11-06-T-S-425-090](#) [TW-06-12-G-D-590-100](#) [TW-08-12-S-D-600-150](#) [TW-13-09-T-S-256-094](#) [TW-10-07-T-D-490-125](#) [TW-12-02-T-D-180-100](#) [TW-20-12-G-D-590-135](#) [TW-08-02-T-S-120-130](#) [TW-10-12-L-D-400-280](#) [TW-13-12-S-D-700-145](#) [TW-11-07-G-S-135-135](#) [TW-12-03-L-D-231-118](#) [TW-19-08-S-S-310-090](#) [TW-10-03-G-D-236-157](#) [TW-10-06-G-D-280-270](#) [TW-18-02-L-D-142-120](#) [TW-14-03-L-D-170-135](#) [TW-16-02-L-S-160-100](#) [TW-20-09-L-D-250-103](#) [TW-12-08-G-D-380-120](#) [TW-15-06-G-D-275-200](#) [TW-20-04-T-D-300-125](#) [TW-24-05-G-D-340-130](#) [TW-02-02-LM-S-230-075](#) [TW-02-02-T-D-189-094](#) [TW-03-07-T-D-470-150](#) [TW-03-07-T-D-158-110](#) [TW-02-01-T-S-134-094](#) [TW-03-03-L-D-197-142](#) [TW-03-03-S-D-195-120](#) [TW-04-02-L-D-120-080](#) [TW-04-02-L-D-120-100](#) [TW-02-02-G-S-190-100](#) [TW-04-03-L-S-222-200](#) [TW-02-05-G-D-315-100](#) [TW-04-03-L-D-290-090](#) [TW-04-05-L-D-320-100](#) [TW-02-06-T-S-254-056](#) [TW-04-01-L-D-120-090](#) [TW-04-02-L-T-160-065](#) [TW-04-03-L-D-235-150](#) [TW-04-09-G-D-220-090](#) [TW-04-10-G-D-375-080](#) [TW-05-02-L-S-153-111](#) [TW-05-03-L-S-222-200](#) [TW-05-06-G-S-325-100](#) [TW-03-12-G-D-625-100](#) [TW-06-10-L-D-415-100](#) [TW-03-09-T-D-143-125](#) [TW-05-09-G-D-130-160](#) [TW-06-03-G-S-335-055](#) [TW-03-10-G-D-360-140](#) [TW-05-05-G-D-290-150](#) [TW-08-04-T-D-315-070](#) [TW-05-06-T-S-510-080](#) [TW-07-02-L-D-125-090](#) [TW-07-06-G-D-455-100](#) [TW-08-03-T-S-345-095](#)