

Analysis of natural language complexity used by open-source developers

Introduction to Natural Language Processing

Komlichenko Ilya, Krzemiński Piotr, Monicz Kamil,
Piotrowska Weronika, Wojnarowski Marcin

May, 2022

Contents

1	Motivation	2
2	Data sourcing	2
2.1	Text processing	2
2.2	Scraping procedure	2
3	Functionalities	2

1 Motivation

In order to improve our NLP skills, we are going to complete simple natural language analysis. The topic of choice should be close to our hearts so we stay engaged throughout the project. In addition, the source data should be freely accessible, so it is easy to work with. And so, our analysis will focus on the natural language complexity used by developers of various programming languages who contribute to open-source platforms (such as GitHub).

We hypothesize that language with a lower barrier of entry (such as Python) will exhibit a lower natural language complexity than languages that expect a higher level of expertise (such as C). Additionally, we are aware of different demographics of programming languages thus expect scientific/research focused languages (such as Julia) programmers will naturally use a more complex natural language to express ideas/problems.

2 Data sourcing

The linguistic data will be primarily scraped from the GitHub issues, where developers, using natural language, often describe bugs or feature requests related to some piece of software. And since the code there is publicly available, it is easy to assign a specific programming language to it.

2.1 Text processing

Every issue will be assigned a complexity/readability score based on industry-standard algorithms and bucketed into their respective programming language. For example, one could compute Flesch-Kincaid Grade Level or check the frequency of passive sentences.

2.2 Scraping procedure

Using the official GitHub API we will first look through active GitHub users and then issues posted by the given user. Only issues written in English will be considered, where the language detection can be trivially and effectively done with simple methods such as letter frequency distribution comparison. The most popular programming language used by a given programmer (as determined by GitHub) will determine the said language label assigned to the scraped issue. We cannot go with the programming language used in the repository where the issue was posted due to the simple fact that code of a non-library repository is usually not used directly by a issue poster, thus being a false connection between the content of an issue and a programming language used by the poster.

Data scraped from GitHub will be cleaned up by removal of any non-natural language texts such as code blocks. We suspect that the dataset will be still full of true-negatives and will require manual labor to review our samples. Finally, the dataset will simply consist of two dimensions: text (issue content) and a label (programming language).

We want to focus on a specific subset of languages with a fairly balanced distribution between classes, also taking into account the repetition of issue posters.

3 Functionalities

After scraping the data, we are planning to perform following operations in order to give us a more complete insight

1. Basic text analysis – this includes average length of sentences, average length of words, most common word occurring etc. We are expecting developers of more complex programming languages to use more sophisticated language in the reported issues, this includes less grammar mistakes, longer sentences and words.

2. Frequency of passive sentences – in order to identify passive sentences we will use Part Of Speech tagging (POS). In English, a passive sentence can be defined by the place of the verb in the sentence and the form of this verb. We suspect the data to have high frequency of passive sentences, as it describes development issues.
3. Flesh-Kincaid Grade Level – by evaluating the Flesh-Kincaid grade level, we can determine whether the text is readable to an average, non-developer person. It measures the length of the sentences and syllables per words, which indicated the easy to read or not. We expect developers of more complex programming languages to write harder to read issue descriptions.

$$0.39 \left(\frac{\text{total words}}{\text{total sentences}} \right) + 11.8 \left(\frac{\text{total syllables}}{\text{total words}} \right) - 15.59$$

4. Flesh readability score – similarly to Flesh-Kincaid Grade Level, this score is used to measure level of difficulty when reading a text. We compute the score as follows:

$$206.835 - 1.015 \left(\frac{\text{total words}}{\text{total sentences}} \right) - 84.6 \left(\frac{\text{total syllables}}{\text{total words}} \right)$$

We hope that after obtaining this data, there will be interesting conclusions that there exists dependency between a developer's primary programming language and the natural language he or she uses when describing issues on GitHub.