

Lec3

HTML MEDIA TAGS

HTML Media Tags are used to **embed audio, video, images, and other multimedia content** into a web page.

Tag	Purpose
<code></code>	Displays an image
<code><audio></code>	Embeds audio files
<code><video></code>	Embeds video files
<code><source></code>	Specifies multiple media sources for audio/video
<code><track></code>	Adds subtitles/captions to videos
<code><iframe></code>	Embeds another webpage, YouTube video, map, etc.
<code><embed></code>	Embeds external content like PDFs
<code><object></code>	Embeds multimedia objects

Example

Image

```

```

Audio

```
<audio controls>
```

```
  <source src="song.mp3" type="audio/mpeg">
```

Your browser does not support audio.

```
</audio>
```

Video

```
<video width="500" controls>
```

```
  <source src="movie.mp4" type="video/mp4">
```

Your browser does not support video.

```
</video>
```

<iframe>

The **<iframe>** (Inline Frame) tag is used to **embed another webpage, video, map, PDF, or external content inside the current webpage.**

Syntax

```
<iframe src="URL"></iframe>
```

Interview Answer

<iframe> is an HTML tag used to embed another document, webpage, video, map, or external content within the current webpage. It creates an inline frame that displays content from a specified URL using the **src** attribute.

Example

Embed a Website

```
<iframe src="https://www.wikipedia.org"  
  width="600"  
  height="400">  
</iframe>
```

Embed a YouTube Video

```
<iframe width="560" height="315"  
  src="https://www.youtube.com/embed/VIDEO_ID"  
  title="YouTube video player">  
</iframe>
```

Embed Google Maps

```
<iframe  
  src="https://www.google.com/maps/embed?pb=..."  
  width="600"  
  height="450">  
</iframe>
```

Common Attributes

Attribute	Purpose
<code>src</code>	URL of the page/content to display
<code>width</code>	Width of the frame
<code>height</code>	Height of the frame
<code>title</code>	Description for accessibility
<code>allowfullscreen</code>	Allows full-screen mode (videos)
<code>loading="lazy"</code>	Loads iframe only when needed

<audio>

The **<audio>** tag is used to **embed and play audio files** on a web page, such as MP3, WAV, or OGG files.

Syntax

```
<audio controls>
```

```
  <source src="song.mp3" type="audio/mpeg">
```

```
</audio>
```

Interview Answer

The **<audio>** tag in HTML is used to embed and play audio files on a webpage. It supports formats such as MP3, WAV, and OGG and provides controls like play, pause, volume, and seek through the **controls** attribute.

Example

```
<!DOCTYPE html>
<html>
<head>
  <title>Audio Example</title>
</head>
<body>

<h2>Play Audio</h2>

<audio controls>
  <source src="song.mp3" type="audio/mpeg">
</audio>

</body>
</html>
```


Common Attributes

Attribute	Purpose
<code>controls</code>	Displays play, pause, volume, and seek controls
<code>autoplay</code>	Starts playing automatically when the page loads
<code>loop</code>	Repeats the audio continuously
<code>muted</code>	Starts the audio in muted mode
<code>preload</code>	Specifies how the audio should be loaded

<video>

The **<video>** tag is used to **embed and play video files** directly on a web page without requiring any external plugin.

Syntax

```
<video controls>  
  <source src="movie.mp4" type="video/mp4">  
</video>
```

Interview Answer

The **<video>** tag in HTML is used to embed and play video content on a webpage. It supports formats such as MP4, WebM, and OGG and provides built-in controls like play, pause, volume, and fullscreen through the **controls** attribute.

Example

```
<!DOCTYPE html>
<html>
<head>
  <title>Video Example</title>
</head>
<body>

<h2>Play Video</h2>

<video width="500" controls>
  <source src="movie.mp4" type="video/mp4">
</video>

</body>
</html>
```

Common Attributes

Attribute	Purpose
<code>controls</code>	Displays play, pause, volume, and fullscreen controls
<code>autoplay</code>	Starts playing automatically when the page loads
<code>loop</code>	Repeats the video continuously
<code>muted</code>	Starts the video without sound
<code>width</code>	Sets the width of the video
<code>height</code>	Sets the height of the video
<code>poster</code>	Displays an image before the video starts playing

Embedding External Content

Embedding external content means displaying content from another source (website, video, map, PDF, etc.) inside your web page.

Tag	Purpose
<code><iframe></code>	Embed webpages, YouTube videos, Google Maps, etc.
<code><embed></code>	Embed PDFs and multimedia files
<code><object></code>	Embed external resources such as PDFs, images, and HTML files

<embed>

The **<embed>** tag is used to **embed external content** such as PDFs, audio files, videos, or other multimedia resources directly into a web page.

It is a **self-closing tag**, meaning it does not require a closing tag.

Syntax

```
<embed src="file.pdf">
```

Interview Answer

The **<embed>** tag in HTML is used to insert external resources such as PDFs, audio files, videos, and other multimedia content into a webpage. It is a self-closing tag and commonly uses attributes like **src**, **width**, and **height** to display the embedded content.

Example

Embed a PDF

```
<embed src="sample.pdf"  
width="600"  
height="500">
```

Embed an Audio File

```
<embed src="song.mp3"  
width="300"  
height="50">
```

Embed a Video

```
<embed src="movie.mp4"  
width="500"  
height="300">
```

Common Attributes

Attribute	Purpose
<code>src</code>	Specifies the file to embed
<code>width</code>	Sets the width
<code>height</code>	Sets the height
<code>type</code>	Specifies the MIME type of the file

<object>

The **<object>** tag is used to **embed external resources** such as PDFs, images, audio, videos, or even another HTML document inside a web page.

Unlike **<embed>**, the **<object>** tag has both **opening and closing tags** and can contain fallback content if the resource cannot be displayed.

Syntax

```
<object data="file.pdf"></object>
```

Interview Answer

The **<object>** tag in HTML is used to embed external resources such as PDFs, images, videos, audio files, and HTML documents into a webpage. It uses the **data** attribute to specify the resource and can include fallback content if the embedded resource cannot be displayed.

Example

Embed a PDF

```
<object data="sample.pdf"
  type="application/pdf"
  width="600"
  height="500">
</object>
```

Display an Image

```
<object data="image.jpg"
  width="300"
  height="200">
</object>
```

Fallback Content

```
<object data="sample.pdf"
  type="application/pdf"
  width="600"
  height="500">
</object>
```

Common Attributes

Attribute	Purpose
data	URL/path of the resource
type	MIME type of the resource
width	Width of the object
height	Height of the object

Homework

SVG

CANVAS

Task

Build a multimedia webpage with images, videos, and embedded content