



deeplearning.ai

Optimization Algorithms

Mini-batch gradient descent

Batch vs. mini-batch gradient descent

Vectorization allows you to efficiently compute on m examples.

$$\begin{array}{c}
 \underline{X}, \underline{Y} \\
 \underline{X^{\{t\}}}, \underline{Y^{\{t\}}}
 \end{array}$$

$$\underline{X} = \begin{bmatrix} x^{(1)} & x^{(2)} & x^{(3)} & \dots & x^{(1000)} & | & x^{(1001)} & \dots & x^{(2000)} & | & \dots & | & \dots & x^{(m)} \end{bmatrix}$$

(n_x, m) $\underbrace{\hspace{10em}}_{X^{\{1\}} (n_x, 1000)}$ $\underbrace{\hspace{10em}}_{X^{\{2\}} (n_x, 1000)}$ $\underbrace{\hspace{10em}}_{X^{\{5,000\}} (n_x, 1000)}$

$$\underline{Y} = \begin{bmatrix} y^{(1)} & y^{(2)} & y^{(3)} & \dots & y^{(1000)} & | & y^{(1001)} & \dots & y^{(2000)} & | & \dots & | & \dots & y^{(m)} \end{bmatrix}$$

$(1, m)$ $\underbrace{\hspace{10em}}_{Y^{\{1\}} (1, 1000)}$ $\underbrace{\hspace{10em}}_{Y^{\{2\}} (1, 1000)}$ $\underbrace{\hspace{10em}}_{Y^{\{5,000\}} (1, 1000)}$

What if $m = \underline{5,000,000}$?

5,000 mini-batches of 1,000 each

Mini-batch t : $X^{\{t\}}, Y^{\{t\}}$

$$\begin{array}{c}
 x^{(i)} \\
 z^{[l]} \\
 \underline{X^{\{t\}}}, \underline{Y^{\{t\}}}
 \end{array}$$

Mini-batch gradient descent

repeat {
for $t = 1, \dots, 5000$ {

Forward prop on X^{t+1} .

$$Z^{(i)} = W^{(i)} X^{t+1} + b^{(i)}$$

$$A^{(i)} = g^{(i)}(Z^{(i)})$$

$$\vdots$$

$$A^{(L)} = g^{(L)}(Z^{(L)})$$

} Vectorized implementation
(1000 examples)

Compute cost $J^{t+1} = \frac{1}{1000} \sum_{i=1}^L \ell(\hat{y}^{(i)}, y^{(i)}) + \frac{\lambda}{2 \cdot 1000} \sum_i \|W^{(i)}\|_F^2$.

↙ ↘ for X^{t+1}, Y^{t+1}

Backprop to compute gradients w.r.t J^{t+1} (using (X^{t+1}, Y^{t+1}))

$$W^{(i)} := W^{(i)} - \alpha dW^{(i)}, \quad b^{(i)} := b^{(i)} - \alpha db^{(i)}$$

"1 epoch"

└ pass through training set.

1 step of gradient descent
using X^{t+1}, Y^{t+1} .
(as if $m=1000$)

X, Y




deeplearning.ai

Optimization Algorithms


Understanding
mini-batch
gradient descent

Training with mini batch gradient descent

Batch gradient descent



Mini-batch gradient descent




Choosing your mini-batch size

→ If mini-batch size = m : Batch gradient descent.

$$(X^{(13)}, Y^{(13)}) = (X, Y)$$

→ If mini-batch size = 1 : Stochastic gradient descent. Every example is its own mini-batch.
 $(X^{(13)}, Y^{(13)}) = (x^{(1)}, y^{(1)}) \dots (x^{(n)}, y^{(n)})$ mini-batch.

In practice: Somewhere in-between 1 and m



Stochastic
gradient
descent



Loss spikes
from vectorization

In-between
(mini-batch size
not too big/small)



Fastest learning.

- Vectorization.
($n \approx 1000$)
- Make passes without
processing entire training set.

Batch
gradient descent
(mini-batch size = m)



Too long
per iteration

Choosing your mini-batch size

If small toy set : Use batch gradient descent.
($m \leq 2000$)

Typical mini-batch sizes:

→ 64, 128, 256, 512
 $2^6, 2^7, 2^8, 2^9$

$\frac{1024}{2^{10}}$

Make sure mini-batch fits in CPU/GPU memory.
 $X^{(t)}, Y^{(t)}$



deeplearning.ai

Optimization Algorithms

Exponentially weighted averages

Temperature in London

$$\theta_1 = 40^\circ\text{F} \quad 4^\circ\text{C} \leftarrow$$

$$\theta_2 = 49^\circ\text{F} \quad 9^\circ\text{C}$$


$$\theta_3 = 45^\circ\text{F} \quad \vdots$$

\vdots

$$\theta_{180} = 60^\circ\text{F} \quad 15^\circ\text{C}$$

$$\theta_{181} = 56^\circ\text{F} \quad \vdots$$

\vdots



$$V_0 = 0$$

$$V_1 = 0.9 V_0 + 0.1 \theta_1$$

$$V_2 = 0.9 V_1 + 0.1 \theta_2$$

$$V_3 = 0.9 V_2 + 0.1 \theta_3$$

\vdots

$$V_t = 0.9 V_{t-1} + 0.1 \theta_t$$

Exponentially weighted averages ^{moving}

$$\underline{V_t} = \underline{\beta} \underline{V_{t-1}} + \underline{(1-\beta)} \underline{\Theta_t} \leftarrow$$


$\beta = 0.9$: ≈ 10 days' temperat.

$\underline{\beta = 0.98}$: ≈ 50 days

$\beta = 0.5$: ≈ 2 days

V_t is approximately
average over
 $\rightarrow \approx \frac{1}{1-\beta}$ days'
temperature.

$$\frac{1}{1-0.98} = 50$$





deeplearning.ai

Optimization Algorithms

Understanding
exponentially
weighted averages


Exponentially weighted averages

$$v_t = \beta v_{t-1} + (1 - \beta)\theta_t$$

$$\beta = 0.9$$

$$0.98$$

$$0.5$$



Exponentially weighted averages

$$v_t = \beta v_{t-1} + (1 - \beta) \theta_t$$

$$v_{100} = 0.9v_{99} + 0.1\theta_{100}$$

$$v_{99} = 0.9v_{98} + 0.1\theta_{99}$$

$$v_{98} = 0.9v_{97} + 0.1\theta_{97}$$



...

$$\begin{aligned} \rightarrow \underline{v_{100}} &= 0.1 \theta_{100} + \underset{\uparrow}{0.9} \cancel{v_{99}} (0.1 \theta_{99} + \underset{\uparrow}{0.9} \cancel{v_{98}}) \\ &= \underbrace{0.1 \theta_{100}} + \underbrace{0.1 \times 0.9 \cdot \theta_{99}} + \underbrace{0.1 (0.9)^2 \theta_{98}} + \underbrace{0.1 (0.9)^3 \theta_{97}} + \underbrace{0.1 (0.9)^4 \theta_{96}} + \dots \end{aligned}$$

$$\underline{0.9^{10}} \approx 0.35 \approx \frac{1}{e}$$

$$\frac{(1-\epsilon)^{1/\epsilon}}{\epsilon} \approx \frac{1}{e}$$

$$\epsilon = 0.02 \rightarrow \underline{0.98^{50}} \approx \frac{1}{e}$$



$$\approx \frac{1}{1-\beta}$$

$$\epsilon = 1 - \beta$$

$$0.1 \theta_{99} + 0.9 v_{98}$$

Implementing exponentially weighted averages

$$v_0 = 0$$

$$v_1 = \beta v_0 + (1 - \beta) \theta_1$$

$$v_2 = \beta v_1 + (1 - \beta) \theta_2$$

$$v_3 = \beta v_2 + (1 - \beta) \theta_3$$

...

$$V_0 := 0$$

$$V_1 := \beta V_0 + (1 - \beta) \theta_1$$

$$V_2 := \beta V_1 + (1 - \beta) \theta_2$$

⋮

$$\rightarrow V_0 = 0$$

Repeat {

Get next θ_t

$$V_t := \beta V_t + (1 - \beta) \theta_t \leftarrow$$

}




deeplearning.ai

Optimization Algorithms

Bias correction
in exponentially
weighted average

Bias correction



$$\beta = 0.98$$

$$\rightarrow v_t = \beta v_{t-1} + (1 - \beta) \theta_t$$

$$v_0 = 0$$

$$v_1 = \cancel{0.98 v_0} + \underline{0.02 \theta_1}$$

$$v_2 = 0.98 v_1 + 0.02 \theta_2$$

$$= 0.98 \times 0.02 \times \theta_1 + 0.02 \theta_2$$

$$= \underline{0.0196 \theta_1} + \underline{0.02 \theta_2}$$

$$\frac{v_t}{1 - \beta^t}$$

$$t=2: 1 - \beta^t = 1 - (0.98)^2 = 0.0396$$

$$\frac{v_2}{0.0396} = \frac{\underline{0.0196 \theta_1} + \underline{0.02 \theta_2}}{0.0396}$$




deeplearning.ai

Optimization Algorithms

Gradient descent with momentum

Gradient descent example



Momentum:

On iteration t :

Compute $\Delta W, \Delta b$ on current mini-batch.

$$V_{\Delta W} = \beta V_{\Delta W} + (1-\beta) \Delta W$$

$$V_{\Delta b} = \beta V_{\Delta b} + (1-\beta) \Delta b$$

Friction \uparrow velocity

$$W := W - \alpha V_{\Delta W}$$

$$b := b - \alpha V_{\Delta b}$$

deep learning ai

$$V_{\theta} = \beta V_{\theta} + (1-\beta) \theta_t$$

Implementation details

$$v_{dW} = 0, \quad v_{db} = 0$$

On iteration t :

Compute dW, db on the current mini-batch

$$\left. \begin{aligned} \rightarrow v_{dW} &= \beta v_{dW} + (1 - \beta) dW \\ \rightarrow v_{db} &= \beta v_{db} + (1 - \beta) db \end{aligned} \right\} \quad \left| \quad \underline{v_{dW}} = \beta v_{dW} + dW \leftarrow$$

$$W = W - \alpha v_{dW}, \quad b = \underline{b} - \alpha v_{db}$$

$$\frac{v_{dW}}{1 - \beta^t}$$

Hyperparameters: α, β

$$\underline{\beta = 0.9}$$

average over last ≈ 10 gradients




deeplearning.ai

Optimization Algorithms

RMSprop

RMSprop



On iteration t :

Compute dw, db on current mini-batch

$$\underline{S_{dw}} = \beta_2 \underline{S_{dw}} + (1 - \beta_2) \underline{dw^2} \leftarrow \text{small}$$

element-wise

$$\rightarrow \underline{S_{db}} = \beta_2 \underline{S_{db}} + (1 - \beta_2) \underline{db^2} \leftarrow \text{large}$$

$$w := w - \alpha \frac{dw}{\sqrt{\underline{S_{dw}} + \epsilon}} \leftarrow$$

$$b := b - \alpha \frac{db}{\sqrt{\underline{S_{db}} + \epsilon}} \leftarrow$$

$$\epsilon = 10^{-8}$$



deeplearning.ai

Optimization Algorithms

Adam optimization algorithm

Adam optimization algorithm

$$V_{dw} = 0, S_{dw} = 0, V_{db} = 0, S_{db} = 0$$

On iteration t :

Compute dw, db using current mini-batch

$$V_{dw} = \beta_1 V_{dw} + (1 - \beta_1) dw, V_{db} = \beta_1 V_{db} + (1 - \beta_1) db \quad \leftarrow \text{"momentum"} \beta_1$$

$$S_{dw} = \beta_2 S_{dw} + (1 - \beta_2) dw^2, S_{db} = \beta_2 S_{db} + (1 - \beta_2) db^2 \quad \leftarrow \text{"RMSprop"} \beta_2$$

`yhat = np.array([.9, 0.2, 0.1, .4, .9])`

$$V_{dw}^{\text{corrected}} = V_{dw} / (1 - \beta_1^t), V_{db}^{\text{corrected}} = V_{db} / (1 - \beta_1^t)$$

$$S_{dw}^{\text{corrected}} = S_{dw} / (1 - \beta_2^t), S_{db}^{\text{corrected}} = S_{db} / (1 - \beta_2^t)$$

$$W := W - \alpha \frac{V_{dw}^{\text{corrected}}}{\sqrt{S_{dw}^{\text{corrected}} + \epsilon}}$$

$$b := b - \alpha \frac{V_{db}^{\text{corrected}}}{\sqrt{S_{db}^{\text{corrected}} + \epsilon}}$$

Hyperparameters choice:

→ α : needs to be tune

→ β_1 : 0.9 → (dw)

→ β_2 : 0.999 → (dw^2)

→ ϵ : 10^{-8}

Adam: Adaptive moment estimation



Adam Coates




deeplearning.ai

Optimization Algorithms

Learning rate decay

Learning rate decay

Slowly reduce α




Learning rate decay


1 epoch = 1 pass through data.

$$\alpha = \frac{1}{1 + \text{decay-rate} * \text{epoch-num}} \alpha_0$$

Epoch	α
1	0.1
2	0.67
3	0.5
4	0.4
\vdots	\vdots




$$\alpha_0 = 0.2$$
$$\text{decay-rate} = 1$$



Other learning rate decay methods

Formula

$$\left\{ \begin{array}{l} \alpha = 0.95^{\text{epoch-num}} \cdot \alpha_0 \quad - \text{exponentially decay.} \\ \alpha = \frac{k}{\sqrt{\text{epoch-num}}} \cdot \alpha_0 \quad \text{or} \quad \frac{k}{\sqrt{t}} \cdot \alpha_0 \end{array} \right.$$


discrete staircase

Manual decay.




deeplearning.ai

Optimization Algorithms


The problem of local optima

Local optima in neural networks



Andrew Ng

Problem of plateaus



- Unlikely to get stuck in a bad local optima
- Plateaus can make learning slow