

WP WORKSHOP1

Politecnico di Torino



















Outline

- 1) Network Models
- 2) case studies
- 3) input needed
- 4) Open Source Modelling
- 5) Out-of Domain

PoliTO:

- T.4.2.4 Tool for multi-component gas networks with quality tracking both for low pressure and high pressure networks.
- T.4.3.2 Parametric analysis, uncertainty quantification and out-ofdomain generalization of results



Gas Network Models


Overview on Fluid-Dynamic Solver for transient gas network modelling


Contribution Task 4.2.1
Definition of network models and case studies

Gas Network Model – transient









Gas Network Model – quality tracking



Quality Tracking section:

→ Transport of the concentration vector along the pipelines

Advective transport equation


$$\frac{\partial \mathbf{Y}}{\partial t} + v \frac{\partial \mathbf{Y}}{\partial x} = 0$$


with:

- v: gas velocity;

- Y: gas composition vector;

Lagrangian coordinates-based BATCH TRACKING METHOD






→ Mixing at network nodes

Coninutiy equation

for each chemical species

$$y_{c.s._i} = \frac{\left(\sum_{j}^{inward} G_j y_{c.s.,j} - G_{ext_i} y_{c.s.,ext_i}\right)}{\left(\sum_{j}^{outward} G_j - G_{ext_i} + \frac{V_i}{c_{i,j}^2 \Delta t} (p_i^{n+1} - p_i^n)\right)}$$

Solving strategy:





Input Data Structure

Gas Network Simulation Models – basic structure



Input

Parameters

- Network Topology


- Junction(nodes)-Pipes connections
- Definition Pipe/Non-Pipe elements
- **Definition of Injection Points**
- Definition of Outlet (consumption) Points
- Definition of Pressure-Controlled nodes

- Pipeline Features

- · Inner Diameters
- Length
- Inner Roughness / Material + year of installation /estimation

- Non-Pipeline Features

Depending on their control mode/governing equations



Inputs

Gas Profiles* -

- Gas Injection profiles
- Gas Consumption profiles

Pressure Profiles* -

• At pressure-controlled nodes

Composition Profiles* -

• At injection nodes


In the framework of multi-gas system the consumptions to be given in terms of chemical energy supplied to the consumption point.

$$oldsymbol{E_{out}}{oldsymbol{Q_{out}}}$$
 , $oldsymbol{HHV_{out}}$

time series of the quantity

Gas Network Simulation Models – basic structure Shimmer





Input Data Structure – EDGE TABLE



Non pipeline elements

nodes

branch	IN	OUT	L (km)	D (m)	epsi[mm]	СОМР	REG	VAL	RES	n°Grid points
1	1	2	530.0	0.7937	0.014					53
2	2	3	1.0	0.7937	0.014	1				1
3	3	4	540.0	0.7937	0.014					54

Topological info: Branch (edges) list and indication of inlet and oulet node

Some additional column may be added as additional information about each pipe:

For example, to take into account the gravitational effect, if the altitude at each node is not available, then the DeltaH or the inclination angle should be indicated for each pipe

Either 0 or 1 to indicate that a specific branch is a Non-pipeline element thus the equations applied are different

Used to create a mesh within each pipe (used both for the fluiddynamic problem and more importantly, for the quality tracking)

Non pipeline elements

Element Types	Description								
Passive Elements									
pipe	models a section of a pipeline, basic properties are length, diameter, roughness and pipe efficiency								
resistor	models passive devices that cause a local pressure drop (e.g. meters, inlet piping, coolers, heaters, scrubbers etc.)								
Active Elements									
compressor	models a compressor station with generic constraints, allows the specification of a control mode of the station (e.g. outlet pressure control, inlet pressure control, flow rate control etc.)								
regulator	models a pressure reduction and metering station located at the interface of two neighbouring networks with different maximum operating pressures, allows the specification of a control mode of the station (e.g. outlet pressure control, inlet pressure control, flow rate control etc.)								
valve •	models a valve station, which is is either opened or closed								

Non-pipeline (NP) elements have not been «structurally» embedded. The structure of the models allows for their integration but a more robust and general organization of the code and the integration of the NP elements should be done

Input Data Structure – NODE TABLE



Others units my be accepted such as kg/s or Sm3/h

Vector of the molar composition of natural gas

Node name	Node	Height [m]	Gas Flow [kW]	Pressure [bar-g]	<u>CH4</u>	<u>N2</u>	<u>CO2</u>	<u>C2H6</u>	<u>C3H8</u>	<u>H2</u>	<u></u>	<u>H2S</u>
Wafa	1	0	-5,203,292	100	85.306	3.882	1.268	6.486	2.058	0		0
Mellitah	2	100	0	65								
Mellitah_out	3	200	0	120								
Gela	4	150	5,203,292	70	85.306	3.882	1.268	6.486	2.058	0.000		0.000

Usually the initial pressure is a given value as a boundary condition

Some additional column may be added
For example, for graphical representation
purposes, colums for x-y coordinates
should be integrated

Usually the outlet gas flow (here given in terms of thermal energy release) is a given value as a boundary condition

Some additional column may be added here as well depending on the number of components of the natural gas we want to consider:
For quality tracking goals I would say that the minimum is 2

This should go together with the choice of the equation of state.

Sign convention:

- + if it is *exiting* form the network;
- If it is entering in the network




Applications


Transient + quality tracking model

Tracking of Solar Hydrogen direct injection





Assumptions:





Open questions:

- Impacts on Gas Quality?
- Transport of the perturbation?

Hydrogen Tracking – distribution system








Simulation of Blended Hydrogen – transnational interconnector









Outlet pressure at Gela Terminal









Gas Network Models


Overview on Fluid-Dynamic Solver for steady state, highly meshed networks


Contribution Task 4.2.1
Definition of network models and case studies



SIMPLE ALGORITHM

Nodal mass balance for each gas component









Applications


Steady State + quality tracking model


Distribution Networks: Modulating Pressure + Hydrogen blending












Regional Networks: De-blending cases








Translation into Open Source

System boundaries




Exchanging data is frequently a challenge. We want to get this right from the beginning:

- Gas network data should be stored in an **open & well supported format**
- Data format should guarantee **data correctness** and **integrity**. For example:
 - impossible to insert a pipe between non-existent stations
 - impossible to remove a station with attached pipes
 - impossible to inject a gas from a non-existent station

SQLite fullfills all the requirements:

- Widely supported on all main OSs and by most of the scientific tools. Example: native support in Matlab, plug-ins for Octave and R
- Full fledged SQL database, data constraints easily specified & enforced
- Graphical tools for data manipulation & import/export exist

Oversimplified relational data model



Relational data models are ubiquitous and well-understood:

- Clear and unambiguous entities and relations
- Data integrity automatically checked: impossible to enter an edge if a node does not exist
- We need to discuss the actual data model offline in order to determine if it fits all the requirements

Technologies

We chose industry standard, portable and widespread technologies.

- SQLite for data storage and exchange: widespread format, extremely portable
- Data manipulation and processing
 - boost::graph for graph manipulation
 - Eigen for linear algebra and numerical methods
- Qt to have a portable graphical toolkit and easy to install development environment

Conclusions

Next tasks:

- Iterate on the data model and finalize its design (DENERG/DISMA)
- Provide formatted & cleaned-up data in Excel/CSV files (DENERG)
- Provide the first two layers of the system (DISMA)
- Re-implement Matlab stuff in the new architecture (DENERG/DISMA)
- Validate the implementation



Parametric analysis, uncertainty quantification and out-of-domain generalization of results

Road to Task 4.3.2

T4.3.2 Background and workplan



Parametric analysis and out-of-domain generalization of results

Time frame: M12 – M35 (...early, but it is extremely important to start collecting info, share ideas and working together)

Subtask of T4.3 Operational strategies for injection and flow transport (lead TNO)

"Evaluation of the effect on operational strategies on variations in the network design and network parameters"

GOAL: support findings and general guidelines in a multi-gas network scenario

Main contribution based on a stable and well-established background experience:

- (1) Generation of synthetic gas networks based on realistic archetypes;
- (2) a robust and efficient **statistical procedure** is suitably designed accounting for **machine learning** tools for parametric analysis and uncertainty quantification.

Background publications




Selection of Journal papers with focus on complex network modeling, machine learning and statistics

- [1] M. Liu, Y. Xie, Y. Chen, R. Trinchero, and I.S. Stievano, "Modeling of Induction in Integrated Power-Gas Systems Due to Geomagnetic Disturbances", IEEE Transactions on Power Delivery, 2023 (in press).
- [2] E. Vaccariello, R. Trinchero, P. Leone, and I.S. Stievano, "Synthetic gas networks for the statistical assessment of low-carbon distribution systems", **Sustainable Energy, Grids and Networks**, vol. 31, September 2022, 100765.
- [3] E. Vaccariello, R. Trinchero, I.S. Stievano, and P. Leone, "A Statistical Assessment of Blending Hydrogen into Gas Networks", Energies 2021, 14(16), 5055.
- [4] E. Vaccariello, P. Leone, F.G. Canavero, and I.S. Stievano, "Topological modelling of gas networks for co-simulation applications in multi-energy systems", **Mathematics and Computers in Simulation**, vol. 183, pp. 244-253, May 2021.
- [5] E. Vaccariello, P. Leone, and I.S. Stievano, "Generation of synthetic models of gas distribution networks with spatial and multi-level features", International Journal of Electrical Power & Energy Systems, vol. 117, May 2020.
- [6] Z.A. Memon, R. Trinchero, P. Manfredi, F. Canavero, and I.S. Stievano, "Compressed Machine Learning Models for the Uncertainty Quantification of Power Distribution Networks", **Energies** 2020, 13(18), 4881.
- [7] P. Manfredi and R. Trinchero, "A probabilistic machine learning approach for the uncertainty quantification of electronic circuits based on Gaussian process regression," **IEEE Transactions on Computer-Aided Design of Integrated Circuits and Systems**, vol. 41, no. 8, pp. 2638-2651, August 2022.

(1) Topological modeling & Synthetic Gas Networks [4,5] & Shimmer




- Automatic tool (algorithm) for the **creation of** synthetic gas network topologies [4,5]
- **Synthetic networks mimic** the topological properties and the spatial distribution of a given reference
- (A) Fitting of a Gaussian Mixture Model (GMM) to the coordinates of nodes in a reference grid
- (B) Sampling of (N random) synthetic nodes
- (C) Iterative inclusion of nodes into a growing spanning tree
- (D) Network reinforcement: creation of loops...




(1) Topological modeling & Synthetic Gas Networks [2]



10 random samples out of the 10,000 synth. grids



- Realistic structural properties (diameters and volumes), comparable with real-world systems
- Hydraulic behavior always comply with target design parameters
- Wide variability of structural properties (D and V) and hydraulic responses (p and v)




(2) Statistical Assessment of Hydrogen Blending [3]



H2 injection is assessed over 100 models of medium-pressure networks at increasing H2 penetrations ranging from 0 - 75% vol (steady-state analysis)

• E.g., H2 is injected nearby the NG city gate (results: Homogeneous composition delivered to users in most cases, injecting 10%vol of H2 does not produce quality violations in most (84%) of cases, systematic violations for penetrations ≥ 20%vol)




- No violations on the system hydraulics are recorded in most cases: structural readiness of the grids
- Main criticality is on the quality of gas
- Larger H₂ volumes are allowed when hydrogen is injected close to the city gate
- Very high sensitivity to injections in peripherical network regions (quality issues)
- Overpressures may arise for H₂ penetrations equal or higher than 40%vol

(2) Statistical Assessment via Machine Learning



☐ In SHIMMER: machine learning (ML) tools (e.g., Gaussian processes or support vector machine regressions) for the generation of compact macromodels accounting for many parameters (topological and/or physical, related to the gas) from a limited number of simulations and for supporting reliability assessment and design



Application for **sensitivity analysis** to quantitatively assess the impact of design or key network parameters or **robustness and reliability assessments**

THANK YOU

