

TECHNICAL DATA SHEET

- SUPPOCIRE NAI 25 A PELLETS -

DEFINITION

Hard fat EP/USP-NF/JPE/ChP.

ORIGIN OF THE RAW MATERIALS

The product is manufactured from raw materials of strictly vegetable origin.

DESCRIPTION

- IUPAC: Glycerides, C10-18 (Glycerides, C12-18)
- CAS: 85665-33-4 (or 67701-26-2)
- EINECS: 288-123-8 (or 266-944-2)

REGULATORY INFORMATION

For information on the regulatory status of this product, please consult the regulatory data sheet (RDS).

FIELD OF USE

This product is a pharmaceutical ingredient. It is recommended for use in pharmaceutical formulations administered by rectal/vaginal routes.

This ingredient must be used according to appropriate regulations. Gattefossé accepts no responsibility for the use of this product in applications other than those recommended.

USES

Rectal drug delivery: suppository base with medium hydroxyl value (20 - 30 mg KOH/g).

STORAGE RECOMMENDATIONS

Store the product in its original packaging sealed tightly, protected from light and moisture.

Store at a temperature inferior or equal to 25 °C.

Product has a shelf-life of 3 years under the recommended storage conditions and should not be used after its expiry date.

HANDLING ADVICE

Presentation: semi-solid in pellets.

For additional information, please consult the product handling sheet.

PACKAGING

TECHNICAL DATA SHEET

- SUPPOCIRE NAI 25 A PELLETS -

PACKAGING

Bag in cardboard box 20 kg (pellets) (PCB).
Sample available upon request.

SAFETY OF USE

For information on the toxicology and safety of this product, please consult the product toxicological file and material safety data sheet (MSDS).

SOLUBILITIES AT 20°C(Eur. Ph.)

- Ethanol 96°: Not very soluble
- Chloroform, Methylene chloride: Soluble
- Water: Insoluble
- Vegetable oils: Soluble

TECHNICAL DATA SHEET

- SUPPOCIRE NAI 25 A PELLETS -

Test	Specification
APPEARANCE	Waxy solid
ODOUR	Faint
COLOUR (Gardner Scale)	<= 2.0
DROP POINT (METTLER)	33.2 to 35.2 °C
MELTING POINT (CAP. TUBE) (NV=34°C)	33 to 35 °C
ACID VALUE	<= 0.5 mgKOH/g
SAPONIFICATION VALUE (NV = 235)	225 to 245 mgKOH/g
IODINE VALUE	<= 2.0 gI ₂ /100g
HYDROXYL VALUE (NV = 25)	20 to 30 mgKOH/g
PEROXIDE VALUE	<= 3.0 meqO ₂ /kg
ALKALINE IMPURITIES	<= 30 ppm NaOH
WATER CONTENT	<= 0.50 %
NICKEL CONTENT	< 1 ppm
SULPHATED ASHES CONTENT	<= 0.05 %
UNSATURIFIABLE MATTER CONTENT (USP/JPE)	<= 3 %
HEAVY METALS CONTENT (Pb) (JPE/ChP)	<= 10 ppm
ARSENIC CONTENT (JPE)	<= 2 ppm
EP IDENTIFICATION TESTS	Conforms
JPE IDENTIFICATION TESTS	Conforms
ChP IDENTIFICATION TESTS	Conforms

The information contained in this data sheet is based on our knowledge of the related product on the date indicated, but does not amount to a guarantee in respect of the product's properties and does not give rise to any contractual legal tie. This information is given in utmost good faith. It cannot substitute for indispensable preliminary tests that must be conducted to ensure product suitability for each intended use. Nothing herein shall be construed as a recommendation or license to use any information that conflicts with any patent or trademark of our company or others. We make no representations or warranties, express or implied that any use of this information will not infringe any such patent or trademark. The user's attention is also drawn to the possible risks incurred if a product is used for a purpose other than its designed purpose. This data sheet does not under any circumstance replace knowledge and application by the user of all laws and regulations relevant to his own operations. The user shall be solely liable for the precautions taken relevant to the use made of the products. This information does not exempt the user from ensuring that he may possibly come under other obligations pursuant to laws or regulations other than those indicated relating to the possession and manipulation of the product for which he shall be solely liable.