# Detect, Refine, Resolve: An Edge-Attention-Inspired Boundary Refiner for Solar Filament Instance Segmentation

A Solution to the Solar Filament Segmentation Challenge 2026

Shingo Hara
ER Systems, Ltd.
Kanagawa, Japan
shingo257@gmail.com

## Abstract

This report describes our solution to the Solar Filament Segmentation Challenge 2026, a Kaggle competition on segmenting solar filaments in GONG H-$\alpha$ observations. Our pipeline detects candidates with a YOLO11-seg instance detector, refines their boundaries with a crop-level U-Net, and resolves overlaps into a disjoint instance set, with design decisions evaluated under leak-free 3-fold cross-validation and an observation-cluster bootstrap — a protocol that rejected five plausible improvements whose single-fold gains did not replicate. One further change — an EdgeAttNet-inspired [9] edge-guided self-attention block at the refiner's bottleneck — initially passed this protocol ($\Delta$PQ= +0.0028, 95% CI $[0.00091, 0.00476]$, all folds agreeing) and moved the public leaderboard score from 0.37 to 0.39. A follow-up matched-parameter ablation (all folds, two seeds) refines this picture: bottleneck attention capacity, with or without the edge prior, tends to help (positive in two folds, neutral in the third), but the edge prior itself shows no consistent benefit over plain attention. Our main finding is this refinement: our acceptance criterion could not separate a general capacity effect from the specific edge-prior mechanism we set out to validate.

## 1 Introduction

This report describes our submitted solution to the Solar Filament Segmentation Challenge 2026 [3], organized by the Earth-Space AI Research (ESAIR) Lab and scored against the MAGFiLO dataset [2]. Our approach treats the task as instance segmentation: detect each filament, refine its boundary, and reconcile overlapping candidates into a disjoint prediction set. Section 2 describes the pipeline; Section 3 reports our evaluation protocol, results, and an honest account of what we tried that did *not* work.

## 2 Methodology

### 2.1 Preprocessing

Raw GONG H-$\alpha$ observations are $2048 \times 2048$ single-channel intensity images. Each image is encoded into a 3-channel input so that the detector backbone can reuse standard RGB-pretrained weights while still operating on physically meaningful contrast bands: channel 1 is a percentile-clipped copy of the raw intensity; channel 2 divides the image by a large-kernel Gaussian estimate of the background (flattening limb darkening and the radial illumination gradient) followed by CLAHE; channel 3 is a black-hat morphological transform of channel 2, which isolates dark, thin, filament-scale detail.

### 2.2 Detection

Filament candidates are generated by **YOLO11m-seg** [5], an anchor-free, NMS-based instance segmentation network, trained and run at $1280 \times 1280$ with a single foreground class. We trained one detector per fold (Section 2.5) for up to 70 epochs (patience 14), batch size 4, seed 3407 + fold, `deterministic=True`. AdamW ($\mathrm{lr}_0$=$7\times10^{-4}$, $\mathrm{lr}_f$=0.05, weight decay $5\times10^{-4}$, 3-epoch warmup); geometric augmentation (rotation $\pm180°$, translate 0.04, scale 0.25, flips $p$=0.5); mosaic 0.20 (off for the final 10 epochs); no hue/saturation jitter (meaningless for this encoding); value jitter 0.18; mask downsample 2. Inference uses confidence 0.26, NMS IoU 0.55; the full machine-readable call is in `scratch/`. We chose YOLO11-seg over RF-DETR-Seg [7] after a same-split comparison: RF-DETR-Seg's raw PQ trailed by $-0.057$. Not a matched-hyperparameter comparison, so this rules out a drop-in replacement, not the architecture family.

### 2.3 Boundary Refinement

Raw detector masks are accurate in extent but imprecise at the pixel boundary, which is exactly where the official metric is least forgiving (Section 3.1). We refine each candidate independently: a square crop is taken around the candidate (1.65× its bounding box, minimum side 96px, $320 \times 320$px after resizing), passed through a U-Net refiner, and the resulting probability map is thresholded (0.45) and intersected with the original candidate mask (*shrink* refinement — the refiner may only remove pixels, not add them outside the detector's proposal).

**Training data.** Positive crops are generated one per ground-truth instance per annotator (a 3-annotator image contributes up to 3× the crops of a single-annotator image), centered and scaled from that instance's box with the same 1.65×-context rule as inference; no hard-negative crops. Augmentation: random 90° rotations, flips, mild gamma jitter on the first two channels.

**Optimization.** We minimize $0.35 \cdot \mathrm{BCE} + 0.65 \cdot \text{soft-Dice} + 0.15 \cdot \text{boundary-}L_1$, where the boundary term compares a morphological-gradient (dilation−erosion, kernel 5) map of prediction and target. AdamW (weight decay $10^{-4}$), lr $2\times10^{-4}$ cosine-annealed, AMP, batch size 8. Per-fold refiners train 14 epochs (seed 3407), keeping the best validation crop-Dice checkpoint. The submitted refiner is fine-tuned from the fold-0 checkpoint on all 707 images for 5

*Kaggle Competition, kaggle.com/competitions/filament-segmentation-2026*
2026.





**Figure 1: End-to-end inference pipeline. Training uses leak-free 3-fold cross-validation (Section 2.5); the submitted model uses a single detector fold plus a refiner fine-tuned on all folds.**

epochs at 0.35× the base lr (Section 2.5); with no held-out data, we keep the final-epoch weights.

Our refiner, `MediSegEdgeAttUNet`, extends this U-Net [8] with a single **edge-guided multi-head self-attention** (EG-MHSA) block at the bottleneck (8 heads), *inspired by* EdgeAttNet [9]: a 3×3 conv on the crop yields an edge prior, projected and added to the attention query and key (not value), before residual and layer norm. EdgeAttNet's public code lacks a usable implementation of this module, so we could not validate against it, and our design deviates: EdgeAttNet stacks *two* 4-head blocks and drops positional encodings (22.7M vs. 31.0M params), while ours *adds* 4.2M (35.2M) — matching EdgeAttNet's own "U-Net + MHSA, no positional encoding" ablation almost exactly. We therefore call it edge-attention-inspired, not a reproduction; Section 3 revisits what this coincidence implies.

## 2.4 Instance Resolution

Refined candidates can still overlap (two proposals covering the same physical filament, or a small proposal nested inside a larger one). We remove near-duplicates whose intersection covers ≥ 90% of the smaller candidate's area, then greedily assign remaining pixels to candidates in ascending order of area (small, precise candidates claim their pixels before large ones), discarding any candidate left with fewer than 20px. This ordering outperformed confidence-first and area-descending orderings by 0.012–0.015 PQ in a final three-fold audit (Section 3.3).

## 2.5 Cross-Validation and Final Model

The competition provides 707 training images, each annotated by one or more experts (8,199 instance annotations; all annotators used as independent targets). We group by observation filename (leak-free by construction) and partition into three folds (236/236/235) with a stratified splitter (seed 3407) on quintiles of reference-annotator instance count. One detector and one refiner are trained per fold. For the final submission we select the best-PQ detector fold and fine-tune the refiner on *all* 707 images (warm-started, 5 epochs, 0.35× base lr), keeping cross-validated model selection intact.

# 3 Evaluation

## 3.1 Evaluation Strategy

The competition's official metric is Panoptic Quality (PQ), following the definition of Kirillov et al. [6] but scored by the competition's own reference implementation [1], which we replicated locally against that notebook's test cases. Unlike the original PQ formulation's one-to-one Hungarian matching, the competition scorer counts *every* prediction-ground-truth pair with IoU above 0.5 as a true positive (i.e. both sides can be matched multiply), so

$$\mathrm{PQ} = \frac{\sum_{(p,g)\in TP} \mathrm{IoU}(p,g)}{|TP| + 0.5|FP| + 0.5|FN|}.$$

A prediction with IoU just under 0.5 scores zero *and* incurs a false-positive/false-negative penalty, so near-miss boundary quality dominates the score far more than raw detection recall. Matching is done per (annotator, image) pair and micro-averaged, not averaged per-image.

Because annotators disagree, we measured a reference-annotation agreement baseline: scoring one expert's annotations as the "prediction" against every other expert on the same image, under the identical official rule, gives PQ= 0.3398 (multi-annotator images only, $n$=296; an earlier version trivially included self-matches, inflating it to 0.76 — corrected). Not a hard ceiling (ours scores above it); it is a benchmark for labeling-task reproducibility.

All model-selection decisions use the leak-free 3-fold cross-validation of Section 2.5. To avoid a failure mode we caught twice — a change that improves one fold but does not replicate — we additionally compute an observation-cluster bootstrap [4] (2000 resamples, PQ as ratio-of-sums) and accept a change only when (a) its sign agrees across all folds and (b) its pooled 95% CI excludes zero. The pooled interval is reported for the one accepted change; rejected changes are summarized in Section 3.3. We apply no multiple-comparisons correction across the ∼dozen ideas evaluated on the same 707 OOF images, so nominal intervals are optimistic; we flag this rather than adjust post hoc.

## 3.2 Results

Table 1 summarizes our out-of-fold (OOF) results under this protocol, and the corresponding public leaderboard scores where we submitted a matching variant. Note that our OOF PQ (0.4426, plain refiner over all 707 images) exceeds the 0.3398 reference-annotation agreement baseline of Section 3.1: this is not evidence the model is more *correct* than a human annotator, but it is consistent with the model, trained on pooled labels of several annotators, converging toward a consensus boundary that matches any single held-out annotator more often than annotators match each other.

The edge-attention refiner's original per-fold deltas over the plain U-Net were +0.0062/+0.0009/+0.0012 (folds 0/1/2), sign-consistent with a pooled bootstrap CI $[0.00091, 0.00476]$ excluding zero, so under our criterion we accepted and submitted it. The ablation below shows that acceptance attributed the effect to the wrong mechanism.

**Matched-parameter ablation.** To isolate whether the edge prior itself drives the effect, or whether added bottleneck attention capacity suffices, we ran seeds 3407/8407 on all three folds for three refiner variants: plain U-Net (31.04M params), bottleneck MHSA with no edge prior, and the edge-attention refiner (both




**Figure 2: Ground truth vs. raw detector vs. plain vs. edge-attention refiner, fold-0 OOF. (a): three filaments where edge attention recovers more true extent than plain (IoU** 0.36→0.59, 0.43→0.62, 0.39→0.56**). (b): the detector merges two ground-truth instances into one candidate and misses a third; refiners inherit this failure. Single-seed run; the ablation did not reproduce (a).**

| Configuration | OOF PQ | SQ / RQ | Public LB |
|---|---|---|---|
| Raw detector only | 0.3937 | 0.652 / 0.604 | — |
| + refiner + resolution | 0.4426 | 0.678 / 0.653 | 0.37 |
| + edge-attention refiner | 0.4454[†] | —[†] | **0.39** |
| *Ablations submitted for direct comparison:* | | | |
| 3-fold ensemble (standard refiner) | — | — | 0.37 |
| 3-fold ensemble (edge-attention) | — | — | 0.38 |
| *Matched-param. ablation, all 3 folds, 2 seeds each*[‡]*:* | | | |
| Plain U-Net (31.04M params) | 0.4418 | 0.678 / 0.651 | — |
| + plain MHSA, no edge prior (35.24M) | 0.4432 | 0.681 / 0.651 | — |
| + edge-guided MHSA (35.24M) | 0.4429 | 0.678 / 0.653 | — |

**Table 1: PQ, SQ, RQ leak-free; first two blocks over all 707 images (raw detector TP/FP/FN =** 4765/2824/3434**; +refiner+resolution** 5082/2286/3117**). [†]The single-seed** 0.4454 **(**$\Delta$ = +0.0028**, 95% CI** [0.00091, 0.00476]**) was originally accepted and submitted (LB** 0.39**); the follow-up ablation did not reproduce it. [‡]Seeds 3407/8407, per-seed values in `output/ablation/`. Public LB is Kaggle's public score; the private leaderboard (undisclosed until competition end) determines final ranking.**




**Figure 3: Fold-2 OOF residual errors. (a) A proposal-blind FN: the GT outline (green) has no candidate even at confidence** 0.02 **(**65% **of misses). (b) A near-miss: the prediction (red) covers only part of the instance (IoU** 0.404**), counting as both FP and FN.**

35.24M, differing by only ~2,100 params — these two *are* matched). Per-fold mean OOF PQ (base/plain-attn/edge-attn): fold 0 0.4414/0.4413/0.4405; fold 1 0.4405/0.4426/0.4417; fold 2 0.4434/0.4458/0.4464. Attention-minus-base is positive in folds 1–2 for both attention variants; edge-minus-plain-attention is at or below zero in two folds — no fold shows the edge prior clearly beating plain attention (`output/ablation/`).

The originally reported improvement (LB 0.39 vs. 0.37 plain) does not survive this check and may reflect leaderboard noise; the re-introduced 3-fold ensemble scored 0.38. An expected-IoU scorer gained +0.0034 exploratory OOF but 0.37 publicly and is neither unbiased OOF nor adoption evidence.

A $\chi^2$ test over file-name metadata found no train/test shift in observation year or site to explain the ~0.06 OOF-to-LB gap ($p$=0.42/0.94).

**Submission evidence.** Plain-MHSA fold-2 and edge-attention fold-2 checkpoint variants scored 0.39 publicly (best-match IoU 0.94/0.93 vs. production), and the final pair is production plus a full-data-detector variant (detector retrained on all observations after a preregistered learning-curve gate, +0.0099 from one- to two-thirds of the data; public 0.39; Kaggle T4 inference ~1.1 s/image). An alternate split copy differs on 489/707 observations, so the weights dataset ships the consumed fold file `grouped_folds_train.csv` (SHA-256 `febb3f67. . .`) alongside the pinned registry copy — retraining must use the former. The reproduction notebook regenerated production and plain-MHSA byte-identically in a clean Kaggle environment; the full-data variant swaps only the detector weights in the same notebook. Other participants' provenance and scores were not independently verified.

## 3.3 Strengths and Weaknesses

**Strengths.** Five candidates were rejected under confirmation across independent folds, bootstrap intervals, or matched public-LB comparison (mask fusion, threshold retuning, refiner retraining, pseudo-labeling, 3-fold ensembling). The one accepted change — edge-guided attention — did not survive the matched-parameter, multi-seed check (Section 3.2): fold-sign agreement plus a bootstrap CI could not attribute the effect to the right mechanism.

**Weaknesses.** Our three-fold agreement conflated attention capacity with the edge prior; in the two-seed ablation it shows no consistent benefit over plain attention. Hard misses (2,138 FN, 1,561 FP) dominate; Figure 2(b) shows an instance-separation failure boundary refinement cannot fix. The residual OOF-to-LB gap is unexplained beyond two ruled-out shift confounds.

A later sweep targeted these error masses. Fold-2 error decomposition (Figure 3) attributes ~65% of false negatives to cases with no proposal at the operating confidence (0.26; median ~715 px, mostly single-annotator objects), yet ~57% of all misses have an IoU > 0.5 candidate below it. Two dozen more mechanisms failed the frozen-point gate ($\Delta$PQ < +0.005) or a fold check, across six families:

*training tricks* (EMA averaging, multi-channel refiner inputs, copy-paste, dense-scene oversampling, confidence/strictness sweeps, a distance-transform loss); *extra proposal sources* (sub-threshold rescue, an RF-DETR union covering 317/612 blind annotations yet flooding ownership, −0.028; a semantic U-Net union, −0.031; native 2×2-tile inference doubling false positives, −0.033); *label structure* (soft annotator-mean targets, union-label retraining); *auxiliary signals* (temporal-neighbor augmentation — tripled data, cut recall; co-temporal magnetograms — no effect); *selection/verification* (a proposal selector, a crop CNN verifier at AUC 0.64 < confidence 0.80); and *pretraining* (SimCLR on 1,707 unlabeled GONG frames, −0.004 refiner PQ, replicated). TTA, ensembling, and rescue each carried ∼ + 0.001–0.002 signal that did not transfer. The binding constraint is detector ranking at usable precision.

Two final mechanisms probed whether that residual mass is fixable at all. A Cellpose-style flow-field instance separator reached the same frontier as the semantic head (163/953 held-out false negatives, 17.1%) yet flooded ownership (−0.021). Expert pairs agree at mean matched IoU 0.634 — below our model's SQ of 0.680 — while a typical record recovers only 56% of the objects another annotator marked, and ∼44% of annotations are single-annotator judgment calls. Under per-(annotator, image) scoring, a prediction matching $k$ of an image's $R$ annotators at IoU $s$ raises PQ iff $ks > \mathrm{PQ} \cdot R/2$: single-annotator objects are worth detecting on one- and two-annotator images (∼63% of labels), and a perfect detector at human boundary agreement would reach PQ ≈0.53–0.55. A preregistered two-class detector labeling instances *weak* (single-annotator) or *strong* (consensus) lost on all twenty swept cells: the head separated the strata (recall 0.73 vs. 0.54) but sacrificed the 76%-majority weak class. The residual gap is therefore mainly recall limited by detector ranking, not a labeling ceiling.

A terminal audit decomposed production errors on all three folds (OOF PQ 0.446 ± 0.001): false positives split evenly across free candidates, annotator-gap candidates (matching only another annotator's labels), and boundary near-misses, and ∼24% of emitted instances carry negative marginal value under per-(annotator, image) pooling. Two consequences reshaped the final evaluation. First, a learned emission gate on 19 inference-time features lost 0.008–0.029 on every held-out fold — annotator-dependent penalties were not predictable from these features, leaving the oracle emission ceiling (∼ + 0.047) unreached. Second, and more consequential for interpreting local experiments, submissions emitting overlapping masks (the refiner's raw output, +0.013 locally; a two-hypothesis-per-object probe, +0.06 locally) were both rejected at ingestion: the host scores only strictly disjoint prediction sets ("score-ordered panoptic painting"), so multi-hypothesis headroom does not exist on the leaderboard. Our resolution stage is already a local optimum under that constraint; the post-processing space is closed. The residual OOF-to-LB gap (0.45 → 0.39) therefore cannot be attributed to submission format and is consistent instead with sparse test annotations and the publicly raised evaluator-version concerns.

A final cross-detector consensus campaign produced the study's most instructive result. Three detectors (production YOLO11m-seg, a 3×3 crop-tile detector, YOLO26m) propose at confidence floor 0.08; mask-IoU ≥ 0.5 clusters emit only when ≥ 2 detectors agree at the operating confidence, with refinement and resolution verbatim. Its first fold-2 reading (+0.0116) cleared the promotion gate, then had to be retracted: the crop detector's training data had silently included the evaluation fold. Leakage-free, it measured ΔPQ = +0.0030 on fold 0 and +0.0086 on fold 2 — positive on both, cutting false positives by 4–119 at near-constant true positives, yet failing the preregistered sequential replication gate (≥ +0.005 on fold 0). A complementary fixed-detection contour vote added +0.0016; the line was closed. Consensus is a real but modest, fold-heterogeneous false-positive filter, not the missing recall mechanism. **Future work:** more seeds, nested validation, better low-confidence ranking, and training-time-only auxiliary teachers (e.g. spine/centerline heads) aimed at the 65% proposal-blind mass.

## 4 Acknowledgment

The organization of the Filament Segmentation Challenge 2026 is partially supported by the U.S. National Science Foundation (NSF) under Grant No. 2209912 and 2433781, directorate for Computer and Information Science and Engineering (CSE), and Office of Advanced Cyberinfrastructure (OAC), and Grant No. 2511630, AST Division Of Astronomical Sciences and MPS Directorate for Mathematical and Physical Sciences.

The Filament Segmentation Challenge 2026 is sponsored by the U.S. National Science Foundation (NSF) National Solar Observatory (NSO).

This work utilizes GONG data obtained by the NSO Integrated Synoptic Program, managed by the National Solar Observatory, which is operated by the Association of Universities for Research in Astronomy (AURA), Inc. under a cooperative agreement with the National Science Foundation and with contribution from the National Oceanic and Atmospheric Administration. The GONG network of instruments is hosted by the Big Bear Solar Observatory, High Altitude Observatory, Learmonth Solar Observatory, Udaipur Solar Observatory, Instituto de Astrofísica de Canarias, and Cerro Tololo Interamerican Observatory.

## References

[1] Azim Ahmadzadeh. 2026. Self-Evaluation Notebook (Solar Filament Segmentation Challenge 2026). https://www.kaggle.com/code/azimahmadzadeh/self-evaluation-notebook Competition's official PQ scorer.

[2] Azim Ahmadzadeh, Rohan Adhyapak, Kartik Chaurasiya, Laxmi Alekhya Nagubandi, V. Aparna, Petrus C. Martens, et al. 2024. A dataset of manually annotated filaments from H-alpha observations. *Scientific Data* 11, Article 1031 (Sept. 2024). doi:10.1038/s41597-024-03876-y

[3] Azim Ahmadzadeh, Dustin J. Kempton, Qin Li, and Alexei A. Pevtsov. 2026. Solar Filament Segmentation Challenge 2026. https://www.kaggle.com/competitions/filament-segmentation-2026.

[4] Bradley Efron and Robert J. Tibshirani. 1993. *An Introduction to the Bootstrap*. Chapman & Hall/CRC. doi:10.1201/9780429246593

[5] Glenn Jocher and Jing Qiu. 2024. Ultralytics YOLO11. https://github.com/ultralytics/ultralytics `ultralytics` package, version 8.3.x.

[6] Alexander Kirillov, Kaiming He, Ross Girshick, Carsten Rother, and Piotr Dollár. 2019. Panoptic Segmentation. In *2019 IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*. 9396–9405. doi:10.1109/CVPR.2019.00963

[7] Roboflow. 2025. RF-DETR: A SOTA Real-Time Object Detection Model. https://github.com/roboflow/rf-detr

[8] Olaf Ronneberger, Philipp Fischer, and Thomas Brox. 2015. U-Net: Convolutional Networks for Biomedical Image Segmentation. In *Medical Image Computing and Computer-Assisted Intervention (MICCAI)*. 234–241. doi:10.1007/978-3-319-24574-4_28

[9] Victor Solomon, Piet Martens, Jingyu Liu, and Rafal Angryk. 2025. EdgeAttNet: Towards Barb-Aware Filament Segmentation. arXiv:2509.02964 [cs.CV]