CAIEMS: An Exploratory LLM-Driven Pipeline for Structuring Construction Accident Narratives into a Queryable Database

Tianhao Sun[1], [Supervisor name][1,*]

2026-09-14

Abstract

Construction accident reports constitute a large but underused source of safety knowledge, and their conversion into analyzable records remains labor-intensive. This paper presents CAIEMS, an exploratory LLM-driven data engineering pipeline that processes publicly available Chinese construction accident narratives into a queryable database prototype of 2,623 records with 33 fields and 16,323 causal annotations. The annotations follow a three-tier evidence scheme: verbatim-evidence codes, semantically induced codes, and domain-prior inference codes, stored and reported separately. The pipeline integrates dual-track collection from web portals and digitized case compilations, LLM text classification, structured field extraction, causal coding under the CAICS operational scheme (5 layers, 19 categories), MECE field standardization, and an interactive Web/REST interface. Three supporting experiments are reported with their scope stated explicitly. First, a constrained comparison of four LLMs on 200 records, in which the adopted model reached 91.2% basic-field accuracy at the lowest cost among candidates; we note that the compared models ran under unequal conditions (differing temperature constraints and output budgets), so the comparison is a system-level selection exercise rather than a general capability ranking. Second, a six-strategy prompt comparison on 100 records with three-expert majority-vote ground truth (Few-Shot best, F1 = 0.669), during which we observed a prompt-phrasing sensitivity that we term the Lexical Gatekeeping Effect: interrogative conditional-check phrasing suppressed paraphrastic evidence for implicit categories (M1 recall 0.141), and a two-step judgment rephrasing raised M1 recall to 0.941 in the same setting. We report this as an observation with a practical remedy, not as an isolated causal mechanism. Third, a protocol study (n = 289) showing high agreement between the LLM and one trained annotator on six basic fields (Cohen's kappa 0.91–0.97 for categorical fields; ICC 0.985 for counts; 99.7% year-month match for dates). The boundaries of these results are stated explicitly throughout: the silver standard is partly model-derived, prompt development and final testing share one sample, and the database reflects publicly retrievable accident coverage rather than a representative sample of all construction accidents.

Keywords: Large language model; Construction safety; Information extraction; Prompt engineering; Accident database; Causal annotation; Inter-annotator agreement

1 Introduction

Construction remains among the most hazardous industries worldwide. Each fatal construction accident generates investigation reports and news narratives that record what happened, how it happened, and why. These texts contain causal information accumulated at national scale over decades, yet they remain unstructured natural language that resists systematic analysis. In China, accident narratives are dispersed across safety information portals, local emergency-management bureaus, news media, and published case compilations, which makes manual compilation expensive and automated compilation a recurring engineering challenge (Kong and Ahn, 2024).

Existing computational approaches to this conversion problem fall into three groups. Supervised classifiers such as BERT (Devlin et al., 2019) and its distilled variants require labeled corpora that are expensive to produce in this domain (Togan et al., 2025). LLM-based studies have demonstrated extraction of accident attributes from OSHA narratives (Ahmadi et al., 2024), HFACS-guided classification of Korean fall accidents (Kim and Han, 2024), and knowledge-graph construction from construction reports (Liu and Luo, 2025). The resulting artifacts, however, are mostly study-bound: extraction feeds a single analysis or a static graph rather than an inspectable, updatable database.

This paper reports on CAIEMS, an exploratory data engineering effort rather than a theory-confirming study. The single organizing question is practical: can a small team, using commodity LLM APIs and modest computing resources, turn publicly available Chinese accident narratives into a queryable database whose labels can be traced to the source text at defined confidence levels? We report what the pipeline produces, what we measured about its reliability, and what we could not yet establish.

Three contributions follow from this framing. (C1) A data engineering pipeline and database prototype: 2,623 records assembled from a dual-track collection — web crawling of public portals and digitization of published case compilations — with 33 fields and 16,323 causal annotations in a three-tier evidence scheme, a Web interface, and a REST API; the data and code are released for inspection upon publication. (C2) The CAICS operational coding scheme — a 5-layer, 19-category set of operational definitions for construction accident causes, positioned explicitly as an operational scheme for this database rather than a new causal theory. (C3) An empirically documented prompt-phrasing sensitivity — the Lexical Gatekeeping Effect — observed during prompt development, together with a two-step judgment remedy, reported with its scope boundaries.

Three supporting experiments anchor the reliability discussion. Experiment 1 compares four LLMs on 200 records for backbone selection under the explicit caveat of unequal running conditions. Experiment 2 compares six prompting strategies on 100 records with three-expert majority-vote ground truth; this experiment surfaced the phrasing sensitivity summarized above. Experiment 3 measures agreement between the LLM and one trained annotator on six basic fields over 289 records. The samples underlying the experiments have known limitations — the silver standard is partly model-derived, and the strategy sample served both prompt development and final reporting — and these limitations are stated at each point of use rather than collected in a single caveat paragraph.

The remainder of the paper is organized as follows. Section 2 reviews related work. Section 3 describes the data sources and corpus construction, the evidence-tier annotation scheme, the CAICS operational definitions, the pipeline architecture, and the database. Section 4 reports the three experiments with their scope statements. Section 5 discusses implications and limitations. Section 6 concludes.

2 Related Work

2.1 Text-based analytics for construction accident documents

Computational analysis of construction safety documents predates LLMs and remains instructive for what it could not do. Association rule mining over manually coded records identified interpretable links between accident types and causal factors (Rafindadi et al., 2023), and decision-tree models over OSHA roofing records produced rules for injury prediction (Onuchukwu et al., 2024). Ayhan and Tokdemir (2019) combined regression and fuzzy logic on an expert-coded incident set. The common constraint across these studies is circular: the analytics are only as good as the structured input, and the structured input was itself produced by costly manual coding. Togan et al. (2025) directly addressed the conversion step, benchmarking TF-IDF, BERT, RoBERTa, XLNet, and DistilBERT for safety-attribute extraction from 5,224 construction accident cases, finding DistilBERT competitive at roughly half the computational cost. Their result typifies the

supervised paradigm: workable accuracy (F1 = 0.72 on severity classification) at the price of a large labeled corpus.

2.2 LLMs for accident information extraction

LLMs shift the bottleneck by inferring structure directly from text without task-specific training (Brown et al., 2020; OpenAI, 2023). Ahmadi et al. (2024) evaluated GPT-3.5, GPT-4.0, Gemini Pro, and LLaMA 3.1 on classifying root cause, injury cause, body part, severity, and time from OSHA construction reports. Zhang, Hou, et al. (2025a) built AIR Agent, a GPT-based chatbot for subway construction report analysis. Liu, Ding, et al. (2025b) applied zero-shot GPT-4o extraction to 1,097 fall-from-height reports, reaching F1 = 0.94 on entity recognition and constructing a weighted risk network. In adjacent domains, Huang et al. (2026) built an LLM pipeline for marine accident knowledge graphs with an accompanying quality assessment framework, and Jiang et al. (2026) constructed a coal mine accident knowledge graph with ontology modeling and interactive visualization. These systems already combine collection, LLM extraction, and graph storage to varying degrees; what varies is the depth of data-quality reporting, the existence of human-validated references, and whether the artifact is maintained as an updatable service.

2.3 HFACS-based causal classification with LLMs

The Human Factors Analysis and Classification System (Shappell and Wiegmann, 2000) dominates causal classification in high-risk industries. Chain-of-thought prompting (Wei et al., 2022) and its variants — zero-shot reasoning (Kojima et al., 2022), self-consistency decoding (Wang et al., 2023), and least-to-most decomposition (Zhou et al., 2023) — form the methodological substrate of prompt-based classification. Liu et al. (2025a) proposed HFACS-CoT, embedding HFACS knowledge into chain-of-thought prompting, and compared six prompting strategies on 113 general aviation narratives with GPT-4o, finding domain CoT superior (recall 74.9%, precision 46.2%). Kim and Han (2024) integrated HFACS with Claude 3.5 Sonnet to analyze 1,816 Korean construction fall cases. Yan et al. (2025) applied HFACS-guided prompting to UAV incident narratives across seven LLMs. Ahmadi et al. (2025) explored GRPO fine-tuning of Llama-3.1 8B for HFACS classification. Across this literature, strategy rankings are established within single model–task pairs, and prompt designs are reported as working configurations without systematic study of how the phrasing of embedded knowledge conditions model behavior.

2.4 Knowledge graphs and accident databases

Kong and Ahn (2024) systematically reviewed knowledge graphs for construction safety management and identified the gap between research prototypes and operational platforms. Liu and Luo (2025) generated construction accident knowledge graphs with iterative CoT prompting. Yang and Park (2025) built a road-accident news knowledge graph. Zhang, Wei, et al. (2025b) developed GRAG-ProSafe, a graph-RAG question-answering system over process-industry accident knowledge. Shi et al. (2025) combined fault trees, Bayesian networks, and ontology reasoning for foundation-pit collapse analysis. Xiao et al. (2026) integrated a knowledge graph as a retrieval layer for LLM-based human reliability analysis. Each of these systems constructs a knowledge artifact of some kind; the present work differs in emphasis rather than in kind — it prioritizes traceable, tiered evidence annotations and an updatable query interface, and it reports the reliability of those annotations with their measured limits.

3 System

3.1 Problem formulation and the evidence-tier annotation scheme

Let $T = \{t_1, t_2, \ldots, t_N\}$ denote a corpus of unstructured accident narratives (median 517 characters in our corpus). The pipeline transforms each t_i into a structured record $r_i = (b_i, c_i)$: a basic information vector b_i covering 33 pre-defined fields, and a causal annotation set $c_i = \{(x_{ij}, e_{ij}, \iota_{ij}, q_{ij})\}$, where x_{ij} is a causal code from the CAICS scheme, e_{ij} is the supporting text, ι_{ij} is the inference chain, and $q_{ij} \in \{\text{explicit}, \text{inferred}, \text{prior}\}$ is the evidence tier.

The three tiers carry different epistemic commitments, and the database stores and reports them separately:

- **explicit**: the source text contains a passage that directly supports the code; e_{ij} is a verbatim quotation. Only explicit codes are presented as evidence-backed in the Web interface.
- **inferred**: the code is induced from the narrative by semantic paraphrase (e.g., a text stating "safety management inadequate" supports M1 without quoting any fixed keyword). The inference chain is recorded.
- **prior**: the code follows from domain assumptions authorized in the prompt (e.g., a fatal accident is taken to imply deficient supervision even when the text is silent). These codes are displayed with a prior label and are excluded from evidence-backed statistics.

This scheme replaces the stronger claim, made in an earlier draft, that every code carries quotable evidence and that evidence-free codes are hallucinations by construction. The tiered scheme is the accurate description of what the production prompt actually does: direct extraction, paraphrase induction, and domain-prior inference are all useful for downstream analysis, but conflating them would present model priors as empirical findings. Across the database, 14,784 annotations (90.6%) are explicit, 1,117 (6.8%) are inferred, and 422 (2.6%) are prior; the remainder of this paper reports totals and, where relevant, tier-level breakdowns.

3.2 Data sources and corpus construction

Every result reported in this paper is bounded by what the corpus contains, and the corpus was assembled rather than sampled. This section describes where the 2,623 records originate and the four procedures applied to them before any modeling — collection, cleaning, relevance filtering, and integration. These procedures elaborate Stage 1 of the pipeline architecture (Section 3.4) and the preprocessing that Stage 1 otherwise summarizes in a single sentence. We describe them at length because, in an end-to-end data engineering pipeline, the properties of the input propagate to every downstream statistic; a reader cannot judge the results in Section 4 without knowing what was collected and what was discarded.

3.2.1 A dual-track corpus

The corpus combines two structurally different acquisition tracks. The **web-collection track** contributes 1,728 records (65.9%) retrieved by purpose-built crawlers from public portals. The **document-digitization track** contributes 895 records (34.1%) recovered from published case compilations distributed as PDF documents. Table 1 reports the composition of both tracks.

Table 1. Corpus composition by source track.

Track	Source	Records	Share	Accident period
Web collection	Safehoo (safehoo.com), safety news portal	1,247	47.5%	2005–2026

Track	Source	Records	Share	Accident period
	Esafety (esafety.cn), safety industry portal	389	14.8%	2005–2026
	Provincial emergency-management bureaus (12 contributing sources)	89	3.4%	2005–2026
	Ministry of Emergency Management (mem.gov.cn)	3	0.1%	2005–2026
	Subtotal	*1,728*	*65.9%*	
Document digitization	Fan Xiren, *800 Cases of Major Fatal Accidents in Building Construction*	703	26.8%	1978–1990
	MOHURD accident case compilations (3 volumes)	192	7.3%	2005–2026
	Subtotal	*895*	*34.1%*	
Total		**2,623**	**100%**	

The two tracks are not interchangeable, and presenting them as a single homogeneous source would misrepresent the database. The digitization track carries the historical depth of the corpus: the 703 records drawn from the Fan compilation are the sole source of the 1978–1990 block, and no web source contributes to that period. The web track supplies the contemporary record, including all government investigation reports, which are the most detailed and most authoritative documents in the corpus. Because the two tracks differ systematically in writing register, length, and field completeness, the pipeline applies the same extraction and coding prompts to both but reports source composition alongside aggregate statistics, and the Web interface exposes the source track as a filterable attribute.

The corpus spans 1978 to 2026 with a pronounced gap. Of the 2,623 records, 698 (26.6%) fall in 1978–1990, 1,895 (72.2%) fall in 2005–2026, and 30 (1.1%) carry no resolvable date. **The period 1991–2004 is absent entirely.** This gap reflects the availability of digital sources rather than any discontinuity in construction safety: the historical compilation covers the early reform period, and sustained public web publication of accident investigation reports begins in the mid-2000s. A longitudinal claim drawn from this database is therefore a comparison between two separated windows, not a continuous trend, and we do not treat the corpus as representative of any underlying population.

3.2.2 Collection schemes

Web-collection track. Twenty-five collectors acquire the web portion. Each implements a common interface and is registered in a central registry; the implementations fall into four families — one search-engine aggregator that issues predefined queries and admits results only from a domain whitelist; nineteen provincial emergency-management bureau collectors that parse HTML listing and detail pages and, in most cases, download and extract attached PDF investigation reports; two national-level collectors (Ministry of Emergency Management and MOHURD); and three auxiliary importers covering open-government datasets, a safety-news special-topic archive, and two published academic accident datasets.

HTTP retrieval uses a single client library across all collectors (httpx, timeouts of 15–60 s). HTML is parsed with BeautifulSoup, using lxml or the standard-library parser according to the source's markup. Main-text extraction prefers trafilatura where page structure permits, falls back to a BeautifulSoup pass that removes script, style, navigation, footer, and form elements, and falls back again to tag stripping with entity unescaping. Attached PDFs are extracted with PyMuPDF when a text layer is present and routed to a document-parsing service with OCR capability when it is not.

Query construction combines two mechanisms. The aggregator issues 17 predefined query templates covering collapse, fall from height, hoisting, excavation, scaffolding, electrocution, fire, poisoning, struck-by, and machinery, together with ministry-level report queries; per-record search

enhancement (Section 3.4) later generates up to three additional queries from each accident's own place names and keywords. Admission of a search result is restricted to a whitelist of 15 news domains plus any 'gov.cn' host, which keeps search-derived material inside the same source population as the targeted collectors.

Politeness and robustness measures are deliberately conventional: a fixed desktop browser user-agent, complete request headers including language preference and, for search-derived requests, a referer, a serial inter-request delay of 1–5 s per collector, and three retrieval attempts per URL with a two-second backoff. **We did not implement proxy rotation, user-agent rotation, JavaScript rendering, or CAPTCHA handling, and collection is entirely serial rather than distributed.** We state this explicitly because it bounds both the collection rate and the extendability of the current corpus: sources that require session handling or dynamic rendering fall outside the present scheme and are represented only insofar as their reports are mirrored on admitted sites.

Document-digitization track. Each volume is converted to text either by extracting its existing text layer or, for scanned volumes, through OCR document parsing, and is then segmented into individual cases. Two segmentation procedures are available. A rule-based splitter anchors on the structural heading convention these compilations use, and an LLM-based splitter returns a start marker and an end marker for each case, after which the cases are cut programmatically by string search rather than accepting model-generated character offsets — the resulting spans are therefore exactly recoverable from the source document and can be audited. Segments below a minimum length (50–100 characters, depending on the splitter) are discarded. Each retained case then enters the same cleaning, filtering, and coding pathway as a web record, so the two tracks converge before any information extraction takes place.

3.2.3 Cleaning, normalization, and rule-based pre-extraction

Cleaning and the bulk of field extraction are performed by deterministic rules rather than by model calls. Three components operate in sequence on every candidate record.

The text cleaner removes boilerplate and rendering artifacts. Ten regular-expression patterns strip recurring site furniture — copyright notices, ICP filing numbers, technical-support lines, sponsorship lines, browser-compatibility notices, disclaimers, and privacy statements — and eight zero-width or invisible code points are deleted. HTML entities are unescaped and text is normalized to NFKC, which folds full-width forms onto their half-width equivalents; runs of whitespace collapse, and more than two consecutive newlines are reduced. Lines shorter than four characters that contain no digit are dropped, a filter that removes stray headings while preserving short lines carrying casualty figures. Documents longer than 50,000 characters are truncated, retaining the leading portion, since accident narratives state the salient facts early. The cleaner is applied identically to web text and to digitized case text.

A rule-based field extractor then applies ordered regular-expression patterns across eight field groups — date, location, casualties, accident type, severity, direct economic loss, contractor, and project name. Patterns are ordered by specificity and carry priority weights; for example, a fully specified date ('YYYY年M月D日') outranks a year-month form, which outranks a month-day form recovered by context. Every extracted value passes plausibility checks (a year within 2000–2030, a death toll below 200, an injury count below 500). A weighted confidence score combines the presence of a date, a city, an accident type, and a death toll, with a small bonus for each additional field recovered.

A normalizer maps both extracted and free-text values onto controlled vocabularies: accident type onto one of twelve categories; severity onto the four statutory tiers defined by Chinese accident regulations — general, relatively major, major, and particularly major, at death-toll thresholds of 3, 10, and 30 — with an explicit severity phrase in the text taking precedence over the inferred tier; province and city onto canonical administrative names through a mapping of more than ninety city-to-province entries; and dates onto ISO format, with Chinese numeral

expressions converted to integers.

The economic rationale for this layer is explicit. Because it is deterministic and incurs no API cost, it runs on every record without qualification, and its confidence output decides what happens next: a record whose confidence falls below 0.7, or which is missing three or more of the four critical fields, is flagged for enhancement, and the remaining records proceed with rule-derived values. This design keeps the majority of field-level values independent of any model, which is what allows Section 4.3 to compare rule-derived and model-derived fields against an independent annotator.

3.2.4 Relevance filtering and deduplication

Relevance filtering. Not every collected page concerns a construction accident; portals also carry regulatory notices, training announcements, and industrial accidents from mining, chemicals, and transport. Filtering proceeds in two gates, the second of which is described with the pipeline stages.

The first gate operates on titles. Twenty-six construction keywords — covering building, municipal works, demolition, scaffolding, tower cranes, foundation pits, formwork, and the standard accident-type terms — admit a title if any one matches, while eight disqualifying patterns reject administrative documents outright (supervision notices, interim measures, management rules, implementation details, training sessions, and the accident-reporting regulation itself). This gate is deliberately permissive: its purpose is to discard obvious non-accidents cheaply, not to decide the borderline cases.

Records passing the title gate face a rule-based classifier that scores four signal vocabularies against the title and the opening of the body text. One vocabulary lists roughly thirty terms that occur almost exclusively on construction sites (tower crane, construction hoist, foundation pit works, formwork support, concrete pouring, rebar tying, earthwork excavation, pile foundations). A second lists roughly twenty-eight construction terms that also appear in industrial settings (construction site, building works, scaffolding, work at height, demolition works). A third lists roughly fifty industrial and extractive terms (mining, steel, cement, chemicals, textiles, power). A fourth lists roughly twenty disqualifying terms (road traffic, highway, railway derailment, coalmine gas, fishing vessels, flood control, hazardous chemicals). Seven ordered rules then combine these signals: specific construction vocabulary admits a record even if an industrial firm is named, an industrial firm with fewer than three construction signals is rejected, a non-industrial firm with two or more construction signals is admitted, and a single construction signal is admitted with low confidence and routed onward rather than decided. The classifier returns a binary judgment with a confidence of *high* or *low*; only high-confidence judgments are final.

Deduplication. Mirrored and reprinted reports of a single accident are common across Chinese news portals, so a record's provenance is not evidence of its uniqueness. The pipeline applies a four-layer procedure, ordered from cheap and exact to expensive and approximate. Layer 1 compares URL identity, using a hash of the URL with the scheme prefix, 'www', trailing slash, and fragment removed. Layer 2 compares a structural fingerprint assembled from year-month, city, death toll, injury toll, and accident type, hashing to twelve hexadecimal characters; because the fingerprint uses year-month rather than the full date, it tolerates the reporting-date discrepancies of a few days that occur when a portal republishes an investigation report. Layer 3 compares title semantics, encoding titles with a Chinese sentence-embedding model and flagging a pair whose cosine similarity reaches 0.85; the candidate set is restricted to a spatial–temporal bucket keyed on month and province, which keeps the comparison from growing with corpus size. When the embedding model is unavailable, an edit-distance ratio with a threshold of 0.80 substitutes. Layer 4 cross-validates four facts independently of title wording — date proximity, city identity, casualty agreement, and accident-type agreement — and requires at least two checks to pass with a normalized agreement above 0.75.

The design intent is that exact and structural layers intercept the large majority of duplicates

and only genuinely ambiguous cases reach the semantic layer. When a duplicate is detected, the pipeline does not discard the incoming record. It merges: the new source URL is appended to the existing record, the source counter increments, and any field the existing record lacks is filled from the new one. Forty-five records in the database carry more than one source URL, and the merged set is exposed through the interface, so a user can see that a given finding rests on, or is corroborated by, more than one publication.

Integration. Accepted records are written to storage under two idempotency rules. Raw candidate text is keyed by a hash of its source URL, so re-running collection over the same source adds nothing and the pipeline can be resumed after interruption. Classification, the most expensive per-record step, checkpoints every ten records, so an interrupted run resumes from the last checkpoint rather than re-issuing model calls. Both properties matter for a corpus of this size assembled by a small team: they make collection and classification restartable without manual bookkeeping.

3.3 CAICS: an operational coding scheme

The Construction Accident Integrated Cause System (CAICS) is a 5-layer, 19-category coding scheme designed for construction accident narratives. Its layers follow the causal leak model: the management layer (M) asks why the site was vulnerable; the protection layer (F) asks why physical barriers failed; the trigger layer (T) asks what material condition initiated the event; the human act layer (H) asks what unsafe behavior preceded it; and the consequence layer (C) asks why the outcome exceeded expectation. Table 2 lists the nineteen categories with operational definitions and typical evidence keywords.

Table 2. The CAICS coding scheme: operational definitions.

Layer	Code	Category	Operational definition	Typical evidence keywords
M — Management foundation	M1	Deficient supervision	No competent supervisor present, or supervision failed to detect and halt an unsafe state	unsupervised work; supervisor absent; no on-site intervention
	M2	Hazard inspection failure	Hazards not inspected, not rectified, or allowed to persist over time	hazard left unrectified; perfunctory inspection; repeated reports ignored
	M3	Inadequate safety training	No induction training or an ineffective safety briefing; workers lacking required safety knowledge	no three-level education; no pre-shift briefing; procedure unknown to workers
	M4	Procedural and regulatory gaps	No safety plan, no emergency plan, or an incomplete site management system	no special construction scheme; emergency plan missing; rules not established
	M5	Irregular market conduct	Contracting without qualification, unlawful subcontracting, delegation, or compressed schedule	contractor unqualified; illegal subcontracting; schedule compressed
F — Protection failure	F1	Missing edge and opening protection	No guardrail, no safety net, an uncovered opening, or an unprotected edge	no guardrail at the shaft; safety net absent; opening left uncovered

Layer	Code	Category	Operational definition	Typical evidence keywords
	F2	Unstable support system	Formwork or scaffold instability, insufficient shoring, or temporary-structure failure	formwork support collapsed; scaffold unstable; shoring insufficient
	F3	Safety device failure	Limit switches defeated, fall arresters failed, or safety devices damaged or not fitted	limiter bypassed; arrester failed; device removed
	F4	Personal protective equipment unused	Safety harness, helmet, or other personal protective equipment not worn where required	harness not attached; helmet not worn; PPE absent
T — Trigger conditions	T1	Equipment and machinery failure	Equipment breakdown, wire-rope failure, mechanical fault, or brake failure	hoist failed; wire rope snapped; brake malfunction
	T2	Abnormal material state	Loading beyond design capacity, defective material, or material instability	stockpile over capacity; material defect; soaked material gained weight
	T3	Geological or ground change	Water ingress, slope instability, foundation settlement, or running sand	sudden water inflow; slope failure; foundation settlement
	T4	Meteorological or hydrological trigger	Heavy rain, high wind, ice and snow, lightning, or sustained rainfall	rainstorm; gale; sustained rainfall; lightning
H — Human acts	H1	Procedure violation	Work performed against the approved method, an unauthorized method change, or non-compliant erection	not built to the scheme; method changed without approval; erected off-code
	H2	Improper command or decision	Work ordered or continued despite a known, identified hazard	ordered to proceed; risk known and work continued
	H3	Risk-perception failure	Hazard not recognized, or recognized but misjudged	hazard not noticed; risk misjudged; inattention
	H4	Improper emergency behavior	Unprotected rescue attempts, delayed evacuation, or rescue methods that worsened the outcome	rescue rushed without protection; wrong rescue method; evacuation delayed
C — Consequence amplification	C1	Delayed rescue response	Rescue began late, no emergency plan was in force, or secondary collapse obstructed rescue	delayed rescue; secondary collapse; no emergency plan in force
	C2	Concealed or delayed reporting	Failure to report, under-reporting, or late reporting of the accident	accident unreported; casualty figure concealed; report filed late

Keywords paraphrase the Chinese expressions that occur in the corpus. The share of codes resting on inference rather than direct quotation varies by layer — 12.0% in the management layer against 3.1% in the trigger layer — consistent with the three-tier evidence scheme of Section 3.1.

Two design features distinguish CAICS from aviation-derived HFACS adaptations (Shappell and Wiegmann, 2000; Liu et al., 2025a): the F layer captures physical protection failures endemic to construction, and the C layer records consequence-amplification factors such as delayed or concealed reporting. The scheme was derived through corpus-driven induction under the leak model: causal statements were extracted from the corpus, clustered into candidate categories, and consolidated into the five layers, with categories below a frequency floor merged or dropped; each retained category received an operational definition and corpus-derived evidence keywords. We emphasize the scope of this claim: the derivation protocol was an iterative engineering procedure rather than a formal content-validity study, and no comparative validation against 24Model (Xuecai et al., 2024), Accimap, or HFACS on independent data has yet been performed. CAICS is therefore positioned in this paper as an operational scheme for this database — a finite, LLM-oriented coding frame with explicit definitions — not as an established causal theory. Its usability evidence consists of the expert annotation agreement on the 100-record strategy sample (Fleiss' kappa 0.859–1.000 across layers, Section 4.1).

3.4 Pipeline architecture

Figure 1 shows the overall architecture. The pipeline consists of six processing stages followed by storage and access layers.

Figure 1. ** **CAIEMS system architecture. Stage 1: Multi-source collection.** Accident reports are acquired from public safety information portals (safehoo.com, esafety.cn), provincial and national emergency-management bureaus, and published case compilations, following the dual-track scheme and the collection, cleaning, and filtering procedures described in Section 3.2. Stage 1 yields the deduplicated working corpus of 2,623 records whose composition is reported in Table 1. Reports at overseas sites of Chinese contractors (22 records) are retained but excluded from provincial statistics.


Stage 2: LLM text classification. Candidate pages are heterogeneous, and a page that mentions accidents is not necessarily a report of one. A lightweight LLM classifier assigns each record one of six text types — *single-accident report*, *multi-accident compilation*, *regulatory document*, *aggregate statistics*, *training material*, or *other* — using few-shot prompting with five annotated examples. The six types reduce to three dispositions: single-accident reports proceed; multi-accident compilations are split into their constituent cases; and the remaining four types are routed out of the corpus. This stage is what removes regulatory notices, aggregate statistics, training material, and advertisement or navigation text that survived the rule-based gates of Section 3.2.4. The 895 digitized records described in Section 3.2 do not pass through this stage; their separation into individual cases is performed at the document level by the segmentation path described there, which effects the same distinction before the records enter the corpus. We note that the classifier is imperfect: in the agreement study's 300-record draw, 11 records were excluded at annotation time as multi-accident texts, indicating residual classification error that the current pipeline does not fully audit, and the multi-accident splitting rules remain partly heuristic.

Stage 3: Basic field extraction (Step 1). For each accepted record, an LLM extracts the 33-field basic information vector under a strict JSON tool schema. Schema-enforced output was obtained for 100% of records in the evaluation runs. The extractor also produces a normalized title summary used for search enrichment.

Stage 4: CAICS causal coding (Step 2). The encoder applies the two-step judgment procedure — explicit matching followed by authorized inference — and records, per code, the evidence tier, the supporting text, and the inference chain (Section 3.1). Figure 2 illustrates the five-layer structure with an example from a real record.

Figure 2. ** **CAICS five-layer causal structure with an example evidence chain. Stage 5: LLM-first MECE enum standardization.** Five free-text fields (work task, equipment, material, worker type, building structure) are normalized through an LLM-first procedure:


Stage 1: Multi-source collection
Crawlers (safehoo, esafety, bureaus)
Stage 2: LLM text classification
single / multi / other (few-shot)
Stage 3: Basic field extraction (Step 1)
33 fields, tool-call structured output
Stage 4: CAICS causal coding (Step 2)
evidence-bound codes + inference chains
Stage 5: MECE enum standardization
LLM-first, 5 fields (WT/EQP/MAT/WKR/BLD)
Stage 6: Storage and access
SQLite (9 tables), Web platform, REST API
Multimodal extension
search enrichment
CLIP image filter
VLM description
2,623 records | 16,323 causal codes | 226 images | 282 VLM analyses



the LLM reviews the value distribution across the corpus, designs a MECE framework, and maps every observed value. Table 3 reports the resulting enumerations with non-null denominators stated explicitly.


Table 3. MECE enumerations produced by the LLM-first procedure.

Field	Categories	Non-null records (share of 2,623)	Largest category (share of non-null)	Residual "other" (share of non-null)
Work task (WT)	11	2,202 (83.9%)	WT02 main structure works (397, 18.0%)	2.9%
Equipment involved (EQP)	13	1,373 (52.3%)	EQP01 hoisting machinery (335, 24.4%)	1.9%
Material involved (MAT)	7	1,465 (55.9%)	MAT01 concrete and cement products (423, 28.9%)	11.1%
Worker type (WKR)	13	1,905 (72.6%)	WKR01 general laborers (928, 48.7%)	6.3%
Building structure (BLD)	12	359 (13.7%)	BLD01 steel structures (127, 35.4%)	3.6%

Stage 6: Storage and access. All artifacts are stored in a SQLite database with nine tables. An interactive Web platform and REST API expose the database: users filter accidents by type, severity, region, work task, and causal code, and inspect the evidence behind each annotation, with evidence tiers displayed separately. The database and code are released for inspection upon publication; until then they are available from the authors on request.

3.5 Multimodal extension

Beyond text, the pipeline enriches records through three display-oriented modules: search enhancement via an aggregated search API (1,636 records, 62.4%), image collection filtered by a zero-shot CLIP classifier (226 images above the 0.5 similarity threshold), and two-phase VLM description with GLM-5V-Turbo (282 analyses across 176 accidents). These modules are extensions rather than evaluated contributions: image quality at the source constrains what VLM analysis can contribute, and the descriptions are presented as supplementary material, not verified annotations.



3.6 Database statistics

Table 4 summarizes the database with counts that close against the total.

Table 4. Database statistics.

Dimension	Value
Records	2,623
Time span	1978-08 to 2026-06 (1991–2004 unrepresented)
Accident types	12 categories, 2,617 records labeled (collapse 1,092; fall-from-height 570; hoisting 225; earthwork collapse 222; electrocution 160; struck-by 119; other 50; fire/explosion 47; mechanical 46; poisoning/asphyxiation 41; vehicle 38; drowning 7); 6 records unlabeled
Severity	general 1,889; relatively major 672; major 53; particularly major 8; 1 record unlabeled
Casualties	5,894 deaths; 5,796 injuries
Causal annotations	16,323 total (explicit 14,784 / inferred 1,117 / prior 422)
Search-enriched records	1,636
CLIP-filtered images	226
VLM analyses	282 across 176 accidents

Figure 3 shows the distribution of the nineteen CAICS categories; the top codes (M1 deficient supervision, H1 procedure violation, H3 failed risk perception) partly reflect the production prompt's authorized prior inference, which is why the tier breakdown is reported alongside the totals.

Figure 3. ** **Distribution of causal annotations across the nineteen CAICS categories.**

4 Experimental Evaluation

The evaluation addresses three questions with explicitly stated scopes: which backbone model the pipeline should adopt under its actual cost constraints (Section 4.3), how the causal-coding

prompt should be phrased (Section 4.4), and whether the LLM's basic-field annotations agree with a trained human annotator (Section 4.5). Sections 4.1 and 4.2 define the datasets and metrics.

4.1 Datasets and sampling

Full corpus. The pipeline produced 2,623 single-accident records spanning 1978–2026, with 33 fields and 16,323 tiered causal annotations. The corpus combines a web-collection track (1,728 records) and a document-digitization track (895 records); Section 3.2 reports its composition and construction, including the 1991–2004 gap.

Silver standard. The 972-record silver standard was constructed by pipeline-version agreement rather than independent human re-annotation: basic fields were adopted directly when two pipeline versions agreed and resolved by rule-based arbitration when they disagreed, and causal-dimension labels merged the two versions' outputs with deduplication. We state this construction explicitly because it bounds what the silver standard can certify: it is reliable to the extent that the two source versions are reliable, and it is not an independent human gold standard. An empty causal dimension in the silver standard indicates that the dimension is not mentioned in the source text. A 100-record subset received fully independent human validation: three construction-safety experts annotated the CAICS codes on the LabelStudio platform, with Fleiss' kappa between 0.859 and 1.000 across the five layers; this subset's ground truth is the majority vote of the three experts and carries 5.1 codes per record on average.

Evaluation samples.


1. *Model comparison sample* (n = 200). Stratified by accident type (11 classes, minimum three per class) drawn from the silver standard. 2. *Strategy comparison sample* (n = 100). Drawn from the silver standard covering all 12 accident types and all 19 CAICS categories; causal ground truth is the three-expert majority vote described above. **Scope statement:** this sample served prompt development — discovering the v1 recall problem, analyzing error categories, designing v2, running the ablation, and selecting the production configuration. Because development and final reporting share one sample, the strategy results carry a development-set reuse risk; the three few-shot examples were drawn from the same silver standard and were not isolated from the test records by an explicit procedure. The reported numbers are therefore best read as a development evaluation, not a frozen-test-set certification. 3. *Agreement sample* (n = 289). Two-stage stratified sampling (accident type × severity, proportional allocation with a floor of two per cell) from the full 2,623-record corpus — not from the silver standard. One trained annotator (a safety-engineering graduate student) labeled six basic features (accident type, severity, province, deaths, injuries, date) via LabelStudio without access to the pipeline's extracted values. Eleven records from the original 300 were excluded as multi-accident texts.

Figure 4 summarizes the sample hierarchy.

Figure 4. Dataset hierarchy and the three evaluation samples.

4.2 Evaluation metrics

Basic field extraction is evaluated with exact-match accuracy per field, with administrative-suffix normalization for location fields. Causal coding is evaluated with per-dimension precision, recall, and F1 under the dimension-level match definition of Liu et al. (2025a); the six-strategy comparison additionally reports percentile bootstrap 95% confidence intervals (1,000 resamples). Inter-annotator agreement uses Cohen's kappa with 95% confidence intervals for categorical fields, ICC(2,1) for count fields, and year-month match rate for dates; these three statistics are reported under their proper names and are not summarized under a single label.



4.3 Experiment 1: Backbone selection under explicit constraints

Four candidate models were evaluated on the model comparison sample: DeepSeek V4, Qwen 3.7, GLM 5.2, and Kimi K2.6, all with the same system prompt and three few-shot examples. Running conditions were not fully equal across models: Kimi K2.6 enforces temperature 1.0 by API specification, GLM 5.2 required a 16,384-token output budget for its reasoning traces, and DeepSeek V4 was accessed with the provider's automatic tier routing enabled, with recorded request identifiers spanning the DeepSeek V4 tier family. Because of these differences, and because each configuration ran once, we frame this experiment as a constrained system comparison supporting an adoption decision, not as a general model capability ranking.

Table 5 reports per-field accuracy. The three strongest models reach 91.2–91.5% overall, with uniformly high accuracy on severity, death toll, and provincial location. City extraction is the hardest field (81.5–88.0%): Chinese reports frequently name county-level cities while the reference records the parent prefecture-level city. Kimi K2.6 lags far behind (63.9%), consistent with its enforced temperature introducing output instability.

Table 5. Basic field extraction accuracy (%), Experiment 1.

Field	DeepSeek V4	Qwen 3.7	GLM 5.2	Kimi K2.6
Accident type	86.0	85.0	84.5	61.5
Severity	98.0	90.5	97.5	69.5
Deaths	96.0	96.0	97.0	68.5
Injuries	90.0	91.0	91.0	58.5
Province	96.0	98.5	96.0	67.0
City	81.5	88.0	83.0	58.5
Overall	**91.2**	**91.5**	**91.5**	**63.9**

Table 6 reports causal coding by dimension. DeepSeek V4 shows the highest average precision (89.5%) and the lowest recall among the capable models (52.7%), while Qwen 3.7 shows the mirror trade-off (78.0% precision, 80.5% recall). Cost and latency complete the adoption picture: USD 0.13 for DeepSeek V4 versus 0.43 (Qwen 3.7), 2.91 (GLM 5.2), and 2.84 (Kimi K2.6) over 200 records; latency 9.8 s versus 8.6 s, 27.0 s, and 74.9 s per record. We adopted DeepSeek V4 for the pipeline.

Table 6. Causal coding precision / recall / F1 (%) by dimension, Experiment 1.

Dimension	DeepSeek V4	Qwen 3.7	GLM 5.2	Kimi K2.6
Management	89.9 / 54.9 / 68.1	67.5 / 95.6 / 79.1	92.3 / 63.7 / 75.4	97.6 / 36.3 / 52.9
Protection	91.9 / 41.9 / 57.6	88.8 / 64.0 / 74.4	87.6 / 67.6 / 76.3	96.4 / 39.0 / 55.5
Trigger	81.0 / 69.4 / 74.7	72.4 / 85.7 / 78.5	73.9 / 69.4 / 71.6	81.5 / 44.9 / 57.9
Human	95.0 / 44.7 / 60.8	83.3 / 76.5 / 79.8	83.9 / 61.2 / 70.7	88.2 / 35.3 / 50.4
Average	**89.5 / 52.7 / 65.3**	**78.0 / 80.5 / 78.0**	**84.4 / 65.5 / 73.5**	**90.9 / 38.9 / 54.2**

4.4 Experiment 2: Prompt strategy comparison and the Lexical Gatekeeping observation

4.4.1 Design

Six prompting strategies were compared on the strategy sample (n = 100, three-expert majority-vote ground truth) using DeepSeek V4 (temperature 0.0): S0 Basic Zero-Shot, S1 Basic Few-Shot (three expert-annotated examples), S2 Auto-CoT, S3 Plan-and-Solve, S4 CAICS-CoT (domain-knowledge CoT with the two-step judgment), and S5 CAICS-CoT+ (serial per-layer calls with summary injection). Appendix A reproduces the prompts in condensed form.


Table 7. Performance of six prompting strategies (majority-vote ground truth, n = 100).

Strategy	Avg. F1 [95% CI]	Avg. Recall	Avg. Precision	Type acc.	Severity acc.	Valid-output rate	Time (s)
S0 Zero-Shot	0.600 [0.520, 0.644]	0.515	0.808	0.630	0.960	96%	1,382
S1 Few-Shot	**0.669 [0.615, 0.722]**	0.634	0.753	0.840	0.970	100%	1,302
S2 Auto-CoT	0.634 [0.564, 0.691]	0.564	0.772	0.860	0.980	85%	2,401
S3 Plan-and-Solve	0.598 [0.529, 0.652]	0.540	0.741	0.850	0.990	92%	1,735
S4 CAICS-CoT	0.656 [0.603, 0.695]	**0.872**	0.565	0.830	0.990	99%	1,843
S5 CAICS-CoT+	0.665 [0.606, 0.719]	0.750	0.618	0.830	0.980	100%	5,430

Notes. Ground truth is the majority vote of three independent expert annotators. Confidence intervals are percentile bootstrap (1,000 resamples). S2's coding metrics and its type/severity accuracies were computed after a post-processing step that recovered 96/100 outputs exhibiting hierarchical-format drift; no other strategy received post-processing, so S2's scores describe a post-processed pipeline rather than raw output. All configurations ran once at temperature 0.0. F1 differences among S1, S4, and S5 are within overlapping confidence intervals; we therefore describe S1 as the highest point estimate rather than as a statistically confirmed winner.

4.4.2 Few-Shot outperforms domain CoT on this model–task pair

Table 7 reports the comparison. S1's examples perform joint format-content calibration: they demonstrate the output schema, the expected code density, code combination patterns, and inference depth. S1's average code density matched the ground truth closely (5.0 vs. 5.1), while S0 under-coded (3.6) and S4 over-coded (6.5). The comparison with Liu et al. (2025a) is informative but confounded: their study and ours differ simultaneously in model (GPT-4o vs. DeepSeek V4), task (aviation HFACS vs. construction CAICS), corpus, and evaluation conditions. The observed ranking difference is therefore consistent with model dependence, task dependence, or both; we do not claim to have isolated model dependence, and the practical reading is simply that the optimal strategy for a new model–task pair cannot be assumed from a single published ranking.



4.4.3 The Lexical Gatekeeping observation and its remedy

The initial S4 prompt (v1) embedded domain knowledge as conditional checks: each code was presented with an interrogative gate ("does the text mention 'no supervision' or 'supervision failure'?") plus an instruction not to fabricate codes. On the strategy sample, v1 reached F1 = 0.503, recall = 0.423, 21% empty outputs, and M1 recall of 0.141 — M1 being the most frequent ground-truth code (present in 85 of 100 records). Most accident narratives never use the exact keyword phrases; they say "safety management inadequate" or "failed to detect and stop in time." Under the conditional-check phrasing, the model appeared to treat the listed keywords as mandatory gates rather than illustrative cues.

We term this observed pattern the **Lexical Gatekeeping Effect**: interrogative conditional-check CoT phrasing suppresses paraphrastic evidence for implicit categories, concentrating recall loss on the highest-frequency implicit codes. The term describes an observation; it does not by itself identify a mechanism.

The remedy replaced the gate with a two-step judgment: (1) explicit matching — does the text support this code directly, under any paraphrase? (2) authorized inference — given the accident's nature and construction-safety knowledge, is this cause necessarily present even without explicit phrasing? The conservative instruction was also replaced by a coverage preference. The combined v1→v2 change raised F1 from 0.503 to 0.656, recall from 0.423 to 0.872, M1 recall from 0.141 to 0.988, and eliminated empty outputs (21% → 0). Figure 5 visualizes the change.

Figure 5. ** **The Lexical Gatekeeping observation and its remedy.**

4.4.4 A constrained ablation of the phrasing change

The v1→v2 transition changed several prompt properties at once — the question form, the addition of the two-step judgment, the explicit authorization of inference, and the output-policy instruction. We therefore ran a four-cell comparison on the same sample: v1 (conditional checks + conservative), v2a (two-step judgment + conservative), v2b (conditional checks + coverage), and v2 (two-step judgment + coverage). Table 8 reports the results. Holding the conservative instruction constant, the phrasing change alone (v1 → v2a) raises M1 recall from 0.141 to 0.941 — 0.800 of the total 0.847 M1-recall recovery — while holding phrasing constant, the policy change alone (v1 → v2b) raises it only to 0.329. At the aggregate level the two manipulations contribute comparably (F1 +0.161 vs. +0.150).

Two scope boundaries follow. First, these are simple pairwise differences, not a formal factorial analysis with interaction estimates, and the four cells ran once each on a development sample shared with the prompt design process. Second, the results describe output behavior, not model-internal mechanisms: whether the interrogative phrasing affects attention, representation, or generation is beyond what this behavioral experiment can establish. The defensible reading is

that, in the current model and CAICS task, prompt phrasing materially changes recall on implicit categories, and the two-step judgment is a practical remedy. We do not claim an isolated causal mechanism.

Table 8. Four-cell comparison of phrasing and output policy (n = 100, majority-vote ground truth, DeepSeek V4, temperature 0.0).

Cell	Phrasing	Output policy	F1	Recall	Precision	Empty output	M1 recall	M3 recall	H3 recall
v1	Conditional checks	Conservative	0.503	0.423	0.856	21%	0.141	0.250	0.111
v2a	Two-step judgment	Conservative	0.665	0.677	0.709	2%	0.941	0.667	0.511
v2b	Conditional checks	Coverage preference	0.653	0.641	0.724	5%	0.329	0.444	0.533
v2	Two-step judgment	Coverage preference	**0.656**	**0.872**	0.565	0%	0.988	0.972	1.000
	Δ(phrasing) = v2a − v1		+0.161	+0.254	−0.147	−19 pp	+0.800	+0.417	+0.400
	Δ(policy) = v2b − v1		+0.150	+0.218	−0.132	−16 pp	+0.188	+0.194	+0.422

4.4.5 Strategy selection for the production pipeline

The production encoder adopts the S4 two-step judgment design rather than S1. The choice favors recall (0.872 vs. 0.634) and the tiered evidence output that the database requires, at the cost of precision (0.565), with an F1 difference from S1 that is small and within overlapping confidence intervals. The three-tier evidence scheme (Section 3.1) is the compensating design: low-precision codes are labeled by tier, so downstream users can distinguish verbatim-evidence codes from prior-inference codes instead of treating every annotation as equally supported.

4.5 Experiment 3: Agreement between the LLM and one trained annotator


The third experiment measures whether the LLM's basic-field annotations agree with a trained human annotator. The scope is stated precisely: this is an agreement study between one LLM configuration and one annotator on six of 33 fields, not a certification of expert-level accuracy and not a test of the causal codes.

On the agreement sample (n = 289), the LLM and the annotator labeled the six fields independently. Table 9 reports the results. For the three categorical fields, Cohen's kappa is 0.9136 (accident type), 0.9477 (severity), and 0.9746 (province). For the two count fields, ICC(2,1) is 0.9849 (deaths) and 0.9853 (injuries), with mean absolute errors of 0.118 and 0.087 per record. Date agreement is 99.7% at year-month granularity. These are three different statistics applied to three different kinds of fields; we report them under their proper names rather than summarizing them under a single kappa label.

Table 9. Agreement between the LLM and one trained annotator on six basic fields (n = 289).

Feature	Metric	Value [95% CI]	Agreement
Accident type	Cohen's κ	0.9136 [0.8747, 0.9466]	93.4%
Severity	Cohen's κ	0.9477 [0.9024, 0.9841]	97.6%
Province	Cohen's κ	0.9746 [0.9563, 0.9927]	97.6%
Deaths	ICC(2,1)	0.9849 [0.9292, 0.9991]	MAE 0.118
Injuries	ICC(2,1)	0.9853 [0.9426, 0.9995]	MAE 0.087
Date (year-month)	Match rate	0.9965	99.7%

Two further boundaries apply. First, agreement does not establish accuracy: both parties can share errors, and no independent arbitration labels exist for this sample. Second, the comparison



spans six basic fields only; the causal codes — the paper's core annotation object — have no analogous large-sample agreement study, and the three-expert annotation covers only the 100-record strategy subset. The earlier draft cited an expert inter-rater range from a separate 100-record three-expert sample as an equivalence band; because that sample differs from the 289-record sample in composition and difficulty, we no longer present it as a bound and report the agreement values on their own terms. Figure 6 plots the kappa values with their confidence intervals.

Figure 6. Agreement between the LLM and one annotator on six fields.

5 Discussion

5.1 Implications

For data engineering practice, three implications follow from the measured results, each stated within its scope. First, the tiered evidence scheme offers a workable alternative to the all-or-nothing claim that every code must carry verbatim support: prior-inference codes are useful for downstream analysis provided they are stored, displayed, and reported separately, which is what the pipeline does. Second, the phrasing observation generalizes as a design caution: in this model and task, interrogative conditional-check phrasing suppressed paraphrastic evidence for implicit categories, and the two-step judgment phrasing recovered most of it (0.800 of the total 0.847 M1-recall recovery). Practitioners designing recall-critical extraction prompts should test phrasing variants rather than assume that listed keywords behave as illustrative cues. Third, the agreement results justify a limited claim: for six basic fields, one LLM configuration and one trained annotator reached high protocol agreement, which supports using the LLM to reduce — not replace — human labeling effort for those fields under human supervision.

5.2 Comparison with prior work

Table 10 positions CAIEMS against representative prior systems along dimensions that can be compared from published reports: data source, record scale, human validation, evidence binding,

and system accessibility. We present this as a descriptive comparison, not as evidence of exclusive novelty; several prior systems already combine collection, LLM extraction, and graph or database storage, and the present work's emphasis is on tiered evidence annotations and an updatable query interface.

Table 10. Descriptive comparison with representative prior systems.

System	Domain	LLM	Coding scheme	Evidence binding	Human validation	Interactive access
Liu et al. (2025a)	Aviation	GPT-4o	HFACS	No	Expert-labeled dataset	No
Kim and Han (2024)	Construction (KR)	Claude 3.5	HFACS	No	No	No
Ahmadi et al. (2024)	Construction (US)	GPT-4.0	None	No	No	No
Liu and Luo (2025)	Construction	GPT-4o	Accimap	No	No	No
Jiang et al. (2026)	Coal mining	LLM	Custom ontology	No	No	Visualization
CAIEMS (this work)	**Construction (CN)**	**DeepSeek V4**	**CAICS (operational)**	**Tiered**	**Partial (100-record subset)**	**Web + API**

5.3 Limitations

We list the limitations that bound the main conclusions, organized by their severity.

(1) *Reference independence.* The 972-record silver standard is partly model-derived (pipeline-version agreement with rule arbitration); only the 100-record causal subset carries independent three-expert validation. Conclusions drawn on the silver standard inherit this bound, and a fully independent human gold standard — with a published annotation guide, annotator backgrounds, blinding, arbitration rules, and per-class sample sizes — remains future work.

(2) *Development–test overlap.* The 100-record strategy sample served prompt development (v1 diagnosis, v2 design, ablation) and final reporting simultaneously, and the three few-shot examples were not isolated from the test records by an explicit procedure. The strategy results therefore carry development-set reuse risk and should be read as a development evaluation; a frozen test set separated from all prompt-design decisions is planned for the next iteration.

(3) *Prompt-phrasing inference.* The four-cell comparison reports simple pairwise differences on one sample with single runs; it does not estimate formal interaction effects, and it cannot support claims about model-internal mechanisms. The Lexical Gatekeeping Effect is reported as an observation with a practical remedy, not as an isolated causal mechanism.

(4) *Model comparison conditions.* The four models ran under unequal conditions (enforced temperature, output budget, tier routing), each configuration ran once, and model identifiers were recorded at family granularity. The comparison supports an adoption decision under these constraints, not a general capability ranking.

(5) *Agreement scope.* The agreement study covers one annotator, six of 33 fields, and no independent arbitration; the causal codes lack a large-sample agreement study. The results support effort reduction on basic fields under supervision, not expert substitution.

(6) *Database audit.* The corpus has known quality gaps: the classifier's residual multi-accident errors are not fully audited, the four-layer deduplication of mirrored reports described in Section 3.2.4 has not been followed by an independent estimate of residual duplication, field missingness varies widely across fields (from 13.7% to 83.9% non-null on the five enum fields), and the corpus overrepresents severe accidents because its sources are public news portals and official investiga-

tion reports. The database covers publicly retrievable accident coverage; it is not a representative sample of all construction accidents.

(7) *Data governance.* The pipeline collects and plans to redistribute text and images from news portals and government sites. Public accessibility does not by itself settle re-publication rights; per-source permissions, takedown mechanisms, and access controls for traumatic imagery are discussed in Section 7 and require completion before any public release.

(8) *Reproducibility.* Data, code, and full prompts are released upon publication rather than at submission; single-run configurations and family-level model identifiers limit exact reproduction. We commit to releasing an anonymous read-only database, verbatim prompts, a minimal reproduction package, and a system demo before resubmission.

6 Conclusion

This paper reported CAIEMS, an exploratory LLM-driven pipeline that converts publicly available Chinese construction accident narratives into a queryable database prototype: 2,623 records drawn from web portals and published case compilations, 33 fields, and 16,323 causal annotations organized in a three-tier evidence scheme, served through a Web interface and REST API. Three supporting experiments, each with stated scope, anchor the reliability discussion: a constrained four-model comparison that motivated the adoption of DeepSeek V4 (91.2% basic-field accuracy at the lowest cost), a six-strategy prompt comparison that surfaced the Lexical Gatekeeping observation and its two-step judgment remedy, and a protocol study showing high agreement between the LLM and one trained annotator on six basic fields. The boundaries of these results are stated throughout: the silver standard is partly model-derived, development and test samples overlap, and no causal mechanism or expert substitution is claimed. The next iteration of this work follows a defined sequence: an independent human gold standard for the causal codes, a frozen test set separated from prompt development, a formal factorial design for the phrasing question, multi-model repetition under matched conditions, and a completed data audit with governance before any public release.

7 Declarations

Data availability. An anonymous read-only snapshot of the database, the field dictionary, the source inventory (composition summarized in Table 1), and the CAICS operational definitions will be provided for peer review upon request and released publicly upon publication. The six prompt templates are reproduced in condensed form in Appendix A; verbatim prompts are included in the reproduction package.

Code availability. The pipeline, evaluation scripts, and experiment runners will be released under an open-source license together with the data upon publication; a minimal reproduction package is available from the authors on request during review.

Ethics and data governance. This study analyzes publicly available news reports and government-published accident briefings; it involves no human subjects or identifiable personal data in the structured records. Public accessibility, however, does not automatically authorize bulk collection, long-term storage, and redistribution. Before any public release, the following will be completed: a per-source permission or fair-use assessment; retention of original URLs and crawl timestamps for every record; removal or masking of names and identifiable faces appearing in images; a takedown and deletion mechanism on request; and access controls for graphic or traumatic imagery. Third-party images for which redistribution rights cannot be established will be excluded from any public release.

CRediT author statement. Tianhao Sun (Nanjing Tech University): Conceptualization, Methodology, Software, Data Curation, Formal Analysis, Investigation, Writing — Original Draft.

[Supervisor name] (Nanjing Tech University): Conceptualization, Supervision, Validation, Writing — Review & Editing.

Declaration of competing interest. The authors declare no competing interests.

Funding. This research received no specific grant from funding agencies in the public, commercial, or not-for-profit sectors.

Use of AI tools. Large language models constitute the research object and the core technical instrument of this study: all extraction, classification, and coding results reported in Sections 3–4 were produced by the evaluated models through the documented pipeline. During manuscript preparation, LLM-based writing assistance was used for language polishing; all scientific content, experimental design, and data originate from the authors' work and were verified by the authors.

References

1. Ahmadi, A., Sharif, S., Banad, Y. (2025). Improving Aviation Safety Analysis: Automated HFACS Classification Using Reinforcement Learning with Group Relative Policy Optimization. arXiv:2508.21201.

Ahmadi, E., Muley, S., Wang, C. (2024). Automatic Construction Accident Report Analysis Using Large Language Models (LLMs). Journal of Intelligent Construction, 3(1). https://doi.org/10.26599/jic.2024.9180039

Ayhan, B.U., Tokdemir, O.B. (2019). Predicting the outcome of construction incidents. Safety Science, 113, 91–104. https://doi.org/10.1016/j.ssci.2018.11.001

Brown, T., Mann, B., Ryder, N., et al. (2020). Language Models are Few-Shot Learners. Advances in Neural Information Processing Systems, 33, 1877–1901.

Devlin, J., Chang, M.-W., Lee, K., Toutanova, K. (2019). BERT: Pre-training of Deep Bidirectional Transformers for Language Understanding. In Proceedings of NAACL-HLT 2019, 4171–4186.

Huang, Y., Yan, R., Zhang, Z. (2026). Automated knowledge extraction from marine accident reports using large language models: Graph construction and evaluation. Ocean & Coastal Management, 272, 108015. https://doi.org/10.1016/j.ocecoaman.2025.108015

Jiang, Y., Nie, B., Wang, J., Peng, P., Wang, L. (2026). Large language model-driven knowledge graph and intelligent analysis for coal mine accidents. Measurement, 277, 121558. https://doi.org/10.1016/j.measurement.2026.121558

Kim, D., Han, S. (2024). Systemic Analysis of Fall Accidents Caused by Worker Inattention at Construction Sites: An Integrated Approach using HFACS and LLM. KIBIM Magazine, 14(4), 23–34. https://doi.org/10.13161/kibim.2024.14.4.023

Kojima, T., Gu, S.S., Reid, M., Matsuo, Y., Iwasawa, Y. (2022). Large Language Models are Zero-Shot Reasoners. Advances in Neural Information Processing Systems, 35, 22199–22213.

Kong, F., Ahn, S. (2024). Use of Knowledge Graphs for Construction Safety Management: A Systematic Literature Review. Information, 15(7), 390. https://doi.org/10.3390/info15070390

Liu, Q., Ding, Y., Luo, X. (2025b). Automated knowledge graph-based risk assessment for fall-from-height accidents in construction. Automation in Construction, 179, 106482. https://doi.org/10.1016/j.autcon.2025.106482

Liu, Q., Li, F., Ng, K.K.H., Han, J., Feng, S. (2025a). Accident investigation via LLMs reasoning: HFACS-guided Chain-of-Thoughts enhance general aviation safety. Expert Systems with Applications, 269, 126422. https://doi.org/10.1016/j.eswa.2025.126422

Liu, Q., Luo, X. (2025). Large language model-based knowledge graph construction of unstructured accident reports to improve construction safety. EG-ICE 2025. https://doi.org/10.17868/strath.00093269

Onuchukwu, I.S., Gholizadeh, P., Liko, G., Esmaeili, B. (2024). Nature of Occupational Incidents among Roofing Contractors: A Data Mining Approach. Buildings, 14(3), 595. https://doi.org/10.3390/buildings14030595

OpenAI (2023). GPT-4 Technical Report. arXiv:2303.08774.

Rafindadi, A.D., Shafiq, N., Othman, I., et al. (2023). Data mining of the essential causes of different types of fatal construction accidents. Heliyon, 9(2), e13389. https://doi.org/10.1016/j.heliyon.2023.e13389

Shappell, S.A., Wiegmann, D.A. (2000). The Human Factors Analysis and Classification System–HFACS. Report DOT/FAA/AM-00/7, Office of Aviation Medicine, Federal Aviation Administration.

Shi, D., Gan, S., Zurada, J., Guan, J., Wang, F., Weichbroth, P. (2025). A multi-model approach to construction site safety: Fault trees, Bayesian networks, and ontology reasoning. Expert Systems with Applications, 288, 127817. https://doi.org/10.1016/j.eswa.2025.127817

Togan, V., Mostofi, F., Tokdemir, O.B., Kadioglu, F. (2025). Efficient Management of Safety Documents Using Text-Based Analytics to Extract Safety Attributes From Construction Accident Reports. IEEE Access, 13, 99758–99777. https://doi.org/10.1109/ACCESS.2025.3576442

Wang, X., Wei, J., Schuurmans, D., et al. (2023). Self-Consistency Improves Chain of Thought Reasoning in Language Models. In Proceedings of ICLR 2023.

Wei, J., Wang, X., Schuurmans, D., et al. (2022). Chain-of-Thought Prompting Elicits Reasoning in Large Language Models. Advances in Neural Information Processing Systems, 35, 24824–24837.

Xiao, X., Chen, P., Qi, B., et al. (2026). KRAIL: A knowledge-driven framework for human reliability analysis integrating IDHEAS-DATA and large language models. Reliability Engineering & System Safety, 265, 111585. https://doi.org/10.1016/j.ress.2025.111585

Xuecai, X., Gui, F., Shifei, S., et al. (2024). Accident case data-accident causation model driven safety training method. Process Safety and Environmental Protection, 182, 1208–1226. https://doi.org/10.1016/j.psep.2023.12.042

Yan, Y., Li, B., Lodewijks, G. (2025). UAV Accident Forensics via HFACS-LLM Reasoning: Low-Altitude Safety Insights. Drones, 9(10), 704. https://doi.org/10.3390/drones9100704

Yang, J., Park, S. (2025). LLM-Assisted Knowledge Graph Construction for Managing Road Accident Information From News Articles. IEEE Access, 13, 217846–217865. https://doi.org/10.1109/ACCESS.2025.3648842

Zhang, L., Hou, Y., Ren, F. (2025a). AIR Agent—A GPT-Based Subway Construction Accident Investigation Report Analysis Chatbot. Buildings, 15(4), 527. https://doi.org/10.3390/buildings15040527

Zhang, J., Zhang, W., Wei, Q., Zhong, H., Miao, Y. (2025b). GRAG-ProSafe QAS: Graph retrieval-augmented generation for process production safety intelligent question and answer system. Expert Systems with Applications. https://doi.org/10.1016/j.eswa.2025.129947

Zhou, D., Schärli, N., Hou, L., et al. (2023). Least-to-Most Prompting Enables Complex Reasoning in Large Language Models. In Proceedings of ICLR 2023.

Prompt Templates

The six prompting strategies are summarized below; verbatim prompts are included in the reproduction package.

A.1 S0 Basic Zero-Shot: the CAICS taxonomy (nineteen codes with definitions) and the JSON output format, with no reasoning guidance.

A.2 S1 Basic Few-Shot: S0 plus three expert-annotated examples (text → codes with evidence), drawn from the silver standard.

A.3 S2 Auto-CoT: S0 plus an instruction to self-organize reasoning along the M→F→T→H→C causal chain before coding.

A.4 S3 Plan-and-Solve: S0 plus an instruction to first draft an analysis plan, then execute it.

A.5 S4 CAICS-CoT: two versions were tested. v1 phrased every code as an interrogative conditional check ("does the text mention …?") with a conservative instruction. v2 replaced the

checks with the two-step judgment (explicit matching + authorized inference, including domain-prior rules such as inferring supervision deficiency from a fatal outcome) and a coverage preference.

A.6 S5 CAICS-CoT+: five independent per-layer API calls with inter-layer summary injection, plus a final aggregation call.

V2 修订说明（供作者与导师查阅，投稿时删除本段）：本版依据综合评阅意见完成以下文字级修订——*(1)*主线确定为"探索性数据工程系统与数据资源"，删除"首次/推翻/证明模型依赖/因果机制/专家级/替代人工/全部编码有证据"等结论；*(2)*致因标注重构为 *explicit/inferred/prior* 三层证据分级（对应数据库 *evidence_quality* 字段），全文统一分层统计口径；*(3)*银标准构建方式如实描述并标注独立性边界；*(4)*开发集与测试集重叠风险在 *4.1* 显式声明；*(5)*2×2 消融降级为"措辞敏感性观察+实用补救"，删除机制性归因与"排除替代解释"表述；*(6)*人机一致性限定为"一名标注者、六项字段、协议一致性"，κ/*ICC*/匹配率分列不再统称 *Kappa*；*(7)*全部计数对账闭合（类型 *2,617+*未标注*6*、等级 *2,622+*未标注*1*、表*2* 补非空分母列）；*(8)M1* 数字全文统一为 *0.847/0.800*；*(9)*表引用勘误（*4.5* 节表 *7*→表 *8*）、表 *6* 脚注与数值矛盾修正；*(10)*数据治理声明扩充（逐源许可/撤回机制/创伤影像访问控制）；*(11)*局限性扩为 *8* 项分级；*(12)*新增 *3.2* 节"数据来源与语料构建"（含 *4* 个子节与表 *1*），端到端呈现采集、清洗、筛选与整合流程，原 *3.2–3.5* 节顺延为 *3.3–3.6* 节、表 *1–9* 顺延为表 *2–10*，并修正阶段 *2* 的两处表述（文本类型实为六类而非三类；*895* 条数字化记录经独立的文献切分路径入库，并非在该阶段被删除）及 *5.3* 节*(6)*枚举字段非空率上限（*52.3%*→*83.9%*）。六张插图已由 *'scripts/gen_paper_figures.py'* 生成并插入（*Figure 1–6*），图中分布数字随主库现读；表 *2*（*5* 层 *19* 类操作定义）已按生产提示词补全，定义与落库类名逐条核对一致，表注给出实测的各层推断占比。