

# Contents

<b>1 Setting</b>	<b>1</b>
1.1 PS	1
<b>2 Math</b>	<b>2</b>
2.1 Basic Arithmetics	2
2.2 FFT	3
2.3 Chinese Remainder	3
<b>3 Data Structure</b>	<b>3</b>
3.1 Fenwick Tree	3
3.2 Merge Sort Tree	3
3.3 SegmentTree Lazy Propagation	4
<b>4 Geometry</b>	<b>4</b>
4.1 Basic Operations	4
4.2 Convex Hull	6
4.3 Pooint in Polygon	6
4.4 Polygon Cut	6
4.5 Rotating Calipers	7
4.6 Seperating Axis Theorem	7
4.7 Two Far Point	7
4.8 Two Nearest Point	8
<b>5 Graph</b>	<b>8</b>
5.1 Dijkstra	8
5.2 Bellman-Ford	8
5.3 Spfa	9
5.4 Topological Sort	9
5.5 Strongly Connected Component	10
5.6 Union Find	10
5.7 MST Kruskal	10
5.8 Lowest Common Ancestor	11
5.9 Maxflow dinic	12
5.10 Maxflow Edmonds-Karp	12
5.11 MCMF SPFA	13
5.12 MCMF	14
<b>6 String</b>	<b>15</b>
6.1 KMP	15
6.2 Manacher	15
6.3 Suffix Array	16
6.4 2nd Suffix Array	16
6.5 Trie	17

6.6 Aho-Corasick	17
<b>7 Dynamic Programming</b>	<b>17</b>
7.1 LIS	17
7.2 LIS only length	18
7.3 KnapSack	18
7.4 Coin Change	18
7.5 Bit Field DP	18

## 1 Setting

### 1.1 PS

```
#include <bits/stdc++.h>

using namespace std;

#define for1(s, e) for(int i = s; i < e; i++)
#define for1j(s, e) for(int j = s; j < e; j++)
#define forEach(k) for(auto i : k)
#define forEachj(k) for(auto j : k)
#define sz(vct) vct.size()
#define all(vct) vct.begin(), vct.end()
#define sortv(vct) sort(vct.begin(), vct.end())
#define uniq(vct) sort(all(vct));vct.erase(unique(all(vct)), vct.end())
#define fi first
#define se second
#define INF (1ll << 60ll)

typedef unsigned long long ull;
typedef long long ll;
typedef ll llint;
typedef unsigned int uint;
typedef unsigned long long int ull;
typedef ull ullint;

typedef pair<int, int> pii;
typedef pair<ll, ll> pll;
typedef pair<double, double> pdd;
typedef pair<double, int> pdi;
typedef pair<string, string> pss;

typedef vector<int> iv1;
typedef vector<iv1> iv2;
typedef vector<ll> llv1;
typedef vector<llv1> llv2;

typedef vector<pii> piiv1;
typedef vector<piiv1> piiv2;
typedef vector<pll> pll1;
typedef vector<pll1> pll2;
typedef vector<pdd> pdd1;
```

```

typedef vector<pddv1> pddv2;

const double EPS = 1e-8;
const double PI = acos(-1);

template<typename T>
T sq(T x) { return x * x; }

int sign(ll x) { return x < 0 ? -1 : x > 0 ? 1 : 0; }
int sign(int x) { return x < 0 ? -1 : x > 0 ? 1 : 0; }
int sign(double x) { return abs(x) < EPS ? 0 : x < 0 ? -1 : 1; }

void solve() {

}

int main() {
    ios::sync_with_stdio(0);
    cin.tie(NULL);cout.tie(NULL);
    int tc = 1; // cin >> tc;
    while(tc--) solve();
}

```

## 2 Math

### 2.1 Basic Arithmetics

```

typedef long long ll;
typedef unsigned long long ull;

// calculate lg2(a)
inline int lg2(ll a) {
    return 63 - __builtin_clzll(a);
}

// calculate the number of 1-bits
inline int bitcount(ll a) {
    return __builtin_popcountll(a);
}

// calculate ceil(a/b)
// |a|, |b| <= (2^63)-1 (does not cover -2^63)
ll ceildiv(ll a, ll b) {
    if (b < 0) return ceildiv(-a, -b);
    if (a < 0) return (-a) / b;
    return ((ull)a + (ull)b - 1ull) / b;
}

// calculate floor(a/b)
// |a|, |b| <= (2^63)-1 (does not cover -2^63)
ll floordiv(ll a, ll b) {
    if (b < 0) return floordiv(-a, -b);
    if (a >= 0) return a / b;
    return -(ll)(((ull)(-a) + b - 1) / b);
}

```

```

}

// calculate a*b % m
// x86-64 only
ll large_mod_mul(ll a, ll b, ll m) {
    return ll((__int128)a*(__int128)b%m);
}

// calculate a*b % m
// |m| < 2^62, x86 available
// O(logb)
ll large_mod_mul(ll a, ll b, ll m) {
    a %= m; b %= m; ll r = 0, v = a;
    while (b) {
        if (b&1) r = (r + v) % m;
        b >>= 1;
        v = (v << 1) % m;
    }
    return r;
}

// calculate n^k % m
ll modpow(ll n, ll k, ll m) {
    ll ret = 1;
    n %= m;
    while (k) {
        if (k & 1) ret = large_mod_mul(ret, n, m);
        n = large_mod_mul(n, n, m);
        k /= 2;
    }
    return ret;
}

// calculate gcd(a, b)
ll gcd(ll a, ll b) {
    return b == 0 ? a : gcd(b, a % b);
}

// find a pair (c, d) s.t. ac + bd = gcd(a, b)
pair<ll, ll> extended_gcd(ll a, ll b) {
    if (b == 0) return { 1, 0 };
    auto t = extended_gcd(b, a % b);
    return { t.second, t.first - t.second * (a / b) };
}

// find x in [0,m) s.t. ax === gcd(a, m) (mod m)
ll modinverse(ll a, ll m) {
    return (extended_gcd(a, m).first % m + m) % m;
}

// calculate modular inverse for 1 ~ n
void calc_range_modinv(int n, int mod, int ret[]) {
    ret[1] = 1;
    for (int i = 2; i <= n; ++i)
        ret[i] = (ll)(mod - mod/i) * ret[mod%i] % mod;
}

```

```
}
```

## 2.2 FFT

```
void fft(int sign, int n, double *real, double *imag) {
    double theta = sign * 2 * pi / n;
    for (int m = n; m >= 2; m >>= 1, theta *= 2) {
        double wr = 1, wi = 0, c = cos(theta), s = sin(theta);
        for (int i = 0, mh = m >> 1; i < mh; ++i) {
            for (int j = i; j < n; j += m) {
                int k = j + mh;
                double xr = real[j] - real[k], xi = imag[j] - imag[k];
                real[j] += real[k], imag[j] += imag[k];
                real[k] = wr * xr - wi * xi, imag[k] = wr * xi + wi * xr;
            }
            double _wr = wr * c - wi * s, _wi = wr * s + wi * c;
            wr = _wr, wi = _wi;
        }
        for (int i = 1, j = 0; i < n; ++i) {
            for (int k = n >> 1; k > (j ^ k); k >>= 1);
            if (j < i) swap(real[i], real[j]), swap(imag[i], imag[j]);
        }
    }
    // Compute Poly(a)*Poly(b), write to r; Indexed from 0
    // O(n*Logn)
    int mult(int *a, int n, int *b, int m, int *r) {
        const int maxn = 100;
        static double ra[maxn], rb[maxn], ia[maxn], ib[maxn];
        int fn = 1;
        while (fn < n + m) fn <= 1; // n + m: interested length
        for (int i = 0; i < n; ++i) ra[i] = a[i], ia[i] = 0;
        for (int i = n; i < fn; ++i) ra[i] = ia[i] = 0;
        for (int i = 0; i < m; ++i) rb[i] = b[i], ib[i] = 0;
        for (int i = m; i < fn; ++i) rb[i] = ib[i] = 0;
        fft(1, fn, ra, ia);
        fft(1, fn, rb, ib);
        for (int i = 0; i < fn; ++i) {
            double real = ra[i] * rb[i] - ia[i] * ib[i];
            double imag = ra[i] * ib[i] + rb[i] * ia[i];
            ra[i] = real, ia[i] = imag;
        }
        fft(-1, fn, ra, ia);
        for (int i = 0; i < fn; ++i) r[i] = (int)floor(ra[i] / fn + 0.5);
        return fn;
    }
}
```

## 2.3 Chinese Remainder

```
// find x s.t. x === a[0] (mod n[0])
//             === a[1] (mod n[1])
//             ...
// assumption: gcd(n[i], n[j]) = 1
ll chinese_remainder(ll* a, ll* n, int size) {
```

```
    if (size == 1) return *a;
    ll tmp = modinverse(n[0], n[1]);
    ll tmp2 = (tmp * (a[1] - a[0]) % n[1] + n[1]) % n[1];
    ll ora = a[1];
    ll tgcd = gcd(n[0], n[1]);
    a[1] = a[0] + n[0] / tgcd * tmp2;
    n[1] *= n[0] / tgcd;
    ll ret = chinese_remainder(a + 1, n + 1, size - 1);
    n[1] /= n[0] / tgcd;
    a[1] = ora;
    return ret;
}
```

## 3 Data Structure

### 3.1 Fenwick Tree

```
const int TSIZE = 100000;
int tree[TSIZE + 1];

// Returns the sum from index 1 to p, inclusive
int query(int p) {
    int ret = 0;
    for (; p > 0; p -= p & -p) ret += tree[p];
    return ret;
}

// Adds val to element with index pos
void add(int p, int val) {
    for (; p <= TSIZE; p += p & -p) tree[p] += val;
}
```

### 3.2 Merge Sort Tree

```
llv1 a;
llv1 mTree[Mx];
void makeTree(ll idx, ll ss, ll se) {
    if (ss == se) {
        mTree[idx].push_back(a[ss]);
        return;
    }
    ll mid = (ss + se) / 2;
    makeTree(2 * idx + 1, ss, mid);
    makeTree(2 * idx + 2, mid + 1, se);
    merge(mTree[2 * idx + 1].begin(), mTree[2 * idx + 1].end(), mTree[2 * idx + 2].begin(), mTree[2 * idx + 2].end(), back_inserter(mTree[idx]));
}
ll query(ll node, ll start, ll end, ll q_s, ll q_e, ll k) {
    // i j k: Ai, Ai+1, ..., Aj 이루어진부분수열중에서보다 k 큰원소의개수를출력한다
    .if (q_s > end || start > q_e) return 0;
    if (q_s <= start && q_e >= end) {
        return mTree[node].size() - (upper_bound(mTree[node].begin(), mTree[node].end(), k) - mTree[node].begin());
    }
}
```

```

    ll mid = (start + end) / 2;
    ll p1 = query(2 * node + 1, start, mid, q_s, q_e, k);
    ll p2 = query(2 * node + 2, mid + 1, end, q_s, q_e, k);
    return p1 + p2;
}

```

### 3.3 SegmentTree Lazy Propagation

```

// example implementation of sum tree
const int TSIZE = 131072; // always 2^k form && n <= TSIZE
int segtree[TSIZE * 2], prop[TSIZE * 2];
void seg_init(int nod, int l, int r) {
    if (l == r) segtree[nod] = dat[l];
    else {
        int m = (l + r) >> 1;
        seg_init(nod << 1, l, m);
        seg_init(nod << 1 | 1, m + 1, r);
        segtree[nod] = segtree[nod << 1] + segtree[nod << 1 | 1];
    }
}
void seg_relax(int nod, int l, int r) {
    if (prop[nod] == 0) return;
    if (l < r) {
        int m = (l + r) >> 1;
        segtree[nod << 1] += (m - l + 1) * prop[nod];
        prop[nod << 1] += prop[nod];
        segtree[nod << 1 | 1] += (r - m) * prop[nod];
        prop[nod << 1 | 1] += prop[nod];
    }
    prop[nod] = 0;
}
int seg_query(int nod, int l, int r, int s, int e) {
    if (r < s || e < l) return 0;
    if (s <= l && r <= e) return segtree[nod];
    seg_relax(nod, l, r);
    int m = (l + r) >> 1;
    return seg_query(nod << 1, l, m, s, e) + seg_query(nod << 1 | 1, m + 1, r, s, e);
}
void seg_update(int nod, int l, int r, int s, int e, int val) {
    if (r < s || e < l) return;
    if (s <= l && r <= e) {
        segtree[nod] += (r - l + 1) * val;
        prop[nod] += val;
        return;
    }
    seg_relax(nod, l, r);
    int m = (l + r) >> 1;
    seg_update(nod << 1, l, m, s, e, val);
    seg_update(nod << 1 | 1, m + 1, r, s, e, val);
    segtree[nod] = segtree[nod << 1] + segtree[nod << 1 | 1];
}
// usage:
// seg_update(1, 0, n - 1, qs, qe, val);
// seg_query(1, 0, n - 1, qs, qe);

```

## 4 Geometry

### 4.1 Basic Operations

```

const double eps = 1e-9;

inline int diff(double lhs, double rhs) {
    if (lhs - eps < rhs && rhs < lhs + eps) return 0;
    return (lhs < rhs) ? -1 : 1;
}

inline bool is_between(double check, double a, double b) {
    if (a < b)
        return (a - eps < check && check < b + eps);
    else
        return (b - eps < check && check < a + eps);
}

struct Point {
    double x, y;
    bool operator==(const Point& rhs) const {
        return diff(x, rhs.x) == 0 && diff(y, rhs.y) == 0;
    }
    Point operator+(const Point& rhs) const {
        return Point{ x + rhs.x, y + rhs.y };
    }
    Point operator-(const Point& rhs) const {
        return Point{ x - rhs.x, y - rhs.y };
    }
    Point operator*(double t) const {
        return Point{ x * t, y * t };
    }
};

struct Circle {
    Point center;
    double r;
};

struct Line {
    Point pos, dir;
};

inline double inner(const Point& a, const Point& b) {
    return a.x * b.x + a.y * b.y;
}

inline double outer(const Point& a, const Point& b) {
    return a.x * b.y - a.y * b.x;
}

inline int ccw_line(const Line& line, const Point& point) {
    return diff(outer(line.dir, point - line.pos), 0);
}

```

```

inline int ccw(const Point& a, const Point& b, const Point& c) {
    return diff(outer(b - a, c - a), 0);
}

inline double dist(const Point& a, const Point& b) {
    return sqrt(inner(a - b, a - b));
}

inline double dist2(const Point &a, const Point &b) {
    return inner(a - b, a - b);
}

inline double dist(const Line& line, const Point& point, bool segment = false) {
    double c1 = inner(point - line.pos, line.dir);
    if (segment && diff(c1, 0) <= 0) return dist(line.pos, point);
    double c2 = inner(line.dir, line.dir);
    if (segment && diff(c2, c1) <= 0) return dist(line.pos + line.dir, point);
    return dist(line.pos + line.dir * (c1 / c2), point);
}

bool get_cross(const Line& a, const Line& b, Point& ret) {
    double mdet = outer(b.dir, a.dir);
    if (diff(mdet, 0) == 0) return false;
    double t2 = outer(a.dir, b.pos - a.pos) / mdet;
    ret = b.pos + b.dir * t2;
    return true;
}

bool get_segment_cross(const Line& a, const Line& b, Point& ret) {
    double mdet = outer(b.dir, a.dir);
    if (diff(mdet, 0) == 0) return false;
    double t1 = -outer(b.pos - a.pos, b.dir) / mdet;
    double t2 = outer(a.dir, b.pos - a.pos) / mdet;
    if (!is_between(t1, 0, 1) || !is_between(t2, 0, 1)) return false;
    ret = b.pos + b.dir * t2;
    return true;
}

Point inner_center(const Point &a, const Point &b, const Point &c) {
    double wa = dist(b, c), wb = dist(c, a), wc = dist(a, b);
    double w = wa + wb + wc;
    return Point{ (wa * a.x + wb * b.x + wc * c.x) / w, (wa * a.y + wb * b.y +
        wc * c.y) / w };
}

Point outer_center(const Point &a, const Point &b, const Point &c) {
    Point d1 = b - a, d2 = c - a;
    double area = outer(d1, d2);
    double dx = d1.x * d1.x * d2.y - d2.x * d2.x * d1.y
        + d1.y * d2.y * (d1.y - d2.y);
    double dy = d1.y * d1.y * d2.x - d2.y * d2.y * d1.x
        + d1.x * d2.x * (d1.x - d2.x);
    return Point{ a.x + dx / area / 2.0, a.y - dy / area / 2.0 };
}

```

```

vector<Point> circle_line(const Circle& circle, const Line& line) {
    vector<Point> result;
    double a = 2 * inner(line.dir, line.dir);
    double b = 2 * (line.dir.x * (line.pos.x - circle.center.x)
        + line.dir.y * (line.pos.y - circle.center.y));
    double c = inner(line.pos - circle.center, line.pos - circle.center)
        - circle.r * circle.r;
    double det = b * b - 2 * a * c;
    int pred = diff(det, 0);
    if (pred == 0)
        result.push_back(line.pos + line.dir * (-b / a));
    else if (pred > 0) {
        det = sqrt(det);
        result.push_back(line.pos + line.dir * ((-b + det) / a));
        result.push_back(line.pos + line.dir * ((-b - det) / a));
    }
    return result;
}

vector<Point> circle_circle(const Circle& a, const Circle& b) {
    vector<Point> result;
    int pred = diff(dist(a.center, b.center), a.r + b.r);
    if (pred > 0) return result;
    if (pred == 0) {
        result.push_back((a.center * b.r + b.center * a.r) * (1 / (a.r + b.r)));
        return result;
    }
    double aa = a.center.x * a.center.x + a.center.y * a.center.y - a.r * a.r;
    double bb = b.center.x * b.center.x + b.center.y * b.center.y - b.r * b.r;
    double tmp = (bb - aa) / 2.0;
    Point cdiff = b.center - a.center;
    if (diff(cdiff.x, 0) == 0) {
        if (diff(cdiff.y, 0) == 0)
            return result; // if (diff(a.r, b.r) == 0): same circle
        return circle_line(a, Line{ Point{ 0, tmp / cdiff.y }, Point{ 1, 0 } });
    }
    return circle_line(a,
        Line{ Point{ tmp / cdiff.x, 0 }, Point{ -cdiff.y, cdiff.x } });
}

Circle circle_from_3pts(const Point& a, const Point& b, const Point& c) {
    Point ba = b - a, cb = c - b;
    Line p{ (a + b) * 0.5, Point{ ba.y, -ba.x } };
    Line q{ (b + c) * 0.5, Point{ cb.y, -cb.x } };
    Circle circle;
    if (!get_cross(p, q, circle.center))
        circle.r = -1;
    else
        circle.r = dist(circle.center, a);
    return circle;
}

Circle circle_from_2pts_rad(const Point& a, const Point& b, double r) {
    double det = r * r / dist2(a, b) - 0.25;
    Circle circle;

```

```

    if (det < 0)
        circle.r = -1;
    else {
        double h = sqrt(det);
        // center is to the left of a->b
        circle.center = (a + b) * 0.5 + Point{ a.y - b.y, b.x - a.x } * h;
        circle.r = r;
    }
    return circle;
}

```

## 4.2 Convex Hull

```

// find convex hull
// O(n*logn)
vector<Point> convex_hull(vector<Point>& dat) {
    if (dat.size() <= 3) return dat;
    vector<Point> upper, lower;
    sort(dat.begin(), dat.end(), [](const Point& a, const Point& b) {
        return (a.x == b.x) ? a.y < b.y : a.x < b.x;
    });
    for (const auto& p : dat) {
        while (upper.size() >= 2 && ccw(*++upper.rbegin(), *upper.rbegin(), p)
            >= 0) upper.pop_back();
        while (lower.size() >= 2 && ccw(*++lower.rbegin(), *lower.rbegin(), p)
            <= 0) lower.pop_back();
        upper.emplace_back(p);
        lower.emplace_back(p);
    }
    upper.insert(upper.end(), ++lower.rbegin(), --lower.rend());
    return upper;
}

```

## 4.3 Pooint in Polygon

```

typedef double coord_t;

inline coord_t is_left(Point p0, Point p1, Point p2) {
    return (p1.x - p0.x) * (p2.y - p0.y) - (p2.x - p0.x) * (p1.y - p0.y);
}

// point in polygon test
// http://geomalgorithms.com/a03-_inclusion.html
bool is_in_polygon(Point p, vector<Point>& poly) {
    int wn = 0;
    for (int i = 0; i < poly.size(); ++i) {
        int ni = (i + 1 == poly.size()) ? 0 : i + 1;
        if (poly[i].y <= p.y) {
            if (poly[ni].y > p.y) {
                if (is_left(poly[i], poly[ni], p) > 0) {
                    ++wn;
                }
            }
        }
    }
}

```

```

    else {
        if (poly[ni].y <= p.y) {
            if (is_left(poly[i], poly[ni], p) < 0) {
                --wn;
            }
        }
    }
}
return wn != 0;
}

```

## 4.4 Polygon Cut

```

// Left side of a->b
vector<Point> cut_polygon(const vector<Point>& polygon, Line line) {
    if (!polygon.size()) return polygon;
    typedef vector<Point>::const_iterator piter;
    piter la, lan, fi, fip, i, j;
    la = lan = fi = fip = polygon.end();
    i = polygon.end() - 1;
    bool lastin = diff(ccw_line(line, polygon[polygon.size() - 1]), 0) > 0;
    for (j = polygon.begin(); j != polygon.end(); j++) {
        bool thisin = diff(ccw_line(line, *j), 0) > 0;
        if (lastin && !thisin) {
            la = i;
            lan = j;
        }
        if (!lastin && thisin) {
            fi = j;
            fip = i;
        }
        i = j;
        lastin = thisin;
    }
    if (fi == polygon.end()) {
        if (!lastin) return vector<Point>();
        return polygon;
    }
    vector<Point> result;
    for (i = fi; i != lan; i++) {
        if (i == polygon.end()) {
            i = polygon.begin();
            if (i == lan) break;
        }
        result.push_back(*i);
    }
    Point lc, fc;
    get_cross(Line{ *la, *lan - *la }, line, lc);
    get_cross(Line{ *fip, *fi - *fip }, line, fc);
    result.push_back(lc);
    if (diff(dist2(lc, fc), 0) != 0) result.push_back(fc);
    return result;
}

```

## 4.5 Rotating Calipers

```
// get all antipodal pairs
// O(n)
void antipodal_pairs(vector<Point>& pt) {
    // calculate convex hull
    sort(pt.begin(), pt.end(), [](const Point& a, const Point& b) {
        return (a.x == b.x) ? a.y < b.y : a.x < b.x;
    });
    vector<Point> up, lo;
    for (const auto& p : pt) {
        while (up.size() >= 2 && ccw(++up.rbegin(), *up.rbegin(), p) >= 0) up.
            pop_back();
        while (lo.size() >= 2 && ccw(*lo.rbegin(), *lo.rbegin(), p) <= 0) lo.
            pop_back();
        up.emplace_back(p);
        lo.emplace_back(p);
    }

    for (int i = 0, j = (int)lo.size() - 1; i + 1 < up.size() || j > 0; ) {
        get_pair(up[i], lo[j]); // DO WHAT YOU WANT
        if (i + 1 == up.size()) {
            --j;
        }
        else if (j == 0) {
            ++i;
        }
        else if ((long long)(up[i + 1].y - up[i].y) * (lo[j].x - lo[j - 1].x)
            > (long long)(up[i + 1].x - up[i].x) * (lo[j].y - lo[j - 1].y)) {
            ++i;
        }
        else {
            --j;
        }
    }
}
```

## 4.6 Separating Axis Theorem

```
pair<double, double> get_projection(vector<Vector2> &points, Vector2 &axis) {
    double min_val = axis.dot(points[0]);
    double max_val = min_val;
    for (int i = 1; i < points.size(); i++) {
        double projected = axis.dot(points[i]);
        min_val = min(min_val, projected);
        max_val = max(max_val, projected);
    }
    return {min_val, max_val};
}

vector<Vector2> get_normals(vector<Vector2> &points) {
    vector<Vector2> ret;
    if (points.size() == 1)
        return ret;
}
```

```
for (int i = 0; i < points.size(); i++) {
    Vector2 &a = points[i];
    Vector2 &b = points[(i + 1) % points.size()];
    ret.push_back(Vector2((b - a).y, -(b - a).x));
}
return ret;
}

bool can_separate(vector<Vector2> &A, vector<Vector2> &B) {
    if (A.size() == 1 && B.size() == 1)
        return true;
    auto c_a = get_convex_hull(A);
    auto c_b = get_convex_hull(B);
    auto n_a = get_normals(c_a);
    auto n_b = get_normals(c_b);

    n_a.insert(n_a.end(), n_b.begin(), n_b.end());
    if (c_a.size() > 1) n_a.push_back(Vector2(c_a[1] - c_a[0]));
    if (c_b.size() > 1) n_a.push_back(Vector2(c_b[1] - c_b[0]));

    for (Vector2 &axis : n_a) {
        auto p_a = get_projection(c_a, axis);
        auto p_b = get_projection(c_b, axis);
        if (!((p_a.second >= p_b.first) && (p_b.second >= p_a.first))) return true;
    }
    return false;
}
```

## 4.7 Two Far Point

```
pair<Vector2, Vector2> get_max_points(vector<Vector2> &points) {
    int left = 0, right = max_element(points.begin(), points.end()) - points.begin();
    int ret1 = left, ret2 = right;
    double max_len = (points[right] - points[left]).norm();
    int end = right;
    Vector2 left_dir = Vector2(0, -1.0);
    vector<Vector2> edges;
    for (int i = 0; i < points.size(); i++)
        edges.push_back((points[(i + 1) % points.size()] - points[i]).normalized());
    while (right != 0 || left != end) {
        double next1 = left_dir.dot(edges[left]);
        double next2 = -left_dir.dot(edges[right]);
        if (left != end && (right == 0 || next1 > next2)) {
            left_dir = edges[left];
            left = (left + 1) % points.size();
        } else {
            left_dir = -edges[right];
            right = (right + 1) % points.size();
        }
    }
    double len = (points[right] - points[left]).norm();
    if (len > max_len) {
        ret1 = left;
        ret2 = right;
        max_len = len;
    }
}
```

```

    }
    return {points[ret1], points[ret2]};
}

```

## 4.8 Two Nearest Point

```

int dist(Point &p, Point &q) {
    return (p.x - q.x) * (p.x - q.x) + (p.y - q.y) * (p.y - q.y);
}

struct Comp {
    bool comp_in_x;
    Comp(bool b) : comp_in_x(b) {}
    bool operator()(Point &p, Point &q) {
        return (this->comp_in_x ? p.x < q.x : p.y < q.y);
    }
};

int nearest(vector<Point>::iterator it, int n) {
    if (n == 2) return dist(it[0], it[1]);
    if (n == 3) return min({dist(it[0], it[1]), dist(it[1], it[2]), dist(it[2], it[0])});
    int line = (it[n / 2 - 1].x + it[n / 2].x) / 2;
    int d = min(nearest(it, n / 2), nearest(it + n / 2, n - n / 2));
    vector<Point> mid;
    for (int i = 0; i < n; i++) {
        int t = line - it[i].x;
        if (t * t < d) mid.push_back(it[i]);
    }
    sort(mid.begin(), mid.end(), Comp(false));
    int mid_sz = mid.size();
    for (int i = 0; i < mid_sz - 1; i++)
        for (int j = i + 1; j < mid_sz && (mid[j].y - mid[i].y) * (mid[j].y - mid[i].y) < d; j++)
            d = min(d, dist(mid[i], mid[j]));
    return d;
}

```

# 5 Graph

## 5.1 Dijkstra

```

template<typename T> struct Dijkstra {
    /*
     * T: 간선가중치타입
     */
    struct Edge {
        ll node;
        T cost;
        bool operator<(const Edge &to) const {
            return cost > to.cost;
        }
    };

    ll n;
    vector<vector<Edge>> adj;

```

```

    vector<ll> prev;

    Dijkstra(ll n) : n{n}, adj(n+1) {}

    void addEdge(ll s, ll e, T cost) {
        adj[s].push_back(Edge(e, cost));
    }

    void addUndirectedEdge(ll s, ll e, T cost) {
        addEdge(s, e, cost);
        addEdge(e, s, cost);
    }

    vector<ll> dijkstra(ll s) {
        vector<ll> dist(n+1, INF);
        prev.resize(n+1, -1);
        priority_queue<edge> pq;
        pq.push({ s, 0ll });
        dist[s] = 0;
        while (!pq.empty()) {
            edge cur = pq.top();
            pq.pop();
            if (cur.cost > dist[cur.node]) continue;
            for (auto &nxt : adj[cur.node])
                if (dist[cur.node] + nxt.cost < dist[nxt.node]) {
                    prev[nxt.node] = cur.node;
                    dist[nxt.node] = dist[cur.node] + nxt.cost;
                    pq.push({ nxt.node, dist[nxt.node] });
                }
            return dist;
        }
    }

    vector<ll> getPath(ll s, ll e) {
        vector<ll> ret;
        ll current = e;
        while(current != -1) {
            ret.push_back(current);
            current = prev[current];
        }
        reverse(ret.begin(), ret.end());
        return ret;
    }
};

```

## 5.2 Bellman-Ford

```

struct BellmanFord {
    struct BellmanEdge {
        ll to, cost;

        BellmanEdge(ll to, ll cost) : to(to), cost(cost) {}
    };

    ll N;

```



```
vector<vector<BellmanEdge>> adj;
llv1 D;
vector<ll> prev;

BellmanFord(ll N) : N(N) {
    adj.resize(N + 1);
}

void addEdge(ll s, ll e, ll cost) {
    adj[s].push_back(BellmanEdge(e, cost));
}

bool run(ll start_point) {
    // 음수간선 cycle 유무를반환합니다 .
    // 거리정보는 D 벡터에저장됩니다 .
    // O(V * E)

    D.resize(N + 1, INF);
    prev.resize(N + 1, -1);
    D[start_point] = 0;

    bool isCycle = false;

    for1(1, N + 1) {
        for1j(1, N + 1) {
            for(int k=0; k < sz(adj[j]); k++) {
                BellmanEdge p = adj[j][k];
                int end = p.to;
                ll dist = D[j] + p.cost;

                if (D[j] != INF && D[end] > dist) {
                    D[end] = dist;
                    if (i == N) isCycle = true;
                }
            }
        }
    }
    return isCycle;
}

llv1 getPath(ll s, ll e) {
    vector<ll> ret;
    ll current = e;
    while(current != -1) {
        ret.push_back(current);
        current = prev[current];
    }
    reverse(ret.begin(), ret.end());
    return ret;
}
};
```

### 5.3 Spfa

// shortest path faster algorithm

```
// average for random graph : O(E) , worst : O(VE)

const int MAXN = 20001;
const int INF = 100000000;
int n, m;
vector<pii> graph[MAXN];

bool inqueue[MAXN];
int dist[MAXN];

void spfa(int start) {
    for (int i = 0; i < n; ++i) dist[i] = INF;
    dist[start] = 0;

    queue<int> q;
    q.push(start);
    inqueue[start] = true;

    while (!q.empty()) {
        int here = q.front();
        q.pop();

        inqueue[here] = false;
        for (auto& nxt : graph[here]) {
            if (dist[here] + nxt.second < dist[nxt.first]) {
                dist[nxt.first] = dist[here] + nxt.second;
                if (!inqueue[nxt.first]) {
                    q.push(nxt.first);
                    inqueue[nxt.first] = true;
                }
            }
        }
    }
}
```

### 5.4 Topological Sort

```
struct TopologicalSort {
    // 1-index

    int n;
    iv1 in_degree;
    iv2 graph;
    iv1 result;

    TopologicalSort(int n) : n(n) {
        in_degree.resize(n + 1, 0);
        graph.resize(n + 1);
    }

    void addEdge(int s, int e) {
        graph[s].push_back(e);
        in_degree[e]++;
    }
}
```

```
void run() {
    queue<int> q;

    for1(1, n+1) {
        if(in_degree[i] == 0) q.push(i);
    }
    while(!q.empty()) {
        int here = q.front(); q.pop();
        result.push_back(here);

        for1(0, sz(graph[here])) {
            int there = graph[here][i];

            if(--in_degree[there]==0) q.push(there);
        }
    }
};
```

## 5.5 Strongly Connected Component

```
struct SCC {
    // 1-index
    // run() 후에에 components 결과가담김 .

    ll V;
    llv2 edges, reversed_edges, components;
    vector<bool> visited;
    stack<ll> visit_log;

    SCC(ll V): V(V) {
        edges.resize(V + 1);
        reversed_edges.resize(V + 1);
    }

    void addEdge(int s, int e) {
        edges[s].push_back(e);
        reversed_edges[e].push_back(s);
    }

    void dfs(int node) {
        visited[node] = true;

        for (int next : edges[node])
            if (!visited[next]) dfs(next);
        visit_log.push(node);
    }

    void dfs2(int node) {
        visited[node] = true;
        for (int next:reversed_edges[node])
            if (!visited[next]) dfs2(next);
        components.back().push_back(node);
    }

    void run() {
```

```
        visited = vector<bool>(V + 1, false);
        for (int node = 1; node <= V; node++)
            if (!visited[node]) dfs(node);

        visited = vector<bool>(V + 1, false);
        while (!visit_log.empty()) {
            ll node = visit_log.top(); visit_log.pop();
            if (!visited[node]) {
                components.push_back(llv1());
                dfs2(node);
            }
        }
    }
};
```

## 5.6 Union Find

```
struct UnionFind {
    int n;
    vector<int> u;

    UnionFind(int n) : n(n) {
        u.resize(n + 1);
        for(int i = 1; i <= n; i++) {
            u[i] = i;
        }
    }

    int find(int k) {
        if(u[u[k]] == u[k]) return u[k];
        else return u[k]=find(u[k]);
    }

    void uni(int a, int b) {
        a = find(a);
        b = find(b);
        if(a < b) u[b] = a;
        else u[a] = b;
    }
};
```

## 5.7 MST Kruskal

```
template <class T> struct MinimumSpanningTree {
    /*
        T: 가중치의타입

        n: 노드개수
        m: 간선개수
        result : MST 결과가중치 ( 합)
    */
    struct Edge {
        int u, v;
        T weight;
```

```

Edge(int u, int v, T weight) : u(u), v(v), weight(weight) {}
bool operator< (Edge other) const { return weight < other.weight; }
};

int n, m;
vector<int> uf;
vector<Edge> edges;
vector<Edge> chosen_edges;

T result; // 의MST 가중치합
int cnt; // 뽑은간선수

MinimumSpanningTree(int n, int m) : n(n), m(m) {
    uf.resize(n + 1);

    for(0, n + 1) {
        uf[i] = i;
    }
    result = 0;
    cnt = 0;
}

int find(int a) {
    /*
     * Union-Find: Find 연산
     */
    if(uf[a] == a) return a;
    return uf[a] = find(uf[a]);
}

int merge(int a, int b) {
    /*
     * Union-Find: Union합쳐진경우
     * true 반환
     */
    a = find(a);
    b = find(b);

    if(a == b) return false;

    uf[b] = a;
    return true;
}

void add_edge(int u, int v, T cost) {
    edges.push_back(Edge(u, v, cost));
}

void run() {
    sort(edges.begin(), edges.end());

    for(int i = 0; i < edges.size(); i++) {
        if(merge(edges[i].u, edges[i].v)) {

```

```

            result += edges[i].weight;

            // chosen_edges.push_back(edges[i]);
            if(++cnt >= n - 1) break;
        }
    }
};

```

## 5.8 Lowest Common Ancestor

```
#define MAX_DEGREE 20
```

```

struct LCA {
    // root: 트리의루트설정 , n: 트리의노드개수
    // addEdge -> init -> query(O(Log(n)))

    ll root, n;
    llv1 depth;
    llv2 adj;
    llv2 parent; // n X MAX_DEGREE

    LCA(ll root, ll n) : root(root), n(n) {
        depth.resize(n + 1);
        adj.resize(n + 1);
        parent.resize(n + 1, llv1(MAX_DEGREE, 0));
    }

    void addEdge(ll a, ll b) {
        adj[a].push_back(b);
        adj[b].push_back(a);
    }

    void init() {
        dfs(root, 0, 1);

        for(int i = 1; i < MAX_DEGREE; i++) {
            for(int j = 1; j <= n; j++) {
                parent[j][i] = parent[parent[j][i-1]][i-1];
            }
        }
    }

    void dfs(int here, int par, int d) {
        depth[here] = d;
        parent[here][0] = par;

        for(int there : adj[here]) {
            if(depth[there] > 0) continue;

            dfs(there, here, d + 1);
        }
    }

    int query(int a, int b) {

```

```

    if(depth[a] > depth[b]) {
        swap(a, b);
    }

    for(int i = MAX_DEGREE - 1; i >= 0; i--) {
        if (depth[b] - depth[a] >= (1 << i)) {
            b = parent[b][i];
        }
    }

    if(a == b) {
        return a;
    }

    for(int i = MAX_DEGREE - 1; i >= 0; i--) {
        if(parent[a][i] != parent[b][i]) {
            a = parent[a][i];
            b = parent[b][i];
        }
    }

    return parent[a][0];
}
};

```

## 5.9 Maxflow dinic

```

// usage:
// MaxFlowDinic::init(n);
// MaxFlowDinic::add_edge(0, 1, 100, 100); // for bidirectional edge
// MaxFlowDinic::add_edge(1, 2, 100); // directional edge
// result = MaxFlowDinic::solve(0, 2); // source -> sink
// graph[i][edgeIndex].res -> residual
//
// in order to find out the minimum cut, use `l`.
// if l[i] == 0, i is unreachable.
//
// O(V*V*E)
// with unit capacities, O(min(V^(2/3), E^(1/2)) * E)
struct MaxFlowDinic {
    typedef int flow_t;
    struct Edge {
        int next;
        size_t inv; /* inverse edge index */
        flow_t res; /* residual */
    };
    int n;
    vector<vector<Edge>> graph;
    vector<int> q, l, start;

    void init(int _n) {
        n = _n;
        graph.resize(n);
        for (int i = 0; i < n; i++) graph[i].clear();
    }
}

```

```

void add_edge(int s, int e, flow_t cap, flow_t caprev = 0) {
    Edge forward{ e, graph[e].size(), cap };
    Edge reverse{ s, graph[s].size(), caprev };
    graph[s].push_back(forward);
    graph[e].push_back(reverse);
}

bool assign_level(int source, int sink) {
    int t = 0;
    memset(&l[0], 0, sizeof(l[0]) * l.size());
    l[source] = 1;
    q[t++] = source;
    for (int h = 0; h < t && !l[sink]; h++) {
        int cur = q[h];
        for (const auto& e : graph[cur]) {
            if (l[e.next] || e.res == 0) continue;
            l[e.next] = l[cur] + 1;
            q[t++] = e.next;
        }
    }
    return l[sink] != 0;
}

flow_t block_flow(int cur, int sink, flow_t current) {
    if (cur == sink) return current;
    for (int& i = start[cur]; i < graph[cur].size(); i++) {
        auto& e = graph[cur][i];
        if (e.res == 0 || l[e.next] != l[cur] + 1) continue;
        if (flow_t res = block_flow(e.next, sink, min(e.res, current))) {
            e.res -= res;
            graph[e.next][e.inv].res += res;
            return res;
        }
    }
    return 0;
}

flow_t solve(int source, int sink) {
    q.resize(n);
    l.resize(n);
    start.resize(n);
    flow_t ans = 0;
    while (assign_level(source, sink)) {
        memset(&start[0], 0, sizeof(start[0]) * n);
        while (flow_t flow = block_flow(source, sink, numeric_limits<flow_t>::max()))
            ans += flow;
    }
    return ans;
}
};

```

## 5.10 Maxflow Edmonds-Karp

```

struct MaxFlowEdgeDemands
{
    MaxFlowDinic mf;
    using flow_t = MaxFlowDinic::flow_t;
}

```

```

vector<flow_t> ind, outd;
flow_t D; int n;

void init(int _n) {
    n = _n; D = 0; mf.init(n + 2);
    ind.clear(); outd.clear();
    ind.resize(n, 0); outd.resize(n, 0);
}

void add_edge(int s, int e, flow_t cap, flow_t demands = 0) {
    mf.add_edge(s, e, cap - demands);
    D += demands; ind[e] += demands; outd[s] += demands;
}

// returns { false, 0 } if infeasible
// { true, maxflow } if feasible
pair<bool, flow_t> solve(int source, int sink) {
    mf.add_edge(sink, source, numeric_limits<flow_t>::max());

    for (int i = 0; i < n; i++) {
        if (ind[i]) mf.add_edge(n, i, ind[i]);
        if (outd[i]) mf.add_edge(i, n + 1, outd[i]);
    }

    if (mf.solve(n, n + 1) != D) return{ false, 0 };

    for (int i = 0; i < n; i++) {
        if (ind[i]) mf.graph[i].pop_back();
        if (outd[i]) mf.graph[i].pop_back();
    }

    return{ true, mf.solve(source, sink) };
}
};

```

## 5.11 MCMF SPFA

```

struct MCMF {
    struct Edge {
        ll to;
        ll capacity;
        ll cost;

        Edge* rev;
        Edge(ll to, ll capacity, ll cost) : to(to), capacity(capacity), cost(cost) {}
    };

    ll n;
    ll source, sink;
    vector<vector<Edge*>> graph;
    vector<bool> check;
    vector<ll> distance;
    vector<pair<ll, ll>> from;

```

```

MCMF(ll n, ll source, ll sink): n(n), source(source), sink(sink) {

    // source: 시작점
    // sink: 도착점
    // n: 모델링한그래프의정점개수
    graph.resize(n + 1);
    check.resize(n + 1);
    from.resize(n + 1, make_pair(-1, -1));
    distance.resize(n + 1);
};

void addEdge(ll u, ll v, ll cap, ll cost) {
    Edge *ori = new Edge(v, cap, cost);
    Edge *rev = new Edge(u, 0, -cost);

    ori->rev = rev;
    rev->rev = ori;

    graph[u].push_back(ori);
    graph[v].push_back(rev);
}

void addEdgeFromSrc(ll v, ll cap, ll cost) {
    // 출발지점에서출발하는간선추가
    addEdge(source, v, cap, cost);
}

void addEdgeToSink(ll u, ll cap, ll cost) {
    // 도착지점으로가는간선추가
    addEdge(u, sink, cap, cost);
}

bool spfa(ll &total_flow, ll &total_cost) {
    // spfa 기반의 MCMF

    fill(check.begin(), check.end(), false);
    fill(distance.begin(), distance.end(), INF);
    fill(from.begin(), from.end(), make_pair(-1, -1));

    distance[source] = 0;
    queue<ll> q;
    q.push(source);

    while(!q.empty()) {
        ll x = q.front(); q.pop();

        check[x] = false;

        for(ll i = 0; i < graph[x].size(); i++) {
            Edge* e = graph[x][i];
            ll y = e->to;

            if(e->capacity > 0 && distance[x] + e->cost < distance[y]) {
                distance[y] = distance[x] + e->cost;

```

```

        from[y] = make_pair(x, i);

        if(!check[y]) {
            check[y] = true;
            q.push(y);
        }
    }
}

if(distance[sink] == INF) return false;

// 간선들에서부터 sink 역추적하여경로를만든다 .
ll x = sink;
ll c = graph[from[x].first][from[x].second]->capacity;

while(from[x].first != -1) {
    if(c > graph[from[x].first][from[x].second]->capacity) {
        c = graph[from[x].first][from[x].second]->capacity;
    }
    x = from[x].first;
}

// 만든경로를따라유량을흘린다 .
x = sink;
while(from[x].first != -1) {
    Edge* e = graph[from[x].first][from[x].second];
    e->capacity -= c;
    e->rev->capacity += c;
    x = from[x].first;
}

total_flow += c;
total_cost += c * distance[sink];

return true;
}

pair <ll, ll> flow() {
    ll total_flow = 0;
    ll total_cost = 0;

    while(spfa(total_flow, total_cost));

    return make_pair(total_flow, total_cost);
}
};

```

## 5.12 MCMF

```

// precondition: there is no negative cycle.
// usage:
// MinCostFlow mcf(n);
// for(each edges) mcf.addEdge(from, to, cost, capacity);

```

```

// mcf.solve(source, sink); // min cost max flow
// mcf.solve(source, sink, 0); // min cost flow
// mcf.solve(source, sink, goal_flow); // min cost flow with total_flow >=
// goal_flow if possible
struct MinCostFlow {
    typedef int cap_t;
    typedef int cost_t;

    bool iszerocap(cap_t cap) { return cap == 0; }

    struct edge {
        int target;
        cost_t cost;
        cap_t residual_capacity;
        cap_t orig_capacity;
        size_t revid;
    };

    int n;
    vector<vector<edge>> graph;

    MinCostFlow(int n) : graph(n), n(n) {}

    void addEdge(int s, int e, cost_t cost, cap_t cap) {
        if (s == e) return;
        edge forward{ e, cost, cap, cap, graph[e].size() };
        edge backward{ s, -cost, 0, 0, graph[s].size() };
        graph[s].emplace_back(forward);
        graph[e].emplace_back(backward);
    }

    pair<cost_t, cap_t> augmentShortest(int s, int e, cap_t flow_limit) {
        auto infinite_cost = numeric_limits<cost_t>::max();
        auto infinite_flow = numeric_limits<cap_t>::max();
        vector<pair<cost_t, cap_t>> dist(n, make_pair(infinite_cost, 0));
        vector<int> from(n, -1), v(n);

        dist[s] = pair<cost_t, cap_t>(0, infinite_flow);
        queue<int> q;
        v[s] = 1; q.push(s);
        while(!q.empty()) {
            int cur = q.front();
            v[cur] = 0; q.pop();
            for (const auto& e : graph[cur]) {
                if (iszerocap(e.residual_capacity)) continue;
                auto next = e.target;
                auto ncost = dist[cur].first + e.cost;
                auto nflow = min(dist[cur].second, e.residual_capacity);
                if (dist[next].first > ncost) {
                    dist[next] = make_pair(ncost, nflow);
                    from[next] = e.revid;
                    if (v[next]) continue;
                    v[next] = 1; q.push(next);
                }
            }
        }
    }
};

```

```

    }

    auto p = e;
    auto pathcost = dist[p].first;
    auto flow = dist[p].second;
    if (iszerocap(flow) || (flow_limit <= 0 && pathcost >= 0)) return pair<
        cost_t, cap_t>(0, 0);
    if (flow_limit > 0) flow = min(flow, flow_limit);

    while (from[p] != -1) {
        auto nedge = from[p];
        auto np = graph[p][nedge].target;
        auto fedge = graph[p][nedge].revid;
        graph[p][nedge].residual_capacity += flow;
        graph[np][fedge].residual_capacity -= flow;
        p = np;
    }
    return make_pair(pathcost * flow, flow);
}

pair<cost_t, cap_t> solve(int s, int e, cap_t flow_minimum = numeric_limits<
    cap_t>::max()) {
    cost_t total_cost = 0;
    cap_t total_flow = 0;
    for(;;) {
        auto res = augmentShortest(s, e, flow_minimum - total_flow);
        if (res.second <= 0) break;
        total_cost += res.first;
        total_flow += res.second;
    }
    return make_pair(total_cost, total_flow);
}
};

```

## 6 String

### 6.1 KMP

```

struct KMP {
    /*
     * s 문자열에서 문자열을 o 찾습니다. 매칭이 시작되는 인덱스 목록을 반환합니다
     *
     * Time: O(n + m)
     */
    vector<int> result;
    int MX;
    string s, o;
    int n, m; // n : s.length(), m : o.length();
    vector<int> fail;

    KMP(string s, string o) : s(s), o(o) {
        n = s.length();
        m = o.length();
        MX = max(n, m) + 1;
    }
}

```

```

fail.resize(MX, 0);

run();
}

void run() {
    for(int i = 1, j = 0; i < m; i++){
        while(j > 0 && o[i] != o[j]) j = fail[j-1];
        if(o[i] == o[j]) fail[i] = ++j;
    }
    for(int i = 0, j = 0; i < n; i++) {
        while(j > 0 && s[i] != o[j]) {
            j = fail[j - 1];
        }
        if(s[i] == o[j]) {
            if(j == m - 1) {
                // matching OK;
                result.push_back(i - m + 1);
                j = fail[j];
            }
            else {
                j++;
            }
        }
    }
}
};

```

### 6.2 Manacher

// Use space to insert space between each character  
 // To get even length palindromes!  
 // O(|str|)

```

vector<int> manacher(string &s) {
    int n = s.size(), R = -1, p = -1;
    vector<int> A(n);
    for (int i = 0; i < n; i++) {
        if (i <= R) A[i] = min(A[2 * p - i], R - i);
        while (i - A[i] - 1 >= 0 && i + A[i] + 1 < n && s[i - A[i] - 1] == s[i + A[i]
            ] + 1))
            A[i]++;
        if (i + A[i] > R)
            R = i + A[i], p = i;
    }
    return A;
}

string space(string &s) {
    string t;
    for (char c : s) t += c, t += ' ';
    t.pop_back();
    return t;
}

```

```
int maxpalin(vector<int> &M, int i) {
    if (i % 2) return (M[i] + 1) / 2 * 2;
    return M[i] / 2 * 2 + 1;
}
```

### 6.3 Suffix Array

```
typedef char T;
```

```
// calculates suffix array.
```

```
// O(n*logn)
```

```
vector<int> suffix_array(const vector<T>& in) {
    int n = (int)in.size(), c = 0;
    vector<int> temp(n), pos2bckt(n), bckt(n), bpos(n), out(n);
    for (int i = 0; i < n; i++) out[i] = i;
    sort(out.begin(), out.end(), [&](int a, int b) { return in[a] < in[b]; });
    for (int i = 0; i < n; i++) {
        bckt[i] = c;
        if (i + 1 == n || in[out[i]] != in[out[i + 1]]) c++;
    }
    for (int h = 1; h < n && c < n; h <= 1) {
        for (int i = 0; i < n; i++) pos2bckt[out[i]] = bckt[i];
        for (int i = n - 1; i >= 0; i--) bpos[bckt[i]] = i;
        for (int i = 0; i < n; i++)
            if (out[i] >= n - h) temp[bpos[bckt[i]]++] = out[i];
        for (int i = 0; i < n; i++)
            if (out[i] >= h) temp[bpos[pos2bckt[out[i] - h]]++] = out[i] - h;
        c = 0;
        for (int i = 0; i + 1 < n; i++) {
            int a = (bckt[i] != bckt[i + 1]) || (temp[i] >= n - h)
                || (pos2bckt[temp[i + 1] + h] != pos2bckt[temp[i] + h]);
            bckt[i] = c;
            c += a;
        }
        bckt[n - 1] = c++;
        temp.swap(out);
    }
    return out;
}
```

```
// calculates lcp array. it needs suffix array & original sequence.
```

```
// O(n)
```

```
vector<int> lcp(const vector<T>& in, const vector<int>& sa) {
    int n = (int)in.size();
    if (n == 0) return vector<int>();
    vector<int> rank(n), height(n - 1);
    for (int i = 0; i < n; i++) rank[sa[i]] = i;
    for (int i = 0, h = 0; i < n; i++) {
        if (rank[i] == 0) continue;
        int j = sa[rank[i] - 1];
        while (i + h < n && j + h < n && in[i + h] == in[j + h]) h++;
        height[rank[i] - 1] = h;
        if (h > 0) h--;
    }
    return height;
}
```

```
}
```

### 6.4 2nd Suffix Array

```
struct SuffixComparator {
    const vector<int> &group;
    int t;
```

```
    SuffixComparator(const vector<int> &_group, int _t) : group(_group), t(_t) {}
    bool operator()(int a, int b) {
        if (group[a] != group[b]) return group[a] < group[b];
        return group[a + t] < group[b + t];
    }
};
```

```
vector<int> getSuffixArr(const string &s) {
    int n = s.size();
    int t = 1;
```

```
    vector<int> group(n + 1);
```

```
    for (int i = 0; i < n; i++) group[i] = s[i];
    group[n] = -1;
```

```
    vector<int> perm(n);
    for (int i = 0; i < n; i++) perm[i] = i;
```

```
    while (t < n) {
        SuffixComparator compare(group, t);
        sort(perm.begin(), perm.end(), compare);
        t *= 2;
        if (t >= n)
            break;
```

```
        vector<int> new_group(n + 1);
        new_group[n] = -1;
        new_group[perm[0]] = 0;
        for (int i = 1; i < n; i++)
            if (compare(perm[i - 1], perm[i]))
                new_group[perm[i]] = new_group[perm[i - 1]] + 1;
            else
                new_group[perm[i]] = new_group[perm[i - 1]];
        group = new_group;
```

```
    }
    return perm;
}
```

```
int getHeight(const string &s, vector<int> &pos) {
    // 최장중복부분문자열의길이
    const int n = pos.size();
    vector<int> rank(n);
    for (int i = 0; i < n; i++)
        rank[pos[i]] = i;
    int h = 0, ret = 0;
    for (int i = 0; i < n; i++) {
```



```

    if (rank[i] > 0) {
        int j = pos[rank[i] - 1];
        while (s[i + h] == s[j + h])
            h++;
        ret = max(ret, h);
        if (h > 0)
            h--;
    }
}
return ret;
}

```

## 6.5 Trie

```

int chToIdx(char ch) { return ch - 'a'; }
struct Trie {
    int terminal = -1;
    Trie *fail; // fail, 은 output 아호코라식에서 사용
    vector<int> output;
    Trie *chil[ALPHABETS];
    Trie() {
        for (int i = 0; i < ALPHABETS; i++)
            chil[i] = NULL;
    }
    ~Trie() {
        for (int i = 0; i < ALPHABETS; i++)
            if (chil[i])
                delete chil[i];
    }
    // number -> 문자열번호 (ith string)
    void insert(string &s, int number, int idx) {
        if (idx == s.size()) {
            terminal = number;
            return;
        }
        int next = chToIdx(s[idx]);
        if (chil[next] == NULL)
            chil[next] = new Trie();
        chil[next]->insert(s, number, idx + 1);
    }
    int find(string &s, int idx = 0) {
        if (idx == s.size())
            return terminal;
        int next = chToIdx(s[idx]);
        if (chil[next] == NULL)
            return false;
        return chil[next]->find(s, idx + 1);
    }
};

```

## 6.6 Aho-Corasick

```

void computeFail(Trie *root) {
    queue<Trie *> q;

```

```

    root->fail = root;
    q.push(root);
    while (!q.empty()) {
        Trie *here = q.front();
        q.pop();
        for (int i = 0; i < ALPHABETS; i++) {
            Trie *child = here->chil[i];
            if (!child) continue;
            if (here == root) child->fail = root;
            else {
                Trie *t = here->fail;
                while (t != root && t->chil[i] == NULL) t = t->fail;
                if (t->chil[i]) t = t->chil[i];
                child->fail = t;
            }
            child->output = child->fail->output;
            if (child->terminal != -1) child->output.push_back(child->terminal);
            q.push(child);
        }
    }
}

vector<pair<int, int>> ahoCorasick(string &s, Trie *root) {
    vector<pair<int, int>> ret;
    Trie *state = root;
    for (int i = 0; i < s.size(); i++) {
        int idx = chToIdx(s[i]);
        while (state != root && state->chil[idx] == NULL) state = state->fail;
        if (state->chil[idx]) state = state->chil[idx];
        for (int j = 0; j < state->output.size(); j++) ret.push_back({i, state->output[j]});
    }
    return ret;
}

```

## 7 Dynamic Programming

### 7.1 LIS

```

struct LIS {
    llv1 ar;

    llv1 v, buffer;
    llv1::iterator vv;
    vector<pair<ll, ll>> d;

    void perform() {
        v.pb(2000000000ll);

        ll n = sz(ar);

        for(0, n){
            if (ar[i] > *v.rbegin()) {
                v.pb(ar[i]);
                d.push_back({ v.size() - 1, ar[i] });
            }

```

```

    }
    else {
        vv = lower_bound(v.begin(), v.end(), ar[i]);
        *vv = ar[i];
        d.push_back({ vv - v.begin(), ar[i] });
    }
}

for(int i = sz(d) - 1; i > -1; i--){
    if(d[i].first == sz(v)-1){
        buffer.pb(d[i].second);
        v.pop_back();
    }
}

reverse(buffer.begin(), buffer.end());
}

ll length() {
    return buffer.size();
}

llv1 result() {
    return buffer;
}
};

```

## 7.2 LIS only length

```

ll lis(llv1& ar) {
    llv1 v, buffer;
    llv1::iterator vv;
    v.pb(2000000000ll);

    ll n = sz(ar);

    for1(0, n){
        if(ar[i] > *v.rbegin()) {
            v.pb(ar[i]);
        }
        else{
            vv = lower_bound(v.begin(), v.end(), ar[i]);
            *vv = ar[i];
        }
    }
    return sz(v);
}

```

## 7.3 KnapSack

```

ll N, maxWeight, ans;
ll D[2][11000];
ll weight[110], cost[110];
void knapsack() {

```

```

    for (int x = 1; x <= N; x++) {
        for (int y = 0; y <= maxWeight; y++) {
            if (y >= weight[x]) {
                D[x % 2][y] = max(D[(x + 1) % 2][y], D[(x + 1) % 2][y - weight[x]] + cost[x]);
            } else {
                D[x % 2][y] = D[(x + 1) % 2][y];
            }
            ans = max(ans, D[x % 2][y]);
        }
    }
}

void input() {
    cin >> N >> maxWeight;
    for (int x = 1; x <= N; x++) {
        cin >> weight[x] >> cost[x];
    }
}

```

## 7.4 Coin Change

```

// 경우의수
ll CC(llv1 &coin, ll money, ll MX) {
    ll D[MX];
    fill(D, D + MX, 0);
    D[0] = 1;
    for (int i = coin.size() - 1; i >= 0; i--) {
        for (int j = coin[i]; j <= money; j++) {
            D[j] += D[j - coin[i]];
            D[j] %= MOD;
        }
    }
    return D[money] % MOD;
}

```

## 7.5 Bit Field DP

```

#define MOD 9901;

int dp[1 << 14 + 1][200];
int n, m;

int solve(int pos, int check, int dep) {
    if (dp[check][pos] != 0) return dp[check][pos];
    int &ret = dp[check][pos];
    if (dep == n * m) return ret = 1;
    if ((check & 1)) return ret = solve(pos - 1, check >> 1, dep) % MOD;

    int sum = 0;
    if (!(check & 1) && (pos - 1) / m > 0)
        sum += solve(pos - 1, (check >> 1) | (1 << (m - 1)), dep + 2) % MOD;
    if (!(check & 1) && pos % m != 1 && !(check & 2) && pos >= 2 && m > 1)
        sum += solve(pos - 2, check >> 2, dep + 2) % MOD;
    // cout<<pos<<" "<<check<<" "<<dep<<" "<<sum<<endl;

```

```
    return ret = sum % MOD;
}
int main() {
    cin >> n >> m;

    if (n * m % 2 == 1)
        cout << 0;
    else
        cout << solve(n * m, 0, 0) % MOD;

    return 0;
}
```