| REGULAR EXPRESSION SYNTAX | | |
|---------------------------|---|--|
| ^ | Start of string | |
| \$ | End of string | |
| | Any single character | |
| (a b) | a or b | |
| () | Group section | |
| [abc] | Item in range (a or b or c) | |
| [^abc] | Not in range (not a or b or c) | |
| a? | Zero or one of a | |
| a* | Zero or more of a | |
| a+ | One or more of a | |
| a{3} | Exactly 3 of a | |
| a{3,} | 3 or more of a | |
| a{3,6} | Between 3 and 6 of a | |
| !(pattern) | "Not" prefix. Apply rule when URL does not match pattern. | |

| Redirection Header Codes | | |
|--------------------------|-------------------|--|
| 301 | Moved permanently | |
| 302 | Moved temporarily | |
| 403 | Forbidden | |
| 404 | Not Found | |
| 410 | Gone | |

| RewriteRule FLAGS | |
|-------------------|--|
| R[=code] | Redirect to new URL, with optional code (see below). |
| F | Forbidden (sends 403 header) |
| G | Gone (no longer exists) |
| Р | Proxy |
| L | Last Rule |
| N | Next (i.e. restart rules) |
| С | Chain |
| T=mime-type | Set Mime Type |
| NS | Skip if internal sub-request |
| NC | Case insensitive |
| QSA | Append query string |
| NE | Do not escape output |
| PT | Pass through |
| S=x | Skip next x rules |
| E=var:value | Set environmental variable "var" to "value". |

| RewriteCond FLAGS | | |
|-------------------|----------------------------------|--|
| NC | Case insensitive | |
| OR | Allows a rule to apply if one of | |
| | a series of conditions are true. | |

Server Variables

Format

%{NAME OF VAR}

HTTP Headers

HTTP USER AGENT HTTP REFERER HTTP_COOKIE HTTP_FORWARDED

HTTP HOST

HTTP_PROXY_CONNECTION HTTP_ACCEPT

Request

REMOTE_ADDR REMOTE_HOST REMOTE_USER REMOTE_IDENT REQUEST_METHOD SCRIPT_FILENAME PATH INFO QUERY_STRING AUTH_TYPE

Server

DOCUMENT_ROOT SERVER_ADMIN SERVER_NAME SERVER_ADDR SERVER_PORT SERVER_PROTOCOL SERVER_SOFTWARE

Time TIME_YEAR TIME MON TIME_DAY TIME_HOUR TIME MIN TIME SEC

TIME_WDAY

TIME

Special

API_VERSION THE REQUEST REQUEST_URI REQUEST FILENAME IS_SUBREQ

Directives RewriteEngine RewriteOptions RewriteLog RewriteLogLevel RewriteLock RewriteMap RewriteBase RewriteCond RewriteRule

Example Rules

- # Site has permanently moved to new domain
- # domain.com to domain2.com

RewriteCond %{HTTP HOST} ^www.domain.com\$ [NC] RewriteRule ^(.*)\$ http://www.domain2.com/\$1 [R=301,L]

- # Page has moved temporarily
- # domain.com/page.htm to domain.com/new_page.htm RewriteRule ^page.htm\$ new_page.htm [R,NC,L]
- # Nice looking URLs (no querystring)
- # domain.com/category-name-1/ to domain.com/categories.php?name=category-name-1 RewriteRule $^{(A-Za-z0-9-]+)/?}$ categories.php?name=\$1 [L]
- # Nice looking URLs (no querystring) with pagination
- # domain.com/articles/title/5/ to domain.com/article.php?name=title&page=5 RewriteRule $\frac{([A-Za-z0-9-]+)}{([0-9]+)/?}$ article.php?name=\$1&page=\$2[L]

Block referrer spam

RewriteCond %{HTTP_REFERER} (weight) [NC,OR] RewriteCond %{HTTP_REFERER} (drugs) [NC] RewriteRule .* - [F]