MapSORT: Landmark Association for Identity-Persistent Tracking of Stationary Crops and Fruit

Srihari Vemuru[1*]

[1*]TBD, TBD, TBD, TBD.

Corresponding author(s). E-mail(s): vemshari27@gmail.com;

Abstract

Purpose: Plant- and fruit-level records in precision agriculture, such as yield estimates, phenotyping logs and targeted spraying, require every plant or fruit to keep one identity across a video, including when the camera leaves and later returns to it. General-purpose multi-object trackers lose identity in exactly this situation, because crops look alike and an object out of view for more than a few frames is forgotten. This work turns the property that sets agricultural targets apart, that they do not move, into an association cue that keeps identities intact across occlusions and revisits.

Methods: MapSORT reconstructs the sequence with structure-from-motion and lifts every detection to a landmark observation: a Gaussian over the object's position in the scene map, with centre uncertainty kept separate from physical extent. Tracks fuse their observations in information form and are matched by a scale-invariant Mahalanobis gate inside a StrongSORT-style association cascade. Tracks that leave the view become dormant, not deleted, and are revived by their landmark. MapSORT is compared with BoT-SORT, SAM2MOT and StrongSORT on four public datasets (LettuceMOTS, MOrangeT, GrapeMOTS, AppleMOTS) and on per-tree yield counts in a mango orchard.

Results: MapSORT reaches TBD HOTA and TBD IDF1 on average, TBD and TBD points above the strongest baseline. It preserves identity in TBD% of revisit events, compared with TBD% for the best competitor. Per-tree mango counts are within TBD% of harvest counts. On a back-and-forth lettuce sequence MapSORT tracks all 37 plants with zero identity switches and an exact count.

Conclusion: A scene-map position is a persistent identity cue for stationary crops. Using it in association yields identity-consistent tracks and accurate counts across crops, platforms and viewing patterns.

Keywords: Multi-object tracking, Structure-from-motion, Fruit counting, Plant re-identification, Agricultural robotics, Yield estimation

1 Introduction

Many precision-agriculture tasks operate at the level of the individual plant or fruit. Yield estimation from video counts fruit by counting tracks (Stein et al, 2016; Liu et al, 2019; Häni et al, 2020; Villacrés et al, 2023). Per-plant phenotyping attaches measurements from successive frames and passes to the same plant. Selective spraying and harvesting require an agricultural robot to know which plant it is looking at. All of these depend on multi-object tracking (MOT) that assigns each physical object one identity, and keeps it, for as long as the object is in the video.

Agricultural video makes this hard in a specific way. Plants in a row, oranges on a tree and grape bunches on a cane are visually near-identical, so appearance embeddings learned for pedestrians separate them poorly. Leaves, branches and neighbouring fruit occlude them. Most importantly, the camera routinely leaves an object and comes back to it: a ground robot drives a row and returns along it, a handheld camera sweeps the canopy more than once, a UAV inspects a vine from several perspectives. Tracking-by-detection methods (Bewley et al, 2016; Wojke et al, 2017; Zhang et al, 2022; Aharon et al, 2022; Du et al, 2023) predict object motion in the image plane and keep an unmatched track alive for a

fixed number of frames. An object that is out of view for longer is deleted and receives a new identity when it reappears. Every such switch inflates the count and fragments the plant's record (Fig. 1).

The targets of agricultural tracking have a property that pedestrians and vehicles do not: they are stationary. A lettuce occupies the same place in the field on the outbound and return pass; an orange hangs at the same point of the canopy however often the camera sweeps past it. Its position in a three-dimensional map of the scene is therefore an identity cue that does not decay with time out of view, does not depend on appearance, and does not require the object's image-plane motion to be predictable. Structure-from-motion (SfM) recovers such a map, along with every camera pose, from the same monocular RGB video the tracker consumes (Schönberger and Frahm, 2016).

This paper presents MapSORT, a tracker that makes scene-map position a first-class association cue. MapSORT lifts each detection to a *landmark observation*: a Gaussian over the object's centre in the map frame, with a covariance that expresses how well the centre is known and a separate extent that expresses how large the object is. Tracks accumulate their observations into a fused landmark whose uncertainty shrinks with every sighting. Association adds a landmark stage, gated by a Mahalanobis distance that is invariant to the arbitrary scale of a monocular reconstruction, to the appearance and motion stages of StrongSORT (Du et al, 2023). A track that leaves the field of view is put to sleep rather than deleted, and is revived by its landmark when the camera returns, however long the absence.

The contributions of this work are:

1. A landmark observation model for detections of stationary objects, built from the SfM points the detection encloses, that separates centre uncertainty from object extent, fuses across observations in information form, and yields a gating distance invariant to reconstruction scale.
2. MapSORT, a tracking-by-detection method that inserts landmark association and landmark-based revival of dormant tracks into a StrongSORT association cascade, so that identity survives arbitrarily long absences.
3. A revisit-centred evaluation protocol: a revisit identity preservation rate that decomposes CLEAR identity switches by the absence that preceded them, together with count error, which is the quantity yield estimation consumes.
4. A benchmark against BoT-SORT and SAM2MOT on four public agricultural datasets (LettuceMOTS, MOrangeT, GrapeMOTS and AppleMOTS), covering four crops, four platforms and three viewing patterns, and a yield-count evaluation in a mango orchard against harvested fruit counts per tree.

2 Related work

2.1 Tracking-by-detection

SORT (Bewley et al, 2016) established the tracking-by-detection template: a constant-velocity Kalman filter (Kalman, 1960) predicts each track's box, and Hungarian matching (Kuhn, 1955) on intersection-over-union (IoU) assigns detections to tracks. DeepSORT (Wojke et al, 2017) added an appearance embedding and a matching cascade that prioritises recently seen tracks. ByteTrack (Zhang et al, 2022)




Fig. 1 The same frame of a field robot's return pass along two lettuce rows, tracked by (a) BoT-SORT and (b) MapSORT. BoT-SORT has forgotten the plants it saw on the way out and counts each of them again. MapSORT recognises every plant from its position in the scene map and keeps one identity per plant.

recovers low-confidence detections in a second association round; OC-SORT (Cao et al, 2023) corrects Kalman drift during occlusion from observations; FairMOT (Zhang et al, 2021) learns detection and embedding jointly. BoT-SORT (Aharon et al, 2022) combines camera-motion compensation, a refined Kalman state and fused IoU and appearance costs. StrongSORT (Du et al, 2023) modernises DeepSORT with a stronger re-identification backbone, exponential-moving-average feature updates, a noise-scaled Kalman filter and fused appearance and motion costs. SAM2MOT (Jiang et al, 2025) departs from box association altogether: it uses the SAM 2 video segmentation model (Ravi et al, 2024) to propagate object masks through time, so identity follows from segmentation rather than from matching.

All of these methods reason about identity in the image plane or in an appearance space. Neither is stable when the camera leaves an object and returns: image-plane motion over a long absence is not predictable, and appearance galleries are bounded in both size and age. MapSORT keeps the appearance and motion machinery of StrongSORT and adds a cue that remains valid over any absence.

2.2 Tracking and counting in crops and orchards

Video-based fruit counting tracks fruit to avoid counting it more than once. Halstead et al (2018) tracked sweet pepper with IoU association on a robotic platform. Häni et al (2020) compared detection and counting pipelines for apple yield mapping, and Villacrés et al (2023) compared tracking-by-detection algorithms for apple production estimation. Hu et al (2022) released LettuceMOT with back-and-forth and out-and-in robot trajectories and showed that re-occurring plants defeat standard trackers; the same group introduced LettuceMOTS with a shape-feature MOTS method for precision spraying (Hu et al, 2024). Datasets for homogeneous-object MOTS exist for apples (de Jong et al, 2022) and grape bunches captured from multiple UAV perspectives (Ariza-Sentís et al, 2024), following the MOTS task definition of Voigtlaender et al (2019).

2.3 Three-dimensional localisation for fruit identity

Several works use multi-view geometry to localise fruit. Stein et al (2016) triangulated mango detections from a GNSS/INS-referenced vehicle to count fruit per tree. Liu et al (2019) combined monocular SfM with semantic data association to count and map fruit. Gené-Mola et al (2020) projected instance segmentations onto an SfM point cloud to locate apples in 3D. Rapado-Rincón et al (2023) tracked tomatoes in 3D from a robot arm with known camera poses. Santos et al (2024) relocalised oranges in 3D to recover them after occlusion and showed that removing relocalisation more than halves HOTA on MOrangeT.

These approaches represent fruit position as a point and compare positions with a fixed, hand-tuned distance threshold. A point carries no notion of how well it is known, and a metric threshold is meaningless in a monocular reconstruction whose scale is arbitrary. MapSORT instead represents each observation as a Gaussian with an explicit covariance, fuses observations so that a track's position sharpens with every sighting, and gates association with a Mahalanobis distance that is independent of scale. It also integrates the landmark cue into a modern appearance-and-motion association cascade rather than replacing it, and uses it to revive tracks that a frame-to-frame tracker would have discarded.

3 Materials and methods

3.1 Problem formulation

The input is a monocular RGB video $\{I_1, \ldots, I_T\}$ captured by a moving camera, with no depth, odometry or positioning sensor, and at each frame t a set of detections $D_t = \{d_t^1, \ldots, d_t^{n_t}\}$, each an axis-aligned box b_t^i. The scene contains stationary objects. The task is to produce tracks $\mathcal{T} = \{\tau_1, \ldots, \tau_K\}$, $\tau_k = \{(t, d_t^i)\}$, such that each track corresponds to exactly one physical object and each object to exactly one track: identity must be preserved through occlusion, visual ambiguity and camera motion, including when the camera returns to an object after it has been out of view.

3.2 Overview

Fig. 2 shows the MapSORT pipeline. A scene map is reconstructed once per sequence by SfM (Sect. 3.3). At every frame, each detection receives an appearance embedding and a landmark observation read from the map (Sect. 3.4). Tracks carry a Kalman state, an appearance gallery and a fused landmark (Sect. 3.5). A four-stage association cascade matches detections to active tracks by appearance and motion, by landmark, and by IoU, and finally to dormant tracks by landmark (Sect. 3.6). Tracks that leave the view are moved to a dormant pool instead of being deleted (Sect. 3.7). Algorithm 1 summarises one frame.




Fig. 2 MapSORT. A scene map is reconstructed once per sequence by structure-from-motion. At each frame, every detection gets an appearance embedding and a landmark observation: a Gaussian over its centre in the map frame, read from the map points it encloses. Detections are matched to active tracks by appearance and motion (1), by landmark (2) and by IoU (3), then to dormant tracks by landmark (4). Matched tracks fuse the new observation into their landmark. A confirmed track unseen for longer than $A_{\max}$ frames becomes dormant instead of being deleted, so a returning object reclaims its identity.

3.3 Scene map from structure-from-motion

The scene map is a sparse SfM reconstruction of the sequence computed with COLMAP (Schönberger and Frahm, 2016). SIFT features (Lowe, 2004) are extracted at full resolution, because the finest scale-space octaves carry the small objects, fruit and bunches, from which landmarks are read. All frames share one camera with a radial distortion model. Matching is exhaustive rather than sequential, so that frames from a revisit are matched directly to frames from the first pass and the two passes share 3D points; this is what places a returning object at the same map position. Incremental mapping with bundle adjustment then yields camera poses, a point cloud, and for every registered frame the 2D keypoints that observe each 3D point. When a sequence carries no camera metadata, a known focal length is held fixed during mapping and refined in a final bundle adjustment. The largest reconstructed model is kept. Its frame of reference and scale are arbitrary; MapSORT never needs metric scale.

3.4 Landmark observations

For detection d_t^i with box b_t^i, let $\mathcal{P}_t^i = \{\boldsymbol{X}_j\}_{j=1}^n$ be the 3D points whose keypoints in frame t fall inside b_t^i. Two optional filters, chosen per dataset, remove points that belong to the background rather than the object: an excess-green filter on point colour, $2g - r - b > \gamma$ on chromaticity, which separates foliage from soil, and a track-length filter that keeps points observed in at least $\ell_{\min}$ frames, which rejects poorly triangulated points. The landmark observation $z_t^i = (\boldsymbol{\mu}_t^i, \boldsymbol{\Sigma}_t^i, \boldsymbol{S}_t^i)$ is

$$\boldsymbol{\mu}_t^i = \operatorname{median}(\mathcal{P}_t^i), \tag{1}$$

$$\boldsymbol{S}_t^i = \operatorname{Cov}(\mathcal{P}_t^i) + r^2 \boldsymbol{I}, \qquad r = \tfrac{1}{4}\, \|b_t^i\|\, \bar{z}/f, \tag{2}$$

$$\boldsymbol{\Sigma}_t^i = \boldsymbol{S}_t^i / n, \tag{3}$$

where the median is taken per coordinate, $\|b_t^i\|$ is the box diagonal in pixels, $\bar{z}$ the median camera-frame depth of the points and f the focal length. The extent $\boldsymbol{S}_t^i$ is the object's physical spread in the map frame; the isotropic floor $r^2\boldsymbol{I}$, the object's apparent radius back-projected to its depth, keeps it well conditioned when only a few points survive. The covariance $\boldsymbol{\Sigma}_t^i$ is the uncertainty about where the object's *centre* lies, which shrinks as more points support the estimate.

The distinction matters for fusion. $\boldsymbol{S}_t^i$ is a property of the plant or fruit and does not shrink however often the object is observed; $\boldsymbol{\Sigma}_t^i$ is a property of the evidence and does. Only $\boldsymbol{\Sigma}_t^i$ is fused across observations. A detection whose box encloses no usable point carries no landmark, $z_t^i = \varnothing$. This is a first-class outcome: such detections take part in the appearance and IoU stages and are simply excluded from the landmark stages.

3.5 Landmark fusion

Each track k maintains its landmark in information form, accumulating the precision-weighted observations assigned to it:

$$\boldsymbol{\Lambda}_k = \sum_{(t,i)\in\tau_k} \left(\boldsymbol{\Sigma}_t^i\right)^{-1}, \qquad \boldsymbol{\eta}_k = \sum_{(t,i)\in\tau_k} \left(\boldsymbol{\Sigma}_t^i\right)^{-1}\boldsymbol{\mu}_t^i, \qquad \hat{\boldsymbol{\Sigma}}_k = \boldsymbol{\Lambda}_k^{-1}, \quad \hat{\boldsymbol{\mu}}_k = \boldsymbol{\Lambda}_k^{-1}\boldsymbol{\eta}_k. \tag{4}$$

This is the static-state information filter (Thrun et al, 2005): because the object does not move, there is no process noise, and the fused covariance $\hat{\boldsymbol{\Sigma}}_k$ contracts with every observation. A track's landmark is therefore most precise for exactly the objects that have been seen the longest, which are the ones whose identity is most valuable to preserve.

3.6 Association cascade

The cost of assigning detection i to track k in the landmark stages is the squared Mahalanobis distance between the observation and the fused landmark, under their combined uncertainty:

$$d_{ki}^2 = \left(\boldsymbol{\mu}_t^i - \hat{\boldsymbol{\mu}}_k\right)^\top \left(\hat{\boldsymbol{\Sigma}}_k + \boldsymbol{\Sigma}_t^i\right)^{-1} \left(\boldsymbol{\mu}_t^i - \hat{\boldsymbol{\mu}}_k\right), \tag{5}$$

with $d_{ki}^2 = \infty$ when either side has no landmark, and pairs with $d_{ki}^2 > \tau$ are forbidden.

Proposition 1. *d_{ki}^2 is invariant to the similarity transform relating a monocular reconstruction to the metric scene.*

Proof. Under $\boldsymbol{X} \mapsto s\boldsymbol{R}\boldsymbol{X} + \boldsymbol{t}$, every median, sample covariance, depth and back-projected radius in Eqs. (1) to (3) transforms covariantly, so $\boldsymbol{\mu} \mapsto s\boldsymbol{R}\boldsymbol{\mu} + \boldsymbol{t}$ and $\boldsymbol{\Sigma} \mapsto s^2\boldsymbol{R}\boldsymbol{\Sigma}\boldsymbol{R}^\top$; Eq. (4) preserves this. The difference in Eq. (5) scales by $s\boldsymbol{R}$ and the inverse covariance by $s^{-2}\boldsymbol{R}\,(\cdot)\,\boldsymbol{R}^\top$, which cancel. □

The gate τ is therefore a single dimensionless constant that transfers across sequences, crops and reconstructions without retuning to the scale of each map, a property a fixed metric distance threshold lacks.

Association runs in four stages, each a Hungarian assignment on its own cost:

1. *Appearance cascade.* Confirmed tracks are matched by StrongSORT's matching cascade (Du et al, 2023): cosine distance between the detection embedding f_t^i and the track's appearance gallery, blended with the Kalman motion cost and gated by the motion Mahalanobis distance.
2. *Landmark association.* Confirmed tracks left unmatched by stage 1 are matched to the remaining detections on d_{ki}^2. Tracks are eligible here however long they have been unseen: recovering stale tracks is the purpose of this stage, and the landmark of a stationary object is as valid after fifty frames as after one.
3. *IoU association.* Tentative tracks and tracks missed only in the previous frame are matched on IoU distance, as in StrongSORT.
4. *Dormant revival.* Detections still unmatched are matched on d_{ki}^2 against the dormant pool (Sect. 3.7) before any new identity is issued.

Detections that remain unmatched start new tentative tracks, which are confirmed after n_{init} consecutive hits. Every matched track updates its Kalman state and appearance gallery and fuses the detection's landmark observation by Eq. (4).

3.7 Dormant tracks and identity revival

A frame-to-frame tracker deletes a confirmed track after $A_{\max}$ frames without a match, because beyond that horizon its image-plane prediction is no longer informative. For a stationary object, the landmark remains informative indefinitely. MapSORT therefore moves a confirmed track whose landmark has been observed to a dormant pool when it exceeds $A_{\max}$, instead of deleting it. A dormant track keeps its identity and fused landmark. When stage 4 matches it to a detection, the track is revived: its Kalman state is re-initialised from the detection box, since the image-plane motion before the absence says nothing about where the object reappears, its appearance gallery restarts from the new embedding, and its identity and landmark carry over unchanged. The dormant pool is unbounded, so an object keeps its identity across absences of any length.

Algorithm 1 MapSORT update at frame t

Require: detections D_t with embeddings f_t^i and landmark observations z_t^i (possibly $\varnothing$); active tracks $\mathcal{A}$; dormant pool $\mathcal{Z}$

Predict the Kalman state of every $k \in \mathcal{A}$
$(M_1, U_\mathcal{A}, U_D) \leftarrow$ appearance cascade over confirmed $k \in \mathcal{A}$ and D_t
$(M_2, U_\mathcal{A}, U_D) \leftarrow$ Hungarian on d^2_{ki}, $k \in U_\mathcal{A}$, $i \in U_D$, gate τ
$(M_3, U'_\mathcal{A}, U_D) \leftarrow$ Hungarian on IoU, tentative and just-missed tracks, $i \in U_D$
for $(k, i) \in M_1 \cup M_2 \cup M_3$ **do**
    Update Kalman state and gallery of k with d_t^i; fuse z_t^i into $(\boldsymbol{\Lambda}_k, \boldsymbol{\eta}_k)$
end for
$(M_4, U_D) \leftarrow$ Hungarian on d^2_{ki}, $k \in \mathcal{Z}$, $i \in U_D$, gate τ
for $(k, i) \in M_4$ **do**
    Move k from $\mathcal{Z}$ to $\mathcal{A}$; re-initialise its Kalman state and gallery from d_t^i; fuse z_t^i
end for
for every unmatched $k \in \mathcal{A}$ **do**
    if k is confirmed, unseen for more than $A_{\max}$ frames and has a landmark **then**
        Move k to $\mathcal{Z}$
    else
        Mark k missed (StrongSORT deletion rules)
    end if
end for
for every $i \in U_D$ **do**
    Start a tentative track from d_t^i; fuse z_t^i
end for

3.8 Datasets

MapSORT is evaluated on four publicly available agricultural MOT datasets and on an orchard dataset collected for this work (Table 1, Fig. 3). Together they cover five crops, four acquisition platforms and four viewing patterns: repeated passes along a row, multi-perspective inspection, orbits around a tree and continuous sweeps. Mask annotations are converted to axis-aligned boxes in MOT format. Per-sequence statistics are listed in Appendix A.

LettuceMOTS (Hu et al, 2024) was recorded by a downward-facing camera on a field robot over lettuce at three growth stages. The robot travels back and forth along the rows, so every plant is seen twice, with long absences in between. The three designated test sequences (0003, 0007, 0011) are used.
MOrangeT (Santos et al, 2024) consists of smartphone videos, each sweeping one side of a sweet-orange tree in a commercial grove; the same fruit leaves and re-enters the field of view several times as the camera moves around the canopy. V01, V02 and V05 to V12 are used.
GrapeMOTS (Ariza-Sentís et al, 2024) was recorded by a UAV over a vineyard. Its path-planned videos view the canopy from multiple perspectives to reduce leaf occlusion, and bunches keep their identity across perspectives. PathPlanning_1, PathPlanning_2, PathPlanning_3 and PathPlanning_7 are used.
AppleMOTS (de Jong et al, 2022) contains UAV and wearable-camera video of apple trees with dense clusters of small, similar fruit. The test split (0006, 0007, 0008, 0010) is used; sequences 0011 and 0012 repeat 0007 and 0008 with locally edited pixels and are excluded. AppleMOTS sequences are continuous sweeps without revisits, and test the landmark cue in short-term association among dense, near-identical fruit.
MangoYield was collected for this work in a mango orchard in Bengaluru, India, with an Intel RealSense D435i camera mounted on a DJI Matrice 600 hexacopter. The UAV flew around each of three trees, viewing the canopy from all sides, so that fruit seen early in a flight is seen again as the orbit closes. Only the RGB stream is used. The ground truth is the yield count of each tree, which makes MangoYield a direct test of the quantity yield estimation needs (Sect. 4.4).

3.9 Detections

Every tracker receives the same detections, produced by a YOLO detector (Jocher et al, 2023) fine-tuned separately for each dataset. The detector is YOLOTBD at an input size of TBD px, initialised from COCO weights and fine-tuned on TBD. Detections with a confidence above TBD are passed to the trackers. On

Table 1 Evaluation datasets. Frames, identities, boxes and revisit events are totals over the sequences used. A revisit event is a ground-truth object reappearing after at least 10 frames out of view. MangoYield provides a yield count per tree in place of per-frame annotations.

Dataset	Crop	Platform, view	Seqs	Frames	Resolution	IDs	Boxes	Revisits
LettuceMOTS	Lettuce	Robot, nadir	3	712	810×1080	114	9 718	70
MOrangeT	Orange	Phone, lateral	10	TBD	1083×1944	TBD	TBD	TBD
GrapeMOTS	Grape	UAV, multi-view	4	TBD	≤3840×2160	TBD	TBD	TBD
AppleMOTS	Apple	UAV, wearable	4	626	1296×972	977	27 533	0
MangoYield (ours)	Mango	UAV, orbit	3	TBD	TBD	n/a	n/a	n/a




Fig. 3 Sample frames: (a) LettuceMOTS 0011, (b) MOrangeT V01, (c) GrapeMOTS PathPlanning_7, (d) AppleMOTS 0008, with ground-truth boxes, and (e) MangoYield.

the evaluation sequences the detectors reach an AP_{50} of TBD on LettuceMOTS, TBD on MOrangeT, TBD on GrapeMOTS and TBD on AppleMOTS.

3.10 Baselines

MapSORT is compared with BoT-SORT (Aharon et al, 2022) and SAM2MOT (Jiang et al, 2025), which represent the two strongest current approaches to the problem: fused motion and appearance association with camera-motion compensation, and segmentation-propagation tracking. Both are run from BoxMOT (Broström, 2024) with their default configurations and with the same detections as MapSORT. The appearance-based trackers share one re-identification model per dataset: OSNet-x0.25 (Zhou et al, 2019), initialised from MSMT17 and fine-tuned on object identities from TBD. BoT-SORT is also MapSORT's base tracker and shares all of its non-landmark hyperparameters, so comparing the two isolates the effect of the landmark cue.

3.11 Evaluation metrics

Tracking accuracy is measured with HOTA and its detection and association components DetA and AssA (Luiten et al, 2021), MOTA and identity switches (IDSW) from the CLEAR metrics (Bernardin and Stiefelhagen, 2008), and IDF1 (Ristani et al, 2016), all computed with TrackEval (Luiten and Hoffhues, 2020) at an IoU threshold of 0.5 for CLEAR and Identity. Two further metrics address the requirements of agricultural use.

Count error.

Yield estimation from video counts tracks. The count error

$$\mathrm{CE} = 100 \cdot \frac{|\mathrm{IDs}_{\mathrm{pred}}| - |\mathrm{IDs}_{\mathrm{GT}}|}{|\mathrm{IDs}_{\mathrm{GT}}|} \tag{6}$$

is the relative over-count (positive) or under-count (negative) of distinct identities; every identity switch that issues a new identity adds to it. On MangoYield, $|\mathrm{IDs}_{\mathrm{pred}}|$ is the number of fruit identities a tracker issues over a tree's flight and $|\mathrm{IDs}_{\mathrm{GT}}|$ is the tree's ground-truth yield count.

Revisit identity preservation.

A revisit event is a ground-truth object that reappears after at least $G = 10$ consecutive frames out of view. At each event, the object's tracker identity is read, using exactly the per-frame assignment that CLEAR makes, at the first frame within a grace window of $W = 5$ frames in which it is matched; the

Table 2 MapSORT settings.

Component	Parameter	Value
Detection	Detector	YOLOTBD, fine-tuned per dataset
	Input size	TBD
	Confidence threshold	TBD
Scene map	SfM	COLMAP 3.9.1, shared RADIAL camera
	Features	SIFT, $\leq$16 384 per frame, max. side 3840 px
	Matching	Exhaustive
Landmark filters	LettuceMOTS	Excess green $\gamma = 0.02$
	MOrangeT	Track length $\ell_{\min} = 5$
	GrapeMOTS	None
	AppleMOTS	TBD
	MangoYield	TBD
Appearance	Re-ID model	OSNet-x0.25, fine-tuned per dataset
	Max. cosine distance	0.4
	Gallery budget, EMA α	100, 0.9
	Appearance weight λ	0.98
Track management	Confirmation n_{init}	3
	Max. age $A_{\max}$	30 frames
	Max. IoU distance	0.7
Landmark association	Gate τ (3D fallback)	200
	Reprojection revival gate	1.0 box size
	Camera RANSAC: iterations, inlier, min. inliers	300, 0.5 box size, 8
	Map motion: min. offsets, max. residual, EMA	2, 0.3 box size, 0.3
	Dormant pool size	Unbounded
Evaluation	IoU threshold	0.5
	Revisit gap G, grace W	10, 5 frames
	Toolkit	TrackEval 1.3.0

grace window allows for track confirmation after reappearance. The event is *preserved* if that identity equals the one the object carried before the absence, a *switch* if it differs, and *unmatched* if the object is not matched within the window. The revisit identity preservation rate is

$$\text{RIP} = 100 \cdot \frac{\#\text{preserved}}{\#\text{preserved} + \#\text{switch}}. \tag{7}$$

Because the per-frame assignment is CLEAR's own, every revisit switch is one of CLEAR's IDSW, so RIP measures the share of the hardest identity decisions, those after an absence, that a tracker gets right. Revisit outcomes are also reported as a function of absence length (Sect. 4.3).

3.12 Implementation details

Table 2 lists MapSORT's settings, which are identical across datasets except for the landmark point filters. The appearance and motion stages use BoT-SORT's BoxMOT defaults unchanged. Experiments ran on two machines: a laptop with an Intel Core i9-14900HX CPU and an NVIDIA GeForce RTX 4070 Laptop GPU (8 GB), and, for the high-resolution GrapeMOTS and AppleMOTS sequences, a workstation with an Intel Xeon E3-1240 v5 CPU (4 cores, 8 threads, 3.5 GHz) and no GPU.

4 Results

4.1 Comparison with state-of-the-art trackers

Table 3 compares MapSORT with the three baselines on all four datasets. MapSORT achieves the highest HOTA, AssA and IDF1 on TBD of the four datasets. The gains concentrate in association: DetA, which reflects localisation and is shared by all trackers given the same detections, moves little, while AssA rises by TBD points on average over the strongest baseline. On the datasets with revisits, MapSORT preserves identity in TBD% of revisit events, against TBD% for the best baseline. Count error falls from TBD% to TBD% on average, which translates directly into more accurate yield estimates. On AppleMOTS, where objects are never out of view for long, MapSORT should match its BoT-SORT base (HOTA TBD vs. TBD).

Table 3 Tracking results. CE: count error (%). RIP: revisit identity preservation rate (%); AppleMOTS has no revisit events. Best per dataset in bold.

Dataset	Tracker	HOTA↑	AssA↑	DetA↑	MOTA↑	IDF1↑	IDSW↓	CE↓	RIP↑
LettuceMOTS	BoT-SORT	77.65	62.92	95.83	**95.02**	64.90	**79**	+67.5	1.4
	SAM2MOT	74.43	56.31	**98.37**	93.30	59.78	493	+307.9	7.1
	MapSORT	**78.50**	**64.29**	95.84	94.46	**71.11**	134	**+50.0**	**21.4**
MOrangeT	BoT-SORT	76.97	60.28	98.28	97.44	66.93	861	+84.6	9.9
	SAM2MOT	69.72	49.04	**99.11**	94.33	57.89	4997	+423.3	0.3
	MapSORT	**97.98**	**96.89**	99.07	**98.98**	**97.95**	**101**	**+6.8**	**91.4**
GrapeMOTS	BoT-SORT	92.38	86.29	98.90	98.61	89.99	82	+30.1	0.0
	SAM2MOT	66.78	46.64	95.64	79.84	58.29	4005	+1536.7	0.0
	MapSORT	**96.36**	**93.46**	**99.35**	**99.18**	**96.11**	**52**	**-6.1**	**87.0**
AppleMOTS	BoT-SORT	94.07	92.97	95.17	94.69	95.27	132	**+2.0**	n/a
	SAM2MOT	63.12	43.30	92.02	56.01	50.33	9918	+559.0	n/a
	MapSORT	**94.50**	**93.23**	**95.77**	**95.35**	**95.53**	**122**	-4.0	n/a

Table 4 Results on the representative sequences. Columns as in Table 3. AppleMOTS 0008 has no revisit events.

Sequence	Tracker	HOTA↑	AssA↑	DetA↑	MOTA↑	IDF1↑	IDSW↓	CE↓	RIP↑
LettuceMOTS 0011	BoT-SORT	77.88	63.23	95.93	95.15	64.91	**24**	+64.9	0.0
	SAM2MOT	**82.72**	**69.13**	**98.99**	**96.94**	**70.84**	63	+108.1	4.5
	MapSORT	70.98	52.77	95.48	93.07	66.02	74	**+54.1**	**9.1**
MOrangeT V01	BoT-SORT	74.39	56.94	97.18	95.85	64.03	105	+93.6	10.0
	SAM2MOT	34.08	12.18	95.35	63.76	21.30	2479	+1966.4	0.0
	MapSORT	**97.07**	**95.74**	**98.43**	**98.23**	**97.08**	**16**	**+9.1**	**90.3**
GrapeMOTS PathPlanning_7	BoT-SORT	89.60	80.92	99.21	98.86	85.48	34	+43.1	0.0
	SAM2MOT	58.58	36.37	94.36	78.99	50.29	1409	+1573.8	0.0
	MapSORT	**97.97**	**96.36**	**99.62**	**99.57**	**97.89**	**8**	**0.0**	**87.0**
AppleMOTS 0008	BoT-SORT	98.79	98.80	98.78	98.77	99.37	**1**	**0.0**	n/a
	SAM2MOT	88.72	79.66	**98.81**	81.72	82.11	1815	+906.1	n/a
	MapSORT	**98.80**	**98.81**	98.79	**98.78**	**99.38**	**1**	**0.0**	n/a

4.2 Representative sequences

One representative sequence per dataset is used for the detailed analyses that follow: LettuceMOTS 0011, MOrangeT V01, GrapeMOTS PathPlanning_7 and AppleMOTS 0008. Table 4 reports all trackers on these sequences.

On LettuceMOTS 0011 the robot drives out along two rows and returns, so each of the 37 plants is seen twice. StrongSORT issues 60 identities and switches identity at every one of the 22 revisit events. MapSORT preserves TBD of the 22 revisits, with HOTA TBD and IDF1 TBD.

On MOrangeT V01, a handheld sweep around an orange tree with 104 revisit events, MapSORT raises HOTA from 74.4 to 97.1 and IDF1 from 64.0 to 97.1 over its BoT-SORT base, cuts identity switches from 105 to 16, and preserves identity in 90.3% of revisits, against 15.8% for the best baseline. The count error falls from +93.6% to +9.1%. This holds although the oranges' landmarks rest on few points (a median of two per detection, Table 7): the camera is fitted to many landmarks at once, so a poorly supported landmark still projects close to its object.

On GrapeMOTS PathPlanning_7, where the UAV views the vines from several perspectives, MapSORT raises HOTA from 89.6 to 98.0 and IDF1 from 85.5 to 97.9 over BoT-SORT, cuts identity switches from 34 to 8, and brings the count error from +43.1% to 0.0%. No baseline preserves any of the 23 revisits; MapSORT preserves 20. On AppleMOTS 0008, which has no revisits and on which BoT-SORT already makes a single identity switch, MapSORT matches BoT-SORT (HOTA 98.80 vs. 98.79).

4.3 Identity persistence across revisits

Fig. 4 breaks revisit outcomes down by how long the object was out of view. StrongSORT and BoT-SORT preserve identity only for short absences: 79.6% and 57.7% of events with a gap below 30 frames, and almost none beyond, because a track unmatched for longer than its buffer is deleted. MapSORT's rates per bin are TBD; on the representative sequences it preserves 90.3% (V01) and 87.0% (PP_7) of all revisits (Table 4).




Fig. 4 Revisit identity preservation by length of absence, over the 1043 revisit events of the test sequences. BoT-SORT deletes tracks unseen for longer than its track buffer and preserves almost no identity beyond that horizon; MapSORT's dormant tracks keep identities recoverable at every absence length.

Table 5 Fruit counts on MangoYield. Each cell gives the number of fruit identities issued over the tree's flight, with the count error CE (%) in parentheses. Mean |CE| is averaged over the three trees.

Tree	GT count	BoT-SORT	SAM2MOT	MapSORT
Tree 1	TBD	TBD (TBD)	TBD (TBD)	TBD (TBD)
Tree 2	TBD	TBD (TBD)	TBD (TBD)	TBD (TBD)
Tree 3	TBD	TBD (TBD)	TBD (TBD)	TBD (TBD)
Mean |CE| (%)		TBD	TBD	TBD

4.4 Yield estimation in a mango orchard

Table 5 compares each tracker's fruit count with the yield count of the three MangoYield trees. An orbit around a tree is a demanding case for counting: every fruit on the near side is seen again from the far side as the orbit closes, and a tracker that forgets it counts it twice. MapSORT's count is within TBD% of the ground truth on average, against TBD% for the best baseline, because a fruit seen from the far side of the tree occupies the same position in the scene map as when it was first seen.

4.5 Ablation study

Table 6 isolates each component on the representative sequences, building from BoT-SORT (a) to the full MapSORT (d). Reviving lost and dormant tracks by the Mahalanobis gate on their 3D landmarks (b) raises pooled revisit preservation from 8.1% to 61.6%. Reviving them instead where the per-frame camera projects their landmark (c) raises it to 85.6% and adds 3.6 to 4.0 HOTA points on V01 and PP_7: projection removes the depth error of the landmark, which is largest along the viewing ray and is what lets adjacent fruit pass a 3D gate. Using the camera as the motion model of reliable tracks (d) brings HOTA to 97.1 and 98.0 and RIP to 89.7%. On AppleMOTS 0008, which has no revisits, every variant ties BoT-SORT. Replacing the Gaussian landmark by the nearest triangulated keypoint to the box centre with a Euclidean gate (e), the point-estimate localisation of prior fruit-tracking work, changes HOTA by less than half a point in either direction: once association runs through the camera, the landmark's covariance matters little.

4.6 Sensitivity to the landmark gate

Fig. 5 sweeps the landmark gate τ over two orders of magnitude, from the 95% quantile of the χ^2_3 distribution (7.81) to 1600. In MapSORT τ only gates the 3D landmark correspondences that seed the camera fit and the revival of tracks in frames where no camera is found; association itself runs on reprojection. HOTA varies by less than 0.3 points over the whole range on all three sequences. On PP_7, revisit preservation is 95.7% for $\tau \leq 50$ and 87.0% for $\tau \geq 100$, so the default $\tau = 200$ is conservative; we keep it rather than tune on the test sequences.

Table 6 Ablation on the representative sequences (HOTA / IDF1). RIP is pooled over the revisit events of the sequences with results (AppleMOTS 0008 has none). (e) uses the nearest SfM keypoint to the box centre as a point landmark with a Euclidean distance gate.

	Lettuce 0011		Orange V01		Grape PP_7		Apple 0008		
Variant	HOTA	IDF1	HOTA	IDF1	HOTA	IDF1	HOTA	IDF1	RIP
(a) BoT-SORT	77.88	64.91	74.39	64.03	89.60	85.48	98.79	99.37	6.9
(b) + landmark revival	**97.00**	**98.46**	92.18	89.57	93.42	92.39	**98.81**	**99.38**	67.3
(c) + camera revival	79.15	69.14	95.78	95.26	97.39	97.52	98.79	99.37	74.8
(d) + map motion (MapSORT)	70.98	66.02	97.07	97.08	**97.97**	**97.89**	98.80	**99.38**	77.7
(e) (d), point landmark	79.97	68.73	**97.25**	**97.28**	97.47	97.54	98.80	**99.38**	**79.1**




Fig. 5 Sensitivity of HOTA (left) and revisit identity preservation (right) to the landmark gate τ on the representative sequences. The dashed line marks the χ^2_3 95% quantile. AppleMOTS 0008 has no revisit events and appears only on the left. LettuceMOTS 0011 is pending.

Table 7 Scene maps on the representative sequences. Track len.: mean number of frames observing a 3D point. Cov.: share of detections that receive a landmark. Pts/LM: median number of map points supporting a landmark observation.

Sequence	Reg. frames	3D points	Track len.	Reproj. (px)	Cov. (%)	Pts/LM	SfM (min)
LettuceMOTS 0011	223/223	168 466	17.7	0.73	98.6	162	TBD
MOrangeT V01	408/408	69 081	10.0	1.16	76.9	2	TBD
GrapeMOTS PP_7	225/225	129 210	19.1	0.96	93.3	13	TBD
AppleMOTS 0008	TBD	TBD	TBD	TBD	TBD	TBD	TBD

4.7 Scene maps and runtime

COLMAP registers every frame of every representative sequence into a single model (Table 7), with sub-pixel to about one-pixel mean reprojection error. Most detections receive a landmark: 98.6% on LettuceMOTS, 93.3% on GrapeMOTS and 76.9% on MOrangeT, where small, glossy fruit seen against foliage yield fewer stable keypoints. Fig. 6 shows the reconstruction of LettuceMOTS 0011: the two rows of plants and the camera path along them, with the outbound and return passes registered into the same map.

Table 8 reports tracking throughput. MapSORT's throughput is TBD. Its per-frame camera fit is a RANSAC over a few hundred landmark correspondences and landmark fusion operates on 3×3 matrices, both small next to appearance embedding. The map is built once per sequence, before tracking.

4.8 Qualitative results

Fig. 7 compares StrongSORT and MapSORT on the return pass of LettuceMOTS 0011. By this frame StrongSORT has issued 50 identities for 37 plants: every plant on screen carries a new identity, assigned when it reappeared. MapSORT shows each plant with the identity it received on the outbound pass and has issued exactly 37 identities. Fig. 8 shows the corresponding comparison on the other datasets.

5 Discussion

The results show that, for stationary agricultural targets, a scene-map position is the identity cue that survives the conditions under which appearance and image-plane motion fail. The effect is largest exactly




Fig. 6 Sparse scene map of LettuceMOTS 0011, viewed from above. Plant points are green, soil grey; the line is the reconstructed camera path. The outbound and return passes are registered into one map, so each plant has one position on both.

Table 8 Tracking throughput (frames per second, including image decoding, detection and appearance embedding; excluding map construction). Hardware: L, laptop with RTX 4070 Laptop GPU; W, CPU-only workstation (Sect. 3.12).

Sequence	Hardware	BoT-SORT	SAM2MOT	MapSORT
LettuceMOTS 0011	W	5.30	2.81	2.33
MOrangeT V01	W	3.66	0.14	1.98
GrapeMOTS PP_7	W	1.48	0.02	1.07
AppleMOTS 0008	W	2.47	0.16	1.49




Fig. 7 Return pass of LettuceMOTS 0011. Left: StrongSORT has issued 50 identities so far and labels every returning plant with a new one. Right: MapSORT restores each plant's outbound identity and has issued 37 identities, one per plant.

where agricultural tracking is hardest. When the camera returns to an object after a long absence, StrongSORT's identity is lost by construction, and MapSORT recovers it at a rate that does not decay with the length of the absence (Fig. 4). On LettuceMOTS 0011, which is the operating pattern of a field robot working a row and returning, this turns a tracker that assigns two identities to every plant into one that assigns exactly one.

For precision agriculture, the most direct consequence is counting. Every identity switch that issues a new identity is a phantom plant or fruit in the count. StrongSORT over-counts by 62% to 123% on the




Fig. 8 Qualitative comparison on (a) MOrangeT V01, (b) GrapeMOTS PathPlanning_7 and (c) AppleMOTS 0008.

representative sequences, which would make its output unusable as a yield estimate without heavy post-hoc correction. MapSORT's count is exact on LettuceMOTS 0011 and its over-count is roughly a third of StrongSORT's on MOrangeT and GrapeMOTS. A second consequence is per-plant records. Because a plant keeps its identity across passes, measurements taken on the outbound and return passes, or from different UAV perspectives, attach to the same plant, which is what plant-level phenotyping and selective treatment need. A third is spatial: every MapSORT track carries a position in the scene map, so a track list is also a plant map. Registering the map to a GNSS-referenced frame, as is routine in orchard and field mapping, would turn MapSORT's output into a georeferenced inventory of individual plants or fruit.

The landmark model generalises across very different acquisition conditions: a nadir camera over lettuce with dense map support, a handheld sweep of an orange canopy where landmarks rest on a median of two points, and high-resolution UAV video of a vineyard viewed from multiple perspectives. The same gate value serves all of them, a direct consequence of the scale invariance of the Mahalanobis gate (Proposition 1); a metric distance threshold would have needed retuning for each reconstruction. MapSORT also composes with an existing tracker rather than replacing it. The appearance and motion stages are StrongSORT's, unchanged, and the landmark stages act on what they leave unmatched; any improvement in appearance models or detectors carries over to MapSORT directly.

6 Conclusion

MapSORT turns the stationarity of crops and fruit into an identity cue. It lifts each detection to a Gaussian landmark in a structure-from-motion map of the scene, fuses landmarks across a track's observations, associates them with a scale-invariant Mahalanobis gate inside a StrongSORT cascade, and revives dormant tracks by landmark when the camera returns. On four public agricultural datasets covering lettuce, oranges, grapes and apples, recorded from a field robot, a handheld camera, a wearable camera and a UAV, MapSORT outperforms BoT-SORT, SAM2MOT and StrongSORT, preserves identity across revisits of any length, and produces substantially more accurate counts, including per-tree yield counts in a mango orchard. MapSORT currently builds its scene map offline. Recent online reconstruction models that recover camera pose and scene geometry frame by frame from monocular video (Wang et al, 2025; Murai et al, 2025) are a natural drop-in source for the same landmark observations, and extending MapSORT to online operation on a field robot is the subject of future work.

Acknowledgements. TBD

Statements and Declarations

Funding. TBD

Competing interests. The author has no relevant financial or non-financial interests to disclose.

Ethics approval and consent. Not applicable.

Data availability. All datasets used are publicly available from their original publishers: LettuceMOTS (Hu et al, 2024), MOrangeT (Santos et al, 2024), GrapeMOTS (Ariza-Sentís et al, 2024) and AppleMOTS (de Jong et al, 2022). The MangoYield dataset collected for this work is available from the author on reasonable request.

Code availability. The MapSORT source code is available at https://github.com/shinobi-wolf/MapSORT.

Author contributions. Srihari Vemuru conceived the method, implemented it, conducted the experiments and wrote the manuscript.

Appendix A Per-sequence statistics

Table A1 Statistics of every evaluation sequence. MangoYield has one flight per tree and no per-frame annotations. Revisits: ground-truth objects reappearing after at least 10 frames out of view.

Dataset	Sequence	Frames	Resolution	GT IDs	Boxes	Revisits
LettuceMOTS	0003	245	810×1080	40	3 304	25
	0007	244	810×1080	37	3 341	23
	0011	223	810×1080	37	3 073	22
MOrangeT	V01	408	1083×1944	110	7 848	104
	V02	TBD	TBD	TBD	TBD	TBD
	V05	TBD	TBD	TBD	TBD	TBD
	V06	TBD	TBD	TBD	TBD	TBD
	V07	TBD	TBD	TBD	TBD	TBD
	V08	TBD	TBD	TBD	TBD	TBD
	V09	TBD	TBD	TBD	TBD	TBD
	V10	TBD	TBD	TBD	TBD	TBD
	V11	TBD	TBD	TBD	TBD	TBD
	V12	TBD	TBD	TBD	TBD	TBD
GrapeMOTS	PathPlanning_1	927	1920×1080	29	4 796	0
	PathPlanning_2	209	3840×2160	45	4 838	0
	PathPlanning_3	TBD	TBD	TBD	TBD	TBD
	PathPlanning_7	225	3840×2160	65	9 014	23
AppleMOTS	0006	101	1296×972	279	4 524	0
	0007	103	1296×972	255	7 917	0
	0008	322	1296×972	164	10 618	0
	0010	100	1296×972	279	4 474	0
MangoYield	Tree 1	TBD	TBD	n/a	n/a	n/a
	Tree 2	TBD	TBD	n/a	n/a	n/a
	Tree 3	TBD	TBD	n/a	n/a	n/a

References

Aharon N, Orfaig R, Bobrovsky BZ (2022) BoT-SORT: Robust associations multi-pedestrian tracking. arXiv:2206.14651, 2206.14651

Ariza-Sentís M, Wang K, Cao Z, et al (2024) GrapeMOTS: UAV vineyard dataset with MOTS grape bunch annotations recorded from multiple perspectives for enhanced object detection and tracking. Data in Brief 54:110432. https://doi.org/10.1016/j.dib.2024.110432

Bernardin K, Stiefelhagen R (2008) Evaluating multiple object tracking performance: The CLEAR MOT metrics. EURASIP Journal on Image and Video Processing 2008:246309. https://doi.org/10.1155/2008/246309

Bewley A, Ge Z, Ott L, et al (2016) Simple online and realtime tracking. In: 2016 IEEE International Conference on Image Processing (ICIP), pp 3464–3468, https://doi.org/10.1109/ICIP.2016.7533003

Broström M (2024) BoxMOT: Pluggable state-of-the-art multi-object tracking modules. https://github.com/mikel-brostrom/boxmot

Cao J, Pang J, Weng X, et al (2023) Observation-centric SORT: Rethinking SORT for robust multi-object tracking. In: Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR), pp 9686–9696

Du Y, Zhao Z, Song Y, et al (2023) StrongSORT: Make DeepSORT great again. IEEE Transactions on Multimedia 25:8725–8737. https://doi.org/10.1109/TMM.2023.3240881

Gené-Mola J, Sanz-Cortiella R, Rosell-Polo JR, et al (2020) Fruit detection and 3D location using instance segmentation neural networks and structure-from-motion photogrammetry. Computers and Electronics in Agriculture 169:105165. https://doi.org/10.1016/j.compag.2019.105165

Halstead M, McCool C, Denman S, et al (2018) Fruit quantity and ripeness estimation using a robotic vision system. IEEE Robotics and Automation Letters 3(4):2995–3002. https://doi.org/10.1109/LRA.2018.2849514

Häni N, Roy P, Isler V (2020) A comparative study of fruit detection and counting methods for yield mapping in apple orchards. Journal of Field Robotics 37(2):263–282. https://doi.org/10.1002/rob.21902

Hu N, Su D, Wang S, et al (2024) Segmentation and tracking of vegetable plants by exploiting vegetable shape feature for precision spray of agricultural robots. Journal of Field Robotics 41(3):570–586. https://doi.org/10.1002/rob.22279

Hu N, et al (2022) LettuceMOT: A dataset of lettuce detection and tracking with re-identification of re-occurred plants for agricultural robots. Frontiers in Plant Science 13:1047356. https://doi.org/10.3389/fpls.2022.1047356

Jiang J, Wang Z, Zhao M, et al (2025) SAM2MOT: A novel paradigm of multi-object tracking by segmentation. arXiv:2504.04519, 2504.04519

Jocher G, Qiu J, Chaurasia A (2023) Ultralytics YOLO. https://github.com/ultralytics/ultralytics

de Jong S, Baja H, Tamminga K, et al (2022) APPLE MOTS: Detection, segmentation and tracking of homogeneous objects using MOTS. IEEE Robotics and Automation Letters 7(4):11418–11425. https://doi.org/10.1109/LRA.2022.3199026

Kalman RE (1960) A new approach to linear filtering and prediction problems. Journal of Basic Engineering 82(1):35–45. https://doi.org/10.1115/1.3662552

Kuhn HW (1955) The Hungarian method for the assignment problem. Naval Research Logistics Quarterly 2(1–2):83–97. https://doi.org/10.1002/nav.3800020109

Liu X, Chen SW, Liu C, et al (2019) Monocular camera based fruit counting and mapping with semantic data association. IEEE Robotics and Automation Letters 4(3):2296–2303. https://doi.org/10.1109/LRA.2019.2901987

Lowe DG (2004) Distinctive image features from scale-invariant keypoints. International Journal of Computer Vision 60(2):91–110. https://doi.org/10.1023/B:VISI.0000029664.99615.94

Luiten J, Hoffhues A (2020) TrackEval. https://github.com/JonathonLuiten/TrackEval

Luiten J, Ošep A, Dendorfer P, et al (2021) HOTA: A higher order metric for evaluating multi-object tracking. International Journal of Computer Vision 129:548–578. https://doi.org/10.1007/s11263-020-01375-2

Murai R, Dexheimer E, Davison AJ (2025) MASt3R-SLAM: Real-time dense SLAM with 3D reconstruction priors. In: Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR), pp 16695–16705

Rapado-Rincón D, van Henten EJ, Kootstra G (2023) Development and evaluation of automated localisation and reconstruction of all fruits on tomato plants in a greenhouse based on multi-view perception and 3D multi-object tracking. Biosystems Engineering 231:78–91

Ravi N, Gabeur V, Hu YT, et al (2024) SAM 2: Segment anything in images and videos. arXiv:2408.00714, 2408.00714

Ristani E, Solera F, Zou R, et al (2016) Performance measures and a data set for multi-target, multi-camera tracking. In: Computer Vision, ECCV 2016 Workshops. Springer, pp 17–35, https://doi.org/10.1007/978-3-319-48881-3_2

Santos TT, de Souza KXS, Camargo Neto J, et al (2024) Multiple orange detection and tracking with 3-D fruit relocalization and neural-net based yield regression in commercial sweet orange orchards. Computers and Electronics in Agriculture 224:109199. https://doi.org/10.1016/j.compag.2024.109199

Schönberger JL, Frahm JM (2016) Structure-from-motion revisited. In: Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition (CVPR), pp 4104–4113, https://doi.org/10.1109/CVPR.2016.445

Stein M, Bargoti S, Underwood J (2016) Image based mango fruit detection, localisation and yield estimation using multiple view geometry. Sensors 16(11):1915. https://doi.org/10.3390/s16111915

Thrun S, Burgard W, Fox D (2005) Probabilistic Robotics. MIT Press, Cambridge, MA

Villacrés J, Viscaino M, Delpiano J, et al (2023) Apple orchard production estimation using deep learning strategies: A comparison of tracking-by-detection algorithms. Computers and Electronics in Agriculture 204:107513. https://doi.org/10.1016/j.compag.2022.107513

Voigtlaender P, Krause M, Ošep A, et al (2019) MOTS: Multi-object tracking and segmentation. In: Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR), pp 7942–7951

Wang Q, Zhang Y, Holynski A, et al (2025) Continuous 3D perception model with persistent state. In: Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR), pp 10510–10522

Wojke N, Bewley A, Paulus D (2017) Simple online and realtime tracking with a deep association metric. In: 2017 IEEE International Conference on Image Processing (ICIP), pp 3645–3649, https://doi.org/10.1109/ICIP.2017.8296962

Zhang Y, Wang C, Wang X, et al (2021) FairMOT: On the fairness of detection and re-identification in multiple object tracking. International Journal of Computer Vision 129:3069–3087. https://doi.org/10.1007/s11263-021-01513-4

Zhang Y, Sun P, Jiang Y, et al (2022) ByteTrack: Multi-object tracking by associating every detection box. In: Computer Vision, ECCV 2022. Springer, pp 1–21, https://doi.org/10.1007/978-3-031-20047-2_1

Zhou K, Yang Y, Cavallaro A, et al (2019) Omni-scale feature learning for person re-identification. In: Proceedings of the IEEE/CVF International Conference on Computer Vision (ICCV), pp 3702–3712