MapSORT: Landmark Association for Identity-Persistent Tracking of Stationary Crops and Fruit

Srihari Vemuru

Corresponding author(s). E-mail(s): vemshari27@gmail.com;

Abstract

Purpose: Plant- and fruit-level records in precision agriculture, such as yield estimates, phenotyping logs and targeted spraying, require every plant or fruit to keep one identity across a video, including when the camera leaves and later returns to it. General-purpose multi-object trackers lose identity in exactly this situation, because crops look alike and an object out of view for more than a few frames is forgotten. This work turns the property that sets agricultural targets apart, that they do not move, into an association cue that keeps identities intact across occlusions and revisits.

Methods: MapSORT reconstructs the scene with structure-from-motion and gives every detection and every track a landmark: a Gaussian over the object's position in the scene map. Built on BoT-SORT, it fits a camera to its own tracks in every frame, from their landmarks and boxes, and uses that camera to place each stationary object in the image. Tracks the frame-to-frame association misses are re-matched where their landmark projects; lost tracks, and tracks that left the view long ago and were kept dormant rather than deleted, are revived the same way, including objects that re-enter at the frame edge. MapSORT is compared with StrongSORT, Deep OC-SORT and BoT-SORT on four public datasets (LettuceMOTS, MOrangeT, GrapeMOTS, AppleMOTS).

Results: Averaged over the four datasets, MapSORT reaches 95.5 HOTA and 96.0 IDF1, 10.2 and 16.7 points above the strongest baseline, BoT-SORT, and cuts identity switches from 1150, the fewest of any baseline, to 223. It preserves identity in 91.9% of 1043 revisit events, against at most 11.5% for the baselines, at every length of absence. It has fewer identity switches than every baseline on 19 of the 21 test sequences.

Conclusion: The position of a stationary object in a map of the scene is an identity cue that survives arbitrarily long absences. Recovering the camera from the tracks themselves turns that position into a motion model and a re-identification cue, giving identity-consistent tracks and accurate counts across crops, platforms and viewing patterns.

Keywords: Multi-object tracking, Structure-from-motion, Camera resection, Fruit counting, Plant re-identification, Yield estimation

1 Introduction

Precision agriculture is moving from field-level statistics to operations on individual plants and fruit. Selective harvesting robots pick only the ripe fruit and leave the rest (Rajendran et al, 2024); targeted sprayers apply agrochemicals where sensing detects a target instead of covering the whole orchard (Mahmud et al, 2021; Wu et al, 2025); and plant-level management and phenotyping aim to sense, and treat, plants individually rather than by field, and to measure their fine-scale traits (Sarkar et al, 2024; Xu and Li, 2022).

Each of these operations needs a plant or fruit to keep one identity across the whole video. The fruit a robot has chosen to pick must still be that fruit when the arm reaches it; the treatments and measurements a plant receives must accumulate on a single record; and a fruit seen again from another side must not become a second fruit. Identity must hold when the camera leaves an object and later returns to it, as on the return pass of a field robot along a row, in a UAV flight that views a vineyard from several perspectives, or in a handheld sweep around a tree. When identity breaks, the consequence




Fig. 1 The same frame of a field robot's return pass along two lettuce rows (LettuceMOTS 0011), tracked by BoT-SORT (left) and MapSORT (right). Identities are numbered in order of first appearance. BoT-SORT has issued 56 identities for 37 plants; MapSORT keeps the identity each plant received on the outbound pass and has issued 39.

is physical rather than statistical: a fruit is picked or treated twice, or skipped. Counting is the coarsest of these tasks, since every identity switch adds a phantom plant to the total.

The state of the art for tracking plants and fruit in video is tracking-by-detection. StrongSORT (Du et al, 2023), Deep OC-SORT (Maggiolino et al, 2023) and BoT-SORT (Aharon et al, 2022) detect objects in every frame and associate the detections with existing tracks mainly through appearance: a re-identification embedding of each detection is compared with those of the tracks, while image-plane motion, through a Kalman-filter prediction and camera-motion compensation, supports and gates the match. This works when targets are visually distinct and mostly stay in view, as in the pedestrian tracking these trackers were developed for.

These trackers fail to keep one identity per plant or fruit once the camera leaves an object and returns to it, and to tell apart neighbouring objects of the same crop. There are three reasons. First, plants and fruit of one crop look almost alike, so appearance separates them poorly, and what does differ, such as viewpoint, occlusion and lighting, changes between passes. Second, motion cues are tied to the image plane and to recent frames; camera motion, and in a canopy the parallax it produces, breaks them. Third, a track is deleted once it has been lost for longer than a buffer, because beyond that horizon its image-plane prediction is no longer informative; an object that stays out of view for longer is forgotten by construction and receives a new identity when it returns. Stronger appearance models and better motion compensation improve short-term association, but not this. Fig. 1 shows the result: on the return pass of a field robot along two lettuce rows (LettuceMOTS; Hu et al 2024), BoT-SORT has issued 56 identities for 37 plants, and every plant in view carries a new one. Each such switch is a phantom plant or fruit, which defeats any task that must act on a specific one.

Agricultural targets do not move, and this is the property that sets them apart from pedestrians. A stationary object's position in a map of the scene does not age: unlike appearance and image-plane motion, it is as valid after a long absence as after a short one. Position can therefore serve as an identity memory that outlasts the track buffer, which is exactly what the failures above lack.

MapSORT builds this memory on top of BoT-SORT (Aharon et al, 2022), whose own association runs first and is left unchanged. A scene map is reconstructed once per sequence by structure-from-motion (Schönberger and Frahm, 2016), and every detection and track receives a Gaussian landmark, a position in the map together with its uncertainty. At every frame, a camera is fitted to the tracker's own landmark and box correspondences, with a plane model for near-planar scenes such as a lettuce field, and this camera predicts where each stationary object should appear in the image, including just beyond the frame edge. Two stages use it: a map-motion stage re-matches the tracks that BoT-SORT left unmatched where the camera places them, and a revival stage reclaims the identity of lost tracks by reprojection. Tracks that leave the view are kept dormant rather than deleted, so an object can reclaim its identity after an absence of any length. Because every track also carries a position in the scene map, a track list is at the same time a map of the plants, which is what an operation on a specific plant needs in addition to an identity.

The contributions of this work are:

1. A Gaussian landmark for every detection and track, compared through a Mahalanobis gate that is invariant to the unknown scale of a monocular reconstruction (Proposition 1), and a per-frame camera resection from the tracker's own landmark-to-box correspondences, robust to wrong matches and to near-coplanar scenes such as a field of lettuce, which places every stationary object, visible or not, in the current image.
2. MapSORT, which adds two stages to BoT-SORT (Aharon et al, 2022): a map-motion stage that re-matches unmatched tracks where the camera places them, and a revival stage that reclaims the identity of lost and dormant tracks by reprojection, including objects that re-enter at the frame edge with only a sliver visible. Tracks that leave the view are kept dormant instead of deleted, so identity survives absences of any length.
3. A revisit-centred evaluation protocol: a revisit identity preservation rate that decomposes CLEAR identity switches (Bernardin and Stiefelhagen, 2008) by the absence that preceded them, together with count error, the quantity that yield estimation consumes.
4. A benchmark against StrongSORT (Du et al, 2023), Deep OC-SORT (Maggiolino et al, 2023) and BoT-SORT (Aharon et al, 2022) on four public agricultural datasets, LettuceMOTS (Hu et al, 2024), MOrangeT (Santos et al, 2024), GrapeMOTS (Ariza-Sentís et al, 2024) and AppleMOTS (de Jong et al, 2022), covering four crops, four platforms and three viewing patterns, with per-sequence results.

The remainder of this paper is organised as follows. Section 2 reviews related work. Section 3 describes the method, together with the datasets, baselines and evaluation metrics, including the revisit protocol. Section 4 reports the comparison with the baselines, identity persistence by length of absence, an ablation, the sensitivity to the landmark gate and runtime. Section 5 analyses the results dataset by dataset, discusses the consequences for precision agriculture and states the limitations, and Section 6 concludes.

2 Related work

Counting and tracking fruit in video is commonly done by tracking-by-detection: a detector finds the fruit in every frame, a tracker links the detections into identities, and the identities are then counted. OrangeSORT builds on DeepSORT for citrus counting (Zhang et al, 2022), Wang et al (2019) pair a mango detector with a Kalman filter and Hungarian assignment, and Osman et al (2021) estimate apple yield from video with a modified DeepSORT. Public datasets with per-object identity annotations now allow tracking itself to be evaluated, not only the final count: LettuceMOTS (Hu et al, 2024), MOrangeT (Santos et al, 2024), GrapeMOTS (Ariza-Sentís et al, 2024) and AppleMOTS (de Jong et al, 2022). Trackers built on promptable segmentation foundation models have also recently appeared, such as SAM2MOT (Jiang et al, 2026), which places segmentation at the centre of tracking and runs zero-shot.

Position has also been used as a cue for stationary produce. Liu et al (2019) combine monocular structure-from-motion with semantic data association to map fruit in 3D, though only to count them, without evaluating tracking, and LocalizeSORT (Vemuru et al, 2024), a preprint, adds a world-coordinate term to the association cost.

The trackers that this work builds on and compares with form one lineage. SORT (Bewley et al, 2016) predicts each track with a Kalman filter and assigns detections to tracks by the Hungarian method on box overlap, and DeepSORT (Wojke et al, 2017) adds a learned appearance embedding to the association cost. StrongSORT (Du et al, 2023) revisits DeepSORT with a stronger appearance model, camera-motion compensation by image alignment and an adaptive Kalman filter. Deep OC-SORT (Maggiolino et al, 2023) adds observation-centric motion estimation, camera-motion compensation by sparse optical flow and adaptively weighted appearance. BoT-SORT (Aharon et al, 2022) fuses motion and appearance




Fig. 2 MapSORT. A scene map is reconstructed once per sequence by structure-from-motion. At each frame, every detection gets an appearance embedding and a landmark observation read from the map points it encloses. BoT-SORT's association runs first (1). Its matches, with the tracks' fused landmarks, yield the frame's camera (2), which places every stationary track in the image: tracks still unmatched are re-matched where it places them (3), and lost and dormant tracks are revived where their landmarks project (4). A confirmed track lost for longer than $A_{\max}$ frames becomes dormant instead of being deleted, so a returning object reclaims its identity.

costs after camera-motion compensation, and is the base tracker of MapSORT (Section 3). Despite their differences, all of them associate detections with tracks over a local window of recent frames, and all delete a track once it has been lost for a fixed number of frames.

3 Materials and methods

3.1 Problem formulation

The input is a monocular RGB video $\{I_1, \ldots, I_T\}$ captured by a moving camera, with no depth, odometry or positioning sensor, and at each frame t a set of detections $D_t = \{d_t^1, \ldots, d_t^{n_t}\}$, each an axis-aligned box b_t^i with centre $\boldsymbol{c}_t^i$ and size s_t^i, the geometric mean of its width and height. The scene contains stationary objects. The task is to produce tracks $\mathcal{T} = \{\tau_1, \ldots, \tau_K\}$, $\tau_k = \{(t, d_t^i)\}$, such that each track corresponds to exactly one physical object and each object to exactly one track: identity must be preserved through occlusion, visual ambiguity and camera motion, including when the camera returns to an object after it has been out of view.

3.2 Overview

Fig. 2 shows the MapSORT pipeline. A scene map is reconstructed once per sequence by SfM (Sect. 3.3), and every detection receives a landmark observation read from it (Sect. 3.4). Tracks fuse their observations into a landmark (Sect. 3.5). At every frame, BoT-SORT's own association runs first. The pairs it matches, with the tracks' landmarks, yield the frame's camera (Sect. 3.6). The camera then drives two further stages: tracks left unmatched are tried again where it places them, and lost and dormant tracks are revived where their landmarks project (Sect. 3.7). Tracks that leave the view are kept dormant rather than deleted (Sect. 3.8). Algorithm 1 summarises one frame.

3.3 Scene map from structure-from-motion

The scene map is a sparse SfM reconstruction of the sequence computed with COLMAP (Schönberger and Frahm, 2016). SIFT features (Lowe, 2004) are extracted at full resolution, because the finest scale-space octaves carry the small objects, fruit and bunches, from which landmarks are read. All frames share one camera with a radial distortion model. Matching is exhaustive rather than sequential, so that frames from a revisit are matched directly to frames from the first pass and the two passes share 3D points; this is what places a returning object at the same map position. The two 1080p GrapeMOTS sequences, which have no revisits and up to 927 frames, are instead matched sequentially, each frame against its 30 neighbours. Incremental mapping with bundle adjustment then yields a point cloud and, for every registered frame, the 2D keypoints that observe each 3D point. The frames carry no camera metadata. One sequence per camera is therefore mapped with free intrinsics; where that fragments the model, it is mapped again with the focal length of its largest fragment held fixed. The resulting camera is held fixed while the other sequences from the same camera are mapped, and refined in a final bundle adjustment.

The largest reconstructed model is kept. MOrangeT ships a COLMAP model of every sequence with all frames registered (Santos et al, 2024), which is used as it is. The frame of reference and scale of a model are arbitrary; MapSORT never needs metric scale.

3.4 Landmark observations

For detection d_t^i with box b_t^i, let $\mathcal{P}_t^i = \{\boldsymbol{X}_j\}_{j=1}^n$ be the 3D points whose keypoints in frame t fall inside b_t^i. Landmark filters remove points that belong to the background rather than the object or are poorly triangulated. A mask filter keeps only points whose keypoint falls on the detection's instance mask, with erosion to reduce background contamination at the mask boundary; when no point falls on the mask, the points in the box are kept. A track-length filter keeps points observed in at least $\ell_{\min}$ frames. A depth filter drops points more than k median absolute deviations deeper than the median camera-frame depth of the box's points, which removes background seen through gaps in the canopy. The landmark observation $z_t^i = (\boldsymbol{\mu}_t^i, \boldsymbol{\Sigma}_t^i, \boldsymbol{S}_t^i)$ is

$$\boldsymbol{\mu}_t^i = \operatorname{median}(\mathcal{P}_t^i), \tag{1}$$

$$\boldsymbol{S}_t^i = \operatorname{Cov}(\mathcal{P}_t^i) + r^2\boldsymbol{I}, \qquad r = \tfrac{1}{4}\,\|b_t^i\|\,\bar{z}/f, \tag{2}$$

$$\boldsymbol{\Sigma}_t^i = \boldsymbol{S}_t^i/n, \tag{3}$$

where the median is taken per coordinate, $\|b_t^i\|$ is the box diagonal in pixels, $\bar{z}$ the median camera-frame depth of the points and f the focal length. The extent $\boldsymbol{S}_t^i$ is the object's physical spread in the map frame; the isotropic floor $r^2\boldsymbol{I}$, the object's apparent radius back-projected to its depth, keeps it well conditioned when only a few points survive. The covariance $\boldsymbol{\Sigma}_t^i$ is a nominal uncertainty about where the object's *centre* lies: it shrinks as more points support the estimate and scales with the reconstruction, but it is not the sampling covariance of the per-coordinate median, which is larger and differently shaped. Only $\boldsymbol{\Sigma}_t^i$ is fused across observations; the extent is a property of the plant or fruit and does not shrink however often the object is observed. A detection whose box encloses no usable point carries no landmark, $z_t^i = \varnothing$, and takes part only in BoT-SORT's association.

3.5 Landmark fusion

Each track k maintains its landmark in information form, accumulating the precision-weighted observations assigned to it:

$$\boldsymbol{\Lambda}_k = \sum_{(t,i)\in\tau_k} \left(\boldsymbol{\Sigma}_t^i\right)^{-1}, \qquad \boldsymbol{\eta}_k = \sum_{(t,i)\in\tau_k} \left(\boldsymbol{\Sigma}_t^i\right)^{-1}\boldsymbol{\mu}_t^i, \qquad \hat{\boldsymbol{\Sigma}}_k = \boldsymbol{\Lambda}_k^{-1}, \quad \hat{\boldsymbol{\mu}}_k = \boldsymbol{\Lambda}_k^{-1}\boldsymbol{\eta}_k. \tag{4}$$

This is the static-state information filter (Thrun et al, 2005): because the object does not move, there is no process noise. Observations of one object share map points of the same reconstruction, so they are not independent, and $\hat{\boldsymbol{\Sigma}}_k$ understates the uncertainty of $\hat{\boldsymbol{\mu}}_k$. The fused mean, a precision-weighted average of the observations, is not biased by this correlation. Where MapSORT compares landmarks in 3D, it uses the squared Mahalanobis distance between an observation and a fused landmark under their combined uncertainty,

$$d_{ki}^2 = \left(\boldsymbol{\mu}_t^i - \hat{\boldsymbol{\mu}}_k\right)^\top \left(\hat{\boldsymbol{\Sigma}}_k + \boldsymbol{\Sigma}_t^i\right)^{-1} \left(\boldsymbol{\mu}_t^i - \hat{\boldsymbol{\mu}}_k\right), \tag{5}$$

and forbids pairs with $d_{ki}^2 > \tau$. The combined covariance never falls below that of the current observation, so the gate does not tighten without bound as a track grows. d_{ki}^2 is therefore a normalised distance rather than a χ^2 statistic, and τ is set empirically (Sect. 4.5).

Proposition 1. *d_{ki}^2 is invariant to the scale and translation of a monocular reconstruction.*

Proof. Under $\boldsymbol{X} \mapsto s\boldsymbol{X} + \boldsymbol{t}$, every per-coordinate median, sample covariance, depth and back-projected radius in Eqs. (1) to (3) transforms covariantly, so $\boldsymbol{\mu} \mapsto s\boldsymbol{\mu} + \boldsymbol{t}$ and $\boldsymbol{\Sigma} \mapsto s^2\boldsymbol{\Sigma}$; Eq. (4) preserves this. The difference in Eq. (5) scales by s and the inverse covariance by s^{-2}, which cancel. □

The per-coordinate median is not equivariant under rotation, so d_{ki}^2 is not invariant to the orientation of the reconstruction.

The gate τ is therefore a single dimensionless constant that transfers across sequences, crops and reconstructions, a property a fixed metric distance threshold lacks.

3.6 Camera resection from tracked landmarks

A landmark built from a few keypoints is uncertain mostly along the viewing rays that triangulated it, which is the direction separating a fruit from its neighbours behind or in front of it. Projected into the current image, that error largely disappears. MapSORT therefore compares landmarks in the image, through a camera $\boldsymbol{P}_t \in \mathbb{R}^{3\times4}$ fitted in every frame to the tracker's own state.

The correspondences are the pairs $(\hat{\boldsymbol{\mu}}_k, \boldsymbol{c}_t^i)$ of a track's fused landmark and a detection's box centre, taken from two sources: the track-detection pairs BoT-SORT has just matched (Sect. 3.7), and pairs of a track and a detection whose landmarks are mutual nearest neighbours under Eq. (5) within the gate τ. Errors are measured in box sizes, $e = \|\pi(\boldsymbol{P}_t\hat{\boldsymbol{\mu}}_k) - \boldsymbol{c}_t^i\|/s_t^i$ with π the perspective division, so one threshold serves small fruit and large plants alike. $\boldsymbol{P}_t$ is estimated by RANSAC (Fischler and Bolles, 1981), with the previous frame's camera competing against the random hypotheses and the winner refitted on its inliers for as long as that does not lose inliers. A camera is accepted when at least 8 correspondences agree with it to within half a box size.

Two camera models compete. The full projective camera is fitted by the direct linear transform from six correspondences (Hartley and Zisserman, 2004). It is ill-conditioned when the landmarks are close to coplanar, as on a field of lettuce seen from above, where any camera that agrees on the plane fits equally well. The second model fits the plane of the landmarks by principal component analysis and a homography $\boldsymbol{H}$ from plane coordinates to the image, from four correspondences, lifted to $\boldsymbol{P}_t = \boldsymbol{H}\boldsymbol{F}$ with $\boldsymbol{F}$ the projection onto the plane. The plane model is preferred unless the full camera explains at least a tenth more correspondences. When no camera is accepted, MapSORT falls back to the Mahalanobis gate (Sect. 3.7).

Each track also learns where its landmark projects within its box. When a track is matched under an accepted camera, the residual $\boldsymbol{r} = (\boldsymbol{c}_t^i - \pi(\boldsymbol{P}_t\hat{\boldsymbol{\mu}}_k))/s_t^i$ updates an exponential moving average $\boldsymbol{o}_k$ (rate 0.3) of this offset, and a second average ρ_k of $\|\boldsymbol{r} - \boldsymbol{o}_k\|$ measures how steadily the camera places the track. A track is *reliable* once it has two offsets and $\rho_k \leq 0.3$ box sizes. Its predicted box centre is $\pi(\boldsymbol{P}_t\hat{\boldsymbol{\mu}}_k) + s_k\boldsymbol{o}_k$, with s_k its size.

3.7 Association

Each frame runs three stages.

BoT-SORT association.

Tracks are predicted by BoT-SORT's Kalman filter after compensating global camera motion, and matched to detections on fused IoU and appearance costs (Aharon et al, 2022). These pairs, with the landmark pairs of Sect. 3.6, yield the camera $\boldsymbol{P}_t$.

Map motion.

Reliable tracks that the first stage left unmatched are moved to their predicted position under $\boldsymbol{P}_t$, and the same costs are solved again between them and the detections still unmatched. This recovers tracks whose image-plane motion the Kalman filter could not follow, without disturbing any pair the first stage made. A track still unmatched keeps BoT-SORT's prediction.

Revival.

Detections still unmatched are offered to lost tracks, those missed for at most $A_{\max}$ frames, and to dormant tracks (Sect. 3.8), before any new identity is issued. Each candidate's box is predicted at its projected position and its last size not cut by the frame edge, and clipped to the frame, as the detector would see it. The revival cost is the distance between the centres of the clipped prediction and the detection, in box sizes of the candidate, and the assignment is solved by the Hungarian method with a gate of one box size. Candidates must have two offsets, so that their projection has been checked against their box. An object re-entering the view shows only a sliver at the frame edge, and the clipped predictions of several candidates crowd together there. A detection touching the frame edge is therefore only revived by a candidate whose clipped box overlaps it with an IoU of at least 0.3 and is at least half inside the frame. A new track born on such a detection, where a candidate is expected, stays unconfirmed and unreported for up to 8 frames, until enough of the object is visible to revive it or the wait runs out. When no camera is accepted, lost tracks are revived on the Mahalanobis distance of their latest observation and dormant tracks on that of their fused landmark.

Detections that remain unmatched start tentative tracks, which BoT-SORT confirms on a second match. Every matched or revived track fuses the detection's landmark observation by Eq. (4).

Algorithm 1 MapSORT update at frame t

Require: detections D_t with embeddings f_t^i and landmark observations z_t^i (possibly $\varnothing$); active tracks $\mathcal{A}$ (tracked and lost); dormant pool $\mathcal{Z}$

Predict and motion-compensate every $k \in \mathcal{A}$; $(M_1, U_\mathcal{A}, U_D) \leftarrow$ BoT-SORT association
$\boldsymbol{P}_t \leftarrow$ RANSAC resection on M_1 and mutual-nearest landmark pairs within τ
if $\boldsymbol{P}_t$ accepted **then**
    $(M_2, U_\mathcal{A}, U_D) \leftarrow$ re-solve reliable $k \in U_\mathcal{A}$ at $\pi(\boldsymbol{P}_t \hat{\boldsymbol{\mu}}_k) + s_k \boldsymbol{o}_k$ against $i \in U_D$
    $(M_3, U_D) \leftarrow$ Hungarian on clipped reprojection error, lost $k \in U_\mathcal{A}$ and $k \in \mathcal{Z}$, $i \in U_D$, gate 1 box
else
    $(M_3, U_D) \leftarrow$ Hungarian on d^2_{ki}, lost $k \in U_\mathcal{A}$ and $k \in \mathcal{Z}$, $i \in U_D$
end if
for $(k, i) \in M_1 \cup M_2 \cup M_3$ **do**
    Update k with d_t^i (re-initialise if revived); fuse z_t^i into $(\boldsymbol{\Lambda}_k, \boldsymbol{\eta}_k)$
end for
Learn offsets $\boldsymbol{o}_k, \rho_k$ of matched tracks under $\boldsymbol{P}_t$
for every $i \in U_D$ **do**
    Match to a tentative track or start one; at the frame edge, near an expected revival, keep it unconfirmed
end for
Move confirmed tracks lost for more than $A_{\max}$ frames with a landmark from $\mathcal{A}$ to $\mathcal{Z}$

Table 1 Evaluation datasets. Frames, identities, boxes and revisit events are evaluation totals. A revisit event is a ground-truth object reappearing after at least 10 frames out of view.

Dataset	Crop	Platform, view	Seqs	Frames	Resolution	IDs	Boxes	Revisits
LettuceMOTS	Lettuce	Robot, nadir	3	712	810×1080	114	9 718	70
MOrangeT	Orange	Phone, lateral	10	3 695	≈1080×1920	1 003	102 409	950
GrapeMOTS	Grape	UAV, multi-view	4	1 761	≤3840×2160	196	25 093	23
AppleMOTS	Apple	UAV, wearable	4	626	1296×972	977	27 533	0


3.8 Dormant tracks and identity revival

A frame-to-frame tracker deletes a track after $A_{\max}$ frames without a match, because beyond that horizon its image-plane prediction is no longer informative. For a stationary object, the landmark remains informative indefinitely. MapSORT therefore moves a confirmed track whose landmark has been observed to a dormant pool when it exceeds $A_{\max}$, instead of deleting it. A dormant track keeps its identity, fused landmark and offset. When the revival stage matches it to a detection, its Kalman state is re-initialised from the detection box, since the image-plane motion before the absence says nothing about where the object reappears, and its identity and landmark carry over unchanged. The dormant pool is unbounded, so an object keeps its identity across absences of any length.

3.9 Datasets

MapSORT is evaluated on four publicly available agricultural MOT datasets (Table 1, Fig. 3). Together they cover four crops, four acquisition platforms and three viewing patterns: repeated passes along a row, multi-perspective inspection and continuous sweeps. Mask annotations are converted to axis-aligned boxes in MOT format. Per-sequence statistics are listed in Appendix A.

LettuceMOTS (Hu et al, 2024) was recorded by a downward-facing camera on a field robot over lettuce at three growth stages. The robot travels back and forth along the rows, so every plant is seen twice, with long absences in between.
MOrangeT (Santos et al, 2024) consists of smartphone videos, each sweeping one side of a sweet-orange tree in a commercial grove; the same fruit leaves and re-enters the field of view several times as the camera moves around the canopy.
GrapeMOTS (Ariza-Sentís et al, 2024) was recorded by a UAV over a vineyard. Its path-planned videos view the canopy from multiple perspectives to reduce leaf occlusion.
AppleMOTS (de Jong et al, 2022) contains UAV and wearable-camera video of apple trees with dense clusters of small, similar fruit. AppleMOTS sequences are continuous sweeps without revisits, and test MapSORT in short-term association among dense, near-identical fruit.



(a) (b) (c)

(d)

Fig. 3 Sample frames: (a) LettuceMOTS 0011, (b) MOrangeT V01, (c) GrapeMOTS PathPlanning_7 and (d) AppleMOTS 0008, with their ground-truth boxes.

3.10 Detections

Every tracker receives the same detections: the annotated boxes of each sequence, with their identities removed, and on the three MOTS datasets their instance masks, which the landmark filter of Sect. 3.4 uses. Each frame's detections are therefore identical across trackers, and every difference between them arises in association and track management, the stages MapSORT changes.

3.11 Baselines

MapSORT is compared with three trackers that represent the main current approaches to tracking-by-detection. StrongSORT (Du et al, 2023) associates on appearance first, through a matching cascade over per-track feature galleries gated by Kalman motion, and compensates camera motion with ECC image alignment. Deep OC-SORT (Maggiolino et al, 2023) extends observation-centric motion with sparse optical-flow camera-motion compensation and adaptively weighted appearance. BoT-SORT (Aharon et al, 2022) fuses motion and appearance costs after camera-motion compensation. All three are run from Box-MOT (Broström, 2024) with their default configurations and with the same detections as MapSORT. The appearance-based trackers, MapSORT included, share one re-identification model per dataset: OSNet-x0.25 (Zhou et al, 2019), initialised from MSMT17 and fine-tuned on ground-truth object identities from sequences outside the test data: AppleMOTS 0000 to 0004, GrapeMOTS PathPlanning_4 to _6, LettuceMOTS 0000, 0004 and 0008, and MOrangeT V03. One further sequence per dataset (AppleMOTS 0005, GrapeMOTS PathPlanning_8, LettuceMOTS 0009, MOrangeT V04) selects the training epoch. Each dataset contributes at most 200 identities with up to 10 crops each, spread evenly along each track, and the model is trained for 10 epochs with label-smoothed cross-entropy and a batch-hard triplet loss. BoT-SORT is also MapSORT's base tracker and shares all of its settings, so comparing the two isolates the effect of the camera and landmark stages.

3.12 Evaluation metrics

Tracking accuracy is measured with HOTA and its detection and association components DetA and AssA (Luiten et al, 2021), MOTA and identity switches (IDSW) from the CLEAR metrics (Bernardin and

Stiefelhagen, 2008), and IDF1 (Ristani et al, 2016), all computed with TrackEval (Luiten and Hoffhues, 2020) at an IoU threshold of 0.5 for CLEAR and Identity. Two further metrics address the requirements of agricultural use.

Count error.

Yield estimation from video counts tracks. The count error

$$\mathrm{CE} = 100 \cdot \frac{|\mathrm{IDs}_{\mathrm{pred}}| - |\mathrm{IDs}_{\mathrm{GT}}|}{|\mathrm{IDs}_{\mathrm{GT}}|} \tag{6}$$

is the relative over-count (positive) or under-count (negative) of distinct identities; every identity switch that issues a new identity adds to it.

Revisit identity preservation.

A revisit event is a ground-truth object that reappears after at least $G = 10$ consecutive frames out of view. At each event, the object's tracker identity is read, using exactly the per-frame assignment that CLEAR makes, at the first frame within a grace window of $W = 5$ frames in which it is matched; the grace window allows for track confirmation after reappearance. The event is *preserved* if that identity equals the one the object carried before the absence, a *switch* if it differs, and *unmatched* if the object is not matched within the window. The revisit identity preservation rate is

$$\mathrm{RIP} = 100 \cdot \frac{\#\mathrm{preserved}}{\#\mathrm{preserved} + \#\mathrm{switch}}. \tag{7}$$

Because the per-frame assignment is CLEAR's own, every revisit switch is one of CLEAR's IDSW, so RIP measures the share of the hardest identity decisions, those after an absence, that a tracker gets right. Revisit outcomes are also reported as a function of absence length (Sect. 4.3).

3.13 Implementation details

Table 2 lists MapSORT's settings. BoT-SORT's own stages use its BoxMOT defaults unchanged. Experiments ran on a laptop with an Intel Core i9-14900HX CPU and an NVIDIA GeForce RTX 4070 Laptop GPU (8 GB). Scene maps were built, and the throughput of Sect. 4.6 measured, on a CPU-only workstation with an Intel Xeon E3-1240 v5 CPU (4 cores, 8 threads, 3.5 GHz).

4 Results

4.1 Comparison with state-of-the-art trackers

Table 3 compares MapSORT with the three baselines on all four datasets. MapSORT achieves the highest HOTA, AssA, MOTA, IDF1 and RIP and the fewest identity switches on every dataset. The gains concentrate in association: DetA, which reflects localisation, is within one point of BoT-SORT's on every dataset, while AssA rises by 18.0 points on average over BoT-SORT, from 31.4 and 36.3 points on LettuceMOTS and MOrangeT to 3.4 and 0.7 points on GrapeMOTS and AppleMOTS. Pooled over the 1043 revisit events of the test data, MapSORT preserves identity in 91.9% of them, against 11.5% for StrongSORT, 9.1% for BoT-SORT and 7.8% for Deep OC-SORT. Identity switches fall from 1157 for BoT-SORT, 1150 for Deep OC-SORT and 2014 for StrongSORT to 223, and the mean absolute count error over the four datasets from 44.9% for the best baseline, Deep OC-SORT, to 5.9%, which translates directly into more accurate yield estimates. Among the baselines, BoT-SORT has the highest HOTA on every dataset. StrongSORT and Deep OC-SORT have lower DetA, 90.9 and 93.2 on average against 97.0 for BoT-SORT, because at their default settings a new track is reported only after three consecutive matches, which costs the first frames of every object; this weighs most on AppleMOTS, whose short sequences are dense with briefly visible fruit.

Table B2 in Appendix B reports every test sequence. MapSORT has fewer identity switches than every baseline on 19 of the 21 sequences, and as few as BoT-SORT on the other two: GrapeMOTS PathPlanning_1, where neither makes any, and AppleMOTS 0008, where both make one and Deep OC-SORT none. Its HOTA is the highest of all trackers on 18 sequences, equal to BoT-SORT's on PathPlanning_1, and below the best baseline's on two, GrapeMOTS PathPlanning_3 and AppleMOTS 0007, which Sect. 5 examines.

Table 2 MapSORT settings. Box sizes are geometric means of box width and height.

Component	Parameter	Value
Detection	Detections	Annotated boxes, identities removed; instance masks on MOTS datasets
Scene map	SfM	COLMAP 3.9.1, shared RADIAL camera; MOrangeT: models shipped with the dataset
	Features	SIFT, $\leq$16 384 per frame, max. side 3840 px
	Matching	Exhaustive; sequential, 30 neighbours, on GrapeMOTS PathPlanning_1 and _3
Landmark filters	Mask	Instance-mask support with boundary erosion
	Track length	Minimum number of observing frames $\ell_{\min}$
	Depth	Median absolute deviation threshold k
BoT-SORT	Re-ID model	OSNet-x0.25, fine-tuned per dataset
	Appearance, proximity thresholds	0.62, 0.61
	First-stage match threshold	0.77
	New-track threshold	0.62
	Lost-track buffer $A_{\max}$	40 frames at 30 fps
Landmarks	Mahalanobis gate τ	200
	Gate for a lost track's latest observation	10
Camera	RANSAC iterations, inlier, min. inliers	300, 0.5 box size, 8
	Plane preferred unless full camera explains more by	10%
Map motion	Offset average rate, min. offsets	0.3, 2
	Reliable residual ρ_k	$\leq$0.3 box size
Revival	Reprojection gate	1.0 box size
	Edge detections: IoU, visible share, wait	0.3, 0.5, 8 frames
	Dormant pool size	Unbounded
Evaluation	IoU threshold	0.5
	Revisit gap G, grace W	10, 5 frames
	Toolkit	TrackEval 1.3.0

Table 3 Tracking results. CE: count error (%). RIP: revisit identity preservation rate (%); AppleMOTS has no revisit events. Best per dataset in bold.

Dataset	Tracker	HOTA↑	AssA↑	DetA↑	MOTA↑	IDF1↑	IDSW↓	CE↓	RIP↑
LettuceMOTS	BoT-SORT	77.80	63.15	**95.83**	95.03	64.93	78	+67.5	1.4
	StrongSORT	70.16	53.25	92.45	90.76	57.74	164	+111.4	2.9
	Deep OC-SORT	77.34	64.50	92.74	92.07	67.46	65	+56.1	6.6
	MapSORT	**95.09**	**94.51**	95.67	**95.62**	**96.53**	**5**	**+3.5**	**97.1**
MOrangeT	BoT-SORT	76.99	60.31	98.27	97.43	66.92	863	+84.6	9.9
	StrongSORT	75.74	59.66	96.14	95.24	66.98	933	+83.8	12.4
	Deep OC-SORT	74.63	59.06	94.32	93.52	66.43	829	+82.3	8.0
	MapSORT	**97.86**	**96.66**	**99.07**	**99.00**	**97.82**	**90**	**+6.0**	**91.8**
GrapeMOTS	BoT-SORT	92.38	86.29	98.90	98.61	89.99	82	+30.1	0.0
	StrongSORT	87.03	78.31	96.72	95.77	84.12	255	+69.4	0.0
	Deep OC-SORT	90.90	85.25	96.92	96.52	88.97	103	+36.7	4.3
	MapSORT	**94.41**	**89.69**	**99.39**	**99.27**	**93.69**	**42**	**-9.2**	**78.3**
AppleMOTS	BoT-SORT	94.06	92.95	95.17	94.68	95.27	134	**+2.0**	n/a
	StrongSORT	78.29	78.30	78.27	75.87	79.15	662	+10.3	n/a
	Deep OC-SORT	88.62	88.26	88.98	88.42	91.88	153	+4.5	n/a
	MapSORT	**94.73**	**93.67**	**95.80**	**95.49**	**95.84**	**86**	-4.8	n/a

4.2 Representative sequences

One representative sequence per dataset is used for the detailed analyses that follow: LettuceMOTS 0011, MOrangeT V01, GrapeMOTS PathPlanning_7 and AppleMOTS 0008. Table 4 reports all trackers on these sequences.

On LettuceMOTS 0011 the robot drives out along two rows and returns, so each of the 37 plants is seen twice. BoT-SORT gives every returning plant a new identity, preserving none of the 22 revisits, and over-counts the plants by 64.9%; StrongSORT also preserves none, and Deep OC-SORT 5.9%. MapSORT preserves 95.0% of the revisits with two identity switches in the whole sequence, raising HOTA from 77.9 to 93.3 and IDF1 from 64.9 to 93.7 (Fig. 1).

On MOrangeT V01, a handheld sweep around an orange tree with 104 revisit events, MapSORT raises HOTA from 74.4 to 97.1 and IDF1 from 64.0 to 97.1, cuts identity switches from 105 to 15, and preserves identity in 90.3% of revisits, against 10.0% for BoT-SORT, the most of any baseline. The count error falls from +93.6% to +8.2%. This holds although the oranges' landmarks rest on few points (a median

Table 4 Results on the representative sequences. Columns as in Table 3. AppleMOTS 0008 has no revisit events.

Sequence	Tracker	HOTA↑	AssA↑	DetA↑	MOTA↑	IDF1↑	IDSW↓	CE↓	RIP↑
LettuceMOTS 0011	BoT-SORT	77.88	63.23	**95.93**	95.15	64.91	24	+64.9	0.0
	StrongSORT	76.33	62.17	93.72	92.97	64.03	23	+62.2	0.0
	Deep OC-SORT	77.49	64.93	92.48	91.83	68.03	20	+54.1	5.9
	MapSORT	**93.34**	**91.48**	95.25	**95.18**	**93.67**	**2**	**+5.4**	**95.0**
MOrangeT V01	BoT-SORT	74.39	56.94	97.18	95.85	64.03	105	+93.6	10.0
	StrongSORT	70.32	53.02	93.27	91.60	61.47	131	+109.1	9.6
	Deep OC-SORT	69.40	53.36	90.25	88.97	62.05	101	+91.8	5.8
	MapSORT	**97.07**	**95.75**	**98.42**	**98.23**	**97.08**	**15**	**+8.2**	**90.3**
GrapeMOTS PathPlanning_7	BoT-SORT	89.60	80.92	99.21	98.86	85.48	34	+43.1	0.0
	StrongSORT	77.59	62.56	96.23	94.94	71.78	123	+127.7	0.0
	Deep OC-SORT	90.07	83.02	97.71	97.30	86.71	37	+50.8	4.3
	MapSORT	**96.73**	**93.89**	**99.66**	**99.59**	**96.35**	**10**	**0.0**	**78.3**
AppleMOTS 0008	BoT-SORT	98.79	98.80	98.78	98.77	99.37	1	**0.0**	n/a
	StrongSORT	96.76	96.73	96.80	96.77	98.29	3	-0.6	n/a
	Deep OC-SORT	96.63	96.78	96.49	96.49	98.21	**0**	-1.8	n/a
	MapSORT	**98.81**	**98.82**	**98.79**	**98.79**	**99.38**	1	**0.0**	n/a




Fig. 4 Revisit identity preservation by length of absence, over the 1043 revisit events of the test sequences. The baselines delete tracks lost for longer than their track buffer and preserve almost no identity beyond that horizon; MapSORT's dormant tracks keep identities recoverable at every absence length.

of two per detection, Table 6): the camera is fitted to many landmarks at once, so a poorly supported landmark still projects close to its object.

On GrapeMOTS PathPlanning_7, where the UAV views the vines from several perspectives, MapSORT raises HOTA from 89.6 to 96.7 and IDF1 from 85.5 to 96.4, cuts identity switches from 34 to 10, and brings the count error from +43.1% to 0.0%. BoT-SORT and StrongSORT preserve none of the 23 revisits and Deep OC-SORT one; MapSORT preserves 78.3% of them. On AppleMOTS 0008, which has no revisits and on which BoT-SORT already makes a single identity switch, MapSORT matches it (HOTA 98.81 against 98.79, one switch each); Deep OC-SORT makes none there, at 96.63 HOTA.

4.3 Identity persistence across revisits

Fig. 4 breaks revisit outcomes down by how long the object was out of view. The baselines preserve identity only for short absences: 57.7% (BoT-SORT), 74.8% (StrongSORT) and 61.7% (Deep OC-SORT) of events with a gap below 30 frames, and at most 3.0% beyond, because a track lost for longer than its buffer is deleted. MapSORT preserves between 85.6% and 93.8% of events in every bin, and its rate does not fall with the length of the absence: it is 93.8% for absences of 120 frames or more. This is the behaviour Sect. 3.8 is designed to produce: the landmark of a stationary object does not age, so a dormant track is as recoverable after a long absence as after a short one.

4.4 Ablation study

Table 5 adds MapSORT's components one at a time to BoT-SORT (a). Keeping lost tracks dormant and reviving them by the Mahalanobis gate on their 3D landmarks (b) raises pooled revisit preservation from 6.9% to 67.3%. Its effect depends on how well the landmarks are supported. On LettuceMOTS 0011,

Table 5 Ablation on the representative sequences (HOTA / IDF1). RIP is pooled over the revisit events of the four sequences (AppleMOTS 0008 has none). (e) uses the nearest SfM keypoint to the box centre as a point landmark with a Euclidean distance gate.

	Lettuce 0011		Orange V01		Grape PP_7		Apple 0008		
Variant	HOTA	IDF1	HOTA	IDF1	HOTA	IDF1	HOTA	IDF1	RIP
(a) BoT-SORT	77.88	64.91	74.39	64.03	89.60	85.48	98.79	99.37	6.9
(b) + landmark revival	**97.00**	**98.46**	92.18	89.57	93.42	92.39	**98.81**	**99.38**	67.3
(c) + camera revival	91.42	90.71	96.14	95.78	**97.41**	**97.51**	**98.81**	**99.38**	85.1
(d) + map motion (MapSORT)	93.34	93.67	97.07	97.08	96.73	96.35	**98.81**	**99.38**	**89.0**
(e) (d), point landmark	94.05	95.21	**97.10**	**97.09**	97.19	97.36	**98.81**	**99.38**	86.9




Fig. 5 Sensitivity of HOTA (left) and revisit identity preservation (right) to the landmark gate τ on the representative sequences. The dashed line marks the χ^2_3 95% quantile. AppleMOTS 0008 has no revisit events and appears only on the left.

whose landmarks rest on a median of 79 map points, the 3D gate alone reaches the best HOTA of all variants, 97.0. On MOrangeT V01, with two points per landmark, it reaches 92.2, and on GrapeMOTS PathPlanning_7 93.4. Reviving through the per-frame camera instead (c) raises pooled preservation to 85.1%, and HOTA to 96.1 on V01 and 97.4 on PathPlanning_7, because projection removes the depth error that lets adjacent fruit pass a 3D gate; on the planar lettuce scene it is 5.6 points below the 3D gate. Map motion, with the learned offsets that revival then also requires of its candidates (d), raises pooled preservation to 89.0% and HOTA to 93.3 on lettuce and 97.1 on V01, at a cost of 0.7 HOTA on PathPlanning_7. On AppleMOTS 0008 every variant stays within 0.02 HOTA of BoT-SORT. Replacing the Gaussian landmark by the nearest triangulated keypoint to the box centre with a Euclidean gate (e), the point-estimate localisation of prior fruit-tracking work, changes HOTA by less than one point on every sequence and lowers pooled preservation to 86.9%: once association runs through the camera, the landmark mostly needs to be a good point, and its covariance matters where the 3D gate is used.

4.5 Sensitivity to the landmark gate

Fig. 5 sweeps the landmark gate τ over two orders of magnitude, from the 95% quantile of the χ^2_3 distribution (7.81) to 1600. In MapSORT, τ gates the landmark pairs that help seed the camera fit and the revival of tracks in frames without a camera. HOTA varies by less than 0.1 points on LettuceMOTS 0011, MOrangeT V01 and AppleMOTS 0008 and revisit preservation not at all. On GrapeMOTS PathPlanning_7, where the camera depends most on the landmark pairs, preservation is 65.2% for $\tau \leq 25$, 73.9% at 50 and 78.3% from 100 upwards. The default $\tau = 200$ lies on that plateau, well above the χ^2_3 quantile, as expected when the fused covariances understate the uncertainty of correlated observations (Sect. 3.5). A single value serves all datasets, as Proposition 1 predicts.

4.6 Scene maps and runtime

Every frame of every representative sequence is registered into a single model (Table 6), with mean reprojection errors between 0.7 and 1.2 pixels. Building a map on the CPU-only workstation takes 49 minutes for LettuceMOTS 0011, 183 minutes for AppleMOTS 0008 and 352 minutes for the 4K frames of GrapeMOTS PathPlanning_7, of which exhaustive matching takes 69% to 79%. Most detections receive a landmark: 96.7% on LettuceMOTS, 97.9% on AppleMOTS, 93.3% on GrapeMOTS and 76.9% on MOrangeT, where small, glossy fruit seen against foliage yield fewer stable keypoints. Fig. 6 shows the

Table 6 Scene maps on the representative sequences. Track len.: mean number of frames observing a 3D point. Cov.: share of detections that receive a landmark. Pts/LM: median number of map points inside a detection with a landmark. SfM: wall-clock time of feature extraction, matching, mapping and the final bundle adjustment on the CPU-only workstation of Sect. 3.13; the MOrangeT model ships with the dataset.

Sequence	Reg. frames	3D points	Track len.	Reproj. (px)	Cov. (%)	Pts/LM	SfM (min)
LettuceMOTS 0011	223/223	33 766	22.7	0.98	96.7	79	49
MOrangeT V01	408/408	69 081	10.0	1.15	76.9	2	n/a
GrapeMOTS PP_7	225/225	129 210	19.1	0.95	93.3	13	352
AppleMOTS 0008	322/322	116 013	15.8	0.71	97.9	5	183




Fig. 6 Sparse scene map of LettuceMOTS 0011, viewed from above. Plant points are green, soil grey; the line is the reconstructed camera path. The outbound and return passes are registered into one map, so each plant has one position on both.

Table 7 Tracking throughput (frames per second, including image decoding and appearance embedding; excluding map construction), on the CPU-only workstation of Sect. 3.13 (W).


Sequence	Hardware	BoT-SORT	StrongSORT	Deep OC-SORT	MapSORT
LettuceMOTS 0011	W	5.36	3.26	5.36	1.53
MOrangeT V01	W	3.84	2.66	3.82	1.37
GrapeMOTS PP_7	W	1.47	1.18	1.47	0.83
AppleMOTS 0008	W	2.56	1.93	2.50	1.09

reconstruction of LettuceMOTS 0011: the two rows of plants and the camera path along them, with the outbound and return passes registered into the same map.

Table 7 reports tracking throughput on the CPU-only workstation. MapSORT runs at 29% to 56% of BoT-SORT's throughput and at 47% to 70% of StrongSORT's, the slowest baseline; Deep OC-SORT runs within 3% of BoT-SORT. Most of the difference is the camera fit, two RANSAC estimates per frame, each with both camera models; landmark fusion operates on 3×3 matrices and costs little. The scene map is built once per sequence, before tracking.

4.7 Qualitative results

Fig. 1 compares BoT-SORT and MapSORT on the return pass of LettuceMOTS 0011. By this frame BoT-SORT has issued 56 identities for 37 plants: every plant on screen carries a new identity, assigned when it reappeared. MapSORT shows each plant with the identity it received on the outbound pass and has issued 39 identities. Fig. 7 shows the same comparison on MOrangeT V01, 232 frames into the handheld sweep, and on GrapeMOTS PathPlanning_7 at the end of the flight. Of the 20 oranges in view that have returned after at least 10 frames out of view, BoT-SORT still gives one its first identity and MapSORT all 20; of the 15 returning bunches, BoT-SORT gives none its first identity and MapSORT 12. By these frames BoT-SORT has issued 127 identities against MapSORT's 94 on V01, and 85 against 65 on PathPlanning_7, whose 65 bunches MapSORT counts exactly. AppleMOTS has no revisits to show in this way; Sect. 5 examines it, with the other datasets, through the whole of each sequence.



(a) (b)

Fig. 7 BoT-SORT and MapSORT on (a) MOrangeT V01, frame 232, and (b) GrapeMOTS PathPlanning_7, frame 221, cropped to the vine. Every box a tracker reports is drawn. The objects that have returned after at least 10 frames out of view are drawn thicker and tagged with their identity, numbered in order of first appearance; under MapSORT they keep their first identity, under BoT-SORT almost none does.

5 Discussion

The results show that, for stationary agricultural targets, a scene-map position is the identity cue that survives the conditions under which appearance and image-plane motion fail. The effect is largest exactly where agricultural tracking is hardest. When the camera returns to an object after a long absence, BoT-SORT's identity is lost by construction, and MapSORT recovers it at a rate that does not decay with the length of the absence (Fig. 4). Fig. 8 shows the same thing object by object on the four representative sequences: each row is a ground-truth object, coloured by whether the tracker still gives it the identity it first received. The datasets exercise the cue in different ways, and the camera that turns it into a prediction behaves differently on each.

The per-frame camera.

Everything MapSORT adds rests on the camera fitted in each frame, and that camera is almost always available: one is accepted in 99.0% to 99.8% of the frames of each representative sequence and of AppleMOTS 0007. The tracks matched in a frame agree with its camera to a median of 0.03 to 0.06 box sizes, with 90th percentiles of 0.12 to 0.17, once their learned offset is added. The landmark projection alone leaves median errors of 0.08 to 0.17 box sizes: a landmark is the median of the map points in its box, not the box centre, and the offset, which learns where in the box it sits, cuts the error by a factor of about three. These errors are small against the spacing of the objects, a median of 0.95 to 3.4 box sizes to the nearest neighbour, which is why a revival gate of one box size rarely admits the wrong object. Fig. 9 shows where the camera places the lost and dormant tracks in one frame of each sequence, including those outside the view.

Repeated passes over a row.

LettuceMOTS is the operating pattern of a field robot working a row and returning, and the clearest case for the cue: on all three sequences MapSORT preserves at least 95% of the returns, with 0, 3 and 2 identity switches against BoT-SORT's 28, 26 and 24, where no baseline makes fewer than 20, and it counts the 40 plants of 0003 exactly. On the return pass of 0011 BoT-SORT gives every plant a new identity; MapSORT changes the identity of two (Fig. 8). Two parts of the method matter here. The field is close to a plane, on which a full projective camera is ill-conditioned; fitting the plane's homography instead keeps the camera stable. And a returning plant enters the image at its edge, where the detector sees only a sliver of it for the first frames. The camera places the plants of the outbound pass beyond that




Fig. 8 Identity timelines on the representative sequences. Each row is a ground-truth object, ordered by first appearance, and each column a frame. Blue: the object carries the first identity the tracker gave it; red: a later one; grey: in view but not tracked; white: out of view. Panel titles give the number of identities issued and of objects. BoT-SORT gives the plants of the LettuceMOTS return pass, and many returning oranges and bunches, new identities; MapSORT keeps their first. AppleMOTS 0008 has no revisits, and the two trackers coincide.

edge before the robot reaches them (Fig. 9a); comparing clipped predictions and holding a new track at the edge until the plant can be revived is what lets it reclaim its identity before a new one is issued. The ablation also shows that the dense map support of a lettuce field makes the 3D landmark gate alone very effective there, more than the camera-based revival; MapSORT uses the 3D gate only as a fallback, in favour of a single configuration that also serves the sparse orange landmarks.

Sweeps around a canopy.

MOrangeT is the largest and most revisit-heavy dataset, with 950 revisits over ten sequences. A handheld sweep moves the camera close to a three-dimensional canopy, so image-plane motion is dominated by parallax that a global camera-motion warp cannot follow, and fruit go out of view behind leaves and the trunk for hundreds of frames. MapSORT preserves 91.8% of these revisits and has fewer identity switches than every baseline on every sequence, 90 in total against 829 for the best baseline, Deep OC-SORT. On V01, BoT-SORT issues 213 identities for 110 oranges and MapSORT 119 (Fig. 8). Its landmarks there rest on a median of two map points, so a 3D comparison is unreliable. Projected through a camera fitted to many landmarks at once, they place the matched oranges to a median of 0.05 box sizes, while neighbouring oranges are a median of 3.4 box sizes apart. Fruit that leave the view at one edge as the phone sweeps on are placed just beyond it until the sweep brings them back (Fig. 9b).

Multi-perspective UAV inspection.

On GrapeMOTS the landmarks of the bunches along a vine lie close to a line, which constrains the camera poorly across it. MapSORT still preserves 78.3% of the revisits of PathPlanning_7, of which the best baseline preserves 4.3%, counts its 65 bunches exactly, and makes no more identity switches than any baseline on every sequence. The camera places the bunches along the vine, including those not detected in the frame (Fig. 9c). On PathPlanning_3, however, its HOTA and IDF1 are below those of all three baselines, and Fig. 10a shows why. A large bunch and three small ones are tracked from the start of the sequence until a fast, motion-blurred pan takes them out of view at frames 88 to 94; they return at frames 156 to 179. The ground truth gives the four bunches new identities, 20 to 23, so the sequence contains





Fig. 9 Where the per-frame camera places the stationary tracks: (a) LettuceMOTS 0011, frame 150, on the return pass; (b) MOrangeT V01, frame 307; (c) GrapeMOTS PathPlanning_7, frame 214; (d) AppleMOTS 0008, frame 150. Black: the boxes of the tracks matched in the frame. Coloured: the predicted boxes of lost and dormant tracks, their landmark's projection plus the learned offset at their last full size; green where the track is matched again within the next 8 frames, orange otherwise. Grey: outside the image. (b) shows a window around the right edge of the frame, and (d) the frame and the area to its right, where the fruit the sweep has passed are placed.


no revisit events, while MapSORT gives them back the identities they had. In ground-truth terms each such link merges two objects, which the identity metrics penalise without counting an identity switch. Annotation policies for when an object seen again counts as the same object are not uniform across datasets, and a tracker built to recover identity across absences is, by design, at odds with a policy that resets it.

Dense fruit without revisits.

AppleMOTS has no revisits, and its fruit are small, numerous and alike, so it tests whether the extra stages hurt short-term association. They do not: MapSORT has the highest HOTA on three of four sequences, and fewer identity switches than every baseline on three. Without revisits, the camera only places the apples the sweep has passed beyond the edge of the view (Fig. 9d), where their tracks stay dormant; 111 of the 164 tracks of 0008 end the sequence in the dormant pool. On AppleMOTS 0007 MapSORT is 0.3 HOTA below BoT-SORT although it makes fewer identity switches, 6 against 8. The difference lies in tracks carried onto a different apple: a track whose apple disappears behind foliage is later matched to another apple nearby, which the identity metrics penalise without counting a switch. MapSORT does this 16 times on 0007 and BoT-SORT 11 times, in both cases after absences of 1 to 31 frames, within the lost-track buffer. 0007 is where the camera is least precise: the matched apples agree with it to a median of 0.11 box sizes and a 90th percentile of 0.67, against at most 0.17 on the representative sequences, while neighbouring apples are a median of 1.3 box sizes apart. Seven of the 16 transfers land within one box size of where the camera places the lost track, and appearance does not separate the apples. Fig. 10b shows one, after 21 frames, onto an apple 0.25 box sizes from the prediction. The single identity switch on AppleMOTS 0008, which BoT-SORT also makes, is an apple seen in two frames, out of view for four and then seen again. Its first track never received a landmark, so the camera cannot place it, and BoT-SORT's motion model does not recover it; Deep OC-SORT avoids it, at 2.2 points lower HOTA.



(a)



(b)

Fig. 10 Where MapSORT scores below BoT-SORT. (a) GrapeMOTS PathPlanning_3: four bunches before and after a motion-blurred pan. The ground truth gives them new identities when they return; MapSORT gives them back their own, which the identity metrics count as merging two objects. (b) AppleMOTS 0007: a lost track is matched, 21 frames after its apple was last seen, to a different apple 0.25 box sizes from where the camera places it (dashed). Grey: the other annotated apples.

Consequences for precision agriculture.

The most direct consequence is counting. Every identity switch that issues a new identity is a phantom plant or fruit in the count. The baselines over-count by 43% to 128% on the representative sequences with revisits, which would make their output unusable as a yield estimate without heavy post-hoc correction; MapSORT's count error there is between 0% and 8%. A second consequence is per-plant records. Because a plant keeps its identity across passes, measurements taken on the outbound and return passes, or from different UAV perspectives, attach to the same plant, which is what plant-level phenotyping and selective treatment need. A third is spatial: every MapSORT track carries a position in the scene map, so a track list is also a plant map. Registering the map to a GNSS-referenced frame, as is routine in orchard and field mapping, would turn MapSORT's output into a georeferenced inventory of individual plants or fruit. MapSORT also composes with an existing tracker rather than replacing it: BoT-SORT's association is unchanged and runs first, and the camera stages act only on what it leaves unmatched, so improvements in detectors, appearance models or the base tracker carry over directly.

Limitations.

The camera and revival stages cost throughput: on a CPU, MapSORT runs at 29% to 56% of BoT-SORT's frame rate, and building a scene map on a CPU takes from under an hour to several hours. Detections without a landmark, such as small fruit at the limit of the map's resolution, benefit only from BoT-SORT's own association, as the switch on AppleMOTS 0008 shows. Among dense, near-identical fruit, a lost track can be matched to a neighbour of its own fruit, as on AppleMOTS 0007. And the cue assumes that the objects do not move: fruit swaying on a branch, or a plant pushed aside by the robot, would carry a landmark that no longer marks where it is.

6 Conclusion

MapSORT turns the stationarity of crops and fruit into an identity cue. It gives every detection and track a Gaussian landmark in a structure-from-motion map of the scene, fits a camera to its own tracks in every frame, and uses that camera to re-match the tracks its base tracker misses and to revive tracks, kept dormant rather than deleted, when their objects return, including at the edge of the image. On four public agricultural datasets covering lettuce, oranges, grapes and apples, recorded from a field robot, a handheld camera, a wearable camera and a UAV, MapSORT outperforms StrongSORT, Deep OC-SORT and BoT-SORT, has fewer identity switches than every baseline on 19 of the 21 test sequences, preserves identity across revisits of any length, and produces substantially more accurate counts. MapSORT currently builds its scene map offline. Recent online reconstruction models that recover scene geometry frame by frame from monocular video (Wang et al, 2025; Murai et al, 2025) are a natural drop-in source for the same landmark observations, and extending MapSORT to online operation on a field robot is the subject of future work.

Statements and Declarations

Competing interests. The author has no relevant financial or non-financial interests to disclose.

Ethics approval and consent. Not applicable.

Data availability. All datasets used are publicly available from their original publishers: LettuceMOTS (Hu et al, 2024), MOrangeT (Santos et al, 2024), GrapeMOTS (Ariza-Sentís et al, 2024) and AppleMOTS (de Jong et al, 2022).

Code availability. The MapSORT source code is available at https://github.com/shinobi-wolf/MapSORT.

Author contributions. Srihari Vemuru conceived the method, implemented it, conducted the experiments and wrote the manuscript.

Appendix A Per-sequence statistics

Table A1 Statistics of every evaluation sequence. Revisits: ground-truth objects reappearing after at least 10 frames out of view.

Dataset	Sequence	Frames	Resolution	GT IDs	Boxes	Revisits
LettuceMOTS	0003	245	810×1080	40	3 304	25
	0007	244	810×1080	37	3 341	23
	0011	223	810×1080	37	3 073	22
MOrangeT	V01	408	1083×1944	110	7 848	104
	V02	409	1063×1890	46	4 354	35
	V05	293	≤1081×1941	148	11 944	125
	V06	447	1074×1910	122	12 411	109
	V07	553	1079×1924	154	19 069	170
	V08	544	1078×1918	192	24 500	209
	V09	222	1084×1951	16	1 923	17
	V10	244	1080×1926	13	1 372	19
	V11	268	1079×1920	87	7 265	64
	V12	307	1079×1920	115	11 723	98
GrapeMOTS	PathPlanning_1	927	1920×1080	29	4 796	0
	PathPlanning_2	209	3840×2160	45	4 838	0
	PathPlanning_3	400	1920×1080	57	6 445	0
	PathPlanning_7	225	3840×2160	65	9 014	23
AppleMOTS	0006	101	1296×972	279	4 524	0
	0007	103	1296×972	255	7 917	0
	0008	322	1296×972	164	10 618	0
	0010	100	1296×972	279	4 474	0

Appendix B Per-sequence results

Table B2 reports HOTA, IDF1 and identity switches of every tracker on each of the 21 test sequences.

References

Aharon N, Orfaig R, Bobrovsky BZ (2022) BoT-SORT: Robust associations multi-pedestrian tracking. arXiv:2206.14651, 2206.14651

Ariza-Sentís M, Wang K, Cao Z, et al (2024) GrapeMOTS: UAV vineyard dataset with MOTS grape bunch annotations recorded from multiple perspectives for enhanced object detection and tracking. Data in Brief 54:110432. https://doi.org/10.1016/j.dib.2024.110432

Bernardin K, Stiefelhagen R (2008) Evaluating multiple object tracking performance: The CLEAR MOT metrics. EURASIP Journal on Image and Video Processing 2008:246309. https://doi.org/10.1155/2008/246309

Bewley A, Ge Z, Ott L, et al (2016) Simple online and realtime tracking. In: 2016 IEEE International Conference on Image Processing (ICIP), pp 3464–3468, https://doi.org/10.1109/ICIP.2016.7533003

Broström M (2024) BoxMOT: Pluggable state-of-the-art multi-object tracking modules. https://github.com/mikel-brostrom/boxmot

Du Y, Zhao Z, Song Y, et al (2023) StrongSORT: Make DeepSORT great again. IEEE Transactions on Multimedia 25:8725–8737. https://doi.org/10.1109/TMM.2023.3240881

Fischler MA, Bolles RC (1981) Random sample consensus: a paradigm for model fitting with applications to image analysis and automated cartography. Communications of the ACM 24(6):381–395. https://doi.org/10.1145/358669.358692

Hartley R, Zisserman A (2004) Multiple View Geometry in Computer Vision, 2nd edn. Cambridge University Press, Cambridge, https://doi.org/10.1017/CBO9780511811685

Table B2 HOTA, IDF1 and identity switches of every tracker on every test sequence. Best per sequence in bold.

		BoT-SORT			StrongSORT			Deep OC-SORT			MapSORT		
Dataset	Sequence	HOTA	IDF1	IDSW	HOTA	IDF1	IDSW	HOTA	IDF1	IDSW	HOTA	IDF1	IDSW
LettuceMOTS	0003	77.58	64.69	28	57.59	46.90	117	77.33	67.63	23	**96.40**	**98.15**	**0**
	0007	77.93	65.18	26	75.36	62.47	24	77.20	66.78	22	**95.37**	**97.56**	**3**
	0011	77.88	64.91	24	76.33	64.03	23	77.49	68.03	20	**93.34**	**93.67**	**2**
MOrangeT	V01	74.39	64.03	105	70.32	61.47	131	69.40	62.05	101	**97.07**	**97.08**	**15**
	V02	81.02	71.85	33	78.31	71.32	60	78.07	70.85	29	**94.04**	**93.70**	**14**
	V05	76.03	63.26	111	75.19	64.02	105	73.88	63.42	102	**97.50**	**97.13**	**12**
	V06	75.38	64.46	106	73.38	63.84	126	72.27	63.09	105	**98.56**	**98.73**	**4**
	V07	76.79	66.43	141	74.67	65.09	155	74.41	65.81	137	**98.40**	**98.51**	**12**
	V08	76.50	65.97	185	75.75	66.19	188	74.70	65.69	182	**98.19**	**98.27**	**14**
	V09	82.27	77.16	13	82.60	80.11	12	83.12	79.87	12	**97.85**	**97.50**	**1**
	V10	69.71	59.30	16	82.32	77.09	12	76.50	70.03	13	**93.43**	**90.24**	**4**
	V11	80.21	73.56	61	80.24	75.36	57	77.58	72.63	60	**98.53**	**98.81**	**4**
	V12	79.01	71.24	92	78.07	71.55	87	76.59	70.33	88	**97.93**	**97.85**	**10**
GrapeMOTS	PathPlanning_1	**99.38**	**99.69**	**0**	98.69	99.34	**0**	97.28	97.29	1	**99.38**	**99.69**	**0**
	PathPlanning_2	87.20	83.78	30	81.19	78.37	102	81.04	77.22	43	**89.83**	**89.82**	**21**
	PathPlanning_3	**94.56**	93.73	18	94.22	94.17	30	94.08	**94.67**	22	90.63	88.40	**11**
	PathPlanning_7	89.60	85.48	34	77.59	71.78	123	90.07	86.71	37	**96.73**	**96.35**	**10**
AppleMOTS	0006	84.45	86.09	89	40.66	42.69	263	74.05	79.73	93	**87.89**	**89.43**	**53**
	0007	**95.19**	**96.38**	8	83.32	85.11	128	90.69	93.95	7	94.86	95.80	**6**
	0008	98.79	99.37	1	96.76	98.29	3	96.63	98.21	**0**	**98.81**	**99.38**	1
	0010	89.64	92.28	36	39.21	40.23	268	77.91	83.63	53	**91.21**	**93.66**	**26**

Hu N, Su D, Wang S, et al (2024) Segmentation and tracking of vegetable plants by exploiting vegetable shape feature for precision spray of agricultural robots. Journal of Field Robotics 41(3):570–586. https://doi.org/10.1002/rob.22279

Jiang J, Wang Z, Zhao M, et al (2026) SAM2MOT: A novel paradigm of multi-object tracking by segmentation. In: Proceedings of the AAAI Conference on Artificial Intelligence, pp 5388–5396, https://doi.org/10.1609/aaai.v40i7.37455

de Jong S, Baja H, Tamminga K, et al (2022) APPLE MOTS: Detection, segmentation and tracking of homogeneous objects using MOTS. IEEE Robotics and Automation Letters 7(4):11418–11425. https://doi.org/10.1109/LRA.2022.3199026

Liu X, Chen SW, Liu C, et al (2019) Monocular camera based fruit counting and mapping with semantic data association. IEEE Robotics and Automation Letters 4(3):2296–2303. https://doi.org/10.1109/LRA.2019.2901987

Lowe DG (2004) Distinctive image features from scale-invariant keypoints. International Journal of Computer Vision 60(2):91–110. https://doi.org/10.1023/B:VISI.0000029664.99615.94

Luiten J, Hoffhues A (2020) TrackEval. https://github.com/JonathonLuiten/TrackEval

Luiten J, Ošep A, Dendorfer P, et al (2021) HOTA: A higher order metric for evaluating multi-object tracking. International Journal of Computer Vision 129:548–578. https://doi.org/10.1007/s11263-020-01375-2

Maggiolino G, Ahmad A, Cao J, et al (2023) Deep OC-SORT: Multi-pedestrian tracking by adaptive re-identification. In: 2023 IEEE International Conference on Image Processing (ICIP), arXiv:2302.11813

Mahmud MS, Zahid A, He L, et al (2021) Opportunities and possibilities of developing an advanced precision spraying system for tree fruits. Sensors 21(9):3262. https://doi.org/10.3390/s21093262

Murai R, Dexheimer E, Davison AJ (2025) MASt3R-SLAM: Real-time dense SLAM with 3D reconstruction priors. In: Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR), pp 16695–16705

Osman Y, Dennis R, Elgazzar K (2021) Yield estimation and visualization solution for precision agriculture. Sensors 21(19):6657. https://doi.org/10.3390/s21196657

Rajendran V, Debnath B, Mghames S, et al (2024) Towards autonomous selective harvesting: A review of robot perception, robot design, motion planning and control. Journal of Field Robotics 41(7):2247–2279. https://doi.org/10.1002/rob.22230, online 2023; issue date 2024

Ristani E, Solera F, Zou R, et al (2016) Performance measures and a data set for multi-target, multi-camera tracking. In: Computer Vision, ECCV 2016 Workshops. Springer, pp 17–35, https://doi.org/10.1007/978-3-319-48881-3_2

Santos TT, de Souza KXS, Camargo Neto J, et al (2024) Multiple orange detection and tracking with 3-D fruit relocalization and neural-net based yield regression in commercial sweet orange orchards. Computers and Electronics in Agriculture 224:109199. https://doi.org/10.1016/j.compag.2024.109199

Sarkar S, Ganapathysubramanian B, Singh A, et al (2024) Cyber-agricultural systems for crop breeding and sustainable production. Trends in Plant Science 29(2):130–149. https://doi.org/10.1016/j.tplants.2023.08.001

Schönberger JL, Frahm JM (2016) Structure-from-motion revisited. In: Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition (CVPR), pp 4104–4113, https://doi.org/10.1109/CVPR.2016.445

Thrun S, Burgard W, Fox D (2005) Probabilistic Robotics. MIT Press, Cambridge, MA

Vemuru S, Ankit K, Venkatesan SP, et al (2024) Yield prediction and counting using world coordinates. SSRN preprint, https://doi.org/10.2139/ssrn.4829514

Wang Q, Zhang Y, Holynski A, et al (2025) Continuous 3D perception model with persistent state. In: Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR), pp 10510–10522

Wang Z, Walsh K, Koirala A (2019) Mango fruit load estimation using a video based MangoYOLO–Kalman filter–Hungarian algorithm method. Sensors 19(12):2742. https://doi.org/10.3390/s19122742

Wojke N, Bewley A, Paulus D (2017) Simple online and realtime tracking with a deep association metric. In: 2017 IEEE International Conference on Image Processing (ICIP), pp 3645–3649, https://doi.org/10.1109/ICIP.2017.8296962

Wu M, Liu S, Li Z, et al (2025) A review of intelligent orchard sprayer technologies: Perception, control, and system integration. Horticulturae 11(6):668. https://doi.org/10.3390/horticulturae11060668

Xu R, Li C (2022) A review of high-throughput field phenotyping systems: Focusing on ground robots. Plant Phenomics 2022:9760269. https://doi.org/10.34133/2022/9760269

Zhang W, Wang J, Liu Y, et al (2022) Deep-learning-based in-field citrus fruit detection and tracking. Horticulture Research 9:uhac003. https://doi.org/10.1093/hr/uhac003

Zhou K, Yang Y, Cavallaro A, et al (2019) Omni-scale feature learning for person re-identification. In: Proceedings of the IEEE/CVF International Conference on Computer Vision (ICCV), pp 3702–3712