

GPU Implementations of HOG-based Object Detection using Deformable Part Models

Manato Hirabayashi, Shinpei Kato,
and Masato Edahiro
Dept. of Information Engineering
Nagoya University

Kazuya Takeda
Dept. of Media Science
Nagoya University

Seiichi Mita
Research Center for Smart Vehicles
Toyota Technological Institute

Vision-based object detection using camera sensors is an essential piece of perception for autonomous vehicles. Various combinations of features and models can be applied to increase the quality and speed of object detection. A well-known approach uses histograms of oriented gradients (HOG) with deformable models to detect a car in an image. A major challenge of this approach can be found in computational cost introducing a real-time constraint problem in the real world. In this paper, we present implementation techniques using graphics processing units (GPUs) to accelerate computations of similarity scores of the input image and the pre-defined models. Our implementation considers not only the algorithm part but also the entire program structure. We experimentally show that our implementation using commodity GPUs can achieve speedups of 1.5x to 3x in frame-rate over sequential and multithreaded implementations using traditional CPUs.

Index Terms—GPGPU; Computer Vision; Object Detection

I. INTRODUCTION

Grand challenges of cyber-physical systems (CPS) include a high computational cost of understanding the physical world. Image-based object detection is one of compute-intensive tasks for CPS. For example, an autonomous vehicle needs to detect and track other vehicles by itself. Current autonomous driving technologies [6], [11], [16] tend to rely on active sensors such as GPS, RADAR, and LIDAR [9], [14] together with very accurate pre-configured maps, but the use of passive camera sensors is becoming more practical due to recent advances in computer vision [2]–[4]: vision-based object detection can be applied for various ranges and orientations. In particular, histograms of oriented gradients (HOG) [2] features provide reliable high-level representations of an image underlying many state-of-the-art object detection algorithms [3], [5], [13], [15], [17]. However, a major concern of HOG-based object detection remains in computational cost.

Previous work on the implementation of HOG-based object detection are limited to either hardware implementations [7], [8], [10] or specific parts of the HOG algorithm [1], [12].

REFERENCES

- [1] Y-P. Chen, S-Z. Li, and X-M. Lin. Fast HOG Feature Computation based on CUDA. In *Proc. of the IEEE International Conference on Computer Science and Automation Engineering*, pages 748–751, 2011.
- [2] N. Dalal and B. Triggs. Histograms of Oriented Gradients for Human Detection. In *Proc. of the IEEE Conference on Compute Vision and Pattern Recognition*, pages 886–893, 2005.
- [3] P. Felzenszwalb, R. Girshick, D. McAllester, and D. Ramanan. Object Detection with Discriminatively Trained Part Based Models. *IEEE Transactions on Pattern Analysis and Machine Intelligence*, 32(9):1627–1645, 2010.
- [4] P. Felzenszwalb and D. Huttenlocher. Pictorial Structures for Object Recognition. *International Journal of Computer Vision*, 61(1), 2005.
- [5] A. Geiger, P. Lenz, and R. Urtasun. Are we ready for Autonomous Driving? The KITTI Vision Benchmark Suite. In *Proc. of the IEEE Conference on Compute Vision and Pattern Recognition*, pages 3354–3361, 2012.
- [6] E. Guizzo11. How Google’s Self-Driving Car Works. *IEEE Spectrum*, 2011.
- [7] R. Kadota, H. Sugano, M. Hiromoto, H. Ochi, R. Miyamoto, and Y. Nakamura. Hardware Architecture for HOG Feature Extraction. In *Proc. of the International Conference on Intelligent Information Hiding and Multimedia Signal Processing*, pages 1330–1333, 2009.
- [8] F. Karakaya, H. Altun, and V. Cavuslu. Implementation of HOG algorithm for real time object recognition applications on FPGA based embedded system. In *Proc. of the IEEE Signal Processing and Communications Applications Conference*, pages 508–511, 2009.
- [9] A. Kirchner and C. Ameling. Integrated Obstacle and Road Tracking using a Laser Scanner. In *Proc. of the IEEE Intelligent Vehicles Symposium*, pages 675–681, 2000.
- [10] M. Komorkiewicz, M. Kluczewski, and M. Gorgon. Floating Point HOG Implementation for Real-Time Multiple Object Detection. In *Proc. of the International Conference on Field Programmable Logic and Applications*, pages 711–714, 2012.
- [11] J. Levinson, J. Askeland, J. Becker, J. Dolson, D. Held, S. Kammel, J.Z. Kolter, D. Langer, O. Pink, V. Pratt, M. Sokolsky, G. Stanek, D. Stavens, A. Teichman, M. Werling, and S. Thrun. Towards Fully Autonomous Driving: Systems and Algorithms. In *Proc. of the IEEE Intelligent Vehicles Symposium*, pages 163–168, 2011.
- [12] V. Prisacariu and I. Reid. fastHOG – a Real-Time GPU Implementation of HOG. Technical Report 2310/09, Department of Engineering Science, University of Oxford, 2009.
- [13] P. Rybski, D. Huber, D. Morris, and R. Hoffman. Visual Classification of Coarse Vehicle Orientation using Histogram of Oriented Gradients Features. In *Proc. of the IEEE Intelligent Vehicles Symposium*, pages 921–928, 2010.
- [14] D. Streller, K. Furstenberg, and K. Dietmayer. Vehicle and Object Models for Robust Tracking in Traffic Scenes using Laser Range Images. In *Proc. of the IEEE International Conference on Intelligent Transportation Systems*, pages 118–123, 2002.
- [15] F. Suard, A. Rakotomamonjy, A. Benshrir, and A. Broggi. Pedestrian Detection using Infrared Images and Histograms of Oriented Gradients. In *Proc. of the IEEE Intelligent Vehicles Symposium*, pages 206–212, 2006.
- [16] C. Urmson, J. Anhalt, H. Bae, D. Bagnell, C. Baker, R. Bittner, T. Brown, M. Clark, M. Darms, D. Demitrich, J. Dolan, D. Duggins, D. Ferguson, T. Galatali, C. Geyer, M. Gittleman, S. Harbaugh, M. Hebert, T. Howard, S. Kolski, M. Likhachev, B. Litkouhi, A. Kelly, M. McNaughton, N. Miller, J. Nickolaou, K. Peterson, B. Pilnick, R. Rajkumar, P. Rybski, V. Sadakar, B. Salesky, Y-W. Seo, S. Singh, J. Snider, J. Struble, A. Stentz, M. Taylor, W. Whittaker, Z. Wolkowicki,

W. Zhang, and J. Ziegler. Autonomous Driving in Urban Environments: Boss and the Urban Challenge. *Journal of Field Robotics*, 25(8):425–466, 2008.

- [17] Q. Zhu, M-C. Yeh, K-T. Cheng, and S. Avidan. Histograms of Oriented Gradients for Human Detection. In *Proc. of the IEEE Conference on Compute Vision and Pattern Recognition*, pages 1491–1498, 2006.