

SNOTE DOCUMENTATION

Snote SDKs and Development Toolchains

Repository-declared SDK constraints, web runtime versions, and platform build requirements.

APPLICATION: Snote Note-Taking Platform

FOUNDER & CREATOR: Sadab

SHOWCASE WEBSITE: snote-showcase.vercel.app

SOURCE REPOSITORY: github.com/shinuXcode/Snote

SDK REFERENCE

Snote SDKs and Development Toolchains

1. FLUTTER AND DART

The Flutter client is in `app/`. Its `pubspec.yaml` declares the Dart SDK constraint `>= 3.12.0 < 4.0.0` and Flutter SDK dependencies. Use the Flutter version selected by the current CI workflow or release build and record `flutter --version` when reproducing builds.

The app package version in `pubspec.yaml` is **1.0.1+3**. Verify the selected release tag before publishing binaries. *Modern Dart features enable high-efficiency vector computations and responsive user interface rendering.*

2. WEBSITE RUNTIME AND FRAMEWORK

`website/package.json` declares **Next.js 15.5.28, React 19.1.0, and React DOM 19.1.0**. The website package version is 0.3.2.

TypeScript is declared as `^5.9.0`. Node.js is required to run the Next.js toolchain. Use the version pinned by Vercel project settings or package manager configuration. *Server-side rendering delivers rapid documentation loading and optimized web showcase search indexation.*

3. SUPABASE SDKS

The Flutter app declares `supabase_flutter ^2.18.0`. The website declares `@supabase/supabase-js ^2.117.2`. Caret ranges allow compatible dependency updates within the package's semver range.

Do not infer that cloud services are enabled merely because SDKs are dependencies. Asynchronous database drivers facilitate seamless cloud synchronization while offline local storage remains active.

4. PLATFORM SDKS AND TOOLCHAINS

Android builds require the **Android SDK and Java/Gradle toolchain**. iOS builds require **Xcode and iOS SDK** on macOS. Windows, macOS, and Linux desktop builds require native build toolchains.

Inspect generated manifests, Gradle files, Xcode project settings, signing configuration, and release workflow before stating official platform requirements. *Native build chains compile optimized machine code for high frame-rate drawing performance.*

5. CORE PACKAGES AND CAPABILITIES

The Flutter dependency manifest includes *Riverpod, SQLite and FFI adapters, path and file access, Supabase, connectivity_plus, file_picker, image_picker, mobile_scanner, pdfx, flutter_quill, flutter_secure_storage, share_plus, URL launching, crypto, archive, wakelock_plus, and vector_math*. *These libraries empower cross-platform hardware access, local file encryption, and rich document formatting.*

6. REPRODUCIBLE VERIFICATION

Flutter: run `flutter --version`, `dart --version`, `flutter pub get`, `flutter analyze`, and `flutter test` from `app/`.

Website: run `node --version`, `npm --version`, `npm ci`, `npm run typecheck`, `npm audit`, and `npm run build` from `website/`. *Standardized CLI commands allow developers to validate static code quality across environments.*

7. SOURCE OF TRUTH AND LIMITATIONS

This reference is derived from repository files. Version ranges are not necessarily exact resolved package versions. Consult matching commit, lockfiles, native build files, CI configuration, and official tool documentation. *Lockfile lock-ins guarantee deterministic dependency resolution during official automated build releases.*

SNOTE • SADAB



End of Document

Official Technical & Guidance Document for Snote Application

Snote Note-Taking Platform

Designed & Maintained by Founder **Sadab**

snote-showcase.vercel.app • github.com/shinuXcode/Snote

SNOTE SADAB