

# C++- Overloading (Operator and Function)

## Introduction

C++ allows you to specify more than one definition for a function name or an operator in the same scope, which is called function overloading and operator overloading respectively.

An overloaded declaration is a declaration that is declared with the same name as a previously declared declaration in the same scope, except that both declarations have different arguments and obviously different definition (implementation).

## Function Overloading in C++

You can have multiple definitions for the same function name in the same scope. The definition of the function must differ from each other by the types and/or the number of arguments in the argument list. You cannot overload function declarations that differ only by return type.

## Operators Overloading in C++

You can redefine or overload most of the built-in operators available in C++. Thus, a programmer can use operators with user-defined types as well.

Overloaded operators are functions with special names: the keyword "*operator*" followed by the symbol for the operator being defined. Like any other function, an overloaded operator has a return type and a parameter list.

## Overloadable/Non-overloadable Operators

Following is the list of operators which can be overloaded:

+	-	*	/	%	^
&		~	!	,	=
<	>	<=	>=	++	--
<<	>>	==	!=	&&	
+=	-=	/=	%=	^=	&=
=	*=	<<=	>>=	[]	()
->	->*	new	new []	delete	delete []

Following is the list of operators, which can not be overloaded:

::	.*	.	?:
----	----	---	----

