# OpenCV – Multiple Inheritance and Polymorphism

## Reading materials

- Class Inheritance
- Class Polymorphism

# Exercise 1: Multiple inheritance and image processing

The goal of this practical work is to create 2 classes: *EdgeDetector* and *BlurFiltering* which inherit from the OpenCV class *Mat* and from a common class *Base*.

The *class Base* is a base class which will contain data and methods common for these two classes.

The *class EdgeDetector* will implement various image processing methods for edge detections defined in OpenCV (you have to list and define the methods you want to implement in this class).

The *class BlurFiltering* will implement various filtering methods for image blurring defined in OpenCV (you have to list and define the methods you want to implement in this class).

Your code must be able to execute the following main function:

```
int main ( void )
  // read an image in source
 cv::Mat source = imread("test.png", CV LOAD IMAGE UNCHANGED);
 cosi::BlurFiltering blurFiltering;
 cosi::EdgeDetector edgeDetector ( source, SOBEL );
  // display edgeDetector result
 namedWindow( edgeDetector.getOpenCVProcessName(), CV WINDOW AUTOSIZE);
 imshow( edgeDetector.getOpenCVProcessName(), edgeDetector);
 blurFiltering.setProcess ( GAUSSIAN );
 blurFiltering.process ( source );
  // display blurFiltering result
 namedWindow( blurFiltering.getOpenCVProcessName(), CV WINDOW AUTOSIZE);
  imshow(blurFiltering.getOpenCVProcessName(), blurFiltering);
 edgeDetector.setProcess ( LAPLACIAN );
 edgeDetector.process ( source );
  // display edgeDetector result
 namedWindow( edgeDetector.getOpenCVProcessName(), CV WINDOW AUTOSIZE);
  imshow( edgeDetector.getOpenCVProcessName(), edgeDetector);
```

```
waitKey(0); //wait infinite time for a keypress
return 0;
}
```

### Exercise 2: Virtual members

Transform your code in order to execute the following code:

```
void globalProcess ( base& imageProcessing, const cv::Mat& imageToProcess )
{
   imageProcessing.process ( imageToProcess );
}
int main ( void )
{
   // read an image in source
   cv::Mat source = imread("test.png", CV_LOAD_IMAGE_UNCHANGED);

   cosi::BlurFiltering blurFiltering;
   blurFiltering.setProcess ( GAUSSIAN );

   globalProcess ( blurFiltering, source );

   // display blurFiltering result
   namedWindow( blurFiltering.getOpenCVProcessName(), CV_WINDOW_AUTOSIZE);
   imshow(blurFiltering.getOpenCVProcessName(), blurFiltering);

   waitKey(0); //wait infinite time for a keypress
   return 0;
}
```

### Exercise 3: Abstract base classes

Make the *class Base* an abstract class.