

Document Processing Flow Using Pandoc and TeX

Center for HPC, SJTU
<http://hpc.sjtu.edu.cn>

Dec 31th, 2014

1	Setup the workflow on Mac OS X	1
2	Setup the workflow on GNU/Linux	2
3	Setup the workflow on Windows	2
4	Reference	3

1 Setup the workflow on Mac OS X

Firstly, please install **pandoc** package from **Homebrew**. If you haven't installed brew on your Mac, please give it a try.

```
$ brew install pandoc
```

Standalone pandoc package is available on <https://github.com/jgm/pandoc/releases>.

Secondaly, install **MacTeX** via **Homebrew Cask**. Yes, cask is highly recommended for Mac users too. Please be patient as it takes time to download the 2.3GB installation file.

```
$ brew cask install mactex
```

Don't forget to add texbin into \$PATH:

```
$ echo 'export PATH=$PATH:/usr/texbin' >> ~/.bash_profile
```

Standalone MacTeX package is available on <https://www.tug.org/mactex/>.

After that, install the necessary fonts by double click the font files. Font files “TeX Gyre Termes” can be retrieved from <http://www.gust.org.pl/projects/e-foundry/tex-gyre/termes>. Please make sure you have authorized files for the Adobe Chinese fonts: AdobStongStd, AdobHeitiStd, AdobeFangsongStd and AdobKaitiStd.

Finally, install zhfonts module for the ConTeXt engine.

```
$ cd ~/Library/  
$ mkdir -p texmf/tex/context/third  
$ cd !$  
$ git clone https://github.com/liyanrui/zhfonts.git  
$ luatools --generate  
$ mtxrun --script fonts --reload  
$ mtxrun --script fonts --list --pattern=\* --all
```

Now you should be able to build the HPC sample documents.

2 Setup the workflow on GNU/Linux

3 Setup the workflow on Windows

At the very beginning, Windows users are required to install **Cygwin** to make the Linux tools take effect. Please check the following tools during installation:

- Base: sed
- Devel: make
- Base: openssl
- Net: openssl
- Devel: git, git-completion.
- Editors: vim, vim-common

After installation, a shortcut of Cygwin will be added on your Desktop.

Firstly, install **pandoc** from its binary release on <https://github.com/jgm/pandoc/releases>.

Secondly, install **TeXLive** 2014 by running `install-tl-windows.bat` in the ISO image. Commands of Tex Live will be automatically added to your PATH.

Then install extra fonts required by the HPC template. Download fonts `AdobStongStd`, `AdobHeitiStd`, `AdobeFangsongStd` and `AdobKaitiStd`, then copy them into `YOUR_SYSTEM_PARTITION:\windows\fonts`.

After that, install `zhfonts` for the context engine.

1. Get `zhfonts` from its [github page](#).
2. Copy the folder `zhfonts` into `texlive\\2014\\texmf-dist\\tex\\context\\third`.
3. Run `luatools --generate` to make `zhfonts` take effect, run `mtxrun --script fonts --reload` to reload the fonts.

Open Cygwin and now you should be able to use git and build the HPC sample documents.

4 Reference

- “gist: Configure ConTeXt environment after installing TeX” <https://gist.github.com/weijianwen/4a3794946982f4cc0b31>
- “TeXLive on Windows” <https://www.tug.org/texlive/windows.html>
- “zhfonts模块的用法” <http://garfileo.is-programmer.com/posts/23740>