RAJALAKSHMI ENGINEERING COLLEGE

S Shirly Deborah Blessy 251001251-2025-IT

S2

| | |
|---|---|
| **Started on** | Thursday, 13 August 2026, 10:48 AM |
| **State** | Finished |
| **Completed on** | Thursday, 13 August 2026, 10:57 AM |
| **Time taken** | 8 mins 28 secs |
| **Marks** | 1.00/1.00 |
| **Grade** | **10.00** out of 10.00 (**100**%) |

**Question 1** | Correct Mark 1.00 out of 1.00

Given an array `nums` of size `n`, return *the majority element*.

The majority element is the element that appears more than `⌊n / 2⌋` times. You may assume that the majority element always exists in the array.

**Example 1:**

```
Input: nums = [3,2,3]
Output: 3
```

**Example 2:**

```
Input: nums = [2,2,1,1,1,2,2]
Output: 2
```

**Constraints:**

- `n == nums.length`
- `1 <= n <= 5 * 10^4`
- `-2^31 <= nums[i] <= 2^31 - 1`

**For example:**

| Input | Result |
|---|---|
| 3<br>3 2 3 | 3 |
| 7<br>2 2 1 1 1 2 2 | 2 |

**Answer:** (penalty regime: 0 %)

```
#include<stdio.h>
int main(){
    int n;
    scanf("%d",&n);
    int arr[n];
    for(int i=0;i<n;i++){
        scanf("%d",&arr[i]);
    }
    for(int i=0;i<n;i++){
        if(arr[i]>arr[i+1]){
            printf("%d",arr[i]);
        }
    }

}
```

| | Input | Expected | Got | |
|---|---|---|---|---|
| ✔ | 3<br>3 2 3 | 3 | 3 | ✔ |

Passed all tests! ✔

Correct

Marks for this submission: 1.00/1.00.

Back to Course