A Comparative Study of AST-Based Winnowing and Tree Edit Distance in Detecting GenAI-Obfuscated Source Code

Group 4 — Software Engineering Department, FPT University
Course: SWP391 - Software Development Project (Research-Based Learning Track, 10 Weeks) | Academic Year: 2026
IEEE Standard Format for Conference Proceedings

Đinh Thành Trung
Lead Author & System Architect
Dept. of Software Engineering
FPT University, Da Nang, Vietnam

Trần Công Tiến
Co-Author & DevOps Specialist
Dept. of Software Engineering
FPT University, Da Nang, Vietnam

Nguyễn Hoàng Vinh
Co-Author & GenAI Specialist
Dept. of Software Engineering
FPT University, Da Nang, Vietnam

Văn Thái Trung
Co-Author & Algorithm Specialist
Dept. of Software Engineering
FPT University, Da Nang, Vietnam

Trần Thanh Nguyên
Co-Author & Correspondence Author
Dept. of Software Engineering
FPT University, Da Nang, Vietnam

Group 4 — Software Engineering Department, FPT University
Course: SWP391 - Software Development Project (Research-Based Learning Track, 10 Weeks)
Academic Year: 2026 | IEEE Standard Format for Conference Proceedings

ABSTRACT

The rapid proliferation of Large Language Models (LLMs) such as OpenAI ChatGPT, GitHub Copilot, and Claude has fundamentally transformed software engineering education. While these generative artificial intelligence (GenAI) assistants accelerate learning, they simultaneously enable students to produce heavily disguised academic submissions through automated identifier renaming, control-flow flattening, dead-code injection, and semantic-equivalent refactoring. Traditional character- and token-level plagiarism detection algorithms (e.g., standard MOSS and Winnowing) suffer drastic degradation when confronted with AI-synthesized code paraphrasing.

This paper investigates the effectiveness, computational efficiency, and limitations of an **Abstract Syntax Tree (AST)-Normalized Winnowing** pipeline engineered within the **AITA-Intelligent** automated grading platform. We rigorously evaluate the pipeline against an empirical 10-pair benchmark dataset featuring nine sophisticated GenAI obfuscation vectors and one negative control pair. Operating under an empirically validated parameter configuration (*k=15, w=10*) and a decision threshold of $\tau \geq 70.0\%$, our architecture achieved **90.00% overall accuracy**, **100.00% precision (zero false accusations)**, and **88.89% recall**. The pipeline processed a 947-line codebase (2,625 tokens, yielding 1,329 fingerprints) within **12.0 ms**, comfortably surpassing the system's strict Definition-of-Done (DoD) latency budget of 200 ms.

Furthermore, we conduct a comprehensive theoretical and empirical comparison between AST Winnowing and Tree Edit Distance (TED, Zhang-Shasha algorithm), delineating the operational boundary where compound obfuscation (Pair 09, 54.07% similarity) evades linear-time fingerprinting, and propose a two-tier hybrid architecture for high-stakes institutional deployment.

Index Terms — Abstract Syntax Tree (AST), Winnowing Algorithm, Plagiarism Detection, GenAI Obfuscation, Source Code Normalization, Tree Edit Distance, Automated Grading System.

I. INTRODUCTION

A. Background and Context

Automated assessment systems (autograders) have become indispensable infrastructure in computer science and software engineering curricula. Modern autograding workflows evaluate programming assignments across three distinct dimensions:

1. **Functional Correctness:** Verifying algorithmic outputs against testcase suites inside isolated sandboxes.
2. **Code Quality and Architecture:** Evaluating adherence to Clean Code and SOLID principles (Single Responsibility, Dependency Inversion).
3. **Academic Integrity:** Detecting source code collusion, cross-student plagiarism, and unauthorized AI synthesis.

In the pre-GenAI era, academic collusion primarily manifested as manual code copying, variable renaming, and cosmetic reformatting. However, modern GenAI tools allow students to apply composite, semantics-preserving transformations with a single natural language prompt. Consequently, modern autograding architectures must provide robust defenses against AI-disguised plagiarism while upholding the paramount legal and pedagogical requirement of academic assessment: **Zero False Positives (*FP = 0*)**. A false accusation inflicts irreparable academic harm, whereas suspected submissions can be safely routed to human faculty review.




Fig. 1. *End-to-end multi-tier autograding and integrity architecture in AITA-Intelligent.*

B. Problem Statement

Character-level string matching (e.g., Levenshtein distance, Diff3) and unnormalized *n*-gram fingerprinting degrade sharply under simple identifier substitution or whitespace adjustments. To resist surface-level disguise, researchers introduced Abstract Syntax Tree (AST) representations. However, full tree comparisons—most notably Tree Edit Distance (TED)—exhibit cubic or quartic time complexity ($O(|T_1| \cdot |T_2| \cdot deg(T_1) \cdot deg(T_2))$, rendering them impractical for synchronous institutional queues handling hundreds of concurrent submissions.

Conversely, the Winnowing algorithm (Schleimer et al., SIGMOD 2003) offers guaranteed bounded match detection with linear execution time $O(N)$ and sub-linear storage requirements. The core research question therefore arises:

> **Research Question (RQ):** *Can an AST-normalized Winnowing pipeline effectively detect sophisticated GenAI-obfuscated code under production latency constraints (≤ 200 ms), and where does its detection capability break down compared to theoretical Tree Edit Distance?*

C. Contributions

This paper provides the following principal contributions:

1. **Formal Architectural Formulation:** We specify the mathematical formulation of an AST-normalized token serialization pipeline coupled with an ensemble similarity function combining Jaccard fingerprint containment (*65%*) and token-frequency cosine similarity (*35%*).
2. **Empirical Evaluation on RBL Benchmark:** We evaluate the system against a standardized 10-pair benchmark suite encompassing nine GenAI obfuscation archetypes (renaming, loop inversion, branch restructuring, helper extraction, expression transformation, ChatGPT refactoring, and compound disguise) plus an independent negative control.
3. **Rigorous Metric Verification:** We verify an empirical accuracy of *90.00%*, precision of *100.00%*, and recall of *88.89%* at the institutional threshold $\tau = 70.0\%$, achieving zero false accusations.
4. **Computational Throughput Measurement:** We prove that AST Winnowing achieves a *12.0* ms execution time on a 947-line codebase, providing a *16.6*× safety margin over the *200* ms SLA.
5. **Analytical TED Boundary Derivation:** We conduct an analytical study comparing Winnowing against Tree Edit Distance, documenting why compound structural rewriting (Pair 09) constitutes the recall limit of fingerprint-based approaches.

II. RELATED WORK & THEORETICAL FOUNDATION

A. The Winnowing Algorithm

Document fingerprinting by hashing all *k*-grams yields an impractical storage footprint and sensitivity to minor insertions. Schleimer, Wilkerson, and Aiken (2003) introduced **Winnowing**, an algorithm guaranteeing that in any text window of length *w*, at least one fingerprint is selected. Given a sequence of hashes $h_1, h_2, ..., h_n$, a sliding window of size *w* selects the minimum hash value:

$$p_i = \arg\min_{j \in [i, i + w - 1]} h_j$$

To maintain determinism when multiple positions share the minimum value, the rightmost minimum is preserved. The algorithm guarantees that any match of length $L \geq w + k - 1$ characters is guaranteed to be detected, while matches shorter than *k* characters are disregarded. In standard AITA production, default operational parameters are set to $k=5, w=3$ for broad sensitivity; however, for structured structural plagiarism detection, we demonstrate that $k=15, w=10$ filters local syntactic noise while capturing overarching algorithm structure.

B. AST Normalization

An Abstract Syntax Tree is a finite, labeled, directed tree whose interior nodes represent programming operators and whose leaves represent operands (identifiers, constants). Standard tokenizers retain surface syntax. In contrast, our AST normalizer executes four reduction steps:

1. **Comment and Layout Stripping:** Discarding all inline docstrings, block comments, and whitespace variations.

2. **Identifier Canonicalization:** Mapping local variables, function names, and parameter tokens into class-invariant symbols (*VAR_i, FUNC_j, PARAM_k*).
3. **Literal Generalization:** Coalescing primitive literals (numeric constants, string literals) into a universal *LIT* token.
4. **Keyword and Control Flow Preservation:** Retaining semantic control tokens (`for` , `while` , `if` , `return` , `class` , `try`).

C. Tree Edit Distance (TED)

Tree Edit Distance, formulated by Zhang and Shasha (1989), defines the distance between two rooted labeled trees *T_1* and *T_2* as the minimum cost sequence of node edit operations (insert, delete, relabel) that transforms *T_1* into *T_2*:


$$TED(T_1, T_2) = \min_{S = \langle op_1, ..., op_m \rangle} \sum_{i=1}^{m} cost(op_i)$$

TED natively recognizes sub-tree movements and function extraction because moving a sub-tree corresponds to a deletion and insertion without disrupting adjacent sub-tree structures. However, computing TED between two ASTs of size $|V_1|$ and $|V_2|$ incurs a worst-case computational complexity of $O(|V_1| \cdot |V_2| \cdot depth(T_1) \cdot depth(T_2))$, which scales to several seconds for medium-sized programs ($N > 300$ AST nodes).

III. DETECTION PIPELINE ARCHITECTURE

The AITA-Intelligent plagiarism detection pipeline operates as a modular subsystem integrated into the NestJS API Gateway and BullMQ worker queues.

A. Pipeline Stages



Stage 1: AST Normalization and Canonical Token Serialization

The AST parser traverses the concrete syntax tree, discarding comments and mapping identifiers into positional canonical forms:

$$T_{norm} = \langle t_1, t_2, ..., t_M \rangle, \quad t_i \in \Sigma_{canonical}$$

Each token *t_i* retains its source file coordinate span *(L_{start}, C_{start}, L_{end}, C_{end})* to enable visual highlight mapping in the Monaco Diff Editor.

Stage 2: K-Gram Construction and Rolling Hash

Sequences of *k* consecutive normalized tokens form *k*-grams:

$$g_i = \langle t_i, t_{i+1}, ..., t_{i+k-1} \rangle$$

Each *k*-gram is hashed using a 64-bit non-cryptographic Murmur3/FNV-1a hash to produce an integer value $h(g_i) \in [0, 2^{64}-1]$.

Stage 3: Sliding Window Fingerprint Selection

A sliding window of width *w* selects the minimum hash value. The resulting set of unique fingerprint hashes forms the document signature:

$$\mathcal{F}(D) = \{ (h, span) \mid h \text{ is selected by Winnowing over } D \}$$

Stage 4: Ensemble Similarity Metric

To mitigate false positives arising from identical length disparities, AITA computes an ensemble score combining **Containment** and **AST Token Histogram Cosine Similarity**:

1. **Jaccard Containment:**

$$C(A, B) = \frac{|\mathcal{F}(A) \cap \mathcal{F}(B)|}{\min(|\mathcal{F}(A)|, |\mathcal{F}(B)|)} \times 100\%$$

2. **AST Token Vector Cosine Similarity:**

$$\cos(\mathbf{v}_A, \mathbf{v}_B) = \frac{\mathbf{v}_A \cdot \mathbf{v}_B}{\|\mathbf{v}_A\| \, \|\mathbf{v}_B\|} \times 100\%$$

3. **Composite Similarity Rate (S_{comb}):**

$$S_{comb} = 0.65 \cdot C(A, B) + 0.35 \cdot \cos(\mathbf{v}_A, \mathbf{v}_B)$$

If containment $C(A, B) \geq 99.0\%$, the system triggers a short-circuit verdict assigning $S_{comb} = 100.0\%$, recognizing complete code transposition.

B. Institutional Classification Bands

In accordance with Rule BR-03 and IEEE autograding guidelines, submissions are triaged into three action bands:

- **Clean Band ($S < 40.0\%$):** Independent work; auto-cleared.
- **Suspected Band ($40.0\% \leq S < 70.0\%$):** Ambiguous overlap; queued for instructor inspection in the Monaco Diff UI.
- **Flagged Plagiarism Band ($S \geq 70.0\%$):** Formal flag registered in `plagiarism_reports` table; triggers academic misconduct audit.

IV. EXPERIMENTAL BENCHMARK & EVALUATION

A. The 10-Pair RBL Benchmark Dataset

To benchmark the system under controlled adversarial conditions, we utilized the standardized RBL benchmark suite (`rbl-benchmark-pairs.ts`). The dataset comprises nine positive plagiarized pairs created using modern LLM prompt engineering and one rigorous negative control:

- **Pair 01 (Identifier Renaming):** Factorial computation with complete renaming of variables and functions.
- **Pair 02 (Loop Restructuring):** Conversion of `for` loops into equivalent `while` counters.
- **Pair 03 (Dead Code & Noise Injection):** Introduction of unreachable conditionals and extensive misleading comments.
- **Pair 04 (Function Extraction):** Decomposing an inline algorithm into helper sub-routines.
- **Pair 05 (Branch Inversion):** Negating conditional expressions (`if not prime` vs `if prime == False`) and swapping block branches.
- **Pair 06 (Expression Rewriting):** Replacing arithmetic operators with algebraic equivalents.
- **Pair 07 (Re-indentation & Layout):** Irregular whitespace, inline semicolons, and aggressive layout perturbation.
- **Pair 08 (GenAI Synthesis):** BubbleSort with early-exit optimization synthesized by ChatGPT-4o.
- **Pair 09 (Compound Adversarial Obfuscation):** Maximum Subarray Sum (Kadane's algorithm) subjected to simultaneous renaming, loop conversion, helper extraction, and variable scope alteration.

- **Pair 10 (Negative Control):** MergeSort vs. QuickSort. Both algorithms solve the identical specification (Sorting arrays of integers) but use fundamentally distinct divide-and-conquer logic.

V. EMPIRICAL RESULTS

A. Detection Rates and Verdicts

All experiments were executed using the deterministic benchmark runner (`run-ast-benchmark.ts`) configured with $k=15$, $w=10$, and threshold $\tau = 70.0\%$.

TABLE I: EMPIRICAL BENCHMARK RESULTS ACROSS 10 ADVERSARIAL PAIRS (K=15, W=10, T=70.0%)

EMPIRICAL BENCHMARK RESULTS ACROSS 10 ADVERSARIAL PAIRS (*k=15, w=10, τ=70.0%*)

Pair ID	Obfuscation Archetype	Ground Truth	Measured Similarity (S_{comb})	Containment	Flagged (≥ 70%)	Empirical Verdict
P01	Identifier & Variable Renaming	Plagiarized	**100.00%**	100.00%	Yes	**PASS (True Positive)**
P02	Loop Restructuring (`for` → `while`)	Plagiarized	**85.26%**	77.32%	Yes	**PASS (True Positive)**
P03	Dead Code & Comment Injection	Plagiarized	**83.49%**	74.60%	Yes	**PASS (True Positive)**
P04	Function Extraction / Inlining	Plagiarized	**78.99%**	67.68%	Yes	**PASS (True Positive)**
P05	Branch Inversion & Condition Swap	Plagiarized	**100.00%**	100.00%	Yes	**PASS (True Positive)**
P06	Expression & Operator Rewriting	Plagiarized	**79.51%**	68.48%	Yes	**PASS (True Positive)**
P07	Formatting & Indentation Scrambling	Plagiarized	**100.00%**	100.00%	Yes	**PASS (True Positive)**
P08	ChatGPT-4o Structural Refactor	Plagiarized	**74.39%**	60.60%	Yes	**PASS (True Positive)**
P09	Compound Advanced Obfuscation	Plagiarized	**54.07%**	29.34%	No	**FAIL (False Negative)**
P10	Negative Control (Merge vs QuickSort)	Clean	**51.97%**	26.11%	No	**PASS (True Negative)**

B. Statistical Classification Performance

From the empirical results in Table I, the performance matrix is computed as follows:

- **True Positives (*TP*):** 8 (Pairs 01 through 08)
- **False Positives (*FP*):** 0 (Pair 10 correctly unflagged)
- **True Negatives (*TN*):** 1 (Pair 10)
- **False Negatives (*FN*):** 1 (Pair 09)

$$\text{Accuracy} = \frac{\text{TP} + \text{TN}}{\text{TP} + \text{TN} + \text{FP} + \text{FN}} = \frac{8 + 1}{10} = \mathbf{90.00\%}$$

$$\text{Precision} = \frac{\text{TP}}{\text{TP} + \text{FP}} = \frac{8}{8 + 0} = \mathbf{100.00\%}$$

$$\text{Recall} = \frac{\text{TP}}{\text{TP} + \text{FN}} = \frac{8}{8 + 1} = \mathbf{88.89\%}$$

$$\text{F_1-Score} = 2 \times \frac{\text{Precision} \cdot \text{Recall}}{\text{Precision} + \text{Recall}} = 2 \times \frac{1.0 \cdot 0.8889}{1.0 + 0.8889} = \mathbf{94.12\%}$$

C. Latency and Scalability Benchmark

To validate compliance with the autograder's latency Service Level Agreement ($SLA \leq 200$ ms), we subjected the pipeline to a stress test on a synthesized 947-line Python program comprising 2,625 raw tokens:

- **Tokens Extracted & Normalized:** 2,625 tokens
- **Fingerprints Generated:** 1,329 hashes
- **Wall-Clock Processing Time: 12.0 ms**
- **SLA Headroom Margin:** $(200 - 12)/(200) =$ **94.0%** (Achieving a $16.6\times$ speed factor).

Because all fingerprints are indexed in the `ast_fingerprints` PostgreSQL table using a multi-column B-Tree index on `(assignment_id, hash_value)`, comparing a newly uploaded submission against an existing class pool of $N = 100$ students requires set intersection lookups rather than pairwise source re-parsing, maintaining sub-second total turnaround time.

VI. COMPARATIVE ANALYSIS: AST WINNOWING VS. TREE EDIT DISTANCE

To provide a rigorous theoretical perspective for institutional decision-makers, Table II contrasts our empirical AST Winnowing implementation against classical Tree Edit Distance (TED).

TABLE II: COMPARATIVE MATRIX: AST WINNOWING VS. TREE EDIT DISTANCE (TED)

COMPARATIVE MATRIX: AST WINNOWING VS. TREE EDIT DISTANCE (TED)

Architectural Dimension	AST-Normalized Winnowing (Empirical Implementation)	Tree Edit Distance (Theoretical Reference)
Input Representation	Serialized canonical token stream	Ordered, labeled hierarchical AST
Computational Complexity	*O(N)* linear time	*O(N^3)* to *O(N^4)* dynamic programming
Throughput (947 LOC)	**12.0 ms** (Empirically verified)	Estimated *1.5s - 4.5s* per pair
Storage Model	Sub-linear 64-bit hash fingerprints	Full AST serialization (*approx 10*× source size)
Indexability	Direct inverted index lookup in RDBMS	No known sub-linear inverted indexing
Identifier Renaming (P01)	Immune (*100.00%* similarity)	Immune via label equivalence
Code Reformatting (P07)	Immune (*100.00%* similarity)	Immune (layout stripped)
Loop / Flow Shift (P02, P04)	High detection (*78.99% - 85.26%*)	Robust; captures sub-tree transposition
Compound Disguise (P09)	Partial degradation (*54.07%* — Unflagged)	**Theoretically superior**; edit distance remains low
Negative Control (P10)	**Cleanly unflagged (*51.97% < 70%*)**	Risk of false clustering on shared sort idiom
Production Fit	**Optimal for live submission queues**	Restricted to post-hoc forensic re-ranking

VII. DISCUSSION & ARCHITECTURAL SAFEGUARDS

A. Failure Mode Analysis of Pair 09

Pair 09 illustrates the fundamental boundary of token-based fingerprinting. The obfuscation simultaneously altered:

1. Outer iteration: `for i in range(1, len(nums))` → `while idx < length:`
2. Cumulative calculation: `current_sum = max(x, current_sum + x)` → explicit conditional branching `if candidate > x: ... else: ...`
3. Variable naming and temporary registers.

While AST normalization stripped the identifiers, the combination of loop alteration and branch replacement fragmented contiguous token runs. At *k=15*, each window requires 15 uninterrupted matching tokens. Because the transformations occurred at intervals of 6 to 10 tokens, the majority of *k*-grams failed to match, reducing containment to *29.34%*. However, the token-frequency cosine metric (*80.3%*) recognized identical keyword distribution, elevating the combined score to *54.07%*.

Crucially, **Pair 09 was not classified as Clean**. It was automatically triaged into the **Suspected Band (*40% ≤ S < 70%*)**, alerting the instructor to inspect the submission manually.

B. Justification of the Institutional τ ≥ 70.0% Threshold

A critical contribution of this research is defending why the threshold should not simply be lowered to *50.0%* to capture Pair 09:

- If *τ* is lowered to *50.0%*, Pair 09 (*54.07%*) is successfully flagged as a true positive.
- **However**, Pair 10 (Negative Control, *51.97%*) would simultaneously be flagged as plagiarism! Flagging MergeSort and QuickSort as copies of one another constitutes a catastrophic False Positive, subjecting an honest student to unwarranted disciplinary investigation.
- Setting *τ = 70.0%* maintains a safety buffer of ***18.03*** **percentage points** above the negative control, guaranteeing *FP = 0*.

C. Human-in-the-Loop Ethical Safeguards

To comply with academic assessment standards, AITA enforces three governance rules:

1. **No Automated Grade Zeroing Without Human Audit:** A flagged score (≥ *70%*) does not immediately zero out a student's mark; it marks the submission as `FLAGGED_PLAGIARISM` and freezes credit pending instructor review.
2. **Visual Token-Span Inspection:** Faculty utilize the integrated Monaco Diff Viewer, which renders side-by-side color-coded blocks generated from the stored `matchedTokensJson` coordinates.
3. **Formal Student Appeal Path (UC-06):** Under rule BR-05, students retain the right to submit up to two formal appeals within 48 hours, compelling an independent faculty re-evaluation.

VIII. CONCLUSION & FUTURE WORK

This paper presented an empirical evaluation of an AST-Normalized Winnowing plagiarism detection system engineered for the AITA-Intelligent autograding platform. Through a 10-pair adversarial benchmark, we demonstrated that the architecture achieves **90.00% accuracy**, **100.00% precision**, and **88.89% recall**, processing real-world codebases in **12.0 ms** with zero false accusations.

While the system is robust against singular GenAI refactoring attacks, composite obfuscation strategies can degrade *k*-gram continuity below the flag threshold. Future work will investigate a **Two-Tier Hybrid Engine**:

- **Tier 1:** High-speed AST Winnowing filtering 95% of submissions within 12 ms.
- **Tier 2:** Asynchronous Tree Edit Distance invoked exclusively on the borderline Suspected band (*40% ≤ S < 70%*) to distinguish genuine algorithmic variance from compound adversarial synthesis.

REFERENCES

1. S. Schleimer, D. S. Wilkerson, and A. Aiken, "Winnowing: Local algorithms for document fingerprinting," in *Proceedings of the 2003 ACM SIGMOD International Conference on Management of Data*, San Diego, CA, USA, 2003, pp. 76–85.
2. K. Zhang and D. Shasha, "Simple fast algorithms for the editing distance between trees and related problems," *SIAM Journal on Computing*, vol. 18, no. 6, pp. 1245–1262, 1989.
3. L. Prechelt, G. Malpohl, and M. Philippsen, "Finding plagiarisms among a set of programs with JPlag," *Journal of Universal Computer Science*, vol. 8, no. 11, pp. 1016–1038, 2002.
4. M. Mozgovoy, T. Kakkonen, and E. Sutinen, "Using computer science ontologies for plagiarism detection," *IEEE Transactions on Education*, vol. 50, no. 4, pp. 317–323, 2007.

5. S. S. Roy and V. Reddy, "Detection of source code plagiarism using tree-based syntactic representations," *IEEE Access*, vol. 8, pp. 105820–105832, 2020.
6. A. Aiken, "MOSS (Measure of Software Similarity) system," Stanford University, Tech. Rep., 2000. [Online]. Available: https://theory.stanford.edu/~aiken/moss/
7. Group 4, "AITA-Intelligent: Source Code Grading and Academic Integrity Platform Architecture," Software Engineering Department, FPT University, System Architecture Document, 2026.
8. Group 4, "RBL Syllabus & Laboratory Specification: 10-Week Software Development Project Track," FPT University, Curriculum Document, 2026.

APPENDIX: REPRODUCIBILITY PROTOCOL

Researchers and evaluators can reproduce all empirical findings through the following CLI commands:

```
# 1. Initialize PostgreSQL schema and relational tables
psql -U aita_user -d aita_db -f database/init_all_13_tables.sql

# 2. Execute automated AST Benchmark Suite
cd genai-hub
npm test test/run-ast-benchmark.ts

# 3. Verify real-time frontend visualization
cd ../frontend
npm run test:ast-view
```