

\*\*\*\*\*Installing MariaDB Server\*\*\*\*\*

1] Put Network on Bridge -

server\_ip-192.168.0.100

2] Give HostName -

server-mariadbsrv1.radical.com

3] Make entry in /etc/hosts file

4] mount /dev/cdrom on /mnt

5] Make repository-

BaseOS

AppStream

6] yum search MariaDB

7] yum install -y mariadb.x86\_64

8] yum install -y mariadb-server.x86\_64

9] systemctl enable --now mariadb.service

10]systemctl status MariaDB.service

PROCEDURE:-

1]Put Network on Bridge - 192.168.0.100

2] Give HostName -mariadbsrv1.radical.com

[root@localhost yum.repos.d]# hostnamectl set-hostname  
mariadbsrv1.radical.com

3] Make entry in /etc/hosts file

[root@localhost yum.repos.d]# vi /etc/hosts

192.168.0.100 mariadbsrv1.radical.com

4] mount /dev/cdrom on /mnt

root@localhost yum.repos.d]# mount /dev/cdrom /mnt/

mount: /mnt: WARNING: source write-protected, mounted read-only.

## 5] Make repository-

BaseOS

```
vi /etc/yum.repos.d/BaseOS.repo
```

```
[BaseOS]
```

```
name=This is BaseOS
```

```
baseurl=file:///mnt/BaseOS
```

```
enabled=1
```

```
gpgcheck=0
```

AppStream

```
vi /etc/yum.repos.d/AppStream.repo
```

```
[AppStream]
```

```
name=This is AppStream
```

```
baseurl=file:///mnt/AppStream
```

```
enabled=1
```

```
gpgcheck=0
```

## 6] yum search MariaDB

```
yum search mariadb
```

```
mariadb.x86_64 : A very fast and robust SQL database server
```

```
mariadb-server.x86_64 : The MariaDB server and related files
```

## 7] yum install -y mariadb.x86\_64

```
[root@localhost yum.repos.d]# yum install -y mariadb.x86_64
```

Updating Subscription Management repositories.

Unable to read consumer identity

This system is not registered with an entitlement server. You can use subscription-manager to register.

Last metadata expiration check: 0:03:18 ago on Wed 10 Jun 2026 10:33:54 PM IST.

Dependencies resolved.

```
=====
=====
=====
```

| Package    | Architecture | Version |
|------------|--------------|---------|
| Repository | Size         |         |
| =====      |              |         |
| =====      |              |         |
| =====      |              |         |

Installing:

|           |        |                   |
|-----------|--------|-------------------|
| mariadb   | x86_64 | 3:10.5.16-2.el9_0 |
| AppStream | 1.6 M  |                   |

Installing dependencies:

|                            |        |                   |
|----------------------------|--------|-------------------|
| mariadb-common             | x86_64 | 3:10.5.16-2.el9_0 |
| AppStream                  | 39 k   |                   |
| mariadb-connector-c        | x86_64 | 3.2.6-1.el9_0     |
| AppStream                  | 203 k  |                   |
| mariadb-connector-c-config | noarch | 3.2.6-1.el9_0     |
| AppStream                  | 11 k   |                   |
| perl-Sys-Hostname          | x86_64 | 1.23-480.el9      |
| AppStream                  | 20 k   |                   |

Transaction Summary

```
=====
=====
=====
```

Install 5 Packages

Total size: 1.8 M

Installed size: 19 M

Downloading Packages:

Running transaction check

Transaction check succeeded.

Running transaction test

Transaction test succeeded.

Running transaction

Preparing :  
1/1

Installing : mariadb-connector-c-config-3.2.6-1.el9\_0.noarch  
1/5

Installing : mariadb-common-3:10.5.16-2.el9\_0.x86\_64  
2/5

Installing : mariadb-connector-c-3.2.6-1.el9\_0.x86\_64  
3/5

Installing : perl-Sys-Hostname-1.23-480.el9.x86\_64  
4/5

Installing : mariadb-3:10.5.16-2.el9\_0.x86\_64  
5/5

Running scriptlet: mariadb-3:10.5.16-2.el9\_0.x86\_64  
5/5

Verifying : mariadb-3:10.5.16-2.el9\_0.x86\_64  
1/5

Verifying : mariadb-common-3:10.5.16-2.el9\_0.x86\_64  
2/5

Verifying : mariadb-connector-c-3.2.6-1.el9\_0.x86\_64  
3/5

Verifying : mariadb-connector-c-config-3.2.6-1.el9\_0.noarch  
4/5

Verifying : perl-Sys-Hostname-1.23-480.el9.x86\_64  
5/5

Installed products updated.

Installed:

```
mariadb-3:10.5.16-2.el9_0.x86_64      mariadb-common-3:10.5.16-2.el9_0.x86_64
mariadb-connector-c-3.2.6-1.el9_0.x86_64  mariadb-connector-c-config-3.2.6-
1.el9_0.noarch
```

```
perl-Sys-Hostname-1.23-480.el9.x86_64
```

Complete!

```
8] yum install -y mariadb-server.x86_64
```

```
[root@localhost yum.repos.d]# yum install -y mariadb-server.x86_64
```

Updating Subscription Management repositories.

Unable to read consumer identity

This system is not registered with an entitlement server. You can use subscription-manager to register.

Last metadata expiration check: 0:04:01 ago on Wed 10 Jun 2026 10:33:54 PM IST.

Dependencies resolved.

```
=====
=====
=====
```

| Package    | Architecture | Version |
|------------|--------------|---------|
| Repository | Size         |         |
| =====      |              |         |
| =====      |              |         |
| =====      |              |         |

Installing:

|                |        |                   |
|----------------|--------|-------------------|
| mariadb-server | x86_64 | 3:10.5.16-2.el9_0 |
| AppStream      | 9.4 M  |                   |

Installing dependencies:

|                |        |                   |
|----------------|--------|-------------------|
| mariadb-errmsg | x86_64 | 3:10.5.16-2.el9_0 |
| AppStream      | 227 k  |                   |
| mysql-selinux  | noarch | 1.0.5-1.el9_0     |
| AppStream      | 37 k   |                   |

|                  |        |               |
|------------------|--------|---------------|
| perl-DBD-MariaDB | x86_64 | 1.21-16.el9_0 |
| AppStream        | 156 k  |               |

|                |        |              |
|----------------|--------|--------------|
| perl-File-Copy | noarch | 2.34-480.el9 |
| AppStream      | 22 k   |              |

Installing weak dependencies:

|                |        |                   |
|----------------|--------|-------------------|
| mariadb-backup | x86_64 | 3:10.5.16-2.el9_0 |
| AppStream      | 6.4 M  |                   |

|                       |        |                   |
|-----------------------|--------|-------------------|
| mariadb-gssapi-server | x86_64 | 3:10.5.16-2.el9_0 |
| AppStream             | 21 k   |                   |

|                      |        |                   |
|----------------------|--------|-------------------|
| mariadb-server-utils | x86_64 | 3:10.5.16-2.el9_0 |
| AppStream            | 222 k  |                   |

Transaction Summary

=====

=====

=====

Install 8 Packages

Total size: 17 M

Installed size: 90 M

Downloading Packages:

Running transaction check

Transaction check succeeded.

Running transaction test

Transaction test succeeded.

Running transaction

Preparing :  
1/1

Installing : perl-File-Copy-2.34-480.el9.noarch  
1/8

Installing : perl-DBD-MariaDB-1.21-16.el9\_0.x86\_64

2/8

Running scriptlet: mysql-selinux-1.0.5-1.el9\_0.noarch

3/8

Installing : mysql-selinux-1.0.5-1.el9\_0.noarch

3/8

Running scriptlet: mysql-selinux-1.0.5-1.el9\_0.noarch

3/8

libsemanage.semanage\_direct\_install\_info: Overriding mysql module at lower priority 100 with module at priority 200.

Installing : mariadb-errmsg-3:10.5.16-2.el9\_0.x86\_64

4/8

Installing : mariadb-gssapi-server-3:10.5.16-2.el9\_0.x86\_64

5/8

Installing : mariadb-server-utils-3:10.5.16-2.el9\_0.x86\_64

6/8

Running scriptlet: mariadb-server-3:10.5.16-2.el9\_0.x86\_64

7/8

Installing : mariadb-server-3:10.5.16-2.el9\_0.x86\_64

7/8

Running scriptlet: mariadb-server-3:10.5.16-2.el9\_0.x86\_64

7/8

Installing : mariadb-backup-3:10.5.16-2.el9\_0.x86\_64

8/8

Running scriptlet: mysql-selinux-1.0.5-1.el9\_0.noarch

8/8

Running scriptlet: mariadb-backup-3:10.5.16-2.el9\_0.x86\_64

8/8

Verifying : mariadb-backup-3:10.5.16-2.el9\_0.x86\_64

1/8

Verifying : mariadb-errmsg-3:10.5.16-2.el9\_0.x86\_64

2/8

Verifying : mariadb-gssapi-server-3:10.5.16-2.el9\_0.x86\_64  
3/8

Verifying : mariadb-server-3:10.5.16-2.el9\_0.x86\_64  
4/8

Verifying : mariadb-server-utils-3:10.5.16-2.el9\_0.x86\_64  
5/8

Verifying : mysql-selinux-1.0.5-1.el9\_0.noarch  
6/8

Verifying : perl-DBD-MariaDB-1.21-16.el9\_0.x86\_64  
7/8

Verifying : perl-File-Copy-2.34-480.el9.noarch  
8/8

Installed products updated.

Installed:

|                                                |                                         |
|------------------------------------------------|-----------------------------------------|
| mariadb-backup-3:10.5.16-2.el9_0.x86_64        | mariadb-errmsg-3:10.5.16-2.el9_0.x86_64 |
| mariadb-gssapi-server-3:10.5.16-2.el9_0.x86_64 | mariadb-server-3:10.5.16-2.el9_0.x86_64 |
| mariadb-server-utils-3:10.5.16-2.el9_0.x86_64  | mysql-selinux-1.0.5-1.el9_0.noarch      |
| perl-DBD-MariaDB-1.21-16.el9_0.x86_64          | perl-File-Copy-2.34-480.el9.noarch      |

Complete!

9] systemctl enable --now mariadb.service

[root@localhost yum.repos.d]# systemctl enable --now mariadb.service

Created symlink /etc/systemd/system/mysql.service →  
/usr/lib/systemd/system/mariadb.service.

Created symlink /etc/systemd/system/mysqld.service →  
/usr/lib/systemd/system/mariadb.service.

Created symlink /etc/systemd/system/multi-  
user.target.wants/mariadb.service → /usr/lib/systemd/system/mariadb.service.

10]systemctl status MariaDB.service

root@localhost yum.repos.d]# systemctl status mariadb.service



mariadb.service - MariaDB 10.5 database server

Loaded: loaded (/usr/lib/systemd/system/mariadb.service; enabled; preset: disabled)

Active: active (running) since Wed 2026-06-10 22:41:24 IST; 19s ago

Docs: man:mariabdb(8)

<https://mariadb.com/kb/en/library/systemd/>

Process: 39753 ExecStartPre=/usr/libexec/mariadb-check-socket (code=exited, status=0/SUCCESS)

Process: 39775 ExecStartPre=/usr/libexec/mariadb-prepare-db-dir mariadb.service (code=exited, status=0/SUCCESS)

Process: 39872 ExecStartPost=/usr/libexec/mariadb-check-upgrade (code=exited, status=0/SUCCESS)

Main PID: 39858 (mariabdb)

Status: "Taking your SQL requests now..."

Tasks: 13 (limit: 10800)

Memory: 73.3M

CPU: 1.354s

CGroup: /system.slice/mariadb.service

└─39858 /usr/libexec/mariabdb --basedir=/usr

Jun 10 22:41:23 mariadbsrv1.radical.com mariadb-prepare-db-dir[39814]: you need to be the system 'mysql' user to connect.

Jun 10 22:41:23 mariadbsrv1.radical.com mariadb-prepare-db-dir[39814]: After connecting you can set the password, if you would need to be

Jun 10 22:41:23 mariadbsrv1.radical.com mariadb-prepare-db-dir[39814]: able to connect as any of these users with a password and without sudo

Jun 10 22:41:23 mariadbsrv1.radical.com mariadb-prepare-db-dir[39814]: See the MariaDB Knowledgebase at <https://mariadb.com/kb>

Jun 10 22:41:23 mariadbsrv1.radical.com mariadb-prepare-db-dir[39814]: Please report any problems at <https://mariadb.org/jira>

Jun 10 22:41:23 mariadbsrv1.radical.com mariadb-prepare-db-dir[39814]: The latest

information about MariaDB is available at <https://mariadb.org/>.

Jun 10 22:41:23 mariadbsrv1.radical.com mariadb-prepare-db-dir[39814]: Consider joining MariaDB's strong and vibrant community:

Jun 10 22:41:23 mariadbsrv1.radical.com mariadb-prepare-db-dir[39814]:  
<https://mariadb.org/get-involved/>

Jun 10 22:41:23 mariadbsrv1.radical.com mariadbd[39858]: 2026-06-10 22:41:23 0 [Note]  
/usr/libexec/mariadbd (mysqld 10.5.16-MariaDB) starting as process 39858 ...

Jun 10 22:41:24 mariadbsrv1.radical.com systemd[1]: Started MariaDB 10.5 database server.

\*\*\*\*\*Installing MariaDB on Client\*\*\*\*\*

1] Put Network on Bridge -

client\_ip-192.168.0.101

2] mount /dev/cdrom on /mnt

3] Make repository-

BaseOS

AppStream

4] yum search MariaDB

5] a) yum install -y mariadb.x86\_64

b) yum install -y mariadb-serve.x86\_64

6] systemctl enable --now mariadb.service

7] systemctl status MariaDB.service

PROCEDURE

1] Put Network on Bridge -

client\_ip-192.168.0.101

2] mount /dev/cdrom on /mnt

root@localhost:/etc/yum.repos.d# mount /dev/cdrom /mnt/

mount: /mnt: WARNING: source write-protected, mounted read-only.

3] Make repository-

BaseOS

AppStream

4] yum search MariaDB

mariadb.x86\_64 : A very fast and robust SQL database server

mariadb-server.x86\_64 : The MariaDB server and related files

5] a) yum install -y mariadb.x86\_64

root@localhost:/etc/yum.repos.d# yum install -y mariadb.x86\_64

Updating Subscription Management repositories.

Unable to read consumer identity

This system is not registered with an entitlement server. You can use "rhc" or "subscription -manager" to register.

This is BaseOS 66 MB/s | 1.5 MB 00:00

This is AppStream 57 MB/s | 1.5 MB 00:00

Dependencies resolved.

=====

| Package | Arch | Version | Repository | Size |
|---------|------|---------|------------|------|
|---------|------|---------|------------|------|

=====

Installing:

|         |        |                   |           |       |
|---------|--------|-------------------|-----------|-------|
| mariadb | x86_64 | 3:10.11.11-1.el10 | AppStream | 1.6 M |
|---------|--------|-------------------|-----------|-------|

Installing dependencies:

|                |        |                   |           |      |
|----------------|--------|-------------------|-----------|------|
| mariadb-common | noarch | 3:10.11.11-1.el10 | AppStream | 36 k |
|----------------|--------|-------------------|-----------|------|

|                     |        |              |        |       |
|---------------------|--------|--------------|--------|-------|
| mariadb-connector-c | x86_64 | 3.4.4-1.el10 | BaseOS | 215 k |
|---------------------|--------|--------------|--------|-------|

|                            |        |              |        |      |
|----------------------------|--------|--------------|--------|------|
| mariadb-connector-c-config | noarch | 3.4.4-1.el10 | BaseOS | 11 k |
|----------------------------|--------|--------------|--------|------|

|                   |        |                   |           |      |
|-------------------|--------|-------------------|-----------|------|
| perl-Sys-Hostname | x86_64 | 1.25-512.2.el10_0 | AppStream | 18 k |
|-------------------|--------|-------------------|-----------|------|

Installing weak dependencies:

mariadb-common-3:10.11.11-1.el10.noarch

mariadb-connector-c-3.4.4-1.el10.x86\_64

mariadb-connector-c-config-3.4.4-1.el10.noarch

perl-Sys-Hostname-1.25-512.2.el10\_0.x86\_64

Complete!

b] yum install -y mariadb-serve.x86\_64

root@localhost:/etc/yum.repos.d# yum install -y mariadb-server.x86\_64

Updating Subscription Management repositories.

Unable to read consumer identity

This system is not registered with an entitlement server. You can use "rhc" or "subscription-manager" to register.

Last metadata expiration check: 0:00:11 ago on Wed 10 Jun 2026 10:17:22 AM IST.

Dependencies resolved.

=====

| Package | Arch | Version | Repository | Size |
|---------|------|---------|------------|------|
|---------|------|---------|------------|------|

=====

Installing:

|                |        |                   |           |       |
|----------------|--------|-------------------|-----------|-------|
| mariadb-server | x86_64 | 3:10.11.11-1.el10 | AppStream | 9.9 M |
|----------------|--------|-------------------|-----------|-------|

Installing dependencies:

|                  |        |                   |           |       |
|------------------|--------|-------------------|-----------|-------|
| mariadb-errmsg   | noarch | 3:10.11.11-1.el10 | AppStream | 267 k |
| mysql-selinux    | noarch | 1.0.14-1.el10_0   | AppStream | 37 k  |
| perl-DBD-MariaDB | x86_64 | 1.23-10.el10      | AppStream | 160 k |
| perl-File-Copy   | noarch | 2.41-512.2.el10_0 | AppStream | 21 k  |

Installing weak dependencies:

|                       |        |                   |           |       |
|-----------------------|--------|-------------------|-----------|-------|
| mariadb-backup        | x86_64 | 3:10.11.11-1.el10 | AppStream | 6.6 M |
| mariadb-gssapi-server | x86_64 | 3:10.11.11-1.el10 | AppStream | 18 k  |

mariadb-server-utils x86\_64 3:10.11.11-1.el10 AppStream 262 k

## Transaction Summary

=====

Install 8 Packages

Total size: 17 M

Installed size: 98 M

Downloading Packages:

Running transaction check

Transaction check succeeded.

Running transaction test

Transaction test succeeded.

Running transaction

Preparing : 1/1

Installing : perl-File-Copy-2.41-512.2.el10\_0.noarch 1/8

Installing : perl-DBD-MariaDB-1.23-10.el10.x86\_64 2/8

Running scriptlet: mysql-selinux-1.0.14-1.el10\_0.noarch 3/8

Installing : mysql-selinux-1.0.14-1.el10\_0.noarch 3/8

Running scriptlet: mysql-selinux-1.0.14-1.el10\_0.noarch 3/8

libsemanage.semanage\_direct\_install\_info: Overriding mysql module at lower priority 100 with module at priority 200.

Installing : mariadb-errmsg-3:10.11.11-1.el10.noarch 4/8

Installing : mariadb-gssapi-server-3:10.11.11-1.el10.x86\_64 5/8

Installing : mariadb-server-utils-3:10.11.11-1.el10.x86\_64 6/8

Running scriptlet: mariadb-server-3:10.11.11-1.el10.x86\_64 7/8

Installing : mariadb-server-3:10.11.11-1.el10.x86\_64 7/8

|                                                            |     |
|------------------------------------------------------------|-----|
| Running scriptlet: mariadb-server-3:10.11.11-1.el10.x86_64 | 7/8 |
| Installing : mariadb-backup-3:10.11.11-1.el10.x86_64       | 8/8 |
| Running scriptlet: mysql-selinux-1.0.14-1.el10_0.noarch    | 8/8 |
| Running scriptlet: mariadb-backup-3:10.11.11-1.el10.x86_64 | 8/8 |

Installed products updated.

Installed:

mariadb-backup-3:10.11.11-1.el10.x86\_64  
mariadb-errmsg-3:10.11.11-1.el10.noarch  
mariadb-gssapi-server-3:10.11.11-1.el10.x86\_64  
mariadb-server-3:10.11.11-1.el10.x86\_64  
mariadb-server-utils-3:10.11.11-1.el10.x86\_64  
mysql-selinux-1.0.14-1.el10\_0.noarch  
perl-DBD-MariaDB-1.23-10.el10.x86\_64  
perl-File-Copy-2.41-512.2.el10\_0.noarch

Complete!

6] systemctl enable --now mariadb.service

root@localhost:/etc/yum.repos.d# systemctl enable --now mariadb.service

Created symlink '/etc/systemd/system/mysql.service' →  
'/usr/lib/systemd/system/mariadb.service'.

Created symlink '/etc/systemd/system/mysqld.service' →  
'/usr/lib/systemd/system/mariadb.service'.

Created symlink '/etc/systemd/system/multi-user.target.wants/mariadb.service' →  
'/usr/lib/systemd/system/mariadb.service'.

root@localhost:/etc/yum.repos.d#

root@localhost:/etc/yum.repos.d#

7]systemctl status MariaDB.service

root@localhost:/etc/yum.repos.d# systemctl status mariadb.service

mariadb.service - MariaDB 10.11 database server

Loaded: loaded (/usr/lib/systemd/system/mariadb.service; enabled; preset: disabled)

Active: active (running) since Thu 2026-06-11 00:01:38 IST; 59s ago

Invocation: 90d0b0734ccd4e8bb9b0a077b24f1777

Docs: man:mariadb(8)

<https://mariadb.com/kb/en/library/systemd/>

Process: 5217 ExecStartPre=/usr/libexec/mariadb-check-socket (code=exited, status=0/SUCCESS)

Process: 5240 ExecStartPre=/usr/libexec/mariadb-prepare-db-dir mariadb.service (code=exited, status=0/SUCCESS)

Process: 5341 ExecStartPost=/usr/libexec/mariadb-check-upgrade (code=exited, status=0/SUCCESS)

Main PID: 5327 (mariabdb)

Status: "Taking your SQL requests now..."

Tasks: 12 (limit: 10148)

Memory: 93.4M (peak: 122.9M)

CPU: 1.546s

CGroup: /system.slice/mariadb.service

└─5327 /usr/libexec/mariabdb --basedir=/usr

Jun 11 00:01:38 localhost.localdomain mariadb-prepare-db-dir[5279]: you need to be the system 'mysql' user to connect.

Jun 11 00:01:38 localhost.localdomain mariadb-prepare-db-dir[5279]: After connecting you can set the password, if you would need to be

Jun 11 00:01:38 localhost.localdomain mariadb-prepare-db-dir[5279]: able to connect as any of these users with a password and without sudo

Jun 11 00:01:38 localhost.localdomain mariadb-prepare-db-dir[5279]: See the MariaDB Knowledgebase at <https://mariadb.com/kb>

Jun 11 00:01:38 localhost.localdomain mariadb-prepare-db-dir[5279]: Please report any problems at <https://mariadb.org/jira>



Jun 11 00:01:38 localhost.localdomain mariadb-prepare-db-dir[5279]: The latest information about MariaDB is available at <https://mariadb.org/>.

Jun 11 00:01:38 localhost.localdomain mariadb-prepare-db-dir[5279]: Consider joining MariaDB's strong and vibrant community:

Jun 11 00:01:38 localhost.localdomain mariadb-prepare-db-dir[5279]: <https://mariadb.org/get-involved/>

Jun 11 00:01:38 localhost.localdomain (mariabdb)[5327]: mariadb.service: Referenced but unset environment variable evaluates to an empty string: MYSQLD\_OPTS, \_WSREP\_NEW\_CLUSTER

Jun 11 00:01:38 localhost.localdomain systemd[1]: Started mariadb.service - MariaDB 10.11 database server.

\*\*\*\*\*ACCESSING MYSQL FROM SERVER\*\*\*\*\*

1]setting password to root user

2]view databases

3]create database

4]use database

5]create tables in database

6]exit

PROCEDURE

1]]login root user

[root@localhost yum.repos.d]# mysql -u root -p

Enter password:

Welcome to the MariaDB monitor. Commands end with ; or \g.

Your MariaDB connection id is 3

Server version: 10.5.16-MariaDB MariaDB Server

Copyright (c) 2000, 2018, Oracle, MariaDB Corporation Ab and others.

Type 'help;' or '\h' for help. Type '\c' to clear the current input statement.

MariaDB [(none)]>

2]view databases

MariaDB [(none)]> show databases;

+-----+

| Database |
|----------|
|----------|

+-----+

|                    |
|--------------------|
| information_schema |
|--------------------|

|       |
|-------|
| mysql |
|-------|

|                    |
|--------------------|
| performance_schema |
|--------------------|

+-----+

3 rows in set (0.003 sec)

3]create database

MariaDB [(none)]> create database sd;

Query OK, 1 row affected (0.001 sec)

MariaDB [(none)]> show databases;

+-----+

| Database |
|----------|
|----------|

+-----+

|                    |
|--------------------|
| information_schema |
|--------------------|

|       |
|-------|
| mysql |
|-------|

|                    |
|--------------------|
| performance_schema |
|--------------------|

|    |
|----|
| sd |
|----|

+-----+

4 rows in set (0.001 sec)

4]use database

MariaDB [(none)]> use sd;

Database changed

5]create tables in database

MariaDB [sd]> create table books (ID INT,Name VARCHAR(30),Author VARCHAR(20));

Query OK, 0 rows affected (0.009 sec)

MariaDB [sd]> show tables;

+-----+

| Tables\_in\_sd |

+-----+

| books |

+-----+

1 row in set (0.001 sec)

6]exit

MariaDB [sd]> exit;

Bye

[root@localhost yum.repos.d]#

\*\*\*\*\*

\*\*\*\*\*CONNECT FROM CLIENT SIDE\*\*\*\*\*

\*\*\*From server side\*\*\*

1]check port 3306 is listening which service

2]add port 3306 to firewall.d

3]edit configuration file /etc/mycnf.d/Mariadb.server.cnf

4]systemctl restart Mariadb

5]Create remote user on server

1-login to MariaDB

2-Create DB user with password

3-Grant all privileges to db user

4-Flush privileges

6]check db user

\*\*\*From client side\*\*\*

1]Ping <server\_ip>

2]check who is using port 3306

3]login from client to server with db user

4]Show databases

5]use sd database

6]Insert data in books

PROCEDURE

1]check port 3306 is listening which service

```
[root@localhost yum.repos.d]# ss -tulnp |grep 3306

tcp    LISTEN 0      80          *:3306      *.*
users:(("mariadb",pid=39858,fd=16))
```

2]add port 3306 to firewall.d

```
[root@localhost yum.repos.d]# firewall-cmd --permanent --add-port=3306/tcp

success
```

```
[root@localhost yum.repos.d]# firewall-cmd --reload

success
```

```
[root@localhost yum.repos.d]# firewall-cmd --list-all |grep 3306

ports: 3306/tcp
```

3]edit configuration file /etc/my.cnf.d/Mariadb.server.cnf

```
[root@localhost yum.repos.d]# vi /etc/my.cnf.d/mariadb-server.cnf

uncomment this line
```

```
#bind-address=0.0.0.0
```

```
bind-address=0.0.0.0
```

4]systemctl restart MariaDB

```
[root@localhost yum.repos.d]# systemctl restart mariadb.service
```

5]Create remote user on server

1-login to MariaDB

```
[root@localhost yum.repos.d]# mysql -u root -p
```

Enter password:

Welcome to the MariaDB monitor. Commands end with ; or \g.

Your MariaDB connection id is 3

Server version: 10.5.16-MariaDB MariaDB Server

Copyright (c) 2000, 2018, Oracle, MariaDB Corporation Ab and others.

Type 'help;' or '\h' for help. Type '\c' to clear the current input statement.

MariaDB [(none)]>

2-Create DB user with password

```
MariaDB [(none)]> CREATE USER 'dbuser'@'%' IDENTIFIED BY 'redhat';
```

Query OK, 0 rows affected (0.002 sec)

MariaDB [(none)]>

3-Grant all privileges to db user

```
MariaDB [(none)]> GRANT ALL PRIVILEGES ON *.* TO 'dbuser'@'%';
```

Query OK, 0 rows affected (0.001 sec)

MariaDB [(none)]>

4-Flush privileges

MariaDB [(none)]> FLUSH PRIVILEGES;

Query OK, 0 rows affected (0.001 sec)

6]check db user

MariaDB [(none)]> SELECT user,host FROM mysql.user;

```
+-----+-----+
| User   | Host   |
+-----+-----+
| dbuser | %      |
| mariadb.sys | localhost |
| mysql  | localhost |
| root   | localhost |
+-----+-----+
```

4 rows in set (0.005 sec)

MariaDB [(none)]>

From client side

1]Ping <server\_ip>

root@localhost:/etc/yum.repos.d# ping -c1 192.168.0.100

PING 192.168.0.100 (192.168.0.100) 56(84) bytes of data.

64 bytes from 192.168.0.100: icmp\_seq=1 ttl=64 time=3.88 ms

--- 192.168.0.100 ping statistics ---

1 packets transmitted, 1 received, 0% packet loss, time 0ms

rtt min/avg/max/mdev = 3.879/3.879/3.879/0.000 ms

2]check who is using port 3306

```
root@localhost:/etc/yum.repos.d# telnet 192.168.0.100 3306
```

```
Trying 192.168.0.100...
```

```
Connected to 192.168.0.100.
```

```
Escape character is '^['.
```

```
Y
```

```
5.5.5-10.5.16-MariaDBzqJ^ygu:\Cz^I2ZRkJ-mysql_native_password
```

```
Connection closed by foreign host.
```

3]login from client to server with db user

```
root@localhost:/etc/yum.repos.d# mysql -u dbuser -p -h 192.168.0.100
```

```
Enter password:
```

```
Welcome to the MariaDB monitor. Commands end with ; or \g.
```

```
Your MariaDB connection id is 5
```

```
Server version: 10.5.16-MariaDB MariaDB Server
```

```
Copyright (c) 2000, 2018, Oracle, MariaDB Corporation Ab and others.
```

```
Type 'help;' or '\h' for help. Type '\c' to clear the current input statement.
```

```
MariaDB [(none)]>
```

4]Show databases

```
MariaDB [(none)]> show databases;
```

```
+-----+
```

```
| Database      |
```

```
+-----+
```

```
| information_schema |
```

```
| mysql          |
```

```
| performance_schema |
```

```
| sd              |
```

```
+-----+
```

4 rows in set (0.003 sec)

5]use sd database

MariaDB [(none)]> use sd

Reading table information for completion of table and column names

You can turn off this feature to get a quicker startup with -A

Database changed

MariaDB [sd]> show tables;

```
+-----+
```

```
| Tables_in_sd |
```

```
+-----+
```

```
| books      |
```

```
+-----+
```

1 row in set (0.002 sec)

6]Insert data in books

MariaDB [sd]> insert into books (ID,Name,Author) value(1,"War as I knew it","Gen Patton");

Query OK, 1 row affected (0.004 sec)

MariaDB [sd]>

MariaDB [sd]>

MariaDB [sd]> select \* from books;

```
+-----+-----+-----+
```

```
| ID | Name          | Author  |
```

```
+-----+-----+-----+
```

```
| 1 | War as I knew it | Gen Patton |
```

```
+-----+-----+-----+
```



1 row in set (0.003 sec)