

Purpose:- How to set path variables in rhel9 for individual users & for all users

Purpose 1:- First we will set path variables for individual users.

Method-1:- Keep the script under path variables directory location.

### Step-1

Lets check the path variables directories

```
[root@rhel9prosrv ~]# echo $PATH
/root/.local/bin:/root/bin:/usr/local/bin:/usr/local/sbin:/usr/bin:/usr/sbin
```

### Step-2

As we are doing it for root user we will keep the file under /root/.local/bin

```
[root@rhel9prosrv ~]# cp /mydata/myscript/netscan /root/.local/bin/
[root@rhel9prosrv ~]# ls /root/.local/bin/
netscan
```

### Verification

```
[root@rhel9prosrv ~]# netscan
***This script will check your private ip is up or not***
***private ip is up***
[root@rhel9prosrv ~]#
```

Method-2:- Set the PATH variables

### Step-1

We will keep the scripts in our desired locations.

```
[root@rhel9prosrv ~]# cd /mydata/myscript/
[root@rhel9prosrv myscript]# ls
netscan
[root@rhel9prosrv myscript]# pwd
/mydata/myscript
[root@rhel9prosrv myscript]#
```

## Step-2

Now we will search using grep command to search PATH keyword under /root

```
[root@rhel9prosrv ~]# grep -r "PATH" /root
grep: /root/.cache/gstreamer-1.0/registry.x86_64.bin: binary file matches
/root/.bash_history:grep -r "PATH" /etc
/root/.bash_history:echo $PATH
/root/.bash_history:echo $PATH
/root/.bash_history:echo $PATH
/root/.bash_history:echo $PATH
/root/.bash_history:echo $PATH
/root/.bashrc:if ! [[ "$PATH" =~ "$HOME/.local/bin:$HOME/bin:" ]]
/root/.bashrc:    PATH="$HOME/.local/bin:$HOME/bin:$PATH"
/root/.bashrc:    # PATH="$HOME/.local/bin:$HOME/bin:$PATH:/mydata/myscript"
```

## Step-3

Now we got the file /root/.bashrc so we will set the path

```
# User specific environment
if ! [[ "$PATH" =~ "$HOME/.local/bin:$HOME/bin:" ]]
then
    # PATH="$HOME/.local/bin:$HOME/bin:$PATH"
    PATH="$HOME/.local/bin:$HOME/bin:$PATH:/mydata/myscript"
fi
export PATH
```

## Step-4

Now we will source that file but still we are not able to see that path.

```
[root@rhel9prosrv ~]# source /root/.bashrc
[root@rhel9prosrv ~]# echo $PATH
/root/.local/bin:/root/bin:/usr/local/bin:/usr/local/sbin:/usr/bin:/usr/sbin
```

So we will perform login & out

Now we are able to see the path under path variable

```
[root@rhel9prosrv ~]# echo $PATH
/root/.local/bin:/root/bin:/usr/local/bin:/usr/local/sbin:/usr/bin:/usr/sbin:/mydata/myscript
[root@rhel9prosrv ~]#
```

### Verification

Now our script is running as a command.

```
[root@rhel9prosrv ~]# netscan
***This script will check your private ip is up or not***
***private ip is up***
[root@rhel9prosrv ~]#
```

Purpose 2:- Now we will set the path variables for all users.

### Step-1

As we want to do it for all users we need to grep the path keywords under /etc which contains all the configuration files.

```
[root@rhel9prosrv ~]# grep -r "PATH" /etc
/etc/skel/.bashrc:if ! [[ "$PATH" =~ "$HOME/.local/bin:$HOME/bin:" ]]
/etc/skel/.bashrc:    PATH="$HOME/.local/bin:$HOME/bin:$PATH"
/etc/skel/.bashrc:export PATH
/etc/X11/xinit/Xsession:SWITCHDESKPATH=/usr/share/switchdesk
/etc/X11/xinit/Xsession:    if [ -x "$SWITCHDESKPATH/Xclients $1" ]; then
```

### Step-2

In the previous version of rhel we do it under /etc/bashrc file so lets check this file.

```
# /etc/bashrc

# System wide functions and aliases
# Environment stuff goes in /etc/profile

# It's NOT a good idea to change this file unless you know what you
# are doing. It's much better to create a custom.sh shell script in
# /etc/profile.d/ to make custom changes to your environment, as this
# will prevent the need for merging in future updates.
```

It is advising us not to edit this file as with future updates these settings made by us might have a chance of reset. It is telling us to create a [custom.sh](#) script in /etc/profile.d/ directory.

### Step-3

We went to the location /etc/profile.d/ & we need to create a file with the .sh extension.

```
[root@rhel9prosrv ~]# cd /etc/profile.d/
[root@rhel9prosrv profile.d]# ls
bash_completion.sh  colorxzgrep.csh  debuginfod.csh  lang.csh  sh.local
colorgrep.csh       colorxzgrep.sh   debuginfod.sh   lang.sh    vite.csh
colorgrep.sh        colorzgrep.csh   flatpak.sh      less.csh   vite.sh
colorls.csh         colorzgrep.sh    gawk.csh        less.sh    which2.csh
colorls.sh          csh.local        gawk.sh         PackageKit.sh  which2.sh
[root@rhel9prosrv profile.d]# touch mylocal.sh
[root@rhel9prosrv profile.d]# ls
bash_completion.sh  colorxzgrep.csh  debuginfod.csh  lang.csh  PackageKit.sh  which2.sh
colorgrep.csh       colorxzgrep.sh   debuginfod.sh   lang.sh    sh.local
colorgrep.sh        colorzgrep.csh   flatpak.sh      less.csh   vite.csh
colorls.csh         colorzgrep.sh    gawk.csh        less.sh    vite.sh
colorls.sh          csh.local        gawk.sh         mylocal.sh which2.csh
[root@rhel9prosrv profile.d]#
```

### Step-4

In this file we need to set the PATH variables.

```
PATH=$PATH:/mydata/myscript
```

Then we need to source this file.

```
[root@rhel9prosrv profile.d]# source /etc/profile.d/mylocal.sh
```

## Verification

Now lets check the path variable & run the command.

```
[root@rhel9prosrv profile.d]# echo $PATH
/root/.local/bin:/root/bin:/usr/local/bin:/usr/local/sbin:/usr/bin:/usr/sbin:/mydata/myscript
```

```
[root@rhel9prosrv profile.d]# netscan
***This script will check your private ip is up or not***
***private ip is up***
```

It's Working.