```cpp
#include <iostream>
#include <unordered_map>
#include <string>

using namespace std;

class Dictionary
{
        private:
                unordered_map<string, string> hashTable; // Stores key-value pairs

        public:
                void insert (const string &key ,const string &value )
                {
                        if (hashTable.find(key) != hashTable.end())
                        {
                        cout << "Key '" << key << "' already exists. Updating its value.\n";
                        }
                        hashTable[key] = value ;
                        cout << "Inserted/Updated: (" << key << ", " << value << ")\n";
                }

                void find (const string &key)
                {
                        if (hashTable.find(key) != hashTable.end( ))
                        {
                                cout <<"Found:("<<key<<","<<hashTable[key]<<")\n";
                        }
                        else
                        {
                                cout << "'Key"<<key<<"'not found .\n";
                        }
                }

                void remove (const string &key)
                {
                        if (hashTable.erase(key))
                        {
                                cout << "Key'"<<key<<"'deletead successfully.\n";
                        }
                        else
                        {
                                cout << "Key '"<<key<<"'not found .\n";
                        }
                }


```

```
                void display()
                {
                        if (hashTable.empty())
                        {
                                cout << "The dictionary is empty.\n";
                        }
                        else
                        {
                                cout << "Current dictionary contents:\n";

                                for (const auto &pair : hashTable)
                                {
                                cout<<"("<<pair.first<<","<<pair.second<<")\n";
                                }
                        }
                }
};

int main ()
{
        Dictionary dict ;
        int choice ;
        string key , value ;

        do {
                cout << "\n Dictionary Operations : \n";
                cout << "1. Insert\n";
                cout << "2. Find\n";
                cout << "3. Delete\n";
                cout << "4. Display\n";
                cout << "5. Exit\n";

                cout << "Enter your chioce :";
                cin >> choice ;

                switch (choice)
                {
                        case 1:
                                cout << "Enter Key : ";
                                cin >> key ;
                                cout << "Enter value : ";
                                cin >> value ;
                                dict.insert (key,value);
                                break;

                        case 2 :
                                cout << "Enter key to find : ";
                                cin >> key ;
                                dict.find (key);
                                break;
```

```
                        case 3 :
                                cout << "Enter key to delete : ";
                                cin >> key ;
                                dict.remove (key);
                                break;

                        case 4:
                                dict.display();
                                break;


                        case 5:
                                cout << "Exiting program.\n";
                                break;

                        default:
                                cout << "Invalid chice . Please try again .\n";
                    }
                }
                while (choice != 5 );
                return 0 ;
}
```

Output:


Select D:\SE Computer\LAB CODES\DSA\DSA2.exe
Dictionary Operations :
1. Insert
2. Find
3. Delete
4. Display
5. Exit
Enter your choice: 1
Enter Key: Name
Enter Value: Shiv
Inserted/Updated: (Name, Shiv)
Dictionary Operations :
1. Insert
2. Find
3. Delete
4. Display
5. Exit
Enter your choice: 1
Enter Key: Age
Enter Value: 20
Inserted/Updated: (Age, 20)
Dictionary Operations :
1. Insert
2. Find
3. Delete
4. Display
5. Exit
Enter your choice: 1
Enter Key: Class
Enter Value: SE
Inserted/Updated: (Class, SE)
Dictionary Operations :
1. Insert
2. Find
3. Delete
4. Display
5. Exit
Enter your choice: 1
Enter Key: Div
Enter Value: C
Inserted/Updated: (Div, C)
Dictionary Operations :
1. Insert
2. Find
3. Delete


Select D:\SE Computer\LAB CODES\DSA\DSA2.exe
3. Delete
4. Display
5. Exit
Enter your choice: 3
Enter key to delete: class
Key 'class' not found.
Dictionary Operations :
1. Insert
2. Find
3. Delete
4. Display
5. Exit
Enter your choice: 3
Enter key to delete: Class
Key 'Class' deleted successfully.
Dictionary Operations :
1. Insert
2. Find
3. Delete
4. Display
5. Exit
Enter your choice: 2
Enter key to find: Name
Found:(Name,Shiv)
Dictionary Operations :
1. Insert
2. Find
3. Delete
4. Display
5. Exit
Enter your choice: 4
Current dictionary contents:
(Age, 20)
(Div, C)
(Name, Shiv)
Dictionary Operations :
1. Insert
2. Find
3. Delete
4. Display
5. Exit
Enter your choice: 5
Exiting program.
