Week 12 APP DEV-2

2025 Dec18 ET

1. [Source Q6; MCQ]

You are working in VS Code terminal with Git CLI. You are currently on branch appdev2, and you want to merge the latest changes from the main branch into appdev2. Which of the following command sequences correctly performs the merge with a commit?

(a)

```
git checkout main
git merge appdev2
git commit -m "Merged main into appdev2"
```

(b)

```
git merge main
git commit -m "Merged main into appdev2"
```

(c)

```
git checkout appdev2
git pull origin main
git commit -m "Pulled changes from main into appdev2"
```

(d)

```
git merge appdev2 main
git commit -m "Merged main into appdev2"
```

[Source ans: b]

2026 May06 ET

2. [Source Q26; MSQ]

Hamza is working on a project using Git and performs the following operations: Creates a new branch and switches to it1. Stages changes for commit2. Commits changes with a message3. Pushes the branch to a remote repository4. Which of the following commands are correctly used for these operations?

(a)
```
git checkout -b feature-branch
```

(b) `git add .`

(c)
```
git commit -m "Initial commit"
```

(d)
```
git push origin feature-branch
```

(e)
```
git branch feature-branch && git checkout main
```

(f)
```
git push feature-branch origin
```

[Source ans: a, b, c, d]

2026 Sep13 ET

3. [Source Q8; MCQ]

Match the testing concept in Column I with the most appropriate description in Column II.

Column I	Column II
1. Unit Testing	A. Testing application behaviour across different browsers
2. E2E Testing	B. Commonly used for writing and running tests
3. Cross-Browser Testing	C. Testing individual Vue components independently
4. Jest / Mocha / Chai	D. Testing a complete application flow including backend interaction

(a) 1-C, 2-B, 3-A, 4-D

(b) 1-B, 2-C, 3-D, 4-A

(c) 1-A, 2-D, 3-B, 4-C

(d) 1-C, 2-D, 3-A, 4-B

[Source ans: d]

4. [Source Q10; MCQ]

A developer has just created a new Vue 2 project using Vue CLI and the following package.json was generated. package.json

```
{
  "name": "my-vue-app",
  "version": "0.1.0",
  "scripts": {
    "serve": "vue-cli-service serve",
    "build": "vue-cli-service build",
    "lint": "vue-cli-service lint"
  },
  "dependencies": {
    "vue": "^2.6.14"
  },
  "devDependencies": {
    "@vue/cli-service": "^5.0.0",
    "babel-eslint": "^10.1.0"
  }
}
```

The developer wants to view the app in the browser locally for development. They run the following command: bash: `npm run build` Which of the following best describes what happens and what the developer should have run instead?

(a) `npm run build` launches the app on `localhost:8080` ; the developer should have run npm start to compile for production instead.

(b) `npm run build` and `npm run serve` do the same thing - both launch the app at `localhost:8080`

(c) `npm run build` is correct for local development; `npm run serve` is only used for deploying to a server.

(d) `npm run build` compiles and bundles the app for production into a `/dist` folder - it does not start a local server. The developer should have run `npm run serve` instead.

[Source ans: d]