Ship detection in Sentinel-1 radar against AIS: six pre-registered tests of what transfers to new water

Shivaji Patil
shivaji@shivajipatil.com https://shivaji-patil.github.io/sar-ship-detection-demo/

Technical note, November 2026

Abstract

A dark-vessel pipeline finds ships in Sentinel-1 radar and flags those that AIS does not explain. Here six choices made on water already used were each tested on new water, under rules committed before any of that water's data was fetched, and each test was scored once. Of five tests in 23 new US areas, three ideas did not transfer and one did. A learned detector that passed its promotion gate produced more false alarms than classical constant false-alarm rate (CFAR) detection re-thresholded to find as many ships. A threshold set for a false-alarm budget gave 20.6 instead of 10 per 1,000 km^2 (22.8 before the platform list was applied). A map of recurring unexplained returns, built from each region's own first six months, cut dark-list false alarms by 34% in five new areas (41% as first scored) and by 65% in five structure-rich ones, once spots where vessels moor were left unmasked. In five dense federal platform fields, where nearly every structure was already listed, it showed no demonstrated improvement (9% fewer false alarms). On the Grand Banks of Newfoundland it found 3 of the 4 listed production installations, short of its pre-registered bar of all four. A flag for vessels hiding beside structures caught about two thirds of injected vessels but raised too many false alarms in dense platform fields; calibrated on each area's own history, it failed both bars in five dense fields (9% caught, 1.04 added). A sixth test, in seven Norwegian and UK production areas scored against the regulators' installation lists, widened the map's recurrence radius from 100 to 300 m for production ships that swing on their moorings: it found 15 of 16 against 12, three more where its bar was five, and added 3 places away from any installation (*no demonstrated improvement*). AI code review (OpenAI Codex) found twelve defects before the fourth test was frozen, and a platform list left out of two scorers was applied after the fact. Every result comes from scripts in the repository run on public data; re-running the first test also needs the trained weights, which are in the repository's release, not in git.

1 Pipeline and data

Sentinel-1 IW ground-range scenes, radiometrically terrain-corrected to γ^0 at 10 m (Microsoft Planetary Computer; Torres et al. 2012; Small 2011), are read for each area's box. Open water comes from Overture Maps water polygons minus piers and bridges, shrunk 150 m off the coast. Detection is two-parameter CFAR on the cross-polarised band in dB (guard window 310 m, background 810 m, threshold k on the local z-score, fragments within 100 m merged, at least three pixels; Crisp 2004); production runs at $k = 5$. Truth is NOAA MarineCadastre AIS for 2024 (Office for Coastal Management 2026), interpolated to the overpass. A detection matches a ship inside a region shaped by the radar geometry: 300 m around the AIS position, stretched along track by the expected azimuth shift of a moving ship and along the course for a held fix. Detections within 150 m of a standing BOEM platform are left out of the score, as are AIS ships there. The headline metric is the probability of detection (Pd) at a fixed false-alarm rate, 5 per 1,000 km^2, read from the operating curve swept over k; false alarms are unmatched detections, an upper bound as vessels without AIS count against the detector.

2 Protocol

For each test, a script chose the passes by a fixed rule from scene metadata alone (for each area and month of 2024, the first scene covering at least 95% of the box), and wrote the rule, the areas, the endpoints and the reading rule to a configuration file, with SHA-256 hashes of what was frozen: for the first test, fingerprints of both detectors; for the second and third, the detector and the code under test; for the fourth to sixth, every file

Test	Rules committed	Scored	Pre-registered reading
1. Learned detector v6 vs CFAR	033e970 4 Nov 01:15	8500765 4 Nov 02:16	v6 worse on fresh water
2. False-alarm budget	fdc8a64 4 Nov 03:18	58cfe24 4 Nov 04:46	budget does not hold
3. Structure map	24e4baf 4 Nov 09:24	13a0041 4 Nov 10:20	improvement
Grand Banks installations	d756a57 4 Nov 18:11	06c75db 4 Nov 18:58	3 of 4 found (bar: 4)
4. Map, occupied spots dropped; alongside flag	82f9dbb 5 Nov 00:21	e0a83ab 5 Nov 01:51	map improvement; flag does not transfer
5. Calibrated alongside flag in dense fields	27dc282 5 Nov 03:57	de50f3b 5 Nov 05:03	flag does not work; map no demonstrated improvement
6. Map radius 300 m against 100 m	79a443c 6 Nov 00:07	5388472 6 Nov 02:32	no demonstrated improvement

Table 1: Pre-registrations: commit and time (UTC, 2026) from the repository history. The Grand Banks rules were a local commit; the others were pushed to GitHub before scoring, the fourth to sixth before fetching.

the scorer uses, the scorer included. That file was committed before any radar or AIS data for those areas was fetched and pushed to GitHub before scoring (for the fourth to sixth tests, before fetching). The scorer refuses to run if a hashed file changed or if a result file already exists, and the git history shows one scoring commit per test (Nosek et al. 2018). The first test's scorer, not hashed, was fixed once after pre-registration (commit f551fd5): its first run stopped on a division by zero before computing any metric. Table 1 lists the commits. Intervals are bootstrap percentiles (Efron and Tibshirani 1993; 20,000 draws). The pre-registered intervals of the first three tests resample passes within each area and hold the areas fixed; the fourth and fifth resample areas, then passes within each drawn area (Field and Welsh 2007), which is the interval for a new set of areas. Zero events are reported with the exact one-sided bound (Clopper and Pearson 1934). The sixth test uses exact methods only (sign test, Clopper–Pearson, Poisson).

3 Results

3.1 Test 1: a learned detector against CFAR

A Sentinel-1-pretrained ResNet-50 scoring CFAR's candidates (registry v6) passed the promotion gate on the 12 earlier test passes. On 36 fresh passes in three new areas, its Pd at 5 FA minus CFAR's was -0.019 (-0.053 to $+0.021$), and at equal recall it produced 59% more false alarms than CFAR re-thresholded to $k = 6.5$ (15% to 116%). It was not promoted, and the gate gained an equal-recall rule; v6 still passes that rule on the original test passes (8.1 against 9.2 false alarms per 1,000 km^2), so only the fresh test caught it.

3.2 Test 2: a false-alarm budget

A threshold fixed at $k = 6$ to give 10 false alarms per 1,000 km^2 on 129 earlier passes gave 22.8 (21.3–24.4) on 60 passes in five new areas, and 58.3 in Mobile Bay. An adaptive threshold did not even out the areas and cost Pd (-0.047 at the same pooled false-alarm rate). Scored again with the platform exclusion, the pooled rate is 20.6; resampling the areas, its interval is 6.7–39.4 and includes the budget, and without Mobile Bay it is 10.1.

3.3 Test 3: a structure map from a region's own history

The map adds no detector: a spot goes on it when returns that no AIS ship explains recur within 100 m on at least three of a region's January–June passes; on July–December passes, unexplained returns within 150 m of a spot leave the dark list, and returns an AIS ship explains are kept. In five new areas, false alarms at $k = 5$ fell 41% and Pd at 5 FA rose +0.082 as scored. *Correction:* the scorer had left out the platform exclusion; 8 BOEM platforms stand in the Sabine Pass box. Scored again with it (post hoc, after reproducing the published numbers exactly), the cut is 34% and the Pd gain +0.046, +0.027 to +0.094 with areas fixed and +0.006 to +0.120 with areas resampled. No AIS ship sat at a spot: 0 of 217 vessels, at most 1.4%.




Figure 1: Left: the structure map's Pd gain at 5 false alarms per 1,000 km^2 (thick, areas fixed; thin, areas resampled). Middle and right: the alongside flag's recovery of injected vessels and its added false alarms, development (diamonds, no interval) and test (dots, areas resampled); dashed lines are the pre-registered bars.

3.4 The Grand Banks: does the map find the regulator's installations?

With no AIS and no list of structures, the map built from six HH/HV passes over the Jeanne d'Arc Basin found 3 of the 4 C-NLOPB production installations (Hibernia 85 m, Hebron 57 m, Terra Nova 134 m) and the new West White Rose platform, with no other spot; the pre-registered bar was all four. SeaRose was missed: its return is on 12 of 12 passes but 1,999 m from the listed point and within about 200 m of two independent published positions, and the turret-moored FPSO swings up to 382 m between passes, beyond the map's 100 m rule.

3.5 Development: vessels at map spots, and a flag for vessels alongside

Masking structures has a cost. In Mobile Bay, 7 of 37 AIS ships on the July–December passes lay within 150 m of a spot built from January–June: some recurring returns are moorings and waiting berths. Leaving unmasked any spot that had an AIS ship beside it on a map pass cut that to 2, at the price of Mobile Bay's dark-list cut falling from 80% to 54%. A second idea flags a structure instead of hiding it: each structure's signature (separate returns within 150 m and the size of the largest) comes from the map passes, and a later pass flags it when it shows an extra return or one more than GROW times the largest seen. It was scored by adding real ship returns 60–140 m from structures (1,537 injections) and counting false flags as added false alarms. GROW = 1.5 was the most sensitive setting within 1.0 added false alarm per 1,000 km^2 (0.94): it flagged 60% of injected vessels (31%, 66% and 84% of small, medium and large returns). Three passes of AI code review (OpenAI Codex) found twelve defects in this scorer before it was frozen; fixing them lowered the recovery from 73% to 60%.

3.6 Test 4: structure-rich new water

Five areas chosen for their structures (four Louisiana fields with 56 standing platforms, and the Santa Barbara Channel, whose platforms are not on the federal Gulf list). The map, occupied spots dropped, cut false alarms by 65% (35–75%) and raised Pd at 5 FA from 0.50 to 0.93 (+0.019 to +0.720, areas resampled), with 2 of 129 AIS ship-passes at a spot (2 of 115 vessels); keeping the occupied spots would have exposed 7 of 129: an *improvement*. The alongside flag caught 66% of 1,547 injected vessels (54–70%), meeting its bar, but added 1.87 false alarms per 1,000 km^2 against a bar of 1.0: it *does not transfer*. Afterwards, 16 of the 23 false flags were found to come from Main Pass's 26-platform field; without it the rate would have been 0.67.

3.7 Test 5: a calibrated flag in dense platform fields

Two calibrations were developed on the ten areas used so far. One GROW per area, chosen by leave-one-pass-out on the area's own map passes, met the false-alarm bar (0.65) by switching the flag off in Main Pass, and caught

only 42%. Calibrating structures with a neighbour within 500 m apart from isolated ones met both bars, narrowly (0.86 and 50%); 1,000 and 2,000 m did not. The fifth test applies it to the five densest federal fields in a scan of the Gulf (18 to 88 standing structures each). On 30 test passes (28 AIS ships) the calibrated flag caught 9% of 3,666 injected vessels (2–19%) for 1.04 added false alarms per 1,000 km^2 (0.40–1.79); 3 of 19 AIS ships beside a structure were flagged when scored as dark. For comparison, the fixed GROW = 1.5 caught 32% for 2.65: clustered platforms change too much from pass to pass for a changed-signature rule. The map, scored again, found 2 spots in all five fields and cut false alarms by 9% (0–21%), with 0 of 27 distinct AIS vessels at a spot: almost every structure there is on the federal list that production already leaves out, so the map had little to add. The pre-registered readings: the calibrated flag *does not work*, and the map showed *no demonstrated improvement*.

3.8 Test 6: a wider radius for production ships that swing

SeaRose swings further between passes than the map's 100 m recurrence radius. A 300 m radius, chosen after seeing that data, was tested in seven Norwegian and UK production areas with no AIS: truth was the regulators' lists (Sodir FactPages; NSTA), and each unit's mooring and independent positions came from public, non-AIS sources, all fixed before any radar was fetched. Both radii built maps from the same CFAR detections on six November–April VV/VH passes per area (84 passes, 22,431 km^2 of map water). Of 16 turret- or buoy-moored units, 100 m found 12 and 300 m 15 within 500 m of the listed position ($b = 3$, $c = 0$; exact one-sided sign test $p = 0.125$; the bar was $b \geq 5$); the gained units swing 389–452 m, and non-swinging floating hulls were found by both. With independent positions also accepted: 13 and 16 (Jotun's listed point is about 600 m off). 300 m lost no other site and masked more later detections at the units (72 against 52 of 99), but added 3 places away from any installation (0.13 per 1,000 km^2; bar 0.1). The reading: *no demonstrated improvement*; production keeps 100 m. The power computed beforehand, at the rate seen here, was about 0.2.

4 What transferred, and what did not

- **Local maps transferred; global settings did not.** A threshold and a learned detector tuned elsewhere failed on new water. A map built from each region's own history was an improvement in 2 of the 3 tests that scored it (in the fifth, almost every structure was already listed), and its one transferable rule (leave a spot unmasked if an AIS ship sat there) was learned from a single bay and held on new water.
- **Dense structures are the hard case.** Mobile Bay decided the budget test, and Main Pass decided the flag test; in five dense fields even a calibrated flag caught only 9%. Pooled results hide this; leave-one-area-out numbers and area-resampled intervals show it.
- **AIS is limited truth near structures.** Many of the flag's false alarms in dense fields are probably small service boats without AIS: real vessels the metric counts against the detector. Progress there needs another kind of truth, such as analyst review.
- **Review and correction are part of the result.** AI code review moved one development number by 13 points before a test, and two published figures were corrected after the fact once the platform list was applied, with both versions kept.
- **A published position is a claim to check.** SeaRose's listed point is about 2 km from its returns and Jotun's about 600 m; a test scored against a registry needs independent positions fixed in advance, as the sixth had.
- **Small effects need many units.** The wider radius found three of the four swinging units that 100 m missed, yet three of 16 cannot pass the sign test; the power table written before the data said this was likely.

5 Limitations

AIS-scored passes are US waters in 2024, VV/VH; the Grand Banks check is HH/HV and the sixth test VV/VH, both with no AIS. Boats under 25 m are often missed at 10 m. Five areas per test give coarse area-resampled intervals. The map needs six months of a region's passes, and the alongside flag is scored on injected returns standing in for moored vessels.

6 Reproducibility

Code: `https://github.com/shivaji-patil/maritime-target-correlation` (GitHub's push log for each test's `fresh*-prereg` branch dates its rules). The note is built from the results files by `tools/build_note.py`. Re-running the first test needs the learned detector's trained weights, and the fourth and fifth check the BOEM platform file against a download of 22 Oct 2026; both are in the release `repro-2026-11-05`, not in git. The fourth re-runs at its scoring commit `e0a83ab`, not on `main`. An AI coding agent wrote much of the code under the author's direction. Data: contains modified Copernicus Sentinel data (2024–2026). Sentinel-1 RTC from Microsoft Planetary Computer (processed by Catalyst), licensed by Microsoft under CC BY 4.0 (`https://creativecommons.org/licenses/by/4.0/`). AIS: Office for Coastal Management (2026), from U.S. Coast Guard Navigation Center data; U.S. Government data, no access constraints. Water and piers: Overture Maps (includes OpenStreetMap data, ODbL); platforms: BOEM (U.S. Government), C-NLOER (formerly C-NLOPB), Government of Newfoundland and Labrador; contains data from the Norwegian Offshore Directorate (Sodir) FactPages, under NLOD 2.0; contains information provided by the North Sea Transition Authority and/or other third parties (NSTA User Agreement, non-commercial use).

References

Clopper, C. J., and Pearson, E. S. (1934). The use of confidence or fiducial limits illustrated in the case of the binomial. *Biometrika* 26(4), 404–413.

Crisp, D. J. (2004). *The State-of-the-Art in Ship Detection in Synthetic Aperture Radar Imagery.* DSTO-RR-0272, Defence Science and Technology Organisation, Australia.

Efron, B., and Tibshirani, R. J. (1993). *An Introduction to the Bootstrap.* Chapman and Hall.

Field, C. A., and Welsh, A. H. (2007). Bootstrapping clustered data. *Journal of the Royal Statistical Society B* 69(3), 369–390.

Nosek, B. A., et al. (2018). The preregistration revolution. *PNAS* 115(11), 2600–2606.

Office for Coastal Management (2026). Nationwide Automatic Identification System 2024 [InPort metadata record]. NOAA. `https://www.fisheries.noaa.gov/inport/item/73064`. Data from the U.S. Coast Guard Navigation Center.

Small, D. (2011). Flattening gamma: radiometric terrain correction for SAR imagery. *IEEE Transactions on Geoscience and Remote Sensing* 49(8), 3081–3093.

Torres, R., et al. (2012). GMES Sentinel-1 mission. *Remote Sensing of Environment* 120, 9–24.