Topic 11: HTTP Request Node

Step 1: Create a New Workflow

1. Open your browser and log into your n8n workspace.
2. In the left navigation, click on **Workflows**.
3. Click the **Add workflow** button in the top-right corner.
4. Rename your workflow in the top-left corner to: `Topic 11 HTTP Request Node Workflow`.
5. Click the orange **Save** button.

Step 2: Add and Configure the HTTP Request GET Node

We will fetch mock user profile data from a public API.

1. Click the **Add first step** button in the center of the canvas grid.
2. Search for and select the **When clicking "Test workflow"** node (Manual Trigger).
3. Click the output connector (+ icon) on the right edge of the **Manual Trigger** node.
4. Search for and select the **HTTP Request** node.
5. Rename the node to `Fetch User`.
6. Double-click the node to open the configuration:
    a. **Method:** Select `GET`.
    b. **URL:** Enter https://jsonplaceholder.typicode.com/users/1.
    c. **Authentication:** Select `None` (JSONPlaceholder is a public API).
7. Close the configuration panel. Hover over the `Fetch User` node and click the **Test step** icon.
8. Verify that the output panel displays user data in structured JSON format (e.g., displaying `id`, `name`, `username`, `email`).

Step 3: Configure the Edit Fields Node to Prepare the Payload

We will capture user details from the GET response and format them into a payload for our POST request.

1. Click the output connector (+ icon) on the right edge of the `Fetch User` node.
2. Search for and select the **Edit Fields (Set)** node.
3. Rename this node to `Prepare Post Payload`.
4. Double-click the node to configure it. Under **Fields to Set**, add the following two string fields:
    a. Field 1 (String):
        i. Name: `title`

        ii. Value: Click the expression button and enter `User Post by {{ $json.name }}`
    b. **Field 2 (String):**
        i. Name: `body`
        ii. Value: Click the expression button and enter `Email: {{ $json.email }}`
5. Close the configuration panel. Hover over the node and click the **Test step** icon to run it and load the mapped output.

Step 4: Add and Configure the HTTP Request POST Node

We will send our prepared payload back to a public mock endpoint using a POST request.

1. Click the output connector (+ icon) on the right edge of the `Prepare Post Payload` node.
2. Search for and select another **HTTP Request** node.
3. Rename the node to `Send Custom Post`.
4. Double-click the node to configure it:
    a. **Method:** Select `POST`.
    b. **URL:** Enter https://jsonplaceholder.typicode.com/posts.
    c. **Send Body:** Toggle this switch to **On** (enabled).
    d. **Body Content Type:** Select `JSON`.
    e. **Specify Body:** Select `Using Fields Below`.
    f. **Fields to Send:** Add two parameter fields:
        i. **Parameter 1:**
            1. Name: `title`
            2. Value: `{{ $json.title }}` (dynamic expression)
        ii. **Parameter 2:**
            1. Name: `body`
            2. Value: `{{ $json.body }}` (dynamic expression)
5. Close the configuration panel.

Step 5: Run and Verify the Entire Workflow

1. Click the large orange **Test workflow** button at the bottom-center of the canvas.
2. Verify that all nodes run successfully and turn green.
3. Click on the final `Send Custom Post` node and inspect the **Output** panel.
4. Verify that:
    a. The status is successful.
    b. The returned JSON contains the submitted `title` (e.g. `User Post by Leanne Graham`) and `body` (e.g. `Email: Sincere@april.biz`).

    c. A mock resource `id` (typically `101`) was returned by JSONPlaceholder, indicating the fake record was successfully "created".
5. Click **Save** in the top-right corner to save your workflow.