

Step 1 — Create ZPO_LONGTEXT in SE11

Field-by-Field SE11 Creation Guide

Confirmed: TDID = F01 | Language = D | EKPO TDNAME = no space | 2026-06-28

■ Confirmed from your system: TDID = F01 for both Header (EKKO) and Item (EKPO) texts Language = D (German) EKPO TDNAME = 450007774400010 (no space between PO# and item#)

What You Will Create

ZPO_LONGTEXT is a custom database table that stores the decompressed, plain-text content of PO long texts. Each row in this table = one line of text. Once created and populated by the BADl (Step 3), any ABAP program can read PO long texts with a simple SELECT — no READ_TEXT function module needed.

Quick Field Summary

#	Field Name	Key	Data Type	Length	Data Element / Note	Description
1	MANDT	✓	CLNT	3	MANDT	Client — always first key field
2	EBELN	✓	CHAR	10	EBELN	Purchase Order Number
3	EBELP	✓	NUMC	5	EBELP	Item — 00000 for header texts
4	TDOBJECT	✓	CHAR	10	TDOBJECT	EKKO or EKPO
5	TDID	✓	CHAR	4	TDID	F01, F02, F09 etc.
6	TDSPRAS	✓	LANG	1	SPRAS	Language key: D
7	LINE_COUNTER	✓	NUMC	5	—	Line sequence 00001, 00002...
8	TDFORMAT		CHAR	2	TDFORMAT	Format indicator (* = normal)
9	TDLINE		CHAR	132	TDLINE	Plain text content
10	MIGRATED_AT		DATS	8	—	Date row was written
11	MIGRATED_BY		CHAR	12	UNAME	User who wrote this row
12	SOURCE		CHAR	1	—	M=Migration, D=Dual-write

A

Open SE11 and Start Table Creation

Transaction SE11 — Database Table — ZPO_LONGTEXT

1

Open SE11

Enter transaction code: SE11 → press Enter

2

Select Database Table

In the Object Type section, select the radio button: Database Table

3

Enter table name

In the input field enter exactly: ZPO_LONGTEXT Click Create button (or press F5)

4

Enter Short Description

Short Description field: PO Long Text New Persistency Press Enter to move to the Fields tab

Initial Table Properties to Set

Delivery Class	A	A = Application table (customer data). Set in Attributes tab.
Data Browser/Table View Maintenance	Display/Maintenance Allowed	Allows SE16N browsing and SM30 maintenance. Set in Attributes tab.
Enhancement Category	Can Be Enhanced (Deep)	Set via menu: Extras → Enhancement Category. Allows future structure appends.

Add Fields — One Row at a Time

B

Fields tab — add each field in order, key fields first

In SE11 Fields tab: each row = one field. Tick the 'Key' checkbox for key fields. Enter the Data Element name — SE11 auto-fills Data Type and Length from the data element. For fields without a standard data element, enter Data Type and Length manually.

Key Fields (tick Key checkbox ✓)

#	Field Name	Key	Data Element	Type	Len	SE11 Entry Instructions
1	MANDT	✓	MANDT	CLNT	3	Enter field name MANDT → Data Element: MANDT → SE11 auto-fills CLNT/3 Tick Key checkbox ✓
2	EBELN	✓	EBELN	CHAR	10	Enter field name EBELN → Data Element: EBELN → SE11 auto-fills CHAR/10 Tick Key checkbox ✓
3	EBELP	✓	EBELP	NUMC	5	Enter field name EBELP → Data Element: EBELP → SE11 auto-fills NUMC/5 Tick Key checkbox ✓ NOTE: Header texts use EBELP = 00000, item texts use actual item number
4	TDOBJECT	✓	TDOBJECT	CHAR	10	Enter field name TDOBJECT → Data Element: TDOBJECT → SE11 auto-fills CHAR/10 Tick Key checkbox ✓ Values: EKKO (header) or EKPO (item)
5	TDID	✓	TDID	CHAR	4	Enter field name TDID → Data Element: TDID → SE11 auto-fills CHAR/4 Tick Key checkbox ✓ Values: F01 (confirmed), F02, F09 etc.
6	TDSPRAS	✓	SPRAS	LANG	1	Enter field name TDSPRAS → Data Element: SPRAS → SE11 auto-fills LANG/1 Tick Key checkbox ✓ Value: D (German in this system)
7	LINE_COUNTER	✓	—	NUMC	5	Enter field name LINE_COUNTER → NO standard data element Enter manually: Data Type = NUMC, Length = 5 Tick Key checkbox ✓ This drives ORDER BY for correct text line sequence

Non-Key Fields (do NOT tick Key checkbox)

#	Field Name	Data Element	Type	Len	SE11 Entry Instructions
8	TDFORMAT	TDFORMAT	CHAR	2	Data Element: TDFORMAT → auto-fills CHAR/2 Stores format indicator. Value * = normal text line (standard SAP).
9	TDLINE	TDLINE	CHAR	132	Data Element: TDLINE → auto-fills CHAR/132 THE MAIN FIELD — stores the actual plain text content of each line. Max 132 characters per line (SAP standard text line limit).
10	MIGRATED_AT	—	DATS	8	NO data element. Enter manually: Data Type = DATS, Length = 8 Stores the date this row was written (sy-datum at write time).
11	MIGRATED_BY	UNAME	CHAR	12	Data Element: UNAME → auto-fills CHAR/12 Stores the user who wrote this row (sy-uname at write time).
12	SOURCE	—	CHAR	1	NO data element. Enter manually: Data Type = CHAR, Length = 1 M = written by migration program D = written by BAdI dual-write on PO save

C

Save, Activate and Verify

Final steps after adding all 12 fields

1

Save the table

Press Ctrl+S → assign to package: ZMM (or your development package) Transport request: assign to your active workbench
transport Save

2

Activate the table

Press Ctrl+F3 (Activate) OR Menu: Table → Activate Status bar must show: Object ZPO_LONGTEXT activated If errors appear →
check field definitions match the table above

3

Verify in SE11

SE11 → Database Table → ZPO_LONGTEXT → Display Top area shows: Active Fields tab shows all 12 fields with correct Key
ticks

4

Create Secondary Index (recommended)

SE11 → ZPO_LONGTEXT → Display → Indexes button → Create Index name: ZPO_LT_I01 Add fields: EBELN, TDOBJECT,
TDID Save → Activate This speeds up queries filtering by PO number + text type

5

Verify table is empty

SE16N → ZPO_LONGTEXT → Execute (no filters) Result: No entries — expected at this stage Table will be populated after Step
3 (BAId) is active

■ Step 1 complete when: SE11 → ZPO_LONGTEXT → Status = Active All 12 fields present with correct Key ticks (7 key fields) SE16N
→ ZPO_LONGTEXT → table accessible (empty = correct)

D

Quick Reference — All 12 Fields at a Glance

Print this page and keep it open while creating the table in SE11

#	Field Name	Key	Data Type	Length	Data Element / Note	Description
1	MANDT	✓	CLNT	3	MANDT — standard	Client
2	EBELN	✓	CHAR	10	EBELN — standard	Purchase Order Number
3	EBELP	✓	NUMC	5	EBELP — standard	PO Item (00000 = header)
4	TDOBJECT	✓	CHAR	10	TDOBJECT — standard	Text Object: EKKO / EKPO
5	TDID	✓	CHAR	4	TDID — standard	Text ID: F01 confirmed
6	TDSPRAS	✓	LANG	1	SPRAS — standard	Language: D confirmed
7	LINE_COUNTER	✓	NUMC	5	Manual — no DE	Line sequence 00001...
8	TDFORMAT		CHAR	2	TDFORMAT — standard	Format indicator (* = normal)
9	TDLINE		CHAR	132	TDLINE — standard	Plain text content ← main field
10	MIGRATED_AT		DATS	8	Manual — no DE	Date row was written
11	MIGRATED_BY		CHAR	12	UNAME — standard	User who wrote this row
12	SOURCE		CHAR	1	Manual — no DE	M=Migration D=Dual-write

Data Elements — Standard vs Manual Entry

Field	Data Element	Entry Method
MANDT	MANDT	Type DE name → SE11 auto-fills Type+Length
EBELN	EBELN	Type DE name → SE11 auto-fills Type+Length
EBELP	EBELP	Type DE name → SE11 auto-fills Type+Length
TDOBJECT	TDOBJECT	Type DE name → SE11 auto-fills Type+Length
TDID	TDID	Type DE name → SE11 auto-fills Type+Length
TDSPRAS	SPRAS	Type DE name → SE11 auto-fills Type+Length
LINE_COUNTER	—	NO data element — enter NUMC / 5 manually
TDFORMAT	TDFORMAT	Type DE name → SE11 auto-fills Type+Length
TDLINE	TDLINE	Type DE name → SE11 auto-fills CHAR/132
MIGRATED_AT	—	NO data element — enter DATS / 8 manually
MIGRATED_BY	UNAME	Type DE name → SE11 auto-fills CHAR/12

SOURCE	—	NO data element — enter CHAR / 1 manually
--------	---	---

After Step 1 is done — proceed to: Step 2: SE24 → Create ZCL_PO_LONGTEXT_HANDLER (handler class) Step 3: SE19 → Create ZCL_PO_TEXT_BADI_IMPL (BAdI implementation) Step 4: ME21N → create PO with text → SE16N → verify ZPO_LONGTEXT populated Full ABAP code for Steps 2 and 3 is in: PO_LongText_4Steps_Guide.pdf