

PO Notes New Persistency

Three Teams — Who They Are, What Code They Own, What They Built

SAP Script X Team | Notes Reuse RAP Team | Sales Team (Reference Implementation)

Sources: Sales SDD, PO Notes Handover PPT, CE2702/CE2708 Sync Meeting, FW S4 PR Support Meeting | 2026-06-30

Team	What They Own	Role for PO Team	Contact
SAP Script X Team	STXH/STXL framework + CL_RSTXT_PERSISTENCE_FRAMEWORK base class + TTXOB HANDLER_CLASS mechanism	Provide plug-in framework + wiki guidelines — PO team registers handler class in TTXOB	Via SAP Script X wiki
Notes Reuse RAP Team	SGBT_NTCEONT generic table + Notes Reuse RAP Business Object + CDS views (BCSRV owned)	Provide reusable notes UI/logic — PO team must clarify if EKKT_TEXT is compatible	BLR04: M K, Visakh and team
Sales Team	SDTP_TEXT own table + handler class + SDM classes (CE2608 PoC delivered)	Reference implementation — PO team follows same pattern for EKKT_TEXT + SDM	Karen Feng, Chris Xie

■ Critical Open Question (blocking Activity 1 of CE2702): Notes Reuse RAP BO is currently documented to work ONLY with SGBT_NTCEONT. If PO team builds own table EKKT_TEXT — can Notes Reuse RAP consume it? This question must be answered by Notes Reuse RAP team BEFORE EKKT_TEXT is designed.

Who They Are

The SAP Script / Forms Services team owns the entire SAP text framework — STXH, STXL, STXB cluster tables and all text APIs (READ_TEXT, SAVE_TEXT, DELETE_TEXT). They enabled the new persistency plug-in mechanism by adding the HANDLER_CLASS field to TTXOB and building the base class CL_RSTXT_PERSISTENCE_FRAMEWORK. They published the wiki guidelines for all applications to follow.

Tables and Objects They Own

STXH	Database Table	Text header — one row per text. TDOBJECT, TDNAME, TDID, TDSRAS, TDREF/TDREFOBJ etc.
STXL	Cluster Table	Text lines — COMPRESSED binary. Cannot be read via plain SQL. Only via READ_TEXT.
STXB	Cluster Table	Text buffer — temporary text storage during editing session
TTXOB	Customising Table	Text object definition. KEY FIELD: HANDLER_CLASS — application registers their class here
TTXID	Customising Table	Text ID definition per object. Links text types to text schemas
CL_RSTXT_PERSISTENCE_FRAMEWORK	ABAP Class	BASE CLASS all application handler classes must inherit. Provides the interface contract.
CL_SDM_PACKAGE_MIGRATION	ABAP Class	BASE CLASS all SDM migration classes must inherit
CL_SDM_PROC_STATUS_API	ABAP Class	API to check if SDM migration is finished — IS_SDM_FINISHED method

Standard Function Modules (SAP Standard — Do NOT Modify)

Function Module	Purpose
READ_TEXT	Decompress text from STXL and return plain TLINE table — main read API
SAVE_TEXT	Compress text to STXH/STXL — main write API. Triggers handler class if registered.
DELETE_TEXT	Delete a text entry from STXH/STXL — triggers handler class if registered
SELECT_TEXT	Read text headers from STXH by range — used in SDM and handler class
READ_TEXT_TABLE	Mass read multiple texts — used in SDM for performance
READ_MULTIPLE_TEXTS	Alternative mass text reader
CONVERT_ITF_TO_STREAM_TEXT	Convert ITF table (TLINE) → plain text string — CRITICAL for migration
CONVERT_STREAM_TO_ITF_TEXT	Convert plain text string → ITF table — used in handler READ method

What They Enabled — The Plug-in Mechanism

BEFORE SAP Script X team enablement:

SAVE_TEXT → always writes to STXH/STXL (no routing possible)

READ_TEXT → always reads from STXH/STXL

AFTER SAP Script X team added HANDLER_CLASS to TTX0B:

SAVE_TEXT called by ME21N



SAP Script framework checks TTX0B.HANDLER_CLASS for EKKO/EKPO



■■■ HANDLER_CLASS empty → write to STXH/STXL (old behaviour)



■■■ HANDLER_CLASS = 'ZCL_PO_RSTXT_PERSISTENCE'

→ call application's handler class

→ application writes to EKKT_TEXT (new table)

→ AND writes to STXH if IS_MIGRATION_FINISHED = FALSE

From PO Notes Handover PPT (Slide 7): "The SAPScript team has already published the guidelines to move to new persistency. Application-specific persistence of SAPscript texts — Forms Services — Wiki@SAP" This wiki is the definitive guide for PO team to follow.

Confirmed Registration — Text Object Level vs Text ID Level

Registration in TTX0B (text OBJECT level — all TDIDs):

TDOBJECT = 'EKKO' → HANDLER_CLASS = 'ZCL_PO_RSTXT_PERSISTENCE'

TDOBJECT = 'EKPO' → HANDLER_CLASS = 'ZCL_PO_RSTXT_PERSISTENCE'

Effect: ALL text IDs (F01, F02, F04...) for EKKO/EKPO route to handler

Alternative — Registration in TTXID (text ID level — specific TDIDs only):

TDOBJECT = 'EKKO', TDID = 'F01' → HANDLER_CLASS = 'ZCL_PO_RSTXT_PERSISTENCE'

Effect: Only F01 routes to handler, other TDIDs still go to STXH

From PO Notes Handover PPT (Slide 9):

'Currently all teams have done this at Text Object level'

Recommendation for PO: register at TDOBJECT level (EKKO + EKPO)

Who They Are

The Notes Reuse RAP team built a reusable RAP Business Object for notes so that any application can include notes functionality without building it from scratch. The Procurement-specific notes reuse topic is owned by the BLR04 team (M K, Visakh and team). Any architectural guideline for PO notes must be aligned with this team in addition to the WDF11 team.

Objects They Own

SGBT_NTCEONT	<i>Database Table (BCSRV component)</i>	Generic notes content table. OBJECT_TYPE + OBJECT_ID (CHAR70) + NOTE_ID + LANGUAGE + NOTE_CONTENT (plain string). Owned by BCSRV — NOT by PO team. CDS views and C1 contract views also owned by BCSRV.
Notes Reuse RAP Business Object	<i>RAP Business Object</i>	Reusable BO providing CRUD for notes. Applications include this as composition in their own RAP BO. Currently documented to work with SGBT_NTCEONT. Already used by: Supplier Confirmation (new feature — no migration needed).
CDS Views on SGBT_NTCEONT	<i>CDS Views (BCSRV owned)</i>	Basic view + analytics view on SGBT_NTCEONT. C1 released for external consumption. Owned by Basis/BCSRV team — PO team cannot add PO-specific joins without Basis involvement.

SGBT_NTCEONT Table Structure

Field	Type	Length	Description
MANDT	CLNT	3	Client
OBJECT_TYPE	CHAR	10	Business Object Type — generic
OBJECT_ID	CHAR	70	Generic document ID — CHAR70 (same limitation as STXH TDNAME)
NOTE_ID	CHAR	4	Note/Text type
LANGUAGE	LANG	1	Language key
NOTE_CONTENT	STRG	—	Plain text content — long string
CREATED_BY	CHAR	12	Created by
CREATED_AT	DATS	8	Created date
CHANGED_BY	CHAR	12	Changed by
CHANGED_AT	DATS	8	Changed date

Key Limitations Confirmed

Limitation	Source	Impact on PO
Text references NOT supported out of the box	PO Notes Handover PPT Slide 8	PO has many reference texts (F02, F04 from Info Record/Vendor) — must handle separately
CHAR70 OBJECT_ID — same as STXH TDNAME	Table design analysis	Cannot JOIN with EKKO on typed EBELN — same limitation as STXH
No PO-specific attributes possible	Table design analysis	Cannot add Purchase Org, Doc Type for auth or reporting
CDS views owned by BCSRV/Basis	Architecture — BCSRV component ownership	PO team cannot add EKKO-specific joins without Basis approval

Only works with SGBT_NTCEONT currently	CE2702/CE2708 sync meeting	EKKT_TEXT compatibility UNKNOWN — critical open question
--	----------------------------	--

■ Critical Open Question for CE2702 Activity 1: 'Can Notes Reuse RAP BO consume an application-specific own table (EKKT_TEXT) instead of SGBT_NTCEONT?' Contact: BLR04 team (M K, Visakh) + Notes Reuse RAP team If YES → EKKT_TEXT can be built and registered with Notes Reuse If NO → must use SGBT_NTCEONT → different table design entirely

Who They Are

Karen Feng and Chris Xie are the SD (Sales & Distribution) development team who completed the reference implementation of the new text persistency in CE2608. They are the go-to team for PO to understand the implementation pattern, lessons learned, and SDM challenges.

What They Built — Complete List

SDTP_TEXT / VX_TEXT	<i>Database Table (SD-owned)</i>	New SD text table. Typed keys: SD_DOCUMENT_ID (VBELN), SD_DOCUMENT_ITEM (POSNR). TEXT_CONTENT as plain text string. REF_ fields for reference chain. Auth fields encoded via TDTITLE. SDM_VERSION tracked in VBAK/VBRK/LIKP.
SD Text Handler Class	<i>ABAP Class (handler)</i>	Inherits CL_RSTXT_PERSISTENCE_FRAMEWORK. Registered in TTXOB for: VBBK (Sales header), VBBP (Sales item). 5 methods: CREATE, CHANGE, DELETE, READ, READ_HEADERS_VIA_RANGES. IS_MIGRATION_FINISHED → calls CL_SDM_PROC_STATUS_API.
CL_SDM_SD_VBAK_TEXT_MIGRATION	<i>ABAP Class (SDM)</i>	SDM for Sales Order documents. Inherits CL_SDM_PACKAGE_MIGRATION. Package size 30,000. Duration: 3.5 hours for 13.9M records in CCW/720 performance test.
CL_SDM_VBRK_TEXT_MIGRATION	<i>ABAP Class (SDM)</i>	SDM for Billing documents. Same pattern as VBAK SDM.
(Delivery SDM — not built)	<i>Gap</i>	Due to capacity issues, Delivery SDM was NOT delivered in 2608. This means IS_MIGRATION_FINISHED is ALWAYS FALSE for Sales — reads always from STXH. PO team does not have this dependency — can potentially finish faster.
P_SalesDocumentText	<i>CDS View (table function)</i>	Existing CDS view — reads from STXH via CL_SD_S4H_STXL_UTILS. Still used in 2608 — CDS on new table not released yet (data incomplete).
Basic CDS View on SDTP_TEXT	<i>CDS View (planned)</i>	Will be released AFTER SDM is confirmed complete for all customers. Analytics view on top (C1 released). This is WHY they did all the work.

What Chris Xie Explained — Key Quotes from Meeting

On dual-write — two handler classes called simultaneously

"The text framework will dedicate the call to two handler classes. One is the defaulted handler class which will take care of old persistence like STXH/STXL, and we will also pass the same information to this text-object-specific handler class — this class will only take care of the new table." — Chris Xie, FW Further S4 PR Support Meeting 2026-06-18

On IS_MIGRATION_FINISHED — true/false routing

"There is a method to control which table will be used — old table, new table. It is very simple, just return true or false. Based on that parameter, it will decide which table to use — at text object level." — Chris Xie

On Delivery blocker — always FALSE

"Since delivery is not joining our development in 2608, that means we will always not finish — because we don't foresee when delivery will finish the migration. So we always set IS_MIGRATION_FINISHED to FALSE. That means READ always goes to the older persistence." — Chris Xie

On SDM execution in customer system

"After customer upgrades to 2608, a few days later, the SDM will be triggered automatically by SDM framework. It will work like a background job — silently in business uptime. Customer will not be aware. We will get SP incident in case there is an error." — Chris Xie

On when to release CDS views

"CDS views will not deliver in 2608 because we cannot ensure all customers finished migration — data is incomplete. We cannot release CDS views to customers when data is incomplete." — Chris Xie

Why Sales Chose Own Table (Not SGBT_NTCEONT)

Reason	Detail
Performance	Needed application-specific attributes for joins — generic table too slow at SD data volumes
Flexibility	Needed to add SD-specific fields: auth fields (Sales Org, Doc Type), reference chain fields
AI / BDC access	Own table enables plain SQL without decompression — SGBT_NTCEONT also plain SQL but no SD-specific joins
Data model	New table for Sales, Billing, Delivery are COMMON — but Procurement and Sales use different text objects so PO can choose different

Karen Fang on PO team's choice (from meeting): "For procurement — whether you want to follow the same approach or create something different, I don't know. The old table is common [STXH]. The new table for sales, billing, delivery are common. But for procurement, whether you want to follow the same or create something different — if there is no further dependency, you could create a table and migrate everything."

Summary — Three Teams Compared



Side by side: what each team owns and what PO team must do

Aspect	SAP Script X Team	Notes Reuse RAP Team	Sales Team
What they own	STXH/STXL framework CL_RSTXT_PERSISTENCE_FRAMEWORK TTXOB HANDLER_CLASS field	SGBT_NTCEONT generic table Notes Reuse RAP BO CDS views (BCSRV)	SDTP_TEXT own table SD handler class SDM classes (VBAK, VBRK) CDS views on SDTP_TEXT (planned)
Their role for PO	Provide plug-in framework — PO registers handler class in TTXOB	Provide reusable notes BO — PO must clarify EKKT_TEXT compatibility	Reference implementation — PO follows same EKKT_TEXT+SDM pattern
Key deliverable	HANDLER_CLASS mechanism Wiki guidelines published	Notes RAP BO with SGBT_NTCEONT C1 CDS views (BCSRV)	Proven SDM pattern Handler class pattern Performance data (3.5h/13M records)
Open question	None — framework available	Can EKKT_TEXT be used? (CRITICAL BLOCKER)	None — implementation complete
PO team must	Register ZCL_PO_RSTXT_PERSISTENCE in TTXOB for EKKO+EKPO	Schedule sync — answer compatibility question before designing EKKT_TEXT	Use SDD + meeting insights as blueprint for EKKT_TEXT + SDM class
Contact	SAP Script X wiki (Rene Zink — confirmed TDTITLE usage)	BLR04: M K, Visakh and team	Karen Feng (karen.feng@sap.com) Chris Xie (chris.xie@sap.com)

Key Technical Objects — Who Owns What

Object	Owner Team	PO Action
STXH / STXL / STXB	SAP Script X	Do NOT modify — read via READ_TEXT only
TTXOB	SAP Script X	Register HANDLER_CLASS for EKKO + EKPO
CL_RSTXT_PERSISTENCE_FRAMEWORK	SAP Script X	Inherit in ZCL_PO_RSTXT_PERSISTENCE
CL_SDM_PACKAGE_MIGRATION	SAP Script X	Inherit in ZCL_SDM_EKKO_TEXT_MIGRATION
CL_SDM_PROC_STATUS_API	SAP Script X	Call IS_SDM_FINISHED in handler IS_MIGRATION_FINISHED
SGBT_NTCEONT	BCSRV / Basis	Use only if Notes Reuse compat confirmed — ask team
Notes Reuse RAP BO	Notes Reuse RAP team	Include in PO RAP model — if EKKT_TEXT is compatible
SDTP_TEXT (Sales)	SD / Sales team	Use as blueprint — NOT as shared table
EKKT_TEXT (to build)	PO team (CE2702)	Build and own — follows Sales pattern
ZCL_PO_RSTXT_PERSISTENCE	PO team (CE2702)	Build — inherits SAP Script X framework class
ZCL_SDM_EKKO_TEXT_MIGRATION	PO team (CE2702)	Build — inherits SAP Script X SDM class