



Apex Institute of Technology

Computer Science & Engineering

Experiment 6

Name: Shivam Abhepal

UID: 24BAI70214

Branch: B.E. CSE (AIML)

Section: 24AIT_KRG-G1

Semester: 4

Date of Performance: 25.03.2026

Subject Name: Database
Management System

Subject Code: 24CSH-298

AIM: This experiment focuses on understanding and implementing cursors in PL/SQL to process multiple rows returned by a query. It demonstrates the use of implicit cursors, explicit cursors, and cursor attributes to apply business logic on database records in a row-by-row manner.

OBJECTIVES:

- To understand the concept of cursors in PL/SQL
- To differentiate between implicit and explicit cursors
- To use cursor attributes such as %FOUND, %NOTFOUND, %ROWCOUNT, and %ISOPEN
- To process multiple rows using explicit cursors
- To apply business logic using cursor-based processing

SOFTWARE REQUIREMENTS:

- Oracle Database Express Edition (Oracle XE)
- Oracle SQL Developer

PROCEDURE/STEPS:

1. Start the system and log in
2. Open Oracle SQL Developer



Apex Institute of Technology

Computer Science & Engineering

3. Connect to the required database
4. Open the SQL Worksheet / Query Tool
5. Create the employee table
6. Insert sample data into the table
7. Execute PL/SQL blocks demonstrating cursor usage
8. Observe outputs in DBMS Output panel
9. Save the work and take screenshots

PRACTICAL/EXPERIMENTAL STEPS:

Table Creation

```
CREATE TABLE employees (  
    emp_id NUMBER PRIMARY KEY,  
    emp_name VARCHAR2(50),  
    salary NUMBER,  
    department VARCHAR2(50)  
);  
INSERT INTO employees VALUES (101, 'Amit', 30000, 'HR');  
INSERT INTO employees VALUES (102, 'Neha', 45000, 'IT');  
INSERT INTO employees VALUES (103, 'Raj', 50000, 'Finance');  
INSERT INTO employees VALUES (104, 'Simran', 40000, 'IT');  
INSERT INTO employees VALUES (105, 'Karan', 35000, 'HR');  
  
COMMIT;
```

Implicit Cursor Example

```
SET SERVEROUTPUT ON;
```

```
DECLARE  
    v_rows NUMBER;  
BEGIN  
    UPDATE employees  
    SET salary = salary + 5000
```



Apex Institute of Technology

Computer Science & Engineering

```
WHERE emp_id = 101;

v_rows := SQL%ROWCOUNT;

DBMS_OUTPUT.PUT_LINE('Rows Updated: ' || v_rows);
END;
/
```

Explicit Cursor Example

```
DECLARE
    CURSOR emp_cursor IS
        SELECT emp_id, emp_name, salary FROM employees;

    v_id employees.emp_id%TYPE;
    v_name employees.emp_name%TYPE;
    v_salary employees.salary%TYPE;

BEGIN
    OPEN emp_cursor;

    LOOP
        FETCH emp_cursor INTO v_id, v_name, v_salary;
        EXIT WHEN emp_cursor%NOTFOUND;

        DBMS_OUTPUT.PUT_LINE(
            'ID: ' || v_id ||
            ', Name: ' || v_name ||
            ', Salary: ' || v_salary
        );
    END LOOP;

    CLOSE emp_cursor;
END;
/
```



Apex Institute of Technology

Computer Science & Engineering

Cursor Attributes Example

```
DECLARE
    CURSOR emp_cursor IS
        SELECT emp_name, salary FROM employees;

    v_name employees.emp_name%TYPE;
    v_salary employees.salary%TYPE;

BEGIN
    OPEN emp_cursor;

    LOOP
        FETCH emp_cursor INTO v_name, v_salary;
        EXIT WHEN emp_cursor%NOTFOUND;

        DBMS_OUTPUT.PUT_LINE(
            'Row ' || emp_cursor%ROWCOUNT ||
            ': ' || v_name || ' earns ' || v_salary
        );
    END LOOP;

    IF emp_cursor%ISOPEN THEN
        DBMS_OUTPUT.PUT_LINE('Cursor is open, now closing...');
        CLOSE emp_cursor;
    END IF;
END;
/
```

Business Logic Example

```
DECLARE
    CURSOR emp_cursor IS
        SELECT emp_id, salary FROM employees;
```



Apex Institute of Technology

Computer Science & Engineering

```
v_id employees.emp_id%TYPE;
v_salary employees.salary%TYPE;

BEGIN
  OPEN emp_cursor;

  LOOP
    FETCH emp_cursor INTO v_id, v_salary;
    EXIT WHEN emp_cursor%NOTFOUND;

    IF v_salary < 40000 THEN
      UPDATE employees
      SET salary = salary + 2000
      WHERE emp_id = v_id;

      DBMS_OUTPUT.PUT_LINE(
        'Bonus added to Employee ID: ' || v_id
      );
    END IF;
  END LOOP;

  CLOSE emp_cursor;
  COMMIT;
END;
/
```




Apex Institute of Technology

Computer Science & Engineering

[SQL Worksheet]*

```
29 IF v_salary < 40000 THEN
30 UPDATE employees
31 SET salary = salary + 2000
32 WHERE emp_id = v_id;
33
34 DBMS_OUTPUT.PUT_LINE(
35 'Bonus added to Employee ID: ' || v_id
36 );
37 END IF;
38 END LOOP;
39
40 CLOSE emp_cursor;
41 COMMIT;
42 END;
43 /
44 SELECT * FROM employees;
```

Query result Script output DBMS output Explain Plan SQL history

Download Execution time: 0.006 seconds

	EMP_ID	EMP_NAME	SALARY	DEPARTMENT
1	101	Yuvraj	37000	HR
2	102	Jaskaran	45000	IT
3	103	Rohit	50000	Finance
4	104	Simran	40000	IT
5	105	Kartik	37000	HR

I/O ANALYSIS:

Input:

- Employee ID
- Employee Name
- Salary
- Department

Output:

- Updated employee salary
- Row-by-row processed employee records
- Salary-based business logic execution



Apex Institute of Technology

Computer Science & Engineering

LEARNING OUTCOMES:

- Learned how cursors work in PL/SQL
- Understood implicit and explicit cursors
- Used cursor attributes effectively
- Implemented row-by-row data processing
- Applied real-world business logic