

# Geo – Location

## Geo-Location:

HTML5 related API's – <https://developer.mozilla.org/en-US/docs/Web/API>

HTML5 Geo-Location is a way to get user location. If we have the latitude and longitude, we can pin point the user anywhere in the world. In order to get the location, there is an object; like we have document related to HTML, there is an object called navigator, attached to the window object, which has everything related to Geo-Location.

```
> navigator| I
< Navigator {vendorSub: "", productSub: "20030107", vendor: "Google Inc.", maxTouc...
```

If we expand onto it, we can see all the properties. One of the properties is geolocation which we will use to know the location of the user. Now, in the HTML file, we will create a button element, “Get Location” with an id="getLcnBtn"

```
<button id="getLcnBtn">Get Location</button>
```

The first step is to get the reference. In JavaScript,

```
var getLcnBtn = document.getElementById('getLcnBtn')
function getUserLocation() {
}
getLcnBtn.addEventListener('click', getUserLocation)
```

in the console, there is a navigator.geolocation, this is the Geolocation object which exists on the navigator object. Basically, there are two objects one is navigator and other is Geolocation object. In the Geolocation, if we expand it, we get clearWatch, getCurrentPosition and watchPosition.

Going back to javascript,

```
navigator.geolocation.getCurrentPosition()
```

3 Parameters –


- Function (should be a function, mandatory)
- Function
- Position related object feature

Like we have passed a function in `addEventListener`, we need to add a function to `getCurrentPosition()`. So,

```
var getLcnBtn = document.getElementById('getLcnBtn')
function onPositionReceived() {
    console.log('Position Received')
}
function getUserLocation() {
    console.log('trying to get the users's position')
    navigator.geolocation.getCurrentPosition(onPositionReceived)
}
```

```
getLcnBtn.addEventListener('click', getUserLocation)
```

Expected behavior is when we click on the `getLcnButton`, which is from the HTML page, JavaScript will call function `getUserLocation()`. When the `getUserLocation()` function is called it would first log the line, `console.log("Trying to get the user's position")` after than it will call `getCurrentPosition()` function. this will create a popup asking to confirm or share the position. Once we allow that to happen, then JavaScript will call on `PositionReceived()` function.



We can clearly see that unless we have not given permission, javascript will not be able to share our location.

When a event listener handler (`getUserLocation`) is called by an `addEventListener` method, it get passed on event object and all the information related gets attached on to it. Similarly, `getCurrentPosition` passes one object to the function we have provided. So in `onPositionReceved()`, it get one more object – position. When the user gives permission, `getCurrentPosition` will send an object to the `onPositionReceved`.

```
Trying to get the user's position      script.js:10
Position Received                      script.js:4
                                       script.js:5
GeoLocationPosition {coords: GeoLocationCoordinates, timestamp: 1615997379911}
```

We can see the coords, and timestamp property. In “coords”, we will get the latitude and longitude values. To access these values, we can write,

```
var getLocationBtn = document.getElementById('getLocationBtn')

function onPositionReceived() {
    console.log('Position Received')
    console.log(position.coords.latitude)
    console.log(position.coords.longitude)
}

function getUserLocation() {
    console.log('trying to get the user location')
    navigator.geolocation.getCurrentPosition(onPositionReceived)
}

getLocationBtn.addEventListener('click', getUserLocation)
```

```
Trying to get the user's position      script.js:11
Position Received                      script.js:4
22.776573199999998                    script.js:5
86.1649925                           script.js:6
```

It might not give the accurate location in desktops, but if the device has GPS, then it would show the exact location of the user.

In the coords property, we have other properties like, speed, accuracy, heading are some properties that google uses to track your location, speed, heading (direction) and plot it. We can create our own Google Maps with these details.

The `getCurrentPosition()` accepts one parameter and the `onPositionReceived()` function gets called only when user gives position. We will create another function, `onPositionDenied()`.

```
function onPositionDenied() {
    console.log('Position Denied!!!')}
```

This function gets called only when use click block on the confirmation popup.

Like, `getCurrentPosition`, there is another function as `watchPosition()`. This is a bit complicated. It continuously gets the current position the user.