



**उत्पाद मैनुअल
आई एस 17634:2022 के अनुसार
भण्डारण इकाइयां के लिए**

दस्तावेज संख्या - पीएम/आईएस 17634/1/सितम्बर 2022

भारतीय मानक ब्यूरो की स्कीम-I (अनुरूपता मूल्यांकन) विनियम, 2018 के तहत यह उत्पाद मैनुअल प्रमाणीकरण के प्रचालन में रीति और पारिश्रिता की सुसंगतता सुनिश्चित करने के लिए सभी क्षेत्रीय/शाखा कार्यालयों और लाइसेंसी द्वारा संदर्भ सामग्री के रूप में उपयोग किया जाएगा। बीआईएस प्रमाणीकरण लाइसेंस/प्रमाणपत्र प्राप्त करने के इच्छुक भावी आवेदकों द्वारा भी इस दस्तावेज का उपयोग किया जा सकता है।

**PRODUCT MANUAL FOR
STORAGE UNITS
ACCORDING TO IS 17634:2022**

Document No.- PM/ IS 17634/1/Sep 2022

This Product Manual shall be used as reference material by all Regional/Branch Offices & licensees to ensure coherence of practice and transparency in operation of certification under Scheme-I of Bureau of Indian Standards (Conformity Assessment) Regulations, 2018 for various products. The document may also be used by prospective applicants desirous of obtaining BIS certification licence/certificate.

भारतीय मानक ब्यूरो
BUREAU OF INDIAN STANDARDS
मानक भवन, ९, बहादुर शाह ज़फ़र मार्ग
Manak Bhawan, 9, Bahadur Shah Zafar Marg
नई दिल्ली- ११०००२
New Delhi – 110002



PRODUCT MANUAL FOR STORAGE UNITS ACCORDING TO IS 17634:2022

This Product Manual shall be used as reference material by all Regional/Branch Offices & licensees to ensure coherence of practice and transparency in operation of certification under Scheme-I of Bureau of Indian Standards (Conformity Assessment) Regulations 2018 for various products. The document may also be used by prospective applicants desirous of obtaining BIS certification licence/certificate.

1.	Product	:	IS 17634:2022
	Title	:	Storage Units
	No. of Amendments	:	Nil
2.	Sampling Guidelines:		
a)	Raw material	:	-
b)	Grouping guidelines	:	Please refer ANNEX – A
c)	Sample Size	:	• 1 Unit – For Dimensional and Safety requirements (clause 4, 5 & 7) • Material cut panels, Fabric & Leather pieces – For Surface Performance tests (clause 6)
3.	List of Test Equipment	:	Please refer ANNEX – B
4.	Scheme of Inspection and Testing	:	Please refer ANNEX – C
5.	Possible tests in a day:		
	Design and Workmanship (Cl 4) Dimensions (Cl 5) All tests except durability test (Cl 7)		
6.	Scope of the Licence:		
	Licence is granted to use Standard Mark as per IS 17634:2022 with the following scope:		
	Name of the product	Storage Units	
	Design/ Model Number		

BUREAU OF INDIAN STANDARDS
Manak Bhawan, 9, Bahadur Shah Zafar Marg,
New Delhi – 110002

ANNEX A

Grouping Guidelines

1. IS 17631:2022 covers covers the requirements related to the performance and safety of storage units, including their movable and non-movable parts intended for domestic usage and for institutional usage such as filing papers or similar.. The Standard applies to completely manufactured/ fabricated storage units as well as ready-to-assemble units. The design/ model shall be declared by the manufacturer.

2. The guidelines given below shall be followed for GoL/ CSoL:

Storage units of each design/model number shall be tested to cover that particular design/model number.

3. The Firm shall declare the varieties of work chairs they intend to cover in the Licence. The Scope of Licence may be restricted based on the manufacturing and testing capabilities of the manufacturer.
4. During the operation of the Licence, BO shall ensure that all varieties covered in the Licence are tested in rotation, to the extent possible.

ANNEX- B**List of Test Equipment***Major test equipment required to test as per the Indian Standard*

Sl. No.	Tests used in with Clause Reference	Test Equipment
1	Dimensions (clause 5)	- Micrometer, Vernier caliper - Measuring tape - Steel scale - Angle protractor
2	Surface Performance (Tests on rigid surfaces of materials)	
	Resistance to mechanical damage	- As per IS 17641:2021, or, as per Annex B-2 of IS 17637:2021
	Pencil hardness	- as per Annex C-1 of IS 17637:2021
	Resistance to wet heat	- Air conditioner, humidifier & hygrometer - as per Clause 5 of IS 17639:2021
	Resistance to dry heat	- as per Clause 5 of IS 17638:2021
	Resistance to marking by cold liquids	- as per Clause 3 of IS 17640:2021
	Resistance to marking by cold oils and fats	- as per Clause 3 of IS 17640:2021
	Adhesive performance	- as per Annex D-2 of IS 17637:2021
3	Surface Performance (Fabric & leather (synthetic & Natural)	
	Breaking load	- as per IS 1969(Part 1) or IS 7016 (Part 2)
	Elongation at break	- as per IS 1969(Part 1) or IS 7016 (Part 2)
	Tear strength for fabric and leather	- as per IS 6489 (Part 1) IS 7016 (Part 3/Sec 1) or - IS 7016 (Part 3/Sec 2)
	Colour fastness to light for fabric and leather	- as per IS/ISO 105-B02
	Colour fastness to rubbing for fabric and leather	- as per IS/ISO 105-X12
	Colour fastness to perspiration	- as per IS/ISO 105-E04
	Colour fastness to water for fabric and leather	- as per IS/ISO 105- E01
	Pilling resistance	- as per IS 10971 (Part 1) or (Part 2)
	Coating adhesion strength	- as per IS 7016 (Part 5)
	Seam slippage	- as per IS/ISO 13936-2
	Resistance to damage by flexing	- as per IS 7016 (Part 4)
	Abrasion resistance	- as per IS 12673 (Part 2)
	Bursting strength	- as per IS 1966 (Part 1)
	Resistance to cold	- as per IS 1259
	Tear strength for natural leather	- as per IS 5914

	Flexing endurance	- as per IS 5914
	Finish adhesion	- as per IS 6191 (Part 5)
	Colour fastness to artificial light	- as per IS/ISO 105 B02
	Colour fastness to rubbing for natural leather	- as per IS 6191 (Part 4)
	Colour fastness to water spotting	- as per IS 6191 (Part 1)
	Water vapour permeability	- as per IS 5914
	Colour fastness to water for natural leather	- as per IS 6191 (Part 2)
Tests on Furniture -		
4	Stability test (Clause 7.3)	- Floor surface as per Clause B-2 of IS 17634 - Wall surface as per Clause B-3 of IS 17634 - Stops as per Clause B-4 of IS 17631 - Loading Pad as per Clause B-5 of IS 17631 - Test apparatus as per Clause B-6 of IS 17631 - Masses as per Clause B-7 of IS 17631 - Glass Marbles as per Clause B-8 of IS 17631 - Loads for Filing Pockets as per Clause B-9 of IS 17631 - Steel Impact Plates as per Clause B-10 of IS 17631 - Impact Bag as per Clause B-11 of IS 17631
5	Static-Load test (Clause 7.4)	
6	Durability test (Clause 7.5)	

The above list is indicative only and may not be treated as exhaustive.

ANNEX C

Scheme of Inspection and Testing

1. LABORATORY- A laboratory shall be maintained which shall be suitably equipped (as per the requirement given in column 2 of Table 1) and staffed, where different tests given in the specification shall be carried out in accordance with the methods given in the specification.

1.1 The manufacturer shall prepare a calibration plan for the test equipment.

2. TEST RECORDS –The manufacturer shall maintain test records for the tests carried out to establish conformity.

3. LABELLING AND MARKING – As per the requirements of IS 17634:2022.

4. CONTROL UNIT – Storage units of the same design/model number manufactured from the same materials and same consignment of materials, in a week under similar conditions of manufacturing shall constitute a control unit.

5. LEVELS OF CONTROL - The tests as indicated in column 1 of Table 1 and the levels of control in column 3 of Table 1, shall be carried out on the whole production of the factory which is covered by this plan and appropriate records maintained in accordance with paragraph 2.0 above.

5.1 All the production which conforms to the Indian Standard and covered by the licence should be marked with Standard Mark.

6. REJECTIONS– Disposal of non-conforming product shall be done in such a way so as to ensure that there is no violation of provisions of BIS Act, 2016.

TABLE 1

(1)				(2)	(3)		
Test Details				Test equipm ent require ment R: Required (or) S: Subcontracti ng permitted	Levels ofControl		
Cl.	Requirement	Test Methods			No. of Sample	Frequency	Remarks
		Clause	Reference				
4	Design and workmanship	4	IS 17634	R	Each storage unit	-	-
5	Dimensions	5	IS 17634	R	Five percent	Each Control Unit	-
6	Surface performance (of materials)						
	Rigid Surfaces	-	IS 17637	S	One	Each Consignment	The test samples for surface performance are to be tested on materials only, after their surface treatment and not on assembled chair
	Fabric and Synthetic Leather						
	Natural Leather						

7	SAFETY TESTS						
7.2	Test on Non-Movable Parts						
	Shelves (CI 7.2.1)						
	General	7.2.1.1	IS 17634	R	One	Each control unit	-
	Deflection of shelves	7.2.1.2					
	Strength of shelf supports	7.2.1.3					
	Tops and Bottoms (CI 7.2.2)						
	Sustained load test for tops and bottoms	7.2.2.1	IS 17634	R	One	Each control unit	-
	Static load test for tops and bottoms	7.2.2.2					
	Strength of Clothes Rails and their Supports (CI 7.2.3)						
	Strength of clothes-rail supports	7.2.3.1	IS 17634	R	One	Each control unit	-
	Dislodgement of clothes rails	7.2.3.2					
	Strength of the Structure (CI 7.2.4)						
	Test for structure and underframe	7.2.4.1	IS 17634	R	One	Each control unit	-
	Drop test	7.2.4.2					
	Tests for units with castors or wheels	7.2.4.3					
7.3	Test Procedures for Movable Parts						
	Pivoted Doors (CI 7.3.1)						
	Strength of pivoted doors - Vertical load on pivoted doors - Horizontal load on pivoted doors	7.3.1.2	IS 17634	R	One	Each control unit	-
	Slam-shut test of pivoted doors	7.3.1.3	IS 17634	R	One	Each control	-

					unit	
Durability of pivoted doors	7.3.1.4	IS 17634	S	One	Once in three months	Each design/model shall be tested in rotation so that all the designs/ models are tested in a period of two years
Sliding Doors and Horizontal Roll-fronts (CI 7.3.2)						
Slam shut/open test of sliding doors and horizontal roll-fronts	7.3.2.2	IS 17634	R	One	Each control unit	-
Durability of sliding doors and horizontal roll-fronts	7.3.2.3	IS 17634	S	One	Once in three months	Each design/model shall be tested in rotation so that all the designs/ models are tested in a period of two years
Flaps (CI 7.3.3)						
Strength of bottom-hinged flaps	7.3.3.1	IS 17634	R	One	Each control unit	-
Durability of flaps	7.3.3.2	IS 17634	S	One	Once in three months	Each design/model shall be tested in rotation so that all the designs/ models are tested in a period of two years
Drop test for top-hinged flaps	7.3.3.3	IS 17634	R	One	Each control unit	-
Vertical Roll-Fronts (CI 7.3.4)						
Slam shut/open test of vertical roll-fronts	7.3.4.1	IS 17634	R	One	Each control unit	-
Durability of vertical roll-fronts	7.3.4.2	IS 17634	S	One	Once in three months	Each design/model shall be tested in rotation so that all the designs/ models are tested in a period of two years
Extension Elements (CI 7.3.5)						
Strength of extension elements	7.3.5.2	IS 17634	R	One	Each control unit	-
Durability of extension elements	7.3.5.3	IS 17634	S	One	Once in three months	Each design/model shall be tested in rotation so that all the designs/ models are tested in a period of two years
Slam shut/open test of extension elements	7.3.5.4	IS 17634	R	One	Each control	-

	Displacement of extension element bottoms	7.3.5.5				unit	
	Interlock test	7.3.5.6					
	Locking and Latching Mechanism Tests (CI 7.3.6)						
	Strength test for locking and latching mechanisms for extension elements	7.3.6.2	IS 17634	R	One	Each control unit	-
	Locking and latching mechanisms for doors, flaps and roll-fronts	7.3.6.3	IS 17634	R	One	Each control unit	-
	Durability test of locking and latching mechanisms	7.3.6.4	IS 17634	S	One	Once in three months	Each design/model shall be tested in rotation so that all the designs/ models are tested in a period of two years
	Pull Force Test	7.3.7	IS 17634	R	One	Each control unit	-
	Top Load Ease Cycle Test	7.3.8	IS 17634	R	One	Each control unit	-
	Durability Test for Units with Seating Surfaces – Cyclic Impact	7.3.9	IS 17634	S	One	Once in three months	Each design/model shall be tested in rotation so that all the designs/ models are tested in a period of two years
	Drop Test – Dynamic – for Units with Seat Surfaces	7.3.10	IS 17634	R	One	Each control unit	-
7.4	Units Mounted to the Building or Other Structure						
	Units Not Supported by the Floor (CI 7.4.1)						
	Movable parts, shelf supports, tops and bottoms	7.4.1.2	IS 17634	R	One	Each control unit	-
	Sustained load test (overload)	7.4.1.3					
	Dislodgement test	7.4.1.4					

	Units Supported by the Floor	7.4.2	IS 17634	R	One	Each control unit	-
7.5	Stability Tests						
	Doors, Extension Elements and Flaps Closed, All Storage Units Unloaded (CI 7.5.2)						
	Units that can be adjusted to a Height of 1 000 mm or less	7.5.2.1	IS 17634	R	One	Each control unit	-
	Units that can be adjusted to a height of more than 1 000 mm	7.5.2.2					
	Opening Doors, Extension Elements and Flaps, All Storage Units Unloaded	7.5.3	IS 17634	R	One	Each control unit	-
	Doors, Extension Elements and Flaps Opened and Unlocked (CI 7.5.4)						
	All storage areas unloaded and all doors, extension elements and flaps open	7.5.4.1	IS 17634	R	One	Each control unit	-
	All storage areas unloaded with overturning load	7.5.4.2					
	All storage areas loaded with overturning load	7.5.4.3					
	Doors, Extension Elements and Flaps Closed and Locked, All Storage Units Loaded	7.5.5	IS 17634	R	One	Each control unit	-
	Vertical Force Stability Test for Storage Units	7.5.6					
	Stability Test for Pedestals/Storage Units with Seat Surfaces	7.5.7					
	Dynamic Stability Test for Units with Castors	7.5.8					

	Strength Test for Wall Attachments	7.5.9					
--	------------------------------------	-------	--	--	--	--	--

Note-1: All applicable safety requirements as mentioned in clause 7 of IS 17634:2022 shall be carried out on the same sample and in the sequence as the clauses are numbered in this standard. All tests specified for a particular component shall be carried out on the same sample.

Note-2: Sub-contracting is permitted to a laboratory recognized by the Bureau or Government laboratories empanelled by the Bureau.

Note-3: Levels of control given in column 3 are only recommendatory in nature. The manufacturer may define the control unit/batch/lot and submit his own levels of control in column 3 with proper justification for approval by BO Head.