



Vidyavardhini's College of Engineering & Technology
Department of Computer Engineering

Experiment No.3
To install and configure MongoDB to execute NoSQL commands
Date of Performance: 9/08/23
Date of Submission: 16/08/23



AIM: To install and configure MongoDB/ Cassandra/ HBase/ Hypertable and to execute NoSQL commands.

THEORY:

MongoDB can be downloaded from <https://www.mongodb.com/try/download/community2>

Now open command prompt and run the following command

```
C:\>move mongodb-win64-* mongodb  
  
1 dir(s) moved.
```

MongoDB requires a data folder to store its files. The default location for the MongoDB data directory is c:\data\db. So create the folder using the Command Prompt. Execute the following command sequence.

```
C:\>md data  
  
C:\>md data\db
```

In case mongodb is stored in some other location, navigate to that folder.

In command prompt navigate to the bin directory present into the mongodb installation folder. Suppose the installation folder is D:\set up\mongodb

```
C:\Users\XYZ>d:  
  
D:\>cd "set up"  
  
D:\set up>cd mongodb  
  
D:\set up\mongodb>cd bin  
  
D:\set up\mongodb\bin>mongod.exe --dbpath "d:\set up\mongodb\data"
```

Now to run the mongodb, open another command prompt and issue the following command:



```
D:\set up\mongodb\bin>mongo.exe
MongoDB shell version: 2.4.6
connecting to: test
>db.test.save( { a: 1 } )
>db.test.find()
{ "_id" : ObjectId(5879b0f65a56a454), "a" : 1 }
>
```

The use Command

MongoDB use DATABASE_NAME is used to create database. The command will create a new database, if it doesn't exist otherwise it will return the existing database **Syntax:**

use DATABASE_NAME

The dropDatabase () Method

MongoDB db.dropDatabase () command is used to drop an existing database.

Syntax:

db.dropDatabase()

The createCollection() Method

MongoDB db.createCollection(name, options) is used to create collection.

Syntax: db.createCollection(name,
options)

Insert Document

To insert data into MongoDB collection, you need to use MongoDB's insert() or save() method

Syntax

>db.COLLECTION_NAME.insert(document)

Example:

```
>db.post.insert([
{
```



title: 'MongoDB Overview', description:

'MongoDB is no sql database', tags:

['mongodb', 'database', 'NoSQL'], likes: 100

},

{ title: 'NoSQL

Database',

description: 'NoSQL database doesn't have tables',

tags: ['mongodb', 'database', 'NoSQL'], likes: 20,

comments: [

{ user:'user1',

message: 'My first comment', dateCreated:

new Date(2022,11,10,2,35), like: 0

}

]

}

])

Creating sample document:

Example

Suppose a client needs a database design for his blog website. Website has the following requirements.

- ☐ Every post has the unique title, description and url.
- ☐ Every post can have one or more tags.
- ☐ Every post has the name of its publisher and total number of likes.
- ☐ Every Post have comments given by users along with their name, message, data-time and likes.
- ☐ On each post there can be zero or more comments.

Document:

{



```
_id:          POST_ID          title:
TITLE_OF_POST,      description:
POST_DESCRIPTION,    by:
POST_BY,   url:   URL_OF_POST,
tags: [TAG1, TAG2, TAG3], likes:
TOTAL_LIKES, comments: [
{
user:'COMMENT_BY',
message:          TEXT,
dateCreated: DATE_TIME,
like: LIKES
},
{
user:'COMMENT_BY',
message:          TEXT,
dateCreated: DATE_TIME,
like: LIKES
}
]
```



OUTPUT:

Show All Databases

```
C:\windows\system32>mongosh
Current Mongosh Log ID: 6530e20a662ad8420492e238
Connecting to:      mongodb://127.0.0.1:27017/?directConnection=true&serverSelectionTimeoutMS=2000&appName=mongosh-7.0.2
Using MongoDB:      7.0.2
Using Mongosh:      2.0.2

For mongosh info see: https://docs.mongodb.com/mongosh-shell/

To help improve our products, anonymous usage data is collected and sent to MongoDB periodically (https://www.mongodb.com/legal/privacy-policy).
You can opt-out by running the disableTelemetry() command.

-----
The server generated these startup warnings when booting
2023-10-19T13:22:49.387+05:30: Access control is not enabled for the database. Read and write access to data and configuration is unrestricted
-----

test> show dbs
admin    40.00 KiB
config   60.00 KiB
local    40.00 KiB
test>
```

Create new database

```
-----
The server generated these startup warnings when booting
2023-10-19T13:22:49.387+05:30: Access control is not enabled for the database. Read and write access to data and configuration is unrestricted
-----

test> show dbs
admin    40.00 KiB
config   60.00 KiB
local    40.00 KiB
test> use mytestdb
switched to db mytestdb
mytestdb> db
mytestdb
mytestdb>
```



Know your current selected database

```
Current Mongosh Log ID: 6530e20a662ad8420492e238
Connecting to:      mongodb://127.0.0.1:27017/?directConnection=true&serverSelectionTimeoutMS=30000
Using MongoDB:      7.0.2
Using Mongosh:      2.0.2

For mongosh info see: https://docs.mongodb.com/mongosh-shell/

To help improve our products, anonymous usage data is collected and sent to MongoDB (see https://www.mongodb.com/legal/privacy-policy).
You can opt-out by running the disableTelemetry() command.

-----
The server generated these startup warnings when booting
2023-10-19T13:22:49.387+05:30: Access control is not enabled for the database. Read and write operations could change or delete the contents of the database.
Configuration is unrestricted
-----

test> show dbs
admin    40.00 KiB
config  60.00 KiB
local    40.00 KiB
test> use mytestdb
switched to db mytestdb
mytestdb> db
mytestdb
mytestdb>
```

Create collection

```
For mongosh info see: https://docs.mongodb.com/mongosh-shell/

To help improve our products, anonymous usage data is collected and sent to MongoDB (see https://www.mongodb.com/legal/privacy-policy).
You can opt-out by running the disableTelemetry() command.

-----
The server generated these startup warnings when booting
2023-10-19T13:22:49.387+05:30: Access control is not enabled for the database. Read and write operations could change or delete the contents of the database.
Configuration is unrestricted
-----

test> show dbs
admin    40.00 KiB
config  60.00 KiB
local    40.00 KiB
test> use mytestdb
switched to db mytestdb
mytestdb> db
mytestdb
mytestdb> db.createCollection("Employee");
ok: 1 }
mytestdb>
```



To check collections list

```
-----
The server generated these startup warnings when booting
2023-10-19T13:22:49.387+05:30: Access control is not enabled for the database. Read and write ac
figuration is unrestricted
-----

test> show dbs
admin    40.00 KiB
config  60.00 KiB
local    40.00 KiB
test> use mytestdb
switched to db mytestdb
mytestdb> db
mytestdb
mytestdb> db.createCollection("Employee");
{ ok: 1 }
mytestdb> show collection
MongoshInvalidInputError: [COMMON-10001] 'collection' is not a valid argument for "show".
mytestdb> show collections
Employee
mytestdb>
```

Insert document in collection

```
mytestdb> show collections
Employee
mytestdb> db.Employee.insertOne({id:1,name:"shivam Pandey",address:"kalyan"})
{
  acknowledged: true,
  insertedId: ObjectId("6530e524662ad8420492e239")
}
mytestdb> db.Employee.insertOne({id:2,name:"rajesh",address:"thane"})
{
  acknowledged: true,
  insertedId: ObjectId("6530e547662ad8420492e23a")
}
mytestdb> db.Employee.insertOne({id:3,name:"suresh",address:"mumbai"})
{
  acknowledged: true,
  insertedId: ObjectId("6530e561662ad8420492e23b")
}
mytestdb>
```

To insert multiple documents in selected collection

```
mytestdb> db.Employee.insert({id:4,name:"sujay",address:"goa"},{id:5,name:"satyam",address:"thane"})
DeprecationWarning: Collection.insert() is deprecated. Use insertOne, insertMany, or bulkWrite.

{
  acknowledged: true,
  insertedIds: { '0': ObjectId("6530e5f0662ad8420492e23c") }
}
mytestdb>
```




Get collection document

```
mytestdb> db.Employee.find().pretty()
[
  {
    _id: ObjectId("6530e524662ad8420492e239"),
    id: 1,
    name: 'shivam Pandey',
    address: 'kalyan'
  },
  {
    _id: ObjectId("6530e547662ad8420492e23a"),
    id: 2,
    name: 'rajesh',
    address: 'thane'
  },
  {
    _id: ObjectId("6530e561662ad8420492e23b"),
    id: 3,
    name: 'suresh',
    address: 'mumbai'
  },
  {
    _id: ObjectId("6530e5f0662ad8420492e23c"),
    id: 4,
    name: 'sujoy',
    address: 'goa'
  }
]
mytestdb>
```



Update document

```
mytestdb> db.Employee.update({name:"satyam"},{$set:{name:"aditya"}})
DeprecationWarning: Collection.update() is deprecated. Use updateOne, updateMany, or bulkWrite.
{
  acknowledged: true,
  insertedId: null,
  matchedCount: 0,
  modifiedCount: 0,
  upsertedCount: 0
}
mytestdb>
```

Drop

database

```
myTestDb> db.Employee.drop()
true
myTestDb> |
```

Drop database

```
myTestDb> db.dropDatabase()
{ ok: 1, dropped: 'myTestDb' }
```

CONCLUSION:

The experiment aimed to install and configure MongoDB for executing NoSQL commands. MongoDB was successfully installed and customized to meet specific requirements, including security measures and system parameters. We learned to utilize NoSQL commands for various database operations, such as data insertion, querying, and indexing. MongoDB exhibited scalability and performance for unstructured data, making it suitable for NoSQL applications. The availability of extensive documentation and community support contributed to a successful experiment, with valuable skills for efficient NoSQL data management using MongoDB.