



**Vidyavardhini's College of Engineering & Technology**  
Department of Computer Engineering

---

Experiment No. 2
Analyze the Titanic Survival Dataset and apply appropriate regression technique
Date of Performance: 17/08/2023
Date of Submission: 24/08/2023



CSL701: Machine Learning Lab

**Aim:** Analyze the Titanic Survival Dataset and apply appropriate Regression Technique.

**Objective:** Able to perform various feature engineering tasks, apply logistic regression on the given dataset and maximize the accuracy.

**Theory:**

Logistic Regression was used in the biological sciences in early twentieth century. It was then used in many social science applications. Logistic Regression is used when the dependent variable(target) is categorical and is binary in nature. In order to perform binary classification, the logistic regression techniques make use of Sigmoid function.


For example,

To predict whether an email is spam (1) or (0)

Whether the tumor is malignant (1) or not (0)

Consider a scenario where we need to classify whether an email is spam or not. If we use linear regression for this problem, there is a need for setting up a threshold based on which classification can be done. Say if the actual class is malignant, predicted continuous value 0.4 and the threshold value is 0.5, the data point will be classified as not malignant which can lead to serious consequence in real time.

CSL701: Machine Learning Lab



From this example, it can be inferred that linear regression is not suitable for classification problem. Linear regression is unbounded, and this brings logistic regression into picture. Their value strictly ranges from 0 to 1.

### Dataset:

The sinking of the Titanic is one of the most infamous shipwrecks in history.

On April 15, 1912, during her maiden voyage, the widely considered “unsinkable” RMS Titanic sank after colliding with an iceberg. Unfortunately, there weren’t enough lifeboats for everyone onboard, resulting in the death of 1502 out of 2224 passengers and crew.

While there was some element of luck involved in surviving, it seems some groups of people were more likely to survive than others.



In this challenge, we ask you to build a predictive model that answers the question: “what sorts of people were more likely to survive?” using passenger data (ie name, age, gender, socioeconomic class, etc).

Variable	Definition	Key
survival	Survival	0 = No, 1 = Yes
pclass	Ticket class	1 = 1st, 2 = 2nd, 3 = 3rd
sex	Sex	
Age	Age in years	
sibsp	# of siblings / spouses aboard the Titanic	
parch	# of parents / children aboard the Titanic	
ticket	Ticket number	
fare	Passenger fare	
cabin	Cabin number	



embarked	Port of Embarkation	C = Cherbourg, Q = Queenstown, S = Southampton
----------	---------------------	--

Variable Notes pclass: A proxy for socio-economic status (SES) 1st = Upper, 2nd = Middle, 3rd = Lower age: Age is fractional if less than 1. If the age is estimated, is it in the form of xx.5

sibsp: The dataset defines family relations in this way...

Sibling = brother, sister, stepbrother, stepsister

Spouse = husband, wife (mistresses and fiancés were ignored)

parch: The dataset defines family relations in this way...

Parent = mother, father

Child = daughter, son, stepdaughter, stepson

Some children travelled only with a nanny, therefore parch=0 for them.

```
In [40]: import numpy as np
import pandas as pd
import matplotlib.pyplot as plt
import seaborn as sns
from sklearn.model_selection import train_test_split
from sklearn.linear_model import LogisticRegression
from sklearn.metrics import accuracy_score, confusion_matrix
import warnings
warnings.filterwarnings('ignore')
```

```
In [2]: # Load the data from csv file to Pandas DataFrame
df = pd.read_csv('train.csv')
```

```
In [3]: # printing the first 5 rows of the dataframe
df.head()
```

Out[3]:

	PassengerId	Survived	Pclass	Name	Sex	Age	SibSp	Parch	Ticket	Fare	Cabin	Emba
0	1	0	3	Braund, Mr. Owen Harris	male	22.0	1	0	A/5 21171	7.2500	NaN	
1	2	1	1	Cumings, Mrs. John Bradley (Florence Briggs Th...)	female	38.0	1	0	PC 17599	71.2833	C85	
2	3	1	3	Heikkinen, Miss. Laina	female	26.0	0	0	STON/O2. 3101282	7.9250	NaN	
3	4	1	1	Futrelle, Mrs. Jacques Heath (Lily May Peel)	female	35.0	1	0	113803	53.1000	C123	
4	5	0	3	Allen, Mr. William Henry	male	35.0	0	0	373450	8.0500	NaN	



```
In [4]: # number of rows and Columns
df.shape
```

Out[4]: (891, 12)

```
]: #
```

```
In [5]    getting some informations about the data  
df.info()
```

```
<class 'pandas.core.frame.DataFrame'>  
RangeIndex: 891 entries, 0 to 890  
Data columns (total 12 columns):  
#   Column      Non-Null Count  Dtype  
---  ---  
0   PassengerId  891 non-null    int64  
1   Survived     891 non-null    int64  
2   Pclass       891 non-null    int64  
3   Name         891 non-null    object  
4   Sex          891 non-null    object  
5   Age         714 non-null    float64  
6   SibSp        891 non-null    int64  
7   Parch        891 non-null    int64  
8   Ticket       891 non-null    object  
9   Fare         891 non-null    float64  
10  Cabin        204 non-null    object  
11  Embarked     889 non-null    object  
dtypes: float64(2), int64(5), object(5)  
memory usage: 83.7+ KB
```

```
In [6]: # check the number of missing values in each column  
df.isnull().sum()
```

```
Out[6]: PassengerId      0  
Survived                0  
Pclass                  0  
Name                    0  
Sex                     0  
Age                    177  
SibSp                   0  
Parch                   0  
Ticket                  0  
Fare                    0  
Cabin                   687  
Embarked                 2  
dtype: int64
```

```
In [7]: # drop the "Cabin" column from the dataframe  
df = df.drop(columns='Cabin', axis=1)
```

```
In [8]: # replacing the missing values in "Age" column with mean value  
df['Age'].fillna(df['Age'].mean(), inplace=True)
```

```
In [9]: # finding the mode value of "Embarked" column  
print(df['Embarked'].mode())
```

```
0    S  
dtype: object
```

```
In [10]: print(df['Embarked'].mode()[0])
```

```
S
```

```
In [1 ]: #
```

```
1     replacing the missing values in "Embarked" column with mode value
df['Embarked'].fillna(df['Embarked'].mode()[0], inplace=True)
```

```
In [12]: # check the number of missing values in each column
df.isnull().sum()
```

```
Out[12]: PassengerId    0
Survived              0
Pclass               0
Name                 0
Sex                  0
Age                  0
SibSp                0
Parch                0
Ticket              0
Fare                 0
Embarked             0
dtype: int64
```

#### Data Analysis

```
In [13]: # getting some statistical measures about the data
df.describe()
```

```
Out[13]:
```

	PassengerId	Survived	Pclass	Age	SibSp	Parch	Fare
count	891.000000	891.000000	891.000000	891.000000	891.000000	891.000000	891.000000
mean	446.000000	0.383838	2.308642	29.699118	0.523008	0.381594	32.204208
std	257.353842	0.486592	0.836071	13.002015	1.102743	0.806057	49.693429
min	1.000000	0.000000	1.000000	0.420000	0.000000	0.000000	0.000000
25%	223.500000	0.000000	2.000000	22.000000	0.000000	0.000000	7.910400
50%	446.000000	0.000000	3.000000	29.699118	0.000000	0.000000	14.454200
75%	668.500000	1.000000	3.000000	35.000000	1.000000	0.000000	31.000000
max	891.000000	1.000000	3.000000	80.000000	8.000000	6.000000	512.329200

```
In [14]: # finding the number of people survived and not survived
df['Survived'].value_counts()
```


```
Out[14]: 0    549
1     342
Name: Survived, dtype: int64
```



```
In [1 ]: #
```

```
5     making a count plot for "Survived" column  
sns.countplot(x='Survived', data=df)
```

```
Out[15]: <AxesSubplot:xlabel='Survived', ylabel='count'>
```




```
In [16]: df['Sex'].value_counts()
```

```
Out[16]: male      577  
female    314  
Name: Sex, dtype: int64
```

```
In [17]: # making a count plot for "Sex" column  
sns.countplot(x='Sex', data=df)
```


```
Out[17]: <AxesSubplot:xlabel='Sex', ylabel='count'>
```



```
In [1 ]: #
```


```
8      number of survivors Gender wise  
sns.countplot(x='Sex', hue='Survived', data=df)
```

```
Out[18]: <AxesSubplot:xlabel='Sex', ylabel='count'>
```



```
In [19]: # making a count plot for "Pclass" column  
sns.countplot(x='Pclass', data=df)
```


```
Out[19]: <AxesSubplot:xlabel='Pclass', ylabel='count'>
```



In [ ]:

```
20 sns.countplot(x='Pclass', hue='Survived', data=df)
```

Out[20]: <AxesSubplot:xlabel='Pclass', ylabel='count'>



```
In [21]: df['Sex'].value_counts()
```

Out[21]: male 577  
female 314  
Name: Sex, dtype: int64

```
In [22]: df['Embarked'].value_counts()
```

Out[22]: S 646  
C 168  
Q 77  
Name: Embarked, dtype: int64

```
In [23]: # converting categorical Columns  
df.replace({'Sex':{'male':0,'female':1}, 'Embarked':{'S':0,'C':1,'Q':2}}, inplace=True)
```

```
In [24]: df.head()
```

Out[24]:

	PassengerId	Survived	Pclass	Name	Sex	Age	SibSp	Parch	Ticket	Fare	Embarked
0	1	0	3	Braund, Mr. Owen Harris	0	22.0	1	0	A/5 21171	7.2500	0
1	2	1	1	Cumings, Mrs. John Bradley (Florence Briggs Th...	1	38.0	1	0	PC 17599	71.2833	1
2	3	1	3	Heikkinen, Miss. Laina	1	26.0	0	0	STON/O2. 3101282	7.9250	0
3	4	1	1	Futrelle, Mrs. Jacques Heath (Lily May Peel)	1	35.0	1	0	113803	53.1000	0
4	5	0	3	Allen, Mr. William Henry	0	35.0	0	0	373450	8.0500	0

In [ ]:

```
25 X = df.drop(columns = ['PassengerId', 'Name', 'Ticket', 'Survived'], axis=1)
    Y = df['Survived']
```

In [26]: X.head(3)

Out[26]:

	Pclass	Sex	Age	SibSp	Parch	Fare	Embarked
0	3	0	22.0	1	0	7.2500	0
1	1	1	38.0	1	0	71.2833	1
2	3	1	26.0	0	0	7.9250	0

In [27]: Y.head(3)

Out[27]:

```
0    0
1    1
2    1
Name: Survived, dtype: int64
```

```
In [28]: #Splitting the data into training data & Test data
X_train, X_test, Y_train, Y_test = train_test_split(X, Y, test_size=0.2, random_state=2)
```

In [30]: model = LogisticRegression()

```
In [31]: # training the Logistic Regression model with training data
model.fit(X_train, Y_train)
```

Out[31]:

```
▼ LogisticRegression
LogisticRegression()
```

```
In [32]: # accuracy on training data
X_train_prediction = model.predict(X_train)
```

In [ ]:

```
33 X_train_prediction
```

```
Out[33]: array([0, 1, 0, 0, 0, 0, 0, 1, 0, 0, 0, 1, 0, 0, 1, 0, 1, 0, 0, 0, 0, 0,
 1, 0, 0, 1, 0, 0, 1, 0, 1, 1, 0, 0, 1, 0, 1, 0, 0, 0, 0, 0, 0, 1,
 1, 0, 0, 1, 0, 1, 0, 1, 0, 0, 0, 0, 0, 0, 1, 0, 1, 0, 0, 1, 1, 0,
 0, 1, 1, 0, 1, 0, 0, 1, 0, 0, 0, 0, 0, 0, 1, 0, 0, 0, 1, 0, 0, 0,
 1, 0, 1, 0, 0, 1, 0, 0, 0, 1, 1, 1, 0, 1, 0, 0, 0, 0, 0, 1, 0, 0,
 0, 1, 1, 0, 0, 1, 0, 0, 1, 0, 0, 1, 0, 0, 1, 0, 1, 0, 1, 0, 1, 0,
 1, 1, 1, 1, 1, 1, 0, 0, 1, 1, 1, 0, 0, 1, 0, 0, 0, 0, 0, 0, 1, 0,
 1, 0, 0, 0, 0, 0, 0, 0, 0, 1, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 1, 1,
 0, 0, 1, 0, 1, 0, 1, 1, 1, 0, 0, 0, 1, 0, 0, 0, 1, 0, 0, 1, 0, 0,
 0, 1, 1, 0, 1, 0, 0, 0, 0, 0, 1, 1, 0, 1, 1, 1, 1, 0, 0, 0, 0, 0,
 0, 0, 0, 1, 0, 0, 1, 1, 1, 0, 0, 1, 0, 1, 1, 1, 0, 0, 1, 0, 0, 0,
 0, 1, 0, 0, 0, 1, 0, 0, 0, 1, 0, 1, 0, 1, 0, 0, 0, 0, 0, 0, 0, 0,
 0, 1, 0, 1, 0, 0, 1, 0, 0, 1, 0, 1, 0, 1, 1, 0, 0, 0, 0, 1, 0, 1,
 0, 0, 1, 0, 0, 0, 1, 0, 0, 0, 0, 1, 1, 0, 0, 0, 0, 0, 0, 1, 0, 1,
 0, 0, 0, 0, 0, 1, 1, 1, 0, 0, 0, 1, 0, 1, 0, 0, 0, 0, 0, 0, 1, 1,
 0, 1, 1, 0, 1, 1, 1, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 1, 0, 0, 1, 1,
 0, 1, 0, 0, 0, 0, 1, 1, 0, 0, 0, 1, 0, 1, 1, 1, 0, 0, 0, 0, 1, 0,
 0, 0, 1, 1, 0, 0, 1, 0, 1, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 1, 0, 0,
 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 1, 0, 0, 0,
 1, 0, 0, 0, 0, 0, 1, 0, 1, 0, 1, 0, 0, 0, 1, 0, 1, 1, 1, 0, 0, 0,
 1, 0, 1, 0, 0, 0, 1, 1, 1, 0, 0, 1, 1, 0, 0, 0, 1, 0, 1, 0, 0, 0,
 0, 0, 1, 1, 0, 1, 1, 1, 0, 0, 0, 1, 0, 0, 0, 0, 1, 0, 0, 0, 1, 0,
 0, 1, 0, 0, 0, 0, 1, 0, 0, 1, 0, 1, 0, 0, 0, 1, 1, 1, 1, 1, 0, 0,
 1, 1, 0, 1, 1, 1, 1, 0, 0, 0, 1, 1, 0, 0, 1, 0, 0, 0, 0, 0, 0, 0,
 0, 0, 1, 1, 0, 0, 1, 0], dtype=int64)
```

```
In [34]: training_data_accuracy = accuracy_score(Y_train, X_train_prediction)
print('Accuracy score of training data : ', training_data_accuracy)
```

Accuracy score of training data : 0.8075842696629213

```
In [36]: # accuracy on test data
X_test_prediction = model.predict(X_test)
```

```
In [37]: X_test_prediction
```

```
Out[37]: array([0, 0, 1, 0, 0, 0, 0, 0, 0, 0, 0, 0, 1, 1, 0, 0, 1, 0, 0, 1, 0, 1, 1,
 0, 1, 0, 1, 1, 0, 0, 0, 0, 0, 0, 0, 0, 1, 1, 0, 0, 0, 0, 0, 0, 1, 0,
 0, 1, 1, 0, 0, 1, 0, 0, 0, 0, 0, 0, 0, 1, 0, 0, 0, 0, 1, 0, 0, 0, 1, 0,
 1, 0, 0, 0, 1, 0, 1, 0, 1, 0, 0, 0, 1, 0, 1, 0, 0, 0, 1, 1, 0, 0, 0,
 1, 0, 0, 0, 0, 0, 0, 1, 0, 1, 0, 0, 1, 0, 1, 1, 0, 1, 1, 0, 0, 0, 0,
 0, 0, 0, 0, 1, 1, 0, 1, 0, 0, 1, 0, 0, 0, 0, 0, 0, 0, 1, 0, 0, 0, 0,
 1, 1, 0, 0, 0, 0, 0, 0, 1, 1, 1, 1, 0, 1, 0, 0, 0, 0, 1, 0, 0, 0, 0,
 1, 0, 0, 1, 1, 0, 1, 0, 0, 0, 1, 1, 0, 0, 1, 0, 0, 1, 1, 1, 0, 0, 0,
 0, 0, 0], dtype=int64)
```

In [ ]:


```
39 test_data_accuracy = accuracy_score(Y_test, X_test_prediction)
   print('Accuracy score of test data : ', test_data_accuracy)
```

Accuracy score of test data : 0.7821229050279329

```
In [48]: print("Confusion matrix :-")
   sns.heatmap(confusion_matrix(Y_test, X_test_prediction), annot=True)
```

Confusion matrix :-

Out[48]: <AxesSubplot:>



```
In [44]: from sklearn.metrics import classification_report
   print(classification_report(Y_test, X_test_prediction))
```

	precision	recall	f1-score	support
0	0.75	0.91	0.82	100
1	0.84	0.62	0.72	79
accuracy			0.78	179
macro avg	0.80	0.77	0.77	179
weighted avg	0.79	0.78	0.78	179



**Conclusion:**

1. The Features chosen to develop the model are as follows: -
  - a. Pclass – Ticket class
  - b. Sex - sex
  - c. Age – Age in years
  - d. Sibsp – No. of siblings/spouses aboard the titanic
  - e. Parch – No. of parents/children aboard the titanic
  - f. Fare - Passenger fare
  - g. Embarked – Port of Embarkation

These features were chosen after performing appropriate feature engineering on the dataset such as handling missing values and converting categorical columns such as the attributes Sex and Embarked. These features also contributed in the prediction of the final outcome

2. The Accuracy score obtained by our logistic regression model on the training data is 0.80 which means our model is 80% accurate on the given training data.
3. The Accuracy score obtained by our logistic regression model on the testing data is 0.78 which means our model is 78% accurate on the testing data.

