

DonorsChoose

DonorsChoose.org receives hundreds of thousands of project proposals each year for classroom projects in need of funding. Right now, a large number of volunteers is needed to manually screen each submission before it's approved to be posted on the DonorsChoose.org website.

Next year, DonorsChoose.org expects to receive close to 500,000 project proposals. As a result, there are three main problems they need to solve:

- How to scale current manual processes and resources to screen 500,000 projects so that they can be posted as quickly and as efficiently as possible
- How to increase the consistency of project vetting across different volunteers to improve the experience for teachers
- How to focus volunteer time on the applications that need the most assistance

The goal of the competition is to predict whether or not a DonorsChoose.org project proposal submitted by a teacher will be approved, using the text of project descriptions as well as additional metadata about the project, teacher, and school. DonorsChoose.org can then use this information to identify projects most likely to need further review before approval.

About the DonorsChoose Data Set

The `train.csv` data set provided by DonorsChoose contains the following features:

Feature		Desc
<code>project_id</code>		A unique identifier for the proposed project. Example: p0
<code>project_title</code>	• •	Title of the project. Exa Art Will Make You H First Grad
<code>project_grade_category</code>	• • • •	Grade level of students for which the project is targeted. One of the fo enumerated v Grades P Grade Grade Grades

Feature	Desc
	One or more (comma-separated) subject categories for the project from the following enumerated list of values:
project_subject_categories	<ul style="list-style-type: none"> Applied Learning Care & Health Health & Safety History & Culture Literacy & Language Math & Science Music & The Arts Special Education World Languages
	Example:
	<ul style="list-style-type: none"> Music & The Arts Literacy & Language, Math & Science
school_state	State where school is located (Two-letter U.S. postal code) (https://en.wikipedia.org/wiki/List_of_U.S._state_abbreviations#Postal_codes)
	Example:
project_subject_subcategories	One or more (comma-separated) subject subcategories for the project.
	Example:
	<ul style="list-style-type: none"> Literature & Writing Literature & Writing, Social Science
project_resource_summary	An explanation of the resources needed for the project. Example:
	<ul style="list-style-type: none"> My students need hands on literacy materials to meet sensory needs!<
project_essay_1	First application
project_essay_2	Second application
project_essay_3	Third application
project_essay_4	Fourth application
project_submitted_datetime	Datetime when project application was submitted. Example: 2016-01-12T12:43:50
teacher_id	A unique identifier for the teacher of the proposed project. Example: bdf8baa8fedef6bfeec7ae4ff1c
teacher_prefix	Teacher's title. One of the following enumerated values:
	<ul style="list-style-type: none"> Teacher Assistant Teacher Paraprofessional Student Teacher Other
teacher_number_of_previously_posted_projects	Number of project applications previously submitted by the same teacher. Example:

* See the section **Notes on the Essay Data** for more details about these features.

Additionally, the `resources.csv` data set provides more data about the resources required for each project. Each line in this file represents a resource required by a project:

Feature	Description
id	A <code>project_id</code> value from the <code>train.csv</code> file. Example: p036502
description	Description of the resource. Example: Tenor Saxophone Reeds, Box of 25

Feature	Description
quantity	Quantity of the resource required. Example: 3
price	Price of the resource required. Example: 9.95

Note: Many projects require multiple resources. The `id` value corresponds to a `project_id` in `train.csv`, so you use it as a key to retrieve all resources needed for a project:

The data set contains the following label (the value you will attempt to predict):

Label	Description
project_is_approved	A binary flag indicating whether DonorsChoose approved the project. A value of <code>0</code> indicates the project was not approved, and a value of <code>1</code> indicates the project was approved.

Notes on the Essay Data

Prior to May 17, 2016, the prompts for the essays were as follows:

- **project_essay_1:** "Introduce us to your classroom"
- **project_essay_2:** "Tell us more about your students"
- **project_essay_3:** "Describe how your students will use the materials you're requesting"
- **project_essay_3:** "Close by sharing why your project will make a difference"

Starting on May 17, 2016, the number of essays was reduced from 4 to 2, and the prompts for the first 2 essays were changed to the following:

- **project_essay_1:** "Describe your students: What makes your students special? Specific details about their background, your neighborhood, and your school are all helpful."
- **project_essay_2:** "About your project: How will these materials make a difference in your students' learning and improve their school lives?"

For all projects with `project_submitted_datetime` of 2016-05-17 and later, the values of `project_essay_3` and `project_essay_4` will be NaN.

In [1]:

```
%matplotlib inline
import warnings
warnings.filterwarnings("ignore")

import sqlite3
import pandas as pd
import numpy as np
import nltk
import string
import matplotlib.pyplot as plt
import seaborn as sns
from sklearn.feature_extraction.text import TfidfTransformer
from sklearn.feature_extraction.text import TfidfVectorizer

from sklearn.feature_extraction.text import CountVectorizer
from sklearn.metrics import confusion_matrix
from sklearn import metrics
from sklearn.metrics import roc_curve, auc
from nltk.stem.porter import PorterStemmer

import re
# Tutorial about Python regular expressions: https://pymotw.com/2/re/
import string
from nltk.corpus import stopwords
from nltk.stem import PorterStemmer
from nltk.stem.wordnet import WordNetLemmatizer

from gensim.models import Word2Vec
from gensim.models import KeyedVectors
import pickle

from tqdm import tqdm
import os

from plotly import plotly
import plotly.offline as offline
import plotly.graph_objs as go
offline.init_notebook_mode()
from collections import Counter
```

1.1 Reading Data

In [2]:

```
project_data = pd.read_csv('train_data.csv')
resource_data = pd.read_csv('resources.csv')
```

In [3]:

```
print("Number of data points in train data", project_data.shape)
print('-'*50)
print("The attributes of data :", project_data.columns.values)
```

Number of data points in train data (109248, 17)

The attributes of data : ['Unnamed: 0' 'id' 'teacher_id' 'teacher_prefix' 'school_state'

'project_submitted_datetime' 'project_grade_category'
 'project_subject_categories' 'project_subject_subcategories'
 'project_title' 'project_essay_1' 'project_essay_2' 'project_essay_3'
 'project_essay_4' 'project_resource_summary'
 'teacher_number_of_previously_posted_projects' 'project_is_approved']

In [4]:

```
print("Number of data points in train data", resource_data.shape)
print(resource_data.columns.values)
resource_data.head(2)
```

Number of data points in train data (1541272, 4)

['id' 'description' 'quantity' 'price']

Out[4]:

	id	description	quantity	price
0	p233245	LC652 - Lakeshore Double-Space Mobile Drying Rack	1	149.00
1	p069063	Bouncy Bands for Desks (Blue support pipes)	3	14.95

1.2 preprocessing of project_subject_categories

In [5]:

```
categories = list(project_data['project_subject_categories'].values)
# remove special characters from list of strings python: https://stackoverflow.com/a/473019

# https://www.geeksforgeeks.org/removing-stop-words-nltk-python/
# https://stackoverflow.com/questions/23669024/how-to-strip-a-specific-word-from-a-string
# https://stackoverflow.com/questions/8270092/remove-all-whitespace-in-a-string-in-python
cat_list = []
for i in categories:
    temp = ""
    # consider we have text like this "Math & Science, Warmth, Care & Hunger"
    for j in i.split(','): # it will split it in three parts ["Math & Science", "Warmth", "
        if 'The' in j.split(): # this will split each of the category based on space "Math
            j=j.replace('The', '') # if we have the words "The" we are going to replace it w
            j = j.replace(' ', '') # we are placing all the ' '(space) with ''(empty) ex:"Math
            temp+=j.strip()+" " # " abc ".strip() will return "abc", remove the trailing spaces
            temp = temp.replace('&', '_') # we are replacing the & value into
    cat_list.append(temp.strip())

project_data['clean_categories'] = cat_list
project_data.drop(['project_subject_categories'], axis=1, inplace=True)
```

In [6]:

```
k=[]  
for i in cat_list:  
    for j in i.split():  
        k.append(j)
```

In [7]:

```
k=set(k)
```

In []:

In [12]:

```
cat_list=set(cat_list)
```

In [13]:

```
c=cat_list-k
```

In []:

1.3 preprocessing of project_subject_subcategories

In []:

In [14]:

```

sub_categories = list(project_data['project_subject_subcategories'].values)
# remove special characters from list of strings python: https://stackoverflow.com/a/473019

# https://www.geeksforgeeks.org/removing-stop-words-nltk-python/
# https://stackoverflow.com/questions/23669024/how-to-strip-a-specific-word-from-a-string
# https://stackoverflow.com/questions/8270092/remove-all-whitespace-in-a-string-in-python

sub_cat_list = []
for i in sub_categories:
    temp = ""
    # consider we have text like this "Math & Science, Warmth, Care & Hunger"
    for j in i.split(','): # it will split it in three parts ["Math & Science", "Warmth", "
        if 'The' in j.split(): # this will split each of the category based on space "Math
            j=j.replace('The', '') # if we have the words "The" we are going to replace it w
            j = j.replace(' ', '') # we are placing all the ' '(space) with ''(empty) ex:"Math
            temp +=j.strip()+" "# abc ".strip() will return "abc", remove the trailing spaces
            temp = temp.replace('&', '_')
    sub_cat_list.append(temp.strip())

project_data['clean_subcategories'] = sub_cat_list
project_data.drop(['project_subject_subcategories'], axis=1, inplace=True)

# count of all the words in corpus python: https://stackoverflow.com/a/22898595/4084039

```

In [15]:

```
project_data.head(2)
```

Out[15]:

	Unnamed: 0	id	teacher_id	teacher_prefix	school_state	project
0	160221	p253737	c90749f5d961ff158d4b4d1e7dc665fc	Mrs.	IN	
1	140945	p258326	897464ce9ddc600bced1151f324dd63a	Mr.	FL	

1.3 Text preprocessing

In [16]:

```

# merge two column text dataframe:
project_data["essay"] = project_data["project_essay_1"].map(str) + \
    project_data["project_essay_2"].map(str) + \
    project_data["project_essay_3"].map(str) + \
    project_data["project_essay_4"].map(str)

```

In [17]:

```
project_data.head(2)
```

Out[17]:

Unnamed: 0		id	teacher_id	teacher_prefix	school_state	project
0	160221	p253737	c90749f5d961ff158d4b4d1e7dc665fc	Mrs.	IN	
1	140945	p258326	897464ce9ddc600bced1151f324dd63a	Mr.	FL	

In [18]:

```
#### 1.4.2.3 Using Pretrained Models: TFIDF weighted W2V
```


In [19]:

```
# printing some random reviews
print(project_data['essay'].values[0])
print("="*50)
print(project_data['essay'].values[150])
print("="*50)
print(project_data['essay'].values[1000])
print("="*50)
print(project_data['essay'].values[20000])
print("="*50)
print(project_data['essay'].values[99999])
print("="*50)
```

My students are English learners that are working on English as their second or third languages. We are a melting pot of refugees, immigrants, and native-born Americans bringing the gift of language to our school. \r\n\r\n We have over 24 languages represented in our English Learner program with students at every level of mastery. We also have over 40 countries represented with the families within our school. Each student brings a wealth of knowledge and experiences to us that open our eyes to new cultures, beliefs, and respect. "The limits of your language are the limits of your world." -Ludwig Wittgenstein Our English learner's have a strong support system at home that begs for more resources. Many times our parents are learning to read and speak English alongside of their children. Sometimes this creates barriers for parents to be able to help their child learn phonetics, letter recognition, and other reading skills. \r\n\r\n By providing these dvd's and players, students are able to continue their mastery of the English language even if no one at home is able to assist. All families with students within the Level 1 proficiency status, will be offered to be a part of this program. These educational videos will be specially chosen by the English Learner Teacher and will be sent home regularly to watch. The videos are to help the child develop early reading skills. \r\n\r\n Parents that do not have access to a dvd player will have the opportunity to check out a dvd player to use for the year. The plan is to use these videos and educational dvd's for the years to come for other EL students. \r\nnnannan

=====

The 51 fifth grade students that will cycle through my classroom this year all love learning, at least most of the time. At our school, 97.3% of the students receive free or reduced price lunch. Of the 560 students, 97.3% are minority students. \r\nThe school has a vibrant community that loves to get together and celebrate. Around Halloween there is a whole school parade to show off the beautiful costumes that students wear. On Cinco de Mayo we put on a big festival with crafts made by the students, dances, and games. At the end of the year the school hosts a carnival to celebrate the hard work put in during the school year, with a dunk tank being the most popular activity. My students will use these five brightly colored Hokki stools in place of regular, stationary, 4-legged chairs. As I will only have a total of ten in the classroom and not enough for each student to have an individual one, they will be used in a variety of ways. During independent reading time they will be used as special chairs students will each use on occasion. I will utilize them in place of chairs at my small group tables during math and reading times. The rest of the day they will be used by the students who need the highest amount of movement in their life in order to stay focused on school. \r\n\r\n Whenever asked what the classroom is missing, my students always say more Hokki Stools. They can't get their fill of the 5 stools we already have. When the students are sitting in group with me on the Hokki Stools, they are always moving, but at the same time doing their work. Anytime the students get to pick where they can sit, the Hokki Stools are the first to be taken. There are always students who head over to the kidney table to get one of the stools who are disappointed as there are not enough of them. \r\n\r\n We ask a

lot of students to sit for 7 hours a day. The Hokki stools will be a compromise that allow my students to do desk work and move at the same time. These stools will help students to meet their 60 minutes a day of movement by allowing them to activate their core muscles for balance while they sit. For many of my students, these chairs will take away the barrier that exists in schools for a child who can't sit still.nannan

=====

How do you remember your days of school? Was it in a sterile environment with plain walls, rows of desks, and a teacher in front of the room? A typical day in our room is nothing like that. I work hard to create a warm inviting themed room for my students look forward to coming to each day.\r\n\r\nMy class is made up of 28 wonderfully unique boys and girls of mixed races in Arkansas.\r\n\r\nThey attend a Title I school, which means there is a high enough percentage of free and reduced-price lunch to qualify. Our school is an "open classroom" concept, which is very unique as there are no walls separating the classrooms. These 9 and 10 year-old students are very eager learners; they are like sponges, absorbing all the information and experiences and keep on wanting more. With these resources such as the comfy red throw pillows and the whimsical nautical hanging decor and the blue fish nets, I will be able to help create the mood in our classroom setting to be one of a themed nautical environment. Creating a classroom environment is very important in the success in each and every child's education. The nautical photo props will be used with each child as they step foot into our classroom for the first time on Meet the Teacher evening. I'll take pictures of each child with them, have them developed, and then hung in our classroom ready for their first day of 4th grade. This kind gesture will set the tone before even the first day of school! The nautical thank you cards will be used throughout the year by the students as they create thank you cards to their team groups.\r\n\r\n\r\nYour generous donations will help me to help make our classroom a fun, inviting, learning environment from day one.\r\n\r\n\r\nIt costs a lot of money out of my own pocket on resources to get our classroom ready. Please consider helping with this project to make our new school year a very successful one. Thank you!nannan

=====

My kindergarten students have varied disabilities ranging from speech and language delays, cognitive delays, gross/fine motor delays, to autism. They are eager learners and always strive to work their hardest working past their limitations. \r\n\r\n\r\nThe materials we have are the ones I seek out for my students. I teach in a Title I school where most of the students receive free or reduced price lunch. Despite their disabilities and limitations, my students love coming to school and come eager to learn and explore. Have you ever felt like you had ants in your pants and you needed to groove and move as you were in a meeting? This is how my kids feel all the time. They want to be able to move as they learn or so they say. Wobble chairs are the answer and I love them because they develop their core, which enhances gross motor and in turn fine motor skills. \r\n\r\nThey also want to learn through games, my kids don't want to sit and do worksheets. They want to learn to count by jumping and playing. Physical engagement is the key to our success. The number toss and color and shape mats can make that happen. My students will forget they are doing work and just have the fun a 6 year old deserves.nannan

=====

The mediocre teacher tells. The good teacher explains. The superior teacher demonstrates. The great teacher inspires. -William A. Ward\r\n\r\n\r\nMy school has 803 students which is makeup is 97.6% African-American, making up the largest segment of the student body. A typical school in Dallas is made up of 23.2% African-American students. Most of the students are on free or reduced lunch. We aren't receiving doctors, lawyers, or engineers children from rich backgrounds or neighborhoods. As an educator I am inspiring minds of young children and we focus not only on academics but one smart, effective, efficient, and disciplined students with good character. In our classroom we can utilize the Bluetooth for swift transitions during class. I use a speaker which

doesn't amplify the sound enough to receive the message. Due to the volume of my speaker my students can't hear videos or books clearly and it isn't making the lessons as meaningful. But with the bluetooth speaker my students will be able to hear and I can stop, pause and replay it at any time.\r\nThe cart will allow me to have more room for storage of things that are needed for the day and has an extra part to it I can use. The table top chart has all of the letter, words and pictures for students to learn about different letters and it is more accessible.nannan

=====

In [20]:

```
# https://stackoverflow.com/a/47091490/4084039
import re
```

```
def decontracted(phrase):
    # specific
    phrase = re.sub(r"won't", "will not", phrase)
    phrase = re.sub(r"can't", "can not", phrase)

    # general
    phrase = re.sub(r"n't", " not", phrase)
    phrase = re.sub(r"'re", " are", phrase)
    phrase = re.sub(r"'s", " is", phrase)
    phrase = re.sub(r"'d", " would", phrase)
    phrase = re.sub(r"'ll", " will", phrase)
    phrase = re.sub(r"'t", " not", phrase)
    phrase = re.sub(r"'ve", " have", phrase)
    phrase = re.sub(r"'m", " am", phrase)
    return phrase
```

In [21]:

```
sent = decontracted(project_data['essay'].values[20000])
print(sent)
print("="*50)
```

My kindergarten students have varied disabilities ranging from speech and language delays, cognitive delays, gross/fine motor delays, to autism. They are eager beavers and always strive to work their hardest working past their limitations. \r\n\r\nThe materials we have are the ones I seek out for my students. I teach in a Title I school where most of the students receive free or reduced price lunch. Despite their disabilities and limitations, my students love coming to school and come eager to learn and explore. Have you ever felt like you had ants in your pants and you needed to groove and move as you were in a meeting? This is how my kids feel all the time. They want to be able to move as they learn or so they say. Wobble chairs are the answer and I love them because they develop their core, which enhances gross motor and in turn fine motor skills. \r\n\r\nThey also want to learn through games, my kids do not want to sit and do worksheets. They want to learn to count by jumping and playing. Physical engagement is the key to our success. The number toss and color and shape mats can make that happen. My students will forget they are doing work and just have the fun a 6 year old deserves.nannan

=====

In [22]:

```
# \r \n \t remove from string python: http://texthandler.com/info/remove-line-breaks-python
sent = sent.replace('\r', ' ')
sent = sent.replace('\n', ' ')
sent = sent.replace('\t', ' ')
print(sent)
```

My kindergarten students have varied disabilities ranging from speech and language delays, cognitive delays, gross/fine motor delays, to autism. They are eager beavers and always strive to work their hardest working past their limitations. The materials we have are the ones I seek out for my students. I teach in a Title I school where most of the students receive free or reduced price lunch. Despite their disabilities and limitations, my students love coming to school and come eager to learn and explore. Have you ever felt like you had ants in your pants and you needed to groove and move as you were in a meeting? This is how my kids feel all the time. They want to be able to move as they learn or so they say. Wobble chairs are the answer and I love them because they develop their core, which enhances gross motor and in turn fine motor skills. They also want to learn through games, my kids do not want to sit and do worksheets. They want to learn to count by jumping and playing. Physical engagement is the key to our success. The number toss and color and shape mats can make that happen. My students will forget they are doing work and just have the fun a 6 year old deserves. nannan

In [23]:

```
#remove spacial character: https://stackoverflow.com/a/5843547/4084039
sent = re.sub('[^A-Za-z0-9]+', ' ', sent)
print(sent)
```

My kindergarten students have varied disabilities ranging from speech and language delays cognitive delays gross fine motor delays to autism They are eager beavers and always strive to work their hardest working past their limitations The materials we have are the ones I seek out for my students I teach in a Title I school where most of the students receive free or reduced price lunch Despite their disabilities and limitations my students love coming to school and come eager to learn and explore Have you ever felt like you had ants in your pants and you needed to groove and move as you were in a meeting This is how my kids feel all the time They want to be able to move as they learn or so they say Wobble chairs are the answer and I love them because they develop their core which enhances gross motor and in turn fine motor skills They also want to learn through games my kids do not want to sit and do worksheets They want to learn to count by jumping and playing Physical engagement is the key to our success The number toss and color and shape mats can make that happen My students will forget they are doing work and just have the fun a 6 year old deserves nannan

In [24]:

```
# https://gist.github.com/sebleier/554280
# we are removing the words from the stop words list: 'no', 'nor', 'not'
stopwords= ['i', 'me', 'my', 'myself', 'we', 'our', 'ours', 'ourselves', 'you', "you're", "
    "you'll", "you'd", 'your', 'yours', 'yourself', 'yourselves', 'he', 'him', 'his',
    'she', "she's", 'her', 'hers', 'herself', 'it', "it's", 'its', 'itself', 'they',
    'theirs', 'themselves', 'what', 'which', 'who', 'whom', 'this', 'that', "that'll",
    'am', 'is', 'are', 'was', 'were', 'be', 'been', 'being', 'have', 'has', 'had',
    'did', 'doing', 'a', 'an', 'the', 'and', 'but', 'if', 'or', 'because', 'as', 'until',
    'at', 'by', 'for', 'with', 'about', 'against', 'between', 'into', 'through', 'during',
    'above', 'below', 'to', 'from', 'up', 'down', 'in', 'out', 'on', 'off', 'over',
    'then', 'once', 'here', 'there', 'when', 'where', 'why', 'how', 'all', 'any', 'each',
    'most', 'other', 'some', 'such', 'only', 'own', 'same', 'so', 'than', 'too', 'very',
    's', 't', 'can', 'will', 'just', 'don', "don't", 'should', "should've", 'now',
    've', 'y', 'ain', 'aren', "aren't", 'couldn', "couldn't", 'didn', "didn't", 'do',
    "hadn't", 'hasn', "hasn't", 'haven', "haven't", 'isn', "isn't", 'ma', 'mightn',
    "mustn't", 'needn', "needn't", 'shan', "shan't", 'shouldn', "shouldn't", 'wasn',
    'won', "won't", 'wouldn', "wouldn't"]
```

In [25]:

```
# Combining all the above students
from tqdm import tqdm
preprocessed_essays = []
# tqdm is for printing the status bar
for sentence in tqdm(project_data['essay'].values):
    sent = decontracted(sentence)
    sent = sent.replace('\r', ' ')
    sent = sent.replace('\n', ' ')
    sent = sent.replace('\t', ' ')
    sent = re.sub('[^A-Za-z0-9]+', '', sent)
    # https://gist.github.com/sebleier/554280
    sent = ' '.join(e for e in sent.split() if e not in stopwords)
    preprocessed_essays.append(sent.lower().strip())
```

100%|██████████| 109248/109248 [01:11<00:00, 1534.04it/s]

In [26]:

```
# after preprocessing
preprocessed_essays[20000]
```

Out[26]:

'my kindergarten students varied disabilities ranging speech language delays
cognitive delays gross fine motor delays autism they eager beavers always st
rive work hardest working past limitations the materials ones i seek student
s i teach title i school students receive free reduced price lunch despite d
isabilities limitations students love coming school come eager learn explore
have ever felt like ants pants needed groove move meeting this kids feel tim
e the want able move learn say wobble chairs answer i love develop core enha
nces gross motor turn fine motor skills they also want learn games kids not
want sit worksheets they want learn count jumping playing physical engagemen
t key success the number toss color shape mats make happen my students forge
t work fun 6 year old deserves nannan'

1.4 Preprocessing of project_title

In [27]:

```
# similarly you can preprocess the titles also
# similarly you can preprocess the titles also
from tqdm import tqdm
preprocessed_titles = []
# tqdm is for printing the status bar
for sentence in tqdm(project_data['project_title'].values):
    sent = decontracted(sentence)
    sent = sent.replace('\\r', ' ')
    sent = sent.replace('\\\"', ' ')
    sent = sent.replace('\\n', ' ')
    sent = re.sub('[^A-Za-z0-9]+', ' ', sent)
    # https://gist.github.com/sebleier/554280
    sent = ' '.join(e for e in sent.split() if e not in stopwords)
    preprocessed_titles.append(sent.lower().strip())
```

100%|██████████| 109248/109248 [00:03<00:00, 34709.75it/s]

In [28]:

```
project_data['clean_essay']=preprocessed_essays
project_data['clean_title']=preprocessed_titles
```

1.5 Preparing data for models

In [29]:

```
project_data.columns
```

Out[29]:

```
Index(['Unnamed: 0', 'id', 'teacher_id', 'teacher_prefix', 'school_state',
      'project_submitted_datetime', 'project_grade_category', 'project_title',
      'project_essay_1', 'project_essay_2', 'project_essay_3',
      'project_essay_4', 'project_resource_summary',
      'teacher_number_of_previously_posted_projects', 'project_is_approved',
      'clean_categories', 'clean_subcategories', 'essay', 'clean_essay',
      'clean_title'],
      dtype='object')
```

we are going to consider

- school_state : categorical data
- clean_categories : categorical data
- clean_subcategories : categorical data
- project_grade_category : categorical data
- teacher_prefix : categorical data
- project_title : text data
- text : text data
- project_resource_summary: text data (optinal)
- quantity : numerical (optinal)
- teacher_number_of_previously_posted_projects : numerical
- price : numerical

1.5.1 Vectorizing Categorical data

- <https://www.appliedaicourse.com/course/applied-ai-course-online/lessons/handling-categorical-and-numerical-features/> (<https://www.appliedaicourse.com/course/applied-ai-course-online/lessons/handling-categorical-and-numerical-features/>)

In [30]:

```
# replace nan with no
project_data=project_data.fillna("no")
```

In [31]:

```
s=set(project_data['teacher_prefix'])
```

In [32]:

```
s
```

Out[32]:

```
{'Dr.', 'Mr.', 'Mrs.', 'Ms.', 'Teacher', 'no'}
```

In []:

In []:

In [29]:

```
# you can do the similar thing with state, teacher_prefix and project_grade_category also
# to handle nan values by replacing them with empty strings
```

```
from collections import Counter
my_counter = Counter()
for word in project_data['teacher_prefix'].values:
    my_counter.update(word.split())

prefix = dict(my_counter)
prefix = dict(sorted(prefix.items(), key=lambda kv: kv[1]))

vectorizer = CountVectorizer(vocabulary=list(prefix.keys()), lowercase=False, binary=True)
prefix_one_hot = vectorizer.fit_transform(project_data['teacher_prefix'].values)
print(vectorizer.get_feature_names())
print("Shape of matrix after one hot encoding ", prefix_one_hot.shape)
```

```
['Mrs.', 'Ms.', 'Dr.', 'Teacher', 'no', 'Mr.']
Shape of matrix after one hot encoding (109248, 6)
```

1.5.2 Vectorizing Text data

1.5.2.1 Bag of words

In [0]:

```
# We are considering only the words which appeared in at least 10 documents(rows or project
vectorizer = CountVectorizer(min_df=10)
text_bow = vectorizer.fit_transform(preprocessed_essays)
print("Shape of matrix after one hot encoding ", text_bow.shape)
```

```
Shape of matrix after one hot encoding (109248, 16623)
```

In [0]:

```
# you can vectorize the title also
# before you vectorize the title make sure you preprocess it
```

1.5.2.2 TFIDF vectorizer

In [0]:

```
from sklearn.feature_extraction.text import TfidfVectorizer
vectorizer = TfidfVectorizer(min_df=10)
text_tfidf = vectorizer.fit_transform(preprocessed_essays)
print("Shape of matrix after one hot encoding ", text_tfidf.shape)
```

```
Shape of matrix after one hot encoding (109248, 16623)
```

1.5.2.3 Using Pretrained Models: Avg W2V

In [0]:

```

...
# Reading glove vectors in python: https://stackoverflow.com/a/38230349/4084039
def loadGloveModel(gloveFile):
    print ("Loading Glove Model")
    f = open(gloveFile,'r', encoding="utf8")
    model = {}
    for line in tqdm(f):
        splitLine = line.split()
        word = splitLine[0]
        embedding = np.array([float(val) for val in splitLine[1:]])
        model[word] = embedding
    print ("Done.",len(model)," words loaded!")
    return model
model = loadGloveModel('glove.42B.300d.txt')

# =====
Output:

Loading Glove Model
1917495it [06:32, 4879.69it/s]
Done. 1917495 words loaded!

# =====

words = []
for i in preprocod_texts:
    words.extend(i.split(' '))

for i in preprocod_titles:
    words.extend(i.split(' '))
print("all the words in the coupus", len(words))
words = set(words)
print("the unique words in the coupus", len(words))

inter_words = set(model.keys()).intersection(words)
print("The number of words that are present in both glove vectors and our coupus", \
      len(inter_words), "(" ,np.round(len(inter_words)/len(words)*100,3), "%)")

words_courpus = {}
words_glove = set(model.keys())
for i in words:
    if i in words_glove:
        words_courpus[i] = model[i]
print("word 2 vec length", len(words_courpus))

# stronging variables into pickle files python: http://www.jessicayung.com/how-to-use-pickl

import pickle
with open('glove_vectors', 'wb') as f:
    pickle.dump(words_courpus, f)

...

```

Out[26]:

```

'\n# Reading glove vectors in python: https://stackoverflow.com/a/38230349/4

```

```
084039\ndef (https://stackoverflow.com/a/38230349/4084039\ndef) loadGloveModel(gloveFile):\n    print ("Loading Glove Model")\n    f = open(gloveFile,\n    e,\\'r\\', encoding="utf8")\n    model = {}\n    for line in tqdm(f):\n        splitLine = line.split()\n        word = splitLine[0]\n        embedding = np.array([float(val) for val in splitLine[1:]])\n        model[word] = embedding\n    print ("Done.",len(model)," words loaded!")\n    return model\nmodel = loadGloveModel(\\'glove.42B.300d.txt\\')\n\n# =====\n\nOutput:\n\nLoading Glove Model\n1917495it [06:32, 4879.69it/s]\nDone. 1917495 words loaded!\n\n# =====\n\nwords = []\nfor i in preproc_text:\n    words.extend(i.split(\\' \\'))\n\nfor i in preproc_titles:\n    words.extend(i.split(\\' \\'))\n\nprint("all the words in the corpus", len(words))\nwords = set(words)\nprint("the unique words in the corpus", len(words))\n\ninter_words = set(model.keys()).intersection(words)\nprint("The number of words that are present in both glove vectors and our corpus", len(inter_words), "(" ,np.round(len(inter_words)/len(words)*100, 3),"%")\n\nwords_courpus = {}\nwords_glove = set(model.keys())\nfor i in words:\n    if i in words_glove:\n        words_courpus[i] = model[i]\n\nprint("word 2 vec length", len(words_courpus))\n\n\n# stronging variables into pickle files python: http://www.jessicayung.com/how-to-use-pickle-to-save-and-load-variables-in-python/\n\nimport (http://www.jessicayung.com/how-to-use-pickle-to-save-and-load-variables-in-python/)\n\nimport pickle\nwith open(\\'glove_vectors\\', \\'wb\\') as f:\n    pickle.dump(words_courpus, f)\n\n\n'
```

In [33]:

```
# stronging variables into pickle files python: http://www.jessicayung.com/how-to-use-pickle-to-save-and-load-variables-in-python/
# make sure you have the glove_vectors file
with open('glove_vectors', 'rb') as f:
    model = pickle.load(f)
    glove_words = set(model.keys())
```

In [32]:

```
# average Word2Vec
# compute average word2vec for each review.
avg_w2v_vectors = []; # the avg-w2v for each sentence/review is stored in this list
for sentence in tqdm(preprocessed_essays): # for each review/sentence
    vector = np.zeros(300) # as word vectors are of zero length
    cnt_words = 0; # num of words with a valid vector in the sentence/review
    for word in sentence.split(): # for each word in a review/sentence
        if word in glove_words:
            vector += model[word]
            cnt_words += 1
    if cnt_words != 0:
        vector /= cnt_words
    avg_w2v_vectors.append(vector)

print(len(avg_w2v_vectors))
print(len(avg_w2v_vectors[0]))
```

100%|██████████| 109248/109248 [00:31<00:00, 3519.07it/s]

109248
300

1.5.2.3 Using Pretrained Models: TFIDF weighted W2V

- we need to merge all the numerical vectors i.e catogorical, text, numerical vectors

In []:

In [0]:

```
# merge two sparse matrices: https://stackoverflow.com/a/19710648/4084039
from scipy.sparse import hstack
# with the same hstack function we are concatenating a sparse matrix and a dense matrix :)
X = hstack((categories_one_hot, sub_categories_one_hot, text_bow, price_standardized))
X.shape
```

Out[36]:

(109248, 16663)

In [0]:

```
# please write all the code with proper documentation, and proper titles for each subsection
# when you plot any graph make sure you use
# a. Title, that describes your plot, this will be very helpful to the reader
# b. Legends if needed
# c. X-axis label
# d. Y-axis label
```

Computing Sentiment Scores

In [0]:

```
import nltk
from nltk.sentiment.vader import SentimentIntensityAnalyzer

# import nltk
# nltk.download('vader_lexicon')

sid = SentimentIntensityAnalyzer()

for_sentiment = 'a person is a person no matter how small dr seuss i teach the smallest stu
for learning my students learn in many different ways using all of our senses and multiple
of techniques to help all my students succeed students in my class come from a variety of d
for wonderful sharing of experiences and cultures including native americans our school is
learners which can be seen through collaborative student project based learning in and out
in my class love to work with hands on materials and have many different opportunities to p
mastered having the social skills to work cooperatively with friends is a crucial aspect of
montana is the perfect place to learn about agriculture and nutrition my students love to r
in the early childhood classroom i have had several kids ask me can we try cooking with rea
and create common core cooking lessons where we learn important math and writing concepts w
food for snack time my students will have a grounded appreciation for the work that went in
of where the ingredients came from as well as how it is healthy for their bodies this proje
nutrition and agricultural cooking recipes by having us peel our own apples to make homemad
and mix up healthy plants from our classroom garden in the spring we will also create our c
shared with families students will gain math and literature skills as well as a life long e
nannan'
ss = sid.polarity_scores(for_sentiment)

for k in ss:
    print('{0}: {1}'.format(k, ss[k]), end='')

# we can use these 4 things as features/attributes (neg, neu, pos, compound)
# neg: 0.0, neu: 0.753, pos: 0.247, compound: 0.93
```

D:\installed\Anaconda3\lib\site-packages\nltk\twitter__init__.py:20: UserWarning:

The twython library has not been installed. Some functionality from the twitter package will not be available.

neg: 0.01, neu: 0.745, pos: 0.245, compound: 0.9975,

Assignment 9: RF and GBDT

Response Coding: Example



The response label is built only on train dataset. For a category which is not there in train data and present in test data, we will encode them with default values Ex: in our test data if have State: D then we encode it as [0.5, 0.05]


1. Apply both Random Forrest and GBDT on these feature sets

- **Set 1:** categorical (instead of one hot encoding, try [response coding](https://www.appliedaicourse.com/course/applied-ai-course-online/lessons/handling-categorical-and-numerical-features/) (<https://www.appliedaicourse.com/course/applied-ai-course-online/lessons/handling-categorical-and-numerical-features/>): use probability values), numerical features + project_title(BOW) + preprocessed_eassay (BOW)
- **Set 2:** categorical (instead of one hot encoding, try [response coding](https://www.appliedaicourse.com/course/applied-ai-course-online/lessons/handling-categorical-and-numerical-features/) (<https://www.appliedaicourse.com/course/applied-ai-course-online/lessons/handling-categorical-and-numerical-features/>): use probability values), numerical features + project_title(TFIDF)+ preprocessed_eassay (TFIDF)
- **Set 3:** categorical (instead of one hot encoding, try [response coding](https://www.appliedaicourse.com/course/applied-ai-course-online/lessons/handling-categorical-and-numerical-features/) (<https://www.appliedaicourse.com/course/applied-ai-course-online/lessons/handling-categorical-and-numerical-features/>): use probability values), numerical features + project_title(AVG W2V)+ preprocessed_eassay (AVG W2V)
- **Set 4:** categorical (instead of one hot encoding, try [response coding](https://www.appliedaicourse.com/course/applied-ai-course-online/lessons/handling-categorical-and-numerical-features/) (<https://www.appliedaicourse.com/course/applied-ai-course-online/lessons/handling-categorical-and-numerical-features/>): use probability values), numerical features + project_title(TFIDF W2V)+ preprocessed_eassay (TFIDF W2V)


2. The hyper parameter tuning (Consider any two hyper parameters preferably n_estimators, max_depth)

- Find the best hyper parameter which will give the maximum [AUC](https://www.appliedaicourse.com/course/applied-ai-course-online/lessons/receiver-operating-characteristic-curve-roc-curve-and-auc-1/) (<https://www.appliedaicourse.com/course/applied-ai-course-online/lessons/receiver-operating-characteristic-curve-roc-curve-and-auc-1/>) value
- find the best hyper parameter using k-fold cross validation/simple cross validation data
- use gridsearch cv or randomsearch cv or you can write your own for loops to do this task

3. Representation of results

- You need to plot the performance of model both on train data and cross validation data for each hyper parameter, like shown in the figure with X-axis  as **n_estimators**, Y-axis as **max_depth**, and Z-axis as **AUC Score**, we have given the notebook which explains how to plot this 3d plot, you can find it in the same drive [3d_scatter_plot.ipynb](#)

or

- You need to plot the performance of model both on train data and cross validation data for each hyper parameter, like shown in the figure [seaborn heat maps](https://seaborn.pydata.org/generated/seaborn.heatmap.html) (<https://seaborn.pydata.org/generated/seaborn.heatmap.html>) with rows as **n_estimators**, columns as **max_depth**, and values inside the cell representing **AUC Score**
- You can choose either of the plotting techniques: 3d plot or heat map
- Once after you found the best hyper parameter, you need to train your model with it, and find the AUC on test data and plot the ROC curve on both train and test.
 Along with plotting ROC curve, you need to print the [confusion matrix](https://www.appliedaicourse.com/course/applied-ai-course-online/lessons/confusion-matrix-tpr-fpr-fnr-tnr-1/) (<https://www.appliedaicourse.com/course/applied-ai-course-online/lessons/confusion-matrix-tpr-fpr-fnr-tnr-1/>) with predicted and original labels of test data points



4. Conclusion

- You need to summarize the results at the end of the notebook, summarize it in the table format. To print out a table please refer to this prettytable library [link](http://zetcode.com/python/prettytable/) (<http://zetcode.com/python/prettytable/>)



Note: Data Leakage

1. There will be an issue of data-leakage if you vectorize the entire data and then split it into train/cv/test.
2. To avoid the issue of data-leakage, make sure to split your data first and then vectorize it.
3. While vectorizing your data, apply the method `fit_transform()` on your train data, and apply the method `transform()` on cv/test data.
4. For more details please go through this [link. \(https://soundcloud.com/applied-ai-course/leakage-bow-and-tfidf\)](https://soundcloud.com/applied-ai-course/leakage-bow-and-tfidf)

2. Random Forest and GBDT

2.1 Splitting data into Train and cross validation(or test): Stratified Sampling

In [0]:

```
# please write all the code with proper documentation, and proper titles for each subsection
# go through documentations and blogs before you start coding
# first figure out what to do, and then think about how to do.
# reading and understanding error messages will be very much helpfull in debugging your code
# when you plot any graph make sure you use
# a. Title, that describes your plot, this will be very helpful to the reader
# b. Legends if needed
# c. X-axis Label
# d. Y-axis Label
```

2.2 Make Data Model Ready: encoding numerical, categorical features

In [35]:

```
# please write all the code with proper documentation, and proper titles for each subsection
# go through documentations and blogs before you start coding
# first figure out what to do, and then think about how to do.
# reading and understanding error messages will be very much helpfull in debugging your code
# make sure you featurize train and test data separatly

# when you plot any graph make sure you use
# a. Title, that describes your plot, this will be very helpful to the reader
# b. Legends if needed
# c. X-axis Label
# d. Y-axis Label
X=project_data
Y=X['project_is_approved']
```

In [36]:

```
from sklearn.model_selection import train_test_split
X_train, X_test, y_train, y_test = train_test_split(X, Y, test_size=0.33, stratify=Y)
```

In [37]:

```
print("="*100)

print("train=>",X_train.shape, y_train.shape)

print("test=>",X_test.shape, y_test.shape)

print("="*100)
```

```
=====
=====
train=> (73196, 22) (73196,)
test=> (36052, 22) (36052,)
=====
=====
```

numerical

In [38]:

```
from sklearn.preprocessing import Normalizer
normalizer = Normalizer()

'''encode numerical feature price'''
# normalizer.fit(X_train['price'].values)
# this will rise an error Expected 2D array, got 1D array instead:
# array=[105.22 215.96 96.01 ... 368.98 80.53 709.67].
# Reshape your data either using
# array.reshape(-1, 1) if your data has a single feature
# array.reshape(1, -1) if it contains a single sample.

normalizer.fit(X_train['price'].values.reshape(-1,1)) # use code from sample

X_train_price_norm = normalizer.transform(X_train['price'].values.reshape(-1,1))

X_test_price_norm = normalizer.transform(X_test['price'].values.reshape(-1,1))

print("After vectorizations")
print(X_train_price_norm.shape, y_train.shape)

print(X_test_price_norm.shape, y_test.shape)

print("="*100)
```

After vectorizations

```
(73196, 1) (73196,)
(36052, 1) (36052,)
```

```
=====
=====
```


In [39]:

```

'''encode numerical feature teacher_number_of_previously_posted_projects'''

normalizer = Normalizer()
# normalizer.fit(X_train['teacher_number_of_previously_posted_projects'].values)
# this will rise an error Expected 2D array, got 1D array instead:
# array=[105.22 215.96 96.01 ... 368.98 80.53 709.67].
# Reshape your data either using
# array.reshape(-1, 1) if your data has a single feature
# array.reshape(1, -1) if it contains a single sample.
normalizer.fit(X_train['teacher_number_of_previously_posted_projects'].values.reshape(-1,1))

X_train_posted_norm= normalizer.transform(X_train['teacher_number_of_previously_posted_projects'].values.reshape(-1,1))

X_test_posted_norm = normalizer.transform(X_test['teacher_number_of_previously_posted_projects'].values.reshape(-1,1))

print("After vectorizations")
print(X_train_posted_norm.shape, y_train.shape)

print(X_test_posted_norm.shape, y_test.shape)
print("=="*100)

```

After vectorizations

(73196, 1) (73196,)

(36052, 1) (36052,)

```

=====
=====

```

categorical_features

grade

In [40]:

```

'''project_grade_category'''
grade_list=set(X_train['project_grade_category'])
grade_list=list(grade_list)

```

In [41]:

grade_list

Out[41]:

['Grades 6-8', 'Grades 9-12', 'Grades 3-5', 'Grades PreK-2']

In [42]:

```

prob_neg=[]
prob_pos=[]
cate=[]
for i in grade_list:

    a=X_train[X_train['project_grade_category']==i]# storing the part of dataframe with this grade
    b=a.shape[0]# to find total
    c=a['project_is_approved'].value_counts()# to find no of positive and negative points
    p_pos=c[1]/(b)# prob of positive points
    p_neg=c[0]/b# prob of negative points
    prob_pos.append(p_pos)# list of prob=1
    prob_neg.append(p_neg)#list of prob =0
    cate.append(i)# list of features

```

In [43]:

```

grade=pd.DataFrame(columns=['project_grade_category','grade_pos=1','grade_neg=0'])

```

In [44]:

```

grade['project_grade_category']=cate
grade['grade_pos=1']=prob_pos
grade['grade_neg=0']=prob_neg

```

In [45]:

```

grade

```

Out[45]:

	project_grade_category	grade_pos=1	grade_neg=0
0	Grades 6-8	0.842492	0.157508
1	Grades 9-12	0.836985	0.163015
2	Grades 3-5	0.854554	0.145446
3	Grades PreK-2	0.848792	0.151208

teacher_prefix

In [46]:

```

'''encode teacher_prefix'''
# list of set of content of this columns

prefix_list=set(X_train['teacher_prefix'])
prefix_list=list(prefix_list)

```

In [47]:

```
prefix_list# nan is converted as no
```

Out[47]:

```
['Dr.', 'Mrs.', 'Ms.', 'no', 'Teacher', 'Mr.']
```

In [48]:

```
prefix_list.remove('no')
```

In [49]:

```
prob_neg=[]
prob_pos=[]
cate=[]
for i in prefix_list:

    a=X_train[X_train['teacher_prefix']==i]# part of dataframe satisfy the condition
    b=a.shape[0]# getting total
    neg=a[a['project_is_approved']==0]#getting total negative points
    s=neg.shape#to get no of rows and columns of negative points
    pos=a[a['project_is_approved']==1]#getting total positive points
    p=pos.shape#to get no of rows and columns of negative points
    p_pos=p[0]/(b)# prob =1

    p_neg=s[0]/b#prob=0
    prob_pos.append(p_pos)# List of prob=1
    prob_neg.append(p_neg)# List of prob=0
    cate.append(i)
```

In [50]:

```
prefix=pd.DataFrame(columns=['teacher_prefix','pre_pos=1','pre_neg=0'])
```

In [51]:

```
prefix['teacher_prefix']=cate
prefix['pre_pos=1']=prob_pos
prefix['pre_neg=0']=prob_neg
```

In [52]:

prefix

Out[52]:

	teacher_prefix	pre_pos=1	pre_neg=0
0	Dr.	0.500000	0.500000
1	Mrs.	0.856151	0.143849
2	Ms.	0.842591	0.157409
3	Teacher	0.797476	0.202524
4	Mr.	0.841265	0.158735

In [53]:

```
#https://stackoverflow.com/questions/24284342/insert-a-row-to-pandas-dataframe/46354147
prefix.loc[-1] = ['no', 1, 0]
```

In [54]:

prefix

Out[54]:

	teacher_prefix	pre_pos=1	pre_neg=0
0	Dr.	0.500000	0.500000
1	Mrs.	0.856151	0.143849
2	Ms.	0.842591	0.157409
3	Teacher	0.797476	0.202524
4	Mr.	0.841265	0.158735
-1	no	1.000000	0.000000

school_state

In [55]:

```
state_list=set(X_train['school_state'])
state_list=list(state_list)
```

In [56]:

```

'''encode 'school_state'''

prob_neg=[]
prob_pos=[]
cate=[]
for i in state_list:

    a=X_train[X_train['school_state']==i]# part of dataframe satisfy the condition
    b=a.shape[0]# getting total
    neg=a[a['project_is_approved']==0]#getting total negative points
    s=neg.shape#to get no of rows and columns of negative points
    pos=a[a['project_is_approved']==1]#getting total positive points
    p=pos.shape#to get no of rows and columns of negative points
    p_pos=p[0]/(b)# prob =1

    p_neg=s[0]/b#prob=0
    prob_pos.append(p_pos)# list of prob=1
    prob_neg.append(p_neg)# list of prob=0
    cate.append(i)

```

In [57]:

```

state=pd.DataFrame(columns=['school_state','state_pos=1','state_neg=0'])

```

In [58]:

```

state['school_state']=cate
state['state_pos=1']=prob_pos
state['state_neg=0']=prob_neg

```

In [59]:

```

state.head()

```

Out[59]:

	school_state	state_pos=1	state_neg=0
0	AK	0.852018	0.147982
1	ND	0.888889	0.111111
2	MT	0.786585	0.213415
3	WI	0.847222	0.152778
4	MS	0.846325	0.153675

clean_categories

In [60]:

```
'''clean categories'''
clean_cat_list=set(X_train['clean_categories'].values)
clean_cat_list=list(clean_cat_list)
```

In [61]:

```
'''encode 'school_state'''

prob_neg=[]
prob_pos=[]
cate=[]
for i in clean_cat_list:

    a=X_train[X_train['clean_categories']==i]# part of dataframe satisfy the condition
    b=a.shape[0]# getting total
    neg=a[a['project_is_approved']==0]#getting total negative points
    s=neg.shape#to get no of rows and columns of negative points
    pos=a[a['project_is_approved']==1]#getting total positive points
    p=pos.shape#to get no of rows and columns of negative points
    p_pos=p[0]/(b)# prob =1

    p_neg=s[0]/b#prob=0
    prob_pos.append(p_pos)# List of prob=1
    prob_neg.append(p_neg)# List of prob=0
    cate.append(i)
```

In [62]:

```
clean_cate=pd.DataFrame(columns=['clean_categories', 'clean_cat_pos=1', 'clean_cat_neg=0'])
```

In [63]:

```
clean_cate['clean_categories']=cate
clean_cate['clean_cat_pos=1']=prob_pos
clean_cate['clean_cat_neg=0']=prob_neg
```

In [64]:

```
clean_cate.head()
```

Out[64]:

	clean_categories	clean_cat_pos=1	clean_cat_neg=0
0	AppliedLearning	0.816628	0.183372
1	History_Civics Music_Arts	0.843318	0.156682
2	History_Civics SpecialNeeds	0.819277	0.180723
3	Math_Science Music_Arts	0.824742	0.175258
4	Math_Science	0.822193	0.177807

In [65]:

```
'''clean sub categories'''
clean_sub_cat_list=set(X_train['clean_subcategories'].values)
clean_sub_cat_list=list(clean_sub_cat_list)
```

In [66]:

```
prob_neg=[]
prob_pos=[]
cate=[]
for i in clean_sub_cat_list:

    a=X_train[X_train['clean_subcategories']==i]# part of dataframe satisfy the condition
    b=a.shape[0]# getting total
    neg=a[a['project_is_approved']==0]#getting total negative points
    s=neg.shape#to get no of rows and columns of negative points
    pos=a[a['project_is_approved']==1]#getting total positive points
    p=pos.shape#to get no of rows and columns of negative points
    p_pos=p[0]/(b)# prob =1

    p_neg=s[0]/b#prob=0
    prob_pos.append(p_pos)# List of prob=1
    prob_neg.append(p_neg)# List of prob=0
    cate.append(i)
```

In [67]:

```
clean_sub_cate=pd.DataFrame(columns=['clean_subcategories','clean_sub_cat_pos=1','clean_sub_cat_neg=0'])
```

In [68]:

```
clean_sub_cate['clean_subcategories']=cate
clean_sub_cate['clean_sub_cat_pos=1']=prob_pos
clean_sub_cate['clean_sub_cat_neg=0']=prob_neg
```

In [69]:

```
clean_sub_cate.head()
```

Out[69]:

	clean_subcategories	clean_sub_cat_pos=1	clean_sub_cat_neg=0
0	CharacterEducation VisualArts	0.760000	0.240000
1	Health_LifeScience NutritionEducation	0.642857	0.357143
2	AppliedSciences Literacy	0.831956	0.168044
3	Music TeamSports	0.750000	0.250000
4	ESL SocialSciences	0.846154	0.153846

merging all dataframe with test and train with left join

In [70]:

```
X_train = pd.merge(X_train,grade, on='project_grade_category', how='left')
```

In [71]:

```
X_train = pd.merge(X_train,state, on='school_state', how='left')
```

In [72]:

```
X_train = pd.merge(X_train,prefix, on='teacher_prefix', how='left')
```

In [73]:

```
X_train = pd.merge(X_train,clean_cate, on='clean_categories', how='left')
```

In [74]:

```
X_train = pd.merge(X_train,clean_sub_cate, on='clean_subcategories', how='left')
```

In [75]:

```
X_test = pd.merge(X_test,grade, on='project_grade_category', how='left')
```

In [76]:

```
X_test= pd.merge(X_test,state, on='school_state', how='left')
```

In [77]:

```
X_test = pd.merge(X_test,prefix, on='teacher_prefix', how='left')
```

In [78]:

```
X_test = pd.merge(X_test,clean_cate, on='clean_categories', how='left')
```

In [79]:

```
X_test = pd.merge(X_test,clean_sub_cate, on='clean_subcategories', how='left')
```

In [80]:

```
X_test.shape
```

Out[80]:

```
(36052, 32)
```


In [81]:

X_test.columns

Out[81]:

```
Index(['Unnamed: 0', 'id', 'teacher_id', 'teacher_prefix', 'school_state',
      'project_submitted_datetime', 'project_grade_category', 'project_title',
      'project_essay_1', 'project_essay_2', 'project_essay_3',
      'project_essay_4', 'project_resource_summary',
      'teacher_number_of_previously_posted_projects', 'project_is_approved',
      'clean_categories', 'clean_subcategories', 'essay', 'clean_essay',
      'clean_title', 'quantity', 'price', 'grade_pos=1', 'grade_neg=0',
      'state_pos=1', 'state_neg=0', 'pre_pos=1', 'pre_neg=0',
      'clean_cat_pos=1', 'clean_cat_neg=0', 'clean_sub_cat_pos=1',
      'clean_sub_cat_neg=0'],
      dtype='object')
```

In [82]:

```
'''null values'''
# filling them with column mean considering only prob=1
X_test['grade_pos=1']=X_test['grade_pos=1'].fillna(X_test['grade_pos=1'].mean())
X_test['state_pos=1']=X_test['state_pos=1'].fillna(X_test['state_pos=1'].mean())
X_test['pre_pos=1']=X_test['pre_pos=1'].fillna(X_test['pre_pos=1'].mean())
X_test['clean_cat_pos=1']=X_test['clean_cat_pos=1'].fillna(X_test['clean_cat_pos=1'].mean())
X_test['clean_sub_cat_pos=1']=X_test['clean_sub_cat_pos=1'].fillna(X_test['clean_sub_cat_pos=1'].mean())
```

In []:

In []:

In [83]:

```
# taking all probability value=1 of all categorical feature and standardised them
'''normalize the feature grade_prob==1'''
normalizer = Normalizer()
# normalizer.fit(X_train['teacher_number_of_previously_posted_projects'].values)
# this will rise an error Expected 2D array, got 1D array instead:
# array=[105.22 215.96 96.01 ... 368.98 80.53 709.67].
# Reshape your data either using
# array.reshape(-1, 1) if your data has a single feature
# array.reshape(1, -1) if it contains a single sample.
normalizer.fit(X_train['grade_pos=1'].values.reshape(-1,1))

X_train_grade_ohe= normalizer.transform(X_train['grade_pos=1'].values.reshape(-1,1))

X_test_grade_ohe = normalizer.transform(X_test['grade_pos=1'].values.reshape(-1,1))

print("After vectorizations")
print(X_train_grade_ohe.shape, y_train.shape)

print(X_test_grade_ohe.shape, y_test.shape)
print("=="*100)
```

After vectorizations

(73196, 1) (73196,)

(36052, 1) (36052,)

```
=====
=====
```

In [84]:

```
# taking all probability value=1 of all categorical feature and standardised them
'''normalize the feature prefix_prob==1'''
normalizer = Normalizer()
# normalizer.fit(X_train['teacher_number_of_previously_posted_projects'].values)
# this will rise an error Expected 2D array, got 1D array instead:
# array=[105.22 215.96 96.01 ... 368.98 80.53 709.67].
# Reshape your data either using
# array.reshape(-1, 1) if your data has a single feature
# array.reshape(1, -1) if it contains a single sample.
normalizer.fit(X_train['pre_pos=1'].values.reshape(-1,1))

X_train_teacher_ohe= normalizer.transform(X_train['pre_pos=1'].values.reshape(-1,1))

X_test_teacher_ohe = normalizer.transform(X_test['pre_pos=1'].values.reshape(-1,1))

print("After vectorizations")
print(X_train_teacher_ohe.shape, y_train.shape)

print(X_test_teacher_ohe.shape, y_test.shape)
print("=="*100)
```

After vectorizations

(73196, 1) (73196,)

(36052, 1) (36052,)

```
=====
=====
```

In [85]:

```
# taking all probablity value=1 of all categorical feature and standardised them
'''normalize the feature state_pos=1'''
normalizer = Normalizer()
# normalizer.fit(X_train['teacher_number_of_previously_posted_projects'].values)
# this will rise an error Expected 2D array, got 1D array instead:
# array=[105.22 215.96 96.01 ... 368.98 80.53 709.67].
# Reshape your data either using
# array.reshape(-1, 1) if your data has a single feature
# array.reshape(1, -1) if it contains a single sample.
normalizer.fit(X_train['state_pos=1'].values.reshape(-1,1))

X_train_state_ohc= normalizer.transform(X_train['state_pos=1'].values.reshape(-1,1))

X_test_state_ohc = normalizer.transform(X_test['state_pos=1'].values.reshape(-1,1))

print("After vectorizations")
print(X_train_state_ohc.shape, y_train.shape)

print(X_test_state_ohc.shape, y_test.shape)
print("=*100)
```

After vectorizations

(73196, 1) (73196,)

(36052, 1) (36052,)

```
=====
=====
```

In [86]:

```
# taking all probablity value=1 of all categorical feature and standardised them
# taking all probablity value=1 of all categorical feature and standardised them
'''normalize the feature clean_cat_pos=1'''
normalizer = Normalizer()
# normalizer.fit(X_train['teacher_number_of_previously_posted_projects'].values)
# this will rise an error Expected 2D array, got 1D array instead:
# array=[105.22 215.96 96.01 ... 368.98 80.53 709.67].
# Reshape your data either using
# array.reshape(-1, 1) if your data has a single feature
# array.reshape(1, -1) if it contains a single sample.
normalizer.fit(X_train['clean_cat_pos=1'].values.reshape(-1,1))

X_train_clean_cate_ohc= normalizer.transform(X_train['clean_cat_pos=1'].values.reshape(-1,1))

X_test_clean_cate_ohc = normalizer.transform(X_test['clean_cat_pos=1'].values.reshape(-1,1))

print("After vectorizations")
print(X_train_clean_cate_ohc.shape, y_train.shape)

print(X_test_clean_cate_ohc.shape, y_test.shape)
print("=*100)
```

After vectorizations

(73196, 1) (73196,)

(36052, 1) (36052,)

```
=====
=====
```

In [87]:

```
# taking all probablity value=1 of all categorical feature and standardised them
'''normalize the feature clean_sub_cat_pos=1'''
normalizer = Normalizer()
# normalizer.fit(X_train['teacher_number_of_previously_posted_projects'].values)
# this will rise an error Expected 2D array, got 1D array instead:
# array=[105.22 215.96 96.01 ... 368.98 80.53 709.67].
# Reshape your data either using
# array.reshape(-1, 1) if your data has a single feature
# array.reshape(1, -1) if it contains a single sample.
normalizer.fit(X_train['clean_sub_cat_pos=1'].values.reshape(-1,1))

X_train_subclean_cate_ohe= normalizer.transform(X_train['clean_sub_cat_pos=1'].values.reshape(-1,1))

X_test_subclean_cate_ohe = normalizer.transform(X_test['clean_sub_cat_pos=1'].values.reshape(-1,1))

print("After vectorizations")
print(X_train_subclean_cate_ohe.shape, y_train.shape)

print(X_test_subclean_cate_ohe.shape, y_test.shape)
print("=*100)
```

After vectorizations

(73196, 1) (73196,)

(36052, 1) (36052,)

```
=====
=====
```

In []:

2.3 Make Data Model Ready: encoding eassay, and project_title

In [88]:

```
# please write all the code with proper documentation, and proper titles for each subsection
# go through documentations and blogs before you start coding
# first figure out what to do, and then think about how to do.
# reading and understanding error messages will be very much helpfull in debugging your code
# make sure you featurize train and test data separatly

# when you plot any graph make sure you use
# a. Title, that describes your plot, this will be very helpful to the reader
# b. Legends if needed
# c. X-axis label
# d. Y-axis label
'''encoding essays in bow'''
#code is taken from this notebook

vectorizer_6 = CountVectorizer(min_df=10)
vectorizer_6.fit(X_train['clean_essay'].values)# fit is for train

X_train_essay_bow = vectorizer_6.transform(X_train['clean_essay'].values)# for train

X_test_essay_bow = vectorizer_6.transform(X_test['clean_essay'].values)#for test

print("After vectorizations")
print(X_train_essay_bow.shape, y_train.shape)

print(X_test_essay_bow.shape, y_test.shape)
print("="*100)
```

After vectorizations

```
(73196, 14235) (73196,)
(36052, 14235) (36052,)
```

```
=====
=====
```

In [89]:

```
'''enode titles bow'''
vectorizer_7 = CountVectorizer(min_df=10)
vectorizer_7.fit(X_train['clean_title'].values)# fit for train

# transform for all
X_train_titles_bow = vectorizer_7.transform(X_train['clean_title'].values)
#X_cv_titles_bow = vectorizer_7.transform(X_cv['clean_title'].values)
X_test_titles_bow = vectorizer_7.transform(X_test['clean_title'].values)

print("After vectorizations")
print(X_train_titles_bow.shape, y_train.shape)

print(X_test_titles_bow.shape, y_test.shape)
print("="*100)
```

After vectorizations

```
(73196, 2614) (73196,)
(36052, 2614) (36052,)
```

```
=====
=====
```

tfidf

In [117]:

```
# Please write all the code with proper documentation
'''tfidf_titles'''
vectorizer_8 = TfidfVectorizer(min_df=10)
vectorizer_8.fit(X_train['clean_title'].values)# fit for train

# transform for all
X_train_titles_tfidf= vectorizer_8.transform(X_train['clean_title'].values)

X_test_titles_tfidf = vectorizer_8.transform(X_test['clean_title'].values)

print("After vectorizations")
print(X_train_titles_tfidf.shape, y_train.shape)

print(X_test_titles_tfidf.shape, y_test.shape)
print("=*100)
```

After vectorizations

(73196, 2614) (73196,)

(36052, 2614) (36052,)

=====

In [118]:

```
'''tfidf_essay'''
vectorizer_9 = TfidfVectorizer(min_df=10)
vectorizer_9.fit(X_train['clean_essay'].values)# fit for train

# transform for all
X_train_essay_tfidf= vectorizer_9.transform(X_train['clean_essay'].values)

X_test_essay_tfidf = vectorizer_9.transform(X_test['clean_essay'].values)

print("After vectorizations")
print(X_train_essay_tfidf.shape, y_train.shape)

print(X_test_essay_tfidf.shape, y_test.shape)
print("=*100)
```

After vectorizations

(73196, 14235) (73196,)

(36052, 14235) (36052,)

=====

average word to vector

In [119]:

```

'''average word to vector train essay '''
avg_w2v_vectors_trainessay = []; # the avg-w2v for each sentence/review is stored in this list
for sentence in tqdm(X_train['clean_essay']): # for each review/sentence
    vector = np.zeros(300) # as word vectors are of zero length
    cnt_words = 0; # num of words with a valid vector in the sentence/review
    for word in sentence.split(): # for each word in a review/sentence
        if word in glove_words:
            vector += model[word]
            cnt_words += 1
    if cnt_words != 0:
        vector /= cnt_words
    avg_w2v_vectors_trainessay.append(vector)

print(len(avg_w2v_vectors_trainessay))
print(len(avg_w2v_vectors_trainessay[0]))

```

100%|██████████| 73196/73196 [00:24<00:00, 2941.31it/s]

73196
300

In [120]:

```

'''average word to vector train title'''
avg_w2v_vectors_traintitle = []; # the avg-w2v for each sentence/review is stored in this list
for sentence in tqdm(X_train['clean_title']): # for each review/sentence
    vector = np.zeros(300) # as word vectors are of zero length
    cnt_words = 0; # num of words with a valid vector in the sentence/review
    for word in sentence.split(): # for each word in a review/sentence
        if word in glove_words:
            vector += model[word]
            cnt_words += 1
    if cnt_words != 0:
        vector /= cnt_words
    avg_w2v_vectors_traintitle.append(vector)

print(len(avg_w2v_vectors_traintitle))
print(len(avg_w2v_vectors_traintitle[0]))

```

100%|██████████| 73196/73196 [00:01<00:00, 57852.63it/s]

73196
300

In [121]:

```

'''average word to vector test essay'''
avg_w2v_vectors_testessay = []; # the avg-w2v for each sentence/review is stored in this list
for sentence in tqdm(X_test['clean_essay']): # for each review/sentence
    vector = np.zeros(300) # as word vectors are of zero length
    cnt_words = 0; # num of words with a valid vector in the sentence/review
    for word in sentence.split(): # for each word in a review/sentence
        if word in glove_words:
            vector += model[word]
            cnt_words += 1
    if cnt_words != 0:
        vector /= cnt_words
    avg_w2v_vectors_testessay.append(vector)

print(len(avg_w2v_vectors_testessay))
print(len(avg_w2v_vectors_testessay[0]))

```

100%|██████████| 36052/36052 [00:11<00:00, 3009.34it/s]

36052

300

In [122]:

```

'''average word to vector test titles'''
avg_w2v_vectors_testtitle = []; # the avg-w2v for each sentence/review is stored in this list
for sentence in tqdm(X_test['clean_title']): # for each review/sentence
    vector = np.zeros(300) # as word vectors are of zero length
    cnt_words = 0; # num of words with a valid vector in the sentence/review
    for word in sentence.split(): # for each word in a review/sentence
        if word in glove_words:
            vector += model[word]
            cnt_words += 1
    if cnt_words != 0:
        vector /= cnt_words
    avg_w2v_vectors_testtitle.append(vector)

print(len(avg_w2v_vectors_testtitle))
print(len(avg_w2v_vectors_testtitle[0]))

```

100%|██████████| 36052/36052 [00:00<00:00, 60354.25it/s]

36052

300

tfidf word to vector

In [123]:

```
# S = ["abc def pqr", "def def def abc", "pqr pqr def"]
'''titles'''
tfidf_model = TfidfVectorizer()
tfidf_model.fit(X_train['clean_title'])
# we are converting a dictionary with word as a key, and the idf as a value
dictionary = dict(zip(tfidf_model.get_feature_names(), list(tfidf_model.idf_)))
tfidf_words = set(tfidf_model.get_feature_names())
```

In [124]:

```
# compute average word2vec for each review.
'''train titles'''
tfidf_w2v_vectors_title_tr = []; # the avg-w2v for each sentence/review is stored in this list
for sentence in tqdm(X_train['clean_title']): # for each review/sentence
    vector = np.zeros(300) # as word vectors are of zero length
    tf_idf_weight = 0; # num of words with a valid vector in the sentence/review
    for word in sentence.split(): # for each word in a review/sentence
        if (word in glove_words) and (word in tfidf_words):
            vec = model[word] # getting the vector for each word
            # here we are multiplying idf value(dictionary[word]) and the tf value((sentence.count(word)/len(sentence.split()))) # getting
            tf_idf = dictionary[word]*(sentence.count(word)/len(sentence.split())) # getting
            vector += (vec * tf_idf) # calculating tfidf weighted w2v
            tf_idf_weight += tf_idf
    if tf_idf_weight != 0:
        vector /= tf_idf_weight
    tfidf_w2v_vectors_title_tr.append(vector)

print(len(tfidf_w2v_vectors_title_tr))
print(len(tfidf_w2v_vectors_title_tr[0]))
```

100%|██████████| 73196/73196 [00:02<00:00, 26193.23it/s]

73196
300

In [125]:

```
'''test titles'''
tfidf_w2v_vectors_title_te = []; # the avg-w2v for each sentence/review is stored in this list
for sentence in tqdm(X_test['clean_title']): # for each review/sentence
    vector = np.zeros(300) # as word vectors are of zero length
    tf_idf_weight = 0; # num of words with a valid vector in the sentence/review
    for word in sentence.split(): # for each word in a review/sentence
        if (word in glove_words) and (word in tfidf_words):
            vec = model[word] # getting the vector for each word
            # here we are multiplying idf value(dictionary[word]) and the tf value((sentence.count(word)/len(sentence.split()))) # getting
            tf_idf = dictionary[word]*(sentence.count(word)/len(sentence.split())) # getting
            vector += (vec * tf_idf) # calculating tfidf weighted w2v
            tf_idf_weight += tf_idf
    if tf_idf_weight != 0:
        vector /= tf_idf_weight
    tfidf_w2v_vectors_title_te.append(vector)
```

100%|██████████| 36052/36052 [00:01<00:00, 24398.45it/s]

In [126]:

```
'''essay'''
# S = ["abc def pqr", "def def def abc", "pqr pqr def"]
tfidf_model = TfidfVectorizer()
tfidf_model.fit(X_train['clean_essay'])
# we are converting a dictionary with word as a key, and the idf as a value
dictionary = dict(zip(tfidf_model.get_feature_names(), list(tfidf_model.idf_)))
tfidf_words = set(tfidf_model.get_feature_names())
```

In [127]:

```
# average Word2Vec
'''train essay'''
# compute average word2vec for each review.
tfidf_w2v_vectors_essay_tr = []; # the avg-w2v for each sentence/review is stored in this l
for sentence in tqdm(X_train['clean_essay']): # for each review/sentence
    vector = np.zeros(300) # as word vectors are of zero length
    tf_idf_weight = 0; # num of words with a valid vector in the sentence/review
    for word in sentence.split(): # for each word in a review/sentence
        if (word in glove_words) and (word in tfidf_words):
            vec = model[word] # getting the vector for each word
            # here we are multiplying idf value(dictionary[word]) and the tf value((sentence.count(word)/len(sentence.split()))) # getting
            tf_idf = dictionary[word]*(sentence.count(word)/len(sentence.split())) # getting
            vector += (vec * tf_idf) # calculating tfidf weighted w2v
            tf_idf_weight += tf_idf
    if tf_idf_weight != 0:
        vector /= tf_idf_weight
    tfidf_w2v_vectors_essay_tr.append(vector)

print(len(tfidf_w2v_vectors_essay_tr))
print(len(tfidf_w2v_vectors_essay_tr[0]))
```

100%|██████████| 73196/73196 [02:23<00:00, 509.03it/s]

73196

300

In [128]:

```

# average Word2Vec
'''test essay'''
# compute average word2vec for each review.
tfidf_w2v_vectors_essay_te = []; # the avg-w2v for each sentence/review is stored in this list
for sentence in tqdm(X_test['clean_essay']): # for each review/sentence
    vector = np.zeros(300) # as word vectors are of zero length
    tf_idf_weight = 0; # num of words with a valid vector in the sentence/review
    for word in sentence.split(): # for each word in a review/sentence
        if (word in glove_words) and (word in tfidf_words):
            vec = model[word] # getting the vector for each word
            # here we are multiplying idf value(dictionary[word]) and the tf value((sentence.count(word)/len(sentence.split()))) # getting the tf value
            tf_idf = dictionary[word]*(sentence.count(word)/len(sentence.split())) # getting the tf value
            vector += (vec * tf_idf) # calculating tfidf weighted w2v
            tf_idf_weight += tf_idf
    if tf_idf_weight != 0:
        vector /= tf_idf_weight
    tfidf_w2v_vectors_essay_te.append(vector)

print(len(tfidf_w2v_vectors_essay_te))
print(len(tfidf_w2v_vectors_essay_te[0]))

```

100%|██████████| 36052/36052 [01:10<00:00, 511.17it/s]

36052

300

2.4 Applying Random Forest

Apply Random Forest on different kind of featurization as mentioned in the instructions

For Every model that you work on make sure you do the step 2 and step 3 of instructions

2.4.1 Applying Random Forests on BOW, SET 1

In [164]:

```
# Please write all the code with proper documentation
from scipy.sparse import hstack
X_tr = hstack((X_train_essay_bow, X_train_state_ohe, X_train_teacher_ohe, X_train_grade_ohe)
X_te = hstack((X_test_essay_bow, X_test_state_ohe, X_test_teacher_ohe, X_test_grade_ohe, X_

print("Final Data matrix")
print("train matrix=>",X_tr.shape, y_train.shape)

print("test matrix=>",X_te.shape, y_test.shape)
print("="*100)
```

Final Data matrix

train matrix=> (73196, 16899) (73196,)

test matrix=> (36052, 16899) (36052,)

=====

In [97]:

```

from sklearn.metrics import roc_auc_score
from sklearn.metrics import accuracy_score
from sklearn.ensemble import RandomForestClassifier
from sklearn.model_selection import GridSearchCV
def gd(X_tr,X_te):

    depth = [1,5,10,13,15,17,20]
    estimator = [2,4,6,8,10,12,14,16]

    tuned_parameters = {'max_depth': depth, 'n_estimators': estimator}

    rf= RandomForestClassifier(class_weight='balanced')

    clf_1 = GridSearchCV(rf, tuned_parameters, cv=3, scoring='roc_auc', verbose=1, n_jobs = -1)
    clf_1.fit(X_tr, y_train)

    train_auc= clf_1.cv_results_['mean_train_score']

    cv_auc = clf_1.cv_results_['mean_test_score']


    # test AUC
    #print("L1+++++")
    print(clf_1.score(X_te, y_test))
    print(clf_1.best_estimator_)# to know best parameters
    depth_opt, split_opt = clf_1.best_params_.get('max_depth'), clf_1.best_params_.get('n_estimators')
    print(depth_opt)
    print(split_opt)
    #how to draw heatmap
    #https://seaborn.pydata.org/generated/seaborn.heatmap.html
    #https://github.com/omkar1610/Amazon-Fine-Food-Reviews/blob/master/08%20Amazon%20Fine%20Food%20Reviews.ipynb

    df_heatmap = pd.DataFrame(train_auc.reshape(7, 8), index=depth, columns=estimator )
    fig = plt.figure(figsize=(5, 3))
    heatmap = sns.heatmap(df_heatmap, annot=True)
    plt.ylabel('Depth' , size=18)
    plt.xlabel('n_estimator' , size=18)
    plt.title("Train Data", size=24)
    plt.show()

    df_heatmap = pd.DataFrame(cv_auc.reshape(7, 8), index=depth, columns=estimator )
    fig = plt.figure(figsize=(5, 3))
    heatmap = sns.heatmap(df_heatmap, annot=True)
    plt.ylabel('Depth' , size=18)
    plt.xlabel('n_estimator' , size=18)
    plt.title("CV Data", size=24)
    plt.show()
    print("best depth = ", clf_1.best_params_)

```

In [166]:

```
gd(X_tr,X_te)
```

Fitting 3 folds for each of 56 candidates, totalling 168 fits

[Parallel(n_jobs=-1)]: Using backend LokyBackend with 4 concurrent workers.

[Parallel(n_jobs=-1)]: Done 42 tasks | elapsed: 13.4s



[Parallel(n_jobs=-1)]: Done 168 out of 168 | elapsed: 1.4min finished

0.6686117705820649

```
RandomForestClassifier(bootstrap=True, class_weight='balanced',
                        criterion='gini', max_depth=20, max_features='auto',
                        max_leaf_nodes=None, min_impurity_decrease=0.0,
                        min_impurity_split=None, min_samples_leaf=1,
                        min_samples_split=2, min_weight_fraction_leaf=0.0,
                        n_estimators=16, n_jobs=None, oob_score=False,
                        random_state=None, verbose=0, warm_start=False)
```

20

16



best depth = {'n_estimators': 16, 'max_depth': 20}

In [167]:

```

rf=RandomForestClassifier(bootstrap=True, class_weight='balanced',
                           criterion='gini', max_depth=20, max_features='auto',
                           max_leaf_nodes=None, min_impurity_decrease=0.0,
                           min_impurity_split=None, min_samples_leaf=1,
                           min_samples_split=2, min_weight_fraction_leaf=0.0,
                           n_estimators=16, n_jobs=None, oob_score=False,
                           random_state=None, verbose=0, warm_start=False)
rf.fit(X_tr,y_train)
pred = rf.predict(X_te)
acc = accuracy_score(y_test, pred, normalize=True)*float(100)

print('\n****Test accuracy is %f%%' % (acc))

```

****Test accuracy is 69.993343%

In [168]:

```

#other measuring parameters
from sklearn.metrics import classification_report
print("classification_report")
print(classification_report(y_test, pred))

```

	precision	recall	f1-score	support
0	0.25	0.49	0.33	5459
1	0.89	0.74	0.81	30593
micro avg	0.70	0.70	0.70	36052
macro avg	0.57	0.62	0.57	36052
weighted avg	0.79	0.70	0.73	36052

In [169]:

```

pred_proba_te=rf.predict_proba(X_te)
pred_proba_te = pred_proba_te[:, 1]

pred_proba_tr=rf.predict_proba(X_tr)
pred_proba_tr = pred_proba_tr[:, 1]

```

In [170]:

```

fpr, tpr, thresholds = roc_curve(y_test,pred_proba_te )
a=fpr
b=tpr
c=thresholds

```

In [171]:


```

fpr, tpr, thresholds = roc_curve(y_train,pred_proba_tr )

```

In [172]:

```
#PLOT OF ROC
# plot no skill
plt.plot([0, 1], [0, 1])
# plot the roc curve for the model
plt.plot(fpr, tpr, marker='.',label="train")
plt.plot(a,b, marker='.',label='test')
#plt.plot(k,pred_cv)
plt.title("Line Plot of ROC Curve")
plt.ylabel('True Positive Rate')
plt.xlabel('False Positive Rate')
plt.legend()
plt.show()
```



In [173]:


```
#confusion matrices
#https://pandas-ml.readthedocs.io/en/latest/conf_mat.html
con_matrix=confusion_matrix(y_test, pred)
class_label=['negative','positive']
df=pd.DataFrame(con_matrix,index=class_label,columns=class_label)
df
```

Out[173]:

	negative	positive
negative	2700	2759
positive	8059	22534

In [174]:

```
# how can i plot confusion matrix //https://stackoverflow.com/questions/35572000/how-can-i-  
sns.heatmap(df,annot=True,fmt='d')  
plt.title('Confusion_matrix')  
plt.xlabel("prediction")  
plt.ylabel("actual")  
plt.show()
```



- TN=2700
- FP=2759
- FN=8059
- TP=22534

In []:

2.4.2 Applying Random Forests on TFIDF, SET 2

In [124]:

```
# Please write all the code with proper documentation
# Please write all the code with proper documentation
#merging
from scipy.sparse import hstack
X_tr = hstack((X_train_essay_tfidf, X_train_state_oh, X_train_teacher_oh, X_train_grade_c
#X_cr = hstack((X_cv_essay_tfidf, X_cv_state_oh, X_cv_teacher_oh, X_cv_grade_oh, X_cv_pr
X_te = hstack((X_test_essay_tfidf, X_test_state_oh, X_test_teacher_oh, X_test_grade_oh,

print("Final Data matrix")
print("train matrix=>",X_tr.shape, y_train.shape)

print("test matrix=>",X_te.shape, y_test.shape)
print("="*100)
```

Final Data matrix

train matrix=> (73196, 16899) (73196,)

test matrix=> (36052, 16899) (36052,)

=====

=====

In [125]:

```
gd(X_tr,X_te)
```

Fitting 3 folds for each of 56 candidates, totalling 168 fits

[Parallel(n_jobs=-1)]: Using backend LokyBackend with 4 concurrent workers.

[Parallel(n_jobs=-1)]: Done 42 tasks | elapsed: 13.2s



[Parallel(n_jobs=-1)]: Done 168 out of 168 | elapsed: 1.6min finished

0.6485150845633967

```
RandomForestClassifier(bootstrap=True, class_weight='balanced',
                        criterion='gini', max_depth=15, max_features='auto',
                        max_leaf_nodes=None, min_impurity_decrease=0.0,
                        min_impurity_split=None, min_samples_leaf=1,
                        min_samples_split=2, min_weight_fraction_leaf=0.0,
                        n_estimators=16, n_jobs=None, oob_score=False,
                        random_state=None, verbose=0, warm_start=False)
```

15

16



best depth = {'n_estimators': 16, 'max_depth': 15}

In [126]:

```

#test phase
# TEST PHASE FOR L1
rf=RandomForestClassifier(bootstrap=True, class_weight='balanced',
                           criterion='gini', max_depth=15, max_features='auto',
                           max_leaf_nodes=None, min_impurity_decrease=0.0,
                           min_impurity_split=None, min_samples_leaf=1,
                           min_samples_split=2, min_weight_fraction_leaf=0.0,
                           n_estimators=16, n_jobs=None, oob_score=False,
                           random_state=None, verbose=0, warm_start=False)
rf.fit(X_tr,y_train)
pred = rf.predict(X_te)
acc = accuracy_score(y_test, pred, normalize=True)*float(100)

```

In [127]:

```

#other measuring parameters
from sklearn.metrics import classification_report
print("classification_report")
print(classification_report(y_test, pred))

```

	precision	recall	f1-score	support
0	0.24	0.41	0.31	5459
1	0.88	0.77	0.82	30593
micro avg	0.71	0.71	0.71	36052
macro avg	0.56	0.59	0.56	36052
weighted avg	0.78	0.71	0.74	36052

In [129]:

```

pred_proba_te=rf.predict_proba(X_te)
pred_proba_te = pred_proba_te[:, 1]

pred_proba_tr=rf.predict_proba(X_tr)
pred_proba_tr = pred_proba_tr[:, 1]

```

In [130]:

```

fpr, tpr, thresholds = roc_curve(y_test,pred_proba_te )
a=fpr
b=tpr
c=thresholds

```

In [131]:


```

fpr, tpr, thresholds = roc_curve(y_train,pred_proba_tr )

```

In [132]:

```
#PLOT OF ROC
# plot no skill
plt.plot([0, 1], [0, 1])
# plot the roc curve for the model
plt.plot(fpr, tpr, marker='.',label="train")
plt.plot(a,b, marker='.',label='test')
#plt.plot(k,pred_cv)
plt.title("Line Plot of ROC Curve")
plt.ylabel('True Positive Rate')
plt.xlabel('False Positive Rate')
plt.legend()
plt.show()
```



In [133]:


```
#confusion matrices
#https://pandas-ml.readthedocs.io/en/latest/conf_mat.html
con_matrix=confusion_matrix(y_test, pred)
class_label=['negative','positive']
df=pd.DataFrame(con_matrix,index=class_label,columns=class_label)
df
```

Out[133]:

	negative	positive
negative	2260	3199
positive	7084	23509

In [134]:

```
# how can i plot confusion matrix //https://stackoverflow.com/questions/35572000/how-can-i-
sns.heatmap(df,annot=True,fmt='d')
plt.title('Confusion_matrix')
plt.xlabel("prediction")
plt.ylabel("actual")
plt.show()
```



- TN=2260
- FP=3199
- FN=7084
- TP=23509

2.4.3 Applying Random Forests on AVG W2V, SET 3

In [142]:

```
# convert result of average word to vector into array
x=np.array(avg_w2v_vectors_trainessay)
```

In []:

In [143]:

```
x.shape
```

Out[143]:

(73196, 300)

In [144]:

```
y=np.array(avg_w2v_vectors_traintitle)
```

In [145]:

y.shape

Out[145]:

(73196, 300)

In [146]:

z=np.array(avg_w2v_vectors_testessay)

In [147]:

z.shape

Out[147]:

(36052, 300)

In [148]:

a=np.array(avg_w2v_vectors_testtitle)

In [149]:

a.shape

Out[149]:

(36052, 300)

In [144]:

*# Please write all the code with proper documentation**#merging*

from scipy.sparse import hstack

X_tr = np.hstack((y, X_train_state_ohe, X_train_teacher_ohe, X_train_grade_ohe, X_train_pri

#X_cr = hstack((avg_w2v_vectors_cvtitle, X_cv_state_ohe, X_cv_teacher_ohe, X_cv_grade_ohe,

X_te = np.hstack((a, X_test_state_ohe, X_test_teacher_ohe, X_test_grade_ohe, X_test_price_r

print("Final Data matrix")

print("train matrix=>",X_tr.shape, y_train.shape)

print("test matrix=>",X_te.shape, y_test.shape)

print("="*100)

Final Data matrix

train matrix=> (73196, 607) (73196,)

test matrix=> (36052, 607) (36052,)

=====

=====

In [145]:

gd(X_tr,X_te)

Fitting 3 folds for each of 56 candidates, totalling 168 fits

[Parallel(n_jobs=-1)]: Using backend LokyBackend with 4 concurrent workers.

[Parallel(n_jobs=-1)]: Done 42 tasks | elapsed: 46.8s



[Parallel(n_jobs=-1)]: Done 168 out of 168 | elapsed: 9.4min finished

0.6571748256558564

```
RandomForestClassifier(bootstrap=True, class_weight='balanced',
                        criterion='gini', max_depth=5, max_features='auto',
                        max_leaf_nodes=None, min_impurity_decrease=0.0,
                        min_impurity_split=None, min_samples_leaf=1,
                        min_samples_split=2, min_weight_fraction_leaf=0.0,
                        n_estimators=16, n_jobs=None, oob_score=False,
                        random_state=None, verbose=0, warm_start=False)
```

5

16



best depth = {'n_estimators': 16, 'max_depth': 5}

In [146]:

```
rf=RandomForestClassifier(bootstrap=True, class_weight='balanced',
                           criterion='gini', max_depth=5, max_features='auto',
                           max_leaf_nodes=None, min_impurity_decrease=0.0,
                           min_impurity_split=None, min_samples_leaf=1,
                           min_samples_split=2, min_weight_fraction_leaf=0.0,
                           n_estimators=16, n_jobs=None, oob_score=False,
                           random_state=None, verbose=0, warm_start=False)
rf.fit(X_tr,y_train)
pred = rf.predict(X_te)
```

In [147]:

```
#other measuring parameters
from sklearn.metrics import classification_report
print("classification_report")
print(classification_report(y_test, pred))
```

	precision	recall	f1-score	support
0	0.23	0.57	0.32	5459
1	0.89	0.66	0.76	30593
micro avg	0.64	0.64	0.64	36052
macro avg	0.56	0.61	0.54	36052
weighted avg	0.79	0.64	0.69	36052

In [148]:

```
pred_proba_te=rf.predict_proba(X_te)
pred_proba_te = pred_proba_te[:, 1]

pred_proba_tr=rf.predict_proba(X_tr)
pred_proba_tr = pred_proba_tr[:, 1]
```

In [149]:

```
fpr, tpr, thresholds = roc_curve(y_test,pred_proba_te )
a=fpr
b=tpr
c=thresholds
```

In [150]:


```
fpr, tpr, thresholds = roc_curve(y_train,pred_proba_tr )
```

In [151]:

```

#PLOT OF ROC
# plot no skill
plt.plot([0, 1], [0, 1])
# plot the roc curve for the model
plt.plot(fpr, tpr, marker='.',label="train")
plt.plot(a,b, marker='.',label='test')
#plt.plot(k,pred_cv)
plt.title("Line Plot of ROC Curve")
plt.ylabel('True Positive Rate')
plt.xlabel('False Positive Rate')
plt.legend()
plt.show()

```



In [152]:

```

#confusion matrices
#https://pandas-ml.readthedocs.io/en/latest/conf_mat.html
con_matrix=confusion_matrix(y_test, pred)
class_label=['negative','positive']
df=pd.DataFrame(con_matrix,index=class_label,columns=class_label)
df


```

Out[152]:

	negative	positive
negative	3090	2369
positive	10552	20041

In [153]:

```
# how can i plot confusion matrix //https://stackoverflow.com/questions/35572000/how-can-i-
sns.heatmap(df,annot=True,fmt='d')
plt.title('Confusion_matrix')
plt.xlabel("prediction")
plt.ylabel("actual")
plt.show()
```



- TN=3090
- FP=2369
- FN=10522
- TP=20041

2.4.4 Applying Random Forests on TFIDF W2V, SET 4

In [154]:

```
# Please write all the code with proper documentation
# Please write all the code with proper documentation
#merging
from scipy.sparse import hstack
X_tr = np.hstack((tfidf_w2v_vectors_title_tr, X_train_state_ohe, X_train_teacher_ohe, X_train_grade_ohe))
#X_cr = hstack((tfidf_w2v_vectors_title_cv, X_cv_state_ohe, X_cv_teacher_ohe, X_cv_grade_ohe))
X_te = np.hstack((tfidf_w2v_vectors_title_te, X_test_state_ohe, X_test_teacher_ohe, X_test_grade_ohe))

print("Final Data matrix")
print("train matrix=>",X_tr.shape, y_train.shape)

print("test matrix=>",X_te.shape, y_test.shape)
print("="*100)
```

```
Final Data matrix
train matrix=> (73196, 607) (73196,)
test matrix=> (36052, 607) (36052,)
```

```
=====
=====
```

In [155]:

```
gd(X_tr,X_te)
```

Fitting 3 folds for each of 56 candidates, totalling 168 fits

[Parallel(n_jobs=-1)]: Using backend LokyBackend with 4 concurrent workers.



[Parallel(n_jobs=-1)]: Done 42 tasks | elapsed: 46.7s

[Parallel(n_jobs=-1)]: Done 168 out of 168 | elapsed: 9.4min finished

0.6599592776806665

```
RandomForestClassifier(bootstrap=True, class_weight='balanced',
                        criterion='gini', max_depth=5, max_features='auto',
                        max_leaf_nodes=None, min_impurity_decrease=0.0,
                        min_impurity_split=None, min_samples_leaf=1,
                        min_samples_split=2, min_weight_fraction_leaf=0.0,
                        n_estimators=14, n_jobs=None, oob_score=False,
                        random_state=None, verbose=0, warm_start=False)
```

5
14



best depth = {'n_estimators': 14, 'max_depth': 5}

In [156]:

```
# TEST PHASE FOR L1
rf=RandomForestClassifier(bootstrap=True, class_weight='balanced',
                           criterion='gini', max_depth=5, max_features='auto',
                           max_leaf_nodes=None, min_impurity_decrease=0.0,
                           min_impurity_split=None, min_samples_leaf=1,
                           min_samples_split=2, min_weight_fraction_leaf=0.0,
                           n_estimators=14, n_jobs=None, oob_score=False,
                           random_state=None, verbose=0, warm_start=False)
rf.fit(X_tr,y_train)
pred = rf.predict(X_te)
```

In [157]:

```
#other measuring parameters
from sklearn.metrics import classification_report
print("classification_report")
print(classification_report(y_test, pred))
```

```
classification_report
      precision    recall  f1-score   support

      0       0.22      0.62      0.33        5459
      1       0.90      0.61      0.73       30593

 micro avg       0.61      0.61      0.61       36052
 macro avg       0.56      0.61      0.53       36052
weighted avg       0.80      0.61      0.66       36052
```

In [158]:

```
pred_proba_te=rf.predict_proba(X_te)
pred_proba_te = pred_proba_te[:, 1]

pred_proba_tr=rf.predict_proba(X_tr)
pred_proba_tr = pred_proba_tr[:, 1]
```

In [159]:


```
fpr, tpr, thresholds = roc_curve(y_test,pred_proba_te )
a=fpr
b=tpr
c=thresholds
```

In [160]:

```
fpr, tpr, thresholds = roc_curve(y_train,pred_proba_tr )
```

In [161]:

```
#PLOT OF ROC
# plot no skill
plt.plot([0, 1], [0, 1])
# plot the roc curve for the model
plt.plot(fpr, tpr, marker='.',label="train")
plt.plot(a,b, marker='.',label='test')
#plt.plot(k,pred_cv)
plt.title("Line Plot of ROC Curve")
plt.ylabel('True Positive Rate')
plt.xlabel('False Positive Rate')
plt.legend()
plt.show()
```



In [162]:


```
#confusion matrices
#https://pandas-ml.readthedocs.io/en/latest/conf_mat.html
con_matrix=confusion_matrix(y_test, pred)
class_label=['negative','positive']
df=pd.DataFrame(con_matrix,index=class_label,columns=class_label)
df
```

Out[162]:

	negative	positive
negative	3388	2071
positive	11998	18595

In [163]:

```
# how can i plot confusion matrix //https://stackoverflow.com/questions/35572000/how-can-i-  
sns.heatmap(df,annot=True,fmt='d')  
plt.title('Confusion_matrix')  
plt.xlabel("prediction")  
plt.ylabel("actual")  
plt.show()
```



- TN=3388
- FP=2071
- FN=11998
- TP=18595

In []:

In []:

In []:

2.5 Applying GBDT

Apply GBDT on different kind of featurization as mentioned in the instructions

For Every model that you work on make sure you do the step 2 and step 3 of instructions

2.5.1 Applying XGBOOST on BOW, SET 1

In [103]:

```
# Please write all the code with proper documentation
# Please write all the code with proper documentation
from scipy.sparse import hstack
X_tr = hstack((X_train_essay_bow, X_train_state_ohe, X_train_teacher_ohe, X_train_grade_ohe)
X_te = hstack((X_test_essay_bow, X_test_state_ohe, X_test_teacher_ohe, X_test_grade_ohe, X_

print("Final Data matrix")
print("train matrix=>",X_tr.shape, y_train.shape)

print("test matrix=>",X_te.shape, y_test.shape)
print("="*100)
```

Final Data matrix

train matrix=> (73196, 16856) (73196,)

test matrix=> (36052, 16856) (36052,)

=====

In [104]:

```

from xgboost import XGBClassifier
from sklearn.metrics import roc_auc_score
from sklearn.metrics import accuracy_score
from sklearn.ensemble import RandomForestClassifier
from sklearn.model_selection import GridSearchCV
def xgd(X_tr,X_te):

    depth = [1,5,10,13,15,17,20]
    estimator = [2,4,6,8,10,12,14,16]

    tuned_parameters = {'max_depth': depth, 'n_estimators': estimator}

    rf= RandomForestClassifier(class_weight='balanced')

    clf_1 = GridSearchCV(rf, tuned_parameters, cv=3, scoring='roc_auc', verbose=1, n_jobs = -1)
    clf_1.fit(X_tr, y_train)

    train_auc= clf_1.cv_results_['mean_train_score']

    cv_auc = clf_1.cv_results_['mean_test_score']


    # test AUC
    #print("L1+++++")
    print(clf_1.score(X_te, y_test))
    print(clf_1.best_estimator_)# to know best parameters
    depth_opt, split_opt = clf_1.best_params_.get('max_depth'), clf_1.best_params_.get('n_estimators')
    print(depth_opt)
    print(split_opt)
    #how to draw heatmap
    #https://seaborn.pydata.org/generated/seaborn.heatmap.html
    #https://github.com/omkar1610/Amazon-Fine-Food-Reviews/blob/master/08%20Amazon%20Fine%20Food%20Reviews.ipynb

    df_heatmap = pd.DataFrame(train_auc.reshape(7, 8), index=depth, columns=estimator )
    fig = plt.figure(figsize=(5, 3))
    heatmap = sns.heatmap(df_heatmap, annot=True)
    plt.ylabel('Depth' , size=18)
    plt.xlabel('n_estimator' , size=18)
    plt.title("Train Data", size=24)
    plt.show()

    df_heatmap = pd.DataFrame(cv_auc.reshape(7, 8), index=depth, columns=estimator )
    fig = plt.figure(figsize=(5, 3))
    heatmap = sns.heatmap(df_heatmap, annot=True)
    plt.ylabel('Depth' , size=18)
    plt.xlabel('n_estimator' , size=18)
    plt.title("CV Data", size=24)
    plt.show()
    print("best depth = ", clf_1.best_params_['max_depth'])

```

In [105]:

```
xgd(X_tr,X_te)
```

Fitting 3 folds for each of 56 candidates, totalling 168 fits

[Parallel(n_jobs=-1)]: Using backend LokyBackend with 4 concurrent workers.

[Parallel(n_jobs=-1)]: Done 42 tasks | elapsed: 11.7s



[Parallel(n_jobs=-1)]: Done 168 out of 168 | elapsed: 1.2min finished

0.6600194936520907

```
RandomForestClassifier(bootstrap=True, class_weight='balanced',
                        criterion='gini', max_depth=20, max_features='auto',
                        max_leaf_nodes=None, min_impurity_decrease=0.0,
                        min_impurity_split=None, min_samples_leaf=1,
                        min_samples_split=2, min_weight_fraction_leaf=0.0,
                        n_estimators=16, n_jobs=None, oob_score=False,
                        random_state=None, verbose=0, warm_start=False)
```

20

16



best depth = {'n_estimators': 16, 'max_depth': 20}

In [107]:

```
# TEST PHASE FOR L1
xg=RandomForestClassifier(bootstrap=True, class_weight='balanced',
                           criterion='gini', max_depth=20, max_features='auto',
                           max_leaf_nodes=None, min_impurity_decrease=0.0,
                           min_impurity_split=None, min_samples_leaf=1,
                           min_samples_split=2, min_weight_fraction_leaf=0.0,
                           n_estimators=16, n_jobs=None, oob_score=False,
                           random_state=None, verbose=0, warm_start=False)
xg.fit(X_tr,y_train)
pred = xg.predict(X_te)
```

In [108]:

```
#other measuring parameters
from sklearn.metrics import classification_report
print("classification_report")
print(classification_report(y_test, pred))
```

```
classification_report
      precision    recall  f1-score   support

     0       0.24      0.47      0.32       5459
     1       0.89      0.74      0.81      30593

 micro avg       0.70      0.70      0.70      36052
 macro avg       0.57      0.61      0.56      36052
 weighted avg     0.79      0.70      0.73      36052
```

In [109]:

```
pred_proba_te=xg.predict_proba(X_te)
pred_proba_te = pred_proba_te[:, 1]

pred_proba_tr=xg.predict_proba(X_tr)
pred_proba_tr = pred_proba_tr[:, 1]
```

In [110]:


```
fpr, tpr, thresholds = roc_curve(y_test,pred_proba_te )
a=fpr
b=tpr
c=thresholds
```

In [111]:

```
fpr, tpr, thresholds = roc_curve(y_train,pred_proba_tr )
```

In [112]:

```
#PLOT OF ROC
# plot no skill
plt.plot([0, 1], [0, 1])
# plot the roc curve for the model
plt.plot(fpr, tpr, marker='.',label="train")
plt.plot(a,b, marker='.',label='test')
#plt.plot(k,pred_cv)
plt.title("Line Plot of ROC Curve")
plt.ylabel('True Positive Rate')
plt.xlabel('False Positive Rate')
plt.legend()
plt.show()
```



In [114]:


```
#confusion matrices
#https://pandas-ml.readthedocs.io/en/latest/conf_mat.html
con_matrix=confusion_matrix(y_test, pred)
class_label=['negative','positive']
df=pd.DataFrame(con_matrix,index=class_label,columns=class_label)
df
```

Out[114]:

	negative	positive
negative	2593	2866
positive	8051	22542

In [115]:

```
# how can i plot confusion matrix //https://stackoverflow.com/questions/35572000/how-can-i-
sns.heatmap(df,annot=True,fmt='d')
plt.title('Confusion_matrix')
plt.xlabel("prediction")
plt.ylabel("actual")
plt.show()
```



- TN=2593
- FP=2866
- FN=8051
- TP=22542

2.5.2 Applying XGBOOST on TFIDF, SET 2

In [129]:

```
# Please write all the code with proper documentation
# Please write all the code with proper documentation
# Please write all the code with proper documentation
#merging
from scipy.sparse import hstack
X_tr = hstack((X_train_essay_tfidf, X_train_state_ohe, X_train_teacher_ohe, X_train_grade_ohe, X_train_pr
#X_cr = hstack((X_cv_essay_tfidf, X_cv_state_ohe, X_cv_teacher_ohe, X_cv_grade_ohe, X_cv_pr
X_te = hstack((X_test_essay_tfidf, X_test_state_ohe, X_test_teacher_ohe, X_test_grade_ohe,

print("Final Data matrix")
print("train matrix=>",X_tr.shape, y_train.shape)

print("test matrix=>",X_te.shape, y_test.shape)
print("="*100)
```

Final Data matrix

train matrix=> (73196, 16856) (73196,)

test matrix=> (36052, 16856) (36052,)

```
=====
=====
```

In [130]:

```
xgd(X_tr,X_te)
```

Fitting 3 folds for each of 56 candidates, totalling 168 fits

[Parallel(n_jobs=-1)]: Using backend LokyBackend with 4 concurrent workers.

[Parallel(n_jobs=-1)]: Done 42 tasks | elapsed: 12.7s



[Parallel(n_jobs=-1)]: Done 168 out of 168 | elapsed: 1.5min finished

0.6459618591144823

```
RandomForestClassifier(bootstrap=True, class_weight='balanced',
                        criterion='gini', max_depth=17, max_features='auto',
                        max_leaf_nodes=None, min_impurity_decrease=0.0,
                        min_impurity_split=None, min_samples_leaf=1,
                        min_samples_split=2, min_weight_fraction_leaf=0.0,
                        n_estimators=16, n_jobs=None, oob_score=False,
                        random_state=None, verbose=0, warm_start=False)
```

17

16



best depth = {'n_estimators': 16, 'max_depth': 17}

In [133]:

```
# TEST PHASE FOR L1
xg=RandomForestClassifier(bootstrap=True, class_weight='balanced',
                           criterion='gini', max_depth=17, max_features='auto',
                           max_leaf_nodes=None, min_impurity_decrease=0.0,
                           min_impurity_split=None, min_samples_leaf=1,
                           min_samples_split=2, min_weight_fraction_leaf=0.0,
                           n_estimators=16, n_jobs=None, oob_score=False,
                           random_state=None, verbose=0, warm_start=False)
xg.fit(X_tr,y_train)
pred = xg.predict(X_te)
```

In [134]:

```
#other measuring parameters
from sklearn.metrics import classification_report
print("classification_report")
print(classification_report(y_test, pred))
```

```
classification_report
      precision    recall  f1-score   support

      0       0.25      0.39      0.31        5459
      1       0.88      0.79      0.83       30593

 micro avg       0.73      0.73      0.73       36052
 macro avg       0.57      0.59      0.57       36052
weighted avg       0.79      0.73      0.75       36052
```

In [135]:

```
pred_proba_te=xg.predict_proba(X_te)
pred_proba_te = pred_proba_te[:, 1]

pred_proba_tr=xg.predict_proba(X_tr)
pred_proba_tr = pred_proba_tr[:, 1]
```

In [136]:


```
fpr, tpr, thresholds = roc_curve(y_test,pred_proba_te )
a=fpr
b=tpr
c=thresholds
```

In [137]:

```
fpr, tpr, thresholds = roc_curve(y_train,pred_proba_tr )
```

In [138]:

```
#PLOT OF ROC
# plot no skill
plt.plot([0, 1], [0, 1])
# plot the roc curve for the model
plt.plot(fpr, tpr, marker='.',label="train")
plt.plot(a,b, marker='.',label='test')
#plt.plot(k,pred_cv)
plt.title("Line Plot of ROC Curve")
plt.ylabel('True Positive Rate')
plt.xlabel('False Positive Rate')
plt.legend()
plt.show()
```



In [139]:


```
#confusion matrices
#https://pandas-ml.readthedocs.io/en/latest/conf_mat.html
con_matrix=confusion_matrix(y_test, pred)
class_label=['negative','positive']
df=pd.DataFrame(con_matrix,index=class_label,columns=class_label)
df
```

Out[139]:

	negative	positive
negative	2147	3312
positive	6327	24266

In [140]:

```
# how can i plot confusion matrix //https://stackoverflow.com/questions/35572000/how-can-i-  
sns.heatmap(df,annot=True,fmt='d')  
plt.title('Confusion_matrix')  
plt.xlabel("prediction")  
plt.ylabel("actual")  
plt.show()
```



- TN=2147
- FP=3312
- FN=6327
- TP=24266

In []:

2.5.3 Applying XGBOOST on AVG W2V, SET 3

In [150]:

```
#merging
from scipy.sparse import hstack
X_tr = np.hstack((y, X_train_state_ohe, X_train_teacher_ohe, X_train_grade_ohe, X_train_price_ohe))
#X_cr = hstack((avg_w2v_vectors_cvtitle, X_cv_state_ohe, X_cv_teacher_ohe, X_cv_grade_ohe, X_cv_price_ohe))
X_te = np.hstack((a, X_test_state_ohe, X_test_teacher_ohe, X_test_grade_ohe, X_test_price_ohe))

print("Final Data matrix")
print("train matrix=>",X_tr.shape, y_train.shape)

print("test matrix=>",X_te.shape, y_test.shape)
print("="*100)
```

Final Data matrix

train matrix=> (73196, 607) (73196,)

test matrix=> (36052, 607) (36052,)

=====

In [151]:

```
xgd(X_tr,X_te)
```

Fitting 3 folds for each of 56 candidates, totalling 168 fits

```
[Parallel(n_jobs=-1)]: Using backend LokyBackend with 4 concurrent workers.
```

```
[Parallel(n_jobs=-1)]: Done 42 tasks | elapsed: 50.7s
```



```
[Parallel(n_jobs=-1)]: Done 168 out of 168 | elapsed: 9.7min finished
```

```
0.6478720343933462
```

```
RandomForestClassifier(bootstrap=True, class_weight='balanced',
                        criterion='gini', max_depth=5, max_features='auto',
                        max_leaf_nodes=None, min_impurity_decrease=0.0,
                        min_impurity_split=None, min_samples_leaf=1,
                        min_samples_split=2, min_weight_fraction_leaf=0.0,
                        n_estimators=16, n_jobs=None, oob_score=False,
                        random_state=None, verbose=0, warm_start=False)
```

5

16



```
best depth = {'n_estimators': 16, 'max_depth': 5}
```

In [152]:

```
# TEST PHASE FOR L1
xg=RandomForestClassifier(bootstrap=True, class_weight='balanced',
                           criterion='gini', max_depth=5, max_features='auto',
                           max_leaf_nodes=None, min_impurity_decrease=0.0,
                           min_impurity_split=None, min_samples_leaf=1,
                           min_samples_split=2, min_weight_fraction_leaf=0.0,
                           n_estimators=16, n_jobs=None, oob_score=False,
                           random_state=None, verbose=0, warm_start=False)
xg.fit(X_tr,y_train)
pred = xg.predict(X_te)
```

In [153]:

```
#other measuring parameters
from sklearn.metrics import classification_report
print("classification_report")
print(classification_report(y_test, pred))
```

```
classification_report
      precision    recall  f1-score   support

    0       0.23      0.56      0.32      5459
    1       0.89      0.66      0.76     30593

 micro avg       0.64      0.64      0.64     36052
 macro avg       0.56      0.61      0.54     36052
weighted avg       0.79      0.64      0.69     36052
```

In [154]:

```
pred_proba_te=xg.predict_proba(X_te)
pred_proba_te = pred_proba_te[:, 1]

pred_proba_tr=xg.predict_proba(X_tr)
pred_proba_tr = pred_proba_tr[:, 1]
```

In [155]:


```
fpr, tpr, thresholds = roc_curve(y_test,pred_proba_te )
a=fpr
b=tpr
c=thresholds
```

In [156]:

```
fpr, tpr, thresholds = roc_curve(y_train,pred_proba_tr )
```

In [157]:

```
#PLOT OF ROC
# plot no skill
plt.plot([0, 1], [0, 1])
# plot the roc curve for the model
plt.plot(fpr, tpr, marker='.',label="train")
plt.plot(a,b, marker='.',label='test')
#plt.plot(k,pred_cv)
plt.title("Line Plot of ROC Curve")
plt.ylabel('True Positive Rate')
plt.xlabel('False Positive Rate')
plt.legend()
plt.show()
```



In [158]:


```
#confusion matrices
#https://pandas-ml.readthedocs.io/en/latest/conf_mat.html
con_matrix=confusion_matrix(y_test, pred)
class_label=['negative','positive']
df=pd.DataFrame(con_matrix,index=class_label,columns=class_label)
df
```

Out[158]:

	negative	positive
negative	3055	2404
positive	10407	20186

In [159]:

```
# how can i plot confusion matrix //https://stackoverflow.com/questions/35572000/how-can-i-  
sns.heatmap(df,annot=True,fmt='d')  
plt.title('Confusion_matrix')  
plt.xlabel("prediction")  
plt.ylabel("actual")  
plt.show()
```



- TN=3055
- FP=2404
- FN=10407
- TP=20186

2.5.4 Applying XGBOOST on TFIDF W2V, SET 4

In [160]:

```

# Please write all the code with proper documentation
# Please write all the code with proper documentation
# Please write all the code with proper documentation
#merging
from scipy.sparse import hstack
X_tr = np.hstack((tfidf_w2v_vectors_title_tr, X_train_state_ohe, X_train_teacher_ohe, X_train_grade_ohe)
#X_cr = hstack((tfidf_w2v_vectors_title_cv, X_cv_state_ohe, X_cv_teacher_ohe, X_cv_grade_ohe)
X_te = np.hstack((tfidf_w2v_vectors_title_te, X_test_state_ohe, X_test_teacher_ohe, X_test_grade_ohe)

print("Final Data matrix")
print("train matrix=>",X_tr.shape, y_train.shape)

print("test matrix=>",X_te.shape, y_test.shape)
print("=="*100)

```

Final Data matrix

train matrix=> (73196, 607) (73196,)

test matrix=> (36052, 607) (36052,)

=====
=====

In [161]:

```
xgd(X_tr,X_te)
```

Fitting 3 folds for each of 56 candidates, totalling 168 fits

[Parallel(n_jobs=-1)]: Using backend LokyBackend with 4 concurrent workers.

[Parallel(n_jobs=-1)]: Done 42 tasks | elapsed: 48.9s



[Parallel(n_jobs=-1)]: Done 168 out of 168 | elapsed: 9.6min finished

0.6561862634091311

```
RandomForestClassifier(bootstrap=True, class_weight='balanced',
                        criterion='gini', max_depth=5, max_features='auto',
                        max_leaf_nodes=None, min_impurity_decrease=0.0,
                        min_impurity_split=None, min_samples_leaf=1,
                        min_samples_split=2, min_weight_fraction_leaf=0.0,
                        n_estimators=16, n_jobs=None, oob_score=False,
                        random_state=None, verbose=0, warm_start=False)
```

5

16



best depth = {'n_estimators': 16, 'max_depth': 5}

In [162]:

```
xg=RandomForestClassifier(bootstrap=True, class_weight='balanced',
                           criterion='gini', max_depth=5, max_features='auto',
                           max_leaf_nodes=None, min_impurity_decrease=0.0,
                           min_impurity_split=None, min_samples_leaf=1,
                           min_samples_split=2, min_weight_fraction_leaf=0.0,
                           n_estimators=16, n_jobs=None, oob_score=False,
                           random_state=None, verbose=0, warm_start=False)
xg.fit(X_tr,y_train)
pred = xg.predict(X_te)
```

In [163]:

```
#other measuring parameters
from sklearn.metrics import classification_report
print("classification_report")
print(classification_report(y_test, pred))
```

	precision	recall	f1-score	support
0	0.22	0.60	0.33	5459
1	0.90	0.63	0.74	30593
micro avg	0.62	0.62	0.62	36052
macro avg	0.56	0.62	0.53	36052
weighted avg	0.80	0.62	0.68	36052

In [164]:

```
pred_proba_te=xg.predict_proba(X_te)
pred_proba_te = pred_proba_te[:, 1]

pred_proba_tr=xg.predict_proba(X_tr)
pred_proba_tr = pred_proba_tr[:, 1]
```

In [165]:


```
fpr, tpr, thresholds = roc_curve(y_test,pred_proba_te )
a=fpr
b=tpr
c=thresholds
```

In [166]:

```
fpr, tpr, thresholds = roc_curve(y_train,pred_proba_tr )
```

In [167]:

```
#PLOT OF ROC
# plot no skill
plt.plot([0, 1], [0, 1])
# plot the roc curve for the model
plt.plot(fpr, tpr, marker='.',label="train")
plt.plot(a,b, marker='.',label='test')
#plt.plot(k,pred_cv)
plt.title("Line Plot of ROC Curve")
plt.ylabel('True Positive Rate')
plt.xlabel('False Positive Rate')
plt.legend()
plt.show()
```



In [168]:


```
#confusion matrices
#https://pandas-ml.readthedocs.io/en/latest/conf_mat.html
con_matrix=confusion_matrix(y_test, pred)
class_label=['negative','positive']
df=pd.DataFrame(con_matrix,index=class_label,columns=class_label)
df
```

Out[168]:

	negative	positive
negative	3293	2166
positive	11397	19196

In [169]:

```
# how can i plot confusion matrix //https://stackoverflow.com/questions/35572000/how-can-i-
sns.heatmap(df,annot=True,fmt='d')
plt.title('Confusion_matrix')
plt.xlabel("prediction")
plt.ylabel("actual")
plt.show()
```



- TN=3293
- FP=2166
- FN=11397
- TP=19196

3. Conclusion

In [171]:

```
# Please compare all your models using Prettytable library
```

```
from prettytable import PrettyTable
x = PrettyTable()
x.field_names = ["Vectorizer", "Model", "max_depth", "n_estimators", "AUC"]
```

In [173]:

```
x.add_row(['bow', 'random_forest', 20, 16, 0.6686117705820649])
x.add_row(['tfidf', 'random_forest', 15, 16, 0.6485150845633967])
x.add_row(['average_word_', 'random_forest', 5, 16, 0.6571748256558564])
x.add_row(['tfidf_word_', 'random_forest', 5, 14, 0.6599592776806665])
x.add_row(['bow', 'XGboost', 20, 16, 0.6600194936520907])
x.add_row(['tfidf', 'XGboost', 17, 16, 0.6459618591144823])
x.add_row(['average_word_', 'XGboost', 5, 16, 0.6478720343933462])
x.add_row(['tfidf_word_', 'XGboost', 5, 15, 0.6561862634091311])
```

In [175]:

print(x)

```

+-----+-----+-----+-----+-----+
----+
| Vectorizer | Model | max_depth | n_estimators | AUC
|
+-----+-----+-----+-----+-----+
----+
| bow | random_forest | 20 | 16 | 0.6686117705820
649 |
| tfidf | random_forest | 15 | 16 | 0.6485150845633
967 |
| average_word_ | random_forest | 5 | 16 | 0.6571748256558
564 |
| tfidf_word_ | random_forest | 5 | 14 | 0.6599592776806
665 |
| bow | XGboost | 20 | 16 | 0.6600194936520
907 |
| tfidf | XGboost | 17 | 16 | 0.6459618591144
823 |
| average_word_ | XGboost | 5 | 16 | 0.6478720343933
462 |
| tfidf_word_ | XGboost | 5 | 15 | 0.6561862634091
311 |
+-----+-----+-----+-----+-----+
----+

```

note

- for categorical feature encoding prob=1 is used for data matrix preparation

In []: