

Server Web Server with other Services TASK – 6

- 1. Install Apache web server and PHP on your Linux machine, then create an index.php file that displays 'Welcome to My Foodie Blog' when accessed via your browser.**

Ans :

- `sudo apt update`
- `sudo apt install apache2 php libapache2-mod-php -y`
- `sudo systemctl start apache2`
- `sudo systemctl enable apache2`
- `cd /var/www/html`
- `sudo rm -f index.html`
- `echo '<?php echo "Welcome to My Foodie Blog"; ?>' | sudo tee /var/www/html/index.php`
- `sudo systemctl restart apache2`
- `php -v`

- 2. Configure your Apache server to serve a custom 404 error page that displays a Zomato-style message: 'Oops! This page is as empty as your cart.'**

Ans :

- `cd /var/www/html`
- `echo '<!DOCTYPE html>`
- `<html>`
- `<head>`
- `<title>404 Not Found</title>`
- `</head>`
- `<body>`
- `<h1>Oops! This page is as empty as your cart.</h1>`

- `</body>`
- `</html>' | sudo tee /var/www/html/404.html`
- `echo 'ErrorDocument 404 /404.html' | sudo tee /etc/apache2/conf-available/custom-404.conf`
- `sudo a2enconf custom-404`
- `sudo systemctl reload apache2`

3. Set up a simple FTP server (vsftpd or any other) on your Linux system and upload a sample image file to your web server's root directory using an FTP client.

Ans :

- `sudo apt update`
- `sudo apt install vsftpd -y`
- `sudo systemctl start vsftpd`
- `sudo systemctl enable vsftpd`
- `sudo cp /etc/vsftpd.conf /etc/vsftpd.conf.bak`
- `sudo nano /etc/vsftpd.conf`

4. Configure your web server to also run a basic Node.js service on a different port (e.g., 3000) that returns JSON data for a mock 'Now Playing' playlist, similar to Spotify. Test accessing both the PHP web page and the Node.js playlist endpoint from your browser.

Ans :

Commands to Configure a Basic Node.js Service

- `sudo apt update`
- `sudo apt install nodejs npm -y`
- `mkdir ~/playlist-service`

- `cd ~/playlist-service`

Paste the following code into **server.js**:

- `const http = require('http');`
- `const playlist = {
 nowPlaying: [
 { title: "Blinding Lights", artist: "The Weeknd" },
 { title: "Levitating", artist: "Dua Lipa" },
 { title: "Shape of You", artist: "Ed Sheeran" }
]
};`
- `http.createServer((req, res) => {
 res.writeHead(200, { "Content-Type": "application/json" });
 res.end(JSON.stringify(playlist, null, 2));
}).listen(3000, () => {
 console.log("Server running on http://localhost:3000");
});``nano server.js`

5. Edit your Apache configuration to restrict access to a specific directory (e.g., /var/www/html/secret) so that only users from localhost (127.0.0.1) can access

it.
Hint: Use the 'Require' directive in your Apache config or .htaccess file.

Ans :

- `sudo mkdir -p /var/www/html/secret`
- `echo "<h1>Secret Page</h1>" | sudo tee /var/www/html/secret/index.html`

- `sudo nano /etc/apache2/conf-available/secret.conf`
- `<Directory "/var/www/html/secret">`
- `Require ip 127.0.0.1`
- `</Directory>`
- `sudo a2enconf secret`
- `sudo systemctl restart apache2`