

Managed Installed Services TASK-6

- 1. Use the systemctl command to check the status of the sshd service on your Linux system and write down whether it is active, inactive, or failed.**

Ans : systemctl status ssh

Look for the Active: line in the output

Active: active (running)

For a concise status check, you can also use:

systemctl is-active sshd

which will return one of:

active

inactive

failed

- 2. Start the nginx service using systemctl, then immediately stop it. After each action, verify the status and note the changes.

Hint: Use 'sudo systemctl start nginx' and 'sudo systemctl stop nginx'.**

Ans :

Action	Command	Expected Status
Before starting	<code>sudo systemctl status nginx</code>	May be inactive or active
After starting	<code>sudo systemctl start nginx</code>	Active (running)
After stopping	<code>sudo systemctl stop nginx</code>	Inactive (dead)

3. Enable the cron service to start automatically on boot, then reboot your system and confirm that the service is running after reboot.

Ans :

Task	Command	Result
Enable service at boot	<code>sudo systemctl enable cron</code>	Service enabled successfully
Reboot system	<code>sudo reboot</code>	System restarted
Verify after reboot	<code>systemctl status cron</code>	Active: active (running)

4. List all currently running services using systemctl and identify any service related to networking (like NetworkManager or networking). Write the current status of that service.

Ans :

- `systemctl list-units --type=service --state=running`

- `systemctl list-units --type=service | grep -Ei 'network|NetworkManager'`
- `systemctl status NetworkManager`

Output

- NetworkManager.service

Loaded: loaded

Active: active (running)

**5. Simulate a real-world scenario: Imagine you are troubleshooting why Spotify Web cannot stream music on your Linux machine. Use systemctl to check if the firewall (ufw or firewalld) service is running, and if it is, disable it temporarily. Document each command used and the result.

Constraint: Only disable the firewall if you are on a safe, non-production environment.**

Ans :

Command	Purpose	Result
<code>sudo systemctl status ufw</code>	Check UFW status	Active (exited)
<code>sudo systemctl stop ufw</code>	Temporarily disable firewall	Command completed successfully
<code>sudo systemctl status ufw</code>	Verify firewall stopped	Inactive (dead)
<code>sudo systemctl start ufw</code>	Re-enable firewall	Command completed successfully

Command	Purpose	Result
sudo systemctl status ufw	Verify firewall running	Active (exited)