

Basic Linux Commands

1.PWD

```
nlr2007@NLR:~$ pwd  
/home/nlr2007  
nlr2007@NLR:~$
```

2. Clear

```
nlr2007@NLR:~$ |
```

3.history

```
nlr2007@NLR:~$ history
 1  dpkg -l
 2  git --version
 3  curl --version
 4  gcc --version
 5  make --version
 6  sudo apt update
 7  sudo apt install build-essential -y
 8  gcc --version
 9  make --version
10  pwd
11  cd E:
12  cal
13  sudo apt install ncal -y
14  cal
15  whoami
16  .
17  ls
18  la-a
19  ls-a
20  ls -a
21  la -l
22  mkdir test
23  ls
24  cd test
25  pws
26  pwd
27  ls
28  cd..
29  cd ..
30  ls
31  history
32  nano
33  sudo apt update
34  sudo apt install cmatrix -y'
35  sudo apt install cmatrix -y
36  cmatrix
37  sudo apt install cmatrix -y
38  cmatrix
39  sudo apt update cmatrix -y
40  sudo apt update
```

4. Whoami

```
nlr2007@NLR:~$ whoami
nlr2007
nlr2007@NLR:~$ |
```

5.date

```
nlr2007@NLR:~$ date
Tue Aug  4 04:15:22 UTC 2026
nlr2007@NLR:~$ |
```

6.cal

```
127 nlr2007@NLR:~$ cal
      August 2026
Su Mo Tu We Th Fr Sa
                1
 2  3  4  5  6  7  8
 9 10 11 12 13 14 15
16 17 18 19 20 21 22
23 24 25 26 27 28 29
30 31
nlr2007@NLR:~$ |
```

7.hostname

```
nlr2007@NLR:~$ hostname
NLR
nlr2007@NLR:~$ |
```

8.uname -a

```
nlr2007@NLR:~$ uname -a
Linux NLR 6.6.87.2-microsoft-standard-WSL2 #1 SMP PREEMPT_DYNAMIC Thu Jun  5
18:30:46 UTC 2025 x86_64 x86_64 x86_64 GNU/Linux
nlr2007@NLR:~$ |
```

9.exit

IT EXITS FROM THE UBUNTU TERMINAL.

Topic 2: Directory Management

1. ls

```
nlr2007@NLR:~$ ls
-e          display_proccess_id.c  e          few          frok.c      hello1.c    parent_child.c  run
a.out      dp          exec.c      fork_exec_wait.c  fw          o           pc           test
display_pc.c  dpc        f          fork_wait.c      hello1      os_4.c      read_user_name.c
```

2. Ls -l

```
nlr2007@NLR:~$ ls -l
total 236
-rwxr-xr-x 1 nlr2007 nlr2007 16048 Jul 31 12:02 -e
-rwxr-xr-x 1 nlr2007 nlr2007 16016 Jul 31 11:39 a.out
-rw-r--r-- 1 nlr2007 nlr2007 296 Jul 31 11:53 display_pc.c
-rw-r--r-- 1 nlr2007 nlr2007 106 Jul 31 10:06 display_proccess_id.c
-rwxr-xr-x 1 nlr2007 nlr2007 16016 Jul 31 11:39 dp
-rwxr-xr-x 1 nlr2007 nlr2007 16096 Jul 31 11:53 dpc
-rwxr-xr-x 1 nlr2007 nlr2007 16048 Jul 31 12:02 e
-rw-r--r-- 1 nlr2007 nlr2007 146 Jul 31 12:02 exec.c
-rwxr-xr-x 1 nlr2007 nlr2007 16000 Jul 31 11:38 f
-rwxr-xr-x 1 nlr2007 nlr2007 16136 Jul 31 12:12 few
-rw-r--r-- 1 nlr2007 nlr2007 321 Jul 31 12:10 fork_exec_wait.c
-rw-r--r-- 1 nlr2007 nlr2007 290 Jul 31 11:58 fork_wait.c
-rw-r--r-- 1 nlr2007 nlr2007 95 Jul 31 10:11 frok.c
-rwxr-xr-x 1 nlr2007 nlr2007 16048 Jul 31 11:59 fw
-rwxr-xr-x 1 nlr2007 nlr2007 15960 Jul 31 11:36 hello1
-rw-r--r-- 1 nlr2007 nlr2007 62 Jul 31 09:27 hello1.c
-rwxr-xr-x 1 nlr2007 nlr2007 15960 Aug 4 03:43 o
-rw-r--r-- 1 nlr2007 nlr2007 69 Aug 4 03:43 os_4.c
-rw-r--r-- 1 nlr2007 nlr2007 240 Jul 31 11:48 parent_child.c
-rwxr-xr-x 1 nlr2007 nlr2007 16008 Jul 31 11:48 pc
-rw-r--r-- 1 nlr2007 nlr2007 144 Jul 31 09:59 read_user_name.c
-rwxr-xr-x 1 nlr2007 nlr2007 16072 Jul 31 11:37 run
drwxr-xr-x 2 nlr2007 nlr2007 4096 Jul 28 03:58 test
nlr2007@NLR:~$
```

3. Ls -a

```
nlr2007@NLR:~$ ls -a
-e          .sudo_as_admin_successful  frok.c
.           a.out                  fw
..          display_pc.c       hello1
.bash_history display_proccess_id.c  hello1.c
.bash_logout dp                      o
.bashrc     dpc              os_4.c
.cache      e              parent_child.c
.config     exec.c         pc
.lesshst    f              read_user_name.c
.local      few           run
.motd_shown fork_exec_wait.c       test
.profile    fork_wait.c
nlr2007@NLR:~$
```

4. cd

```
nlr2007@NLR:~$ cd
nlr2007@NLR:~$
```

5. Cd ..

```
nlr2007@NLR:~$ cd ..
nlr2007@NLR:/home$
```

6. Rmdir and mkdir

```
nlr2007@NLR:~$ mkdir oslab
nlr2007@NLR:~$ ls
-e          e          frok.c      oslab
a.out       exec.c         fw          parent_child.c
display_pc.c f              hello1      pc
display_proccess_id.c few           hello1.c    read_user_name.c
dp          fork_exec_wait.c o            run
dpc         fork_wait.c   os_4.c      test
nlr2007@NLR:~$ rmdir oslab
nlr2007@NLR:~$ ls
-e          e          frok.c      parent_child.c
a.out       exec.c         fw          pc
display_pc.c f              hello1      read_user_name.c
display_proccess_id.c few           hello1.c    run
dp          fork_exec_wait.c o            test
dpc         fork_wait.c   os_4.c
nlr2007@NLR:~$
```

8. Find

```
nlr2007@NLR:~$ find
.
./.bash_logout
./e
./fw
./.config
./.config/byobu
./.config/byobu/.tmux.conf
./.config/byobu/keybindings.tmux
./.config/byobu/profile.tmux
./.config/byobu/windows.tmux
./.config/byobu/windows
./.config/byobu/.screenrc
./.config/byobu/status
./.config/byobu/backend
./.config/byobu/profile
./.config/byobu/statusrc
./.config/byobu/bin
./.config/byobu/color.tmux
./.config/byobu/prompt
./.config/byobu/datetime.tmux
./.config/byobu/color
./.config/byobu/keybindings
./.config/htop
```

9. Locate

10. Touch

```
Ubuntu x + v
wsl: Failed to translate 'L:\Flutter\flutter\bin'
nlr2007@NLR:~$ touch file1.txt
nlr2007@NLR:~$ ls
-e          exec.c          fw          parent_child.c
a.out      f              hello.c     pc
display_pc.c  few          hello1      read_user_name.c
display_proccess_id.c file1.txt    hello1.c   run
dp          fork_exec_wait.c o          test
dpc         fork_wait.c   os_4.c
e           frok.c        oslab
nlr2007@NLR:~$ |
```

11. Cat

```
cat: hello.c: is a directory
1 nlr2007@NLR:~$ cat hello1.c
#include <stdio.h>
int main() {
printf("Hello");
return 0;
}

nlr2007@NLR:~$ |
```

12 cp

```
nlr2007@NLR:~$ nano file1.txt
nlr2007@NLR:~$ cat file1.txt
Hello this a .txt file that is craeted using the touch. and copied the .txt
using cp command in file2.txt

nlr2007@NLR:~$ cp file1.txt copy_file1.txt
nlr2007@NLR:~$ cat copy_file1.txt
Hello this a .txt file that is craeted using the touch. and copied the .txt
using cp command in file2.txt

nlr2007@NLR:~$ |
```

13. Mv

```
nlr2007@NLR:~$ mv copy_file1.txt newfile
nlr2007@NLR:~$ cat newfile
Hello this a .txt file that is craeted using the touch. and copied the .txt
using cp command in file2.txt

nlr2007@NLR:~$ |
```

14. Rm

```
nlr2007@NLR:~$ rm file1.txt
nlr2007@NLR:~$ ls
-e          e          frok.c      o          run
a.out      exec.c      fw          os_4.c     test
display_pc.c  f          hello.c     oslab
display_proccess_id.c few        hello1      parent_child.c
dp          fork_exec_wait.c hello1.c    pc
dpc         fork_wait.c  newfile     read_user_name.c
nlr2007@NLR:~$ |
```

15. Head

```
nlr2007@NLR:~$ head newfile
Hello this a .txt file that is craeted using the touch. and copied the .txt
using cp command in file2.txt

nlr2007@NLR:~$ |
```

16. Tail

```
nlr2007@NLR:~$ tail newfile
Hello this a .txt file that is craeted using the touch. and copied the .txt
using cp command in file2.txt

nlr2007@NLR:~$ |
```

17. More

```
nlr2007@NLR:~$ more newfile
Hello this a .txt file that is craeted using the touch. and copied the .txt
using cp command in file2.txt

nlr2007@NLR:~$ |
```

18. Less



```
nlr2007@NLR:~$ wc newfile
  2  20 108 newfile
nlr2007@NLR:~$
```

20. Diff

```
nlr2007@NLR:~$ echo "Apple" > a.txt
nlr2007@NLR:~$ echo "Banana" > b.txt
nlr2007@NLR:~$ diff a.txt b.txt
1c1
< Apple
---
> Banana
1 nlr2007@NLR:~$ |
```

21. sort

```
1 nlr2007@NLR:~$ echo -e "Manago\nApple\nBanana" > data.txt
nlr2007@NLR:~$ cat data.txt
Manago
Apple
Banana
nlr2007@NLR:~$ sort data.txt
sort: cannot read: data.txt: No such file or directory
2 nlr2007@NLR:~$ sort data.txt
Apple
Banana
Manago
nlr2007@NLR:~$ |
```

22. uniq

```
nlr2007@NLR:~$ echo -e "Apple\nApple\nBanana\nBanana\nMango" > data.txt
nlr2007@NLR:~$ cat data.txt
Apple
Apple
Banana
Banana
Mango
nlr2007@NLR:~$ uniq data.txt
Apple
Banana
Mango
nlr2007@NLR:~$ |
```

23. grep

```
nlr2007@NLR:~$ echo -e "Apple\nBanana\nManago\nOrange" > fruits.txt
nlr2007@NLR:~$ grep "Orange" fruits.txt
Orange
nlr2007@NLR:~$ |
```

24.nano

```
nlr2007@NLR:~$ nano hello7.c
nlr2007@NLR:~$ gcc hello7.c -o h7
nlr2007@NLR:~$ ./h7
Hello World
nlr2007@NLR:~$ cat hello7.c
#include <stdio.h>

int main() {
    printf("Hello World\n");
    return 0;
}
nlr2007@NLR:~$ |
```

25.vi

```
nlr2007@NLR:~$ vi hello7.c
nlr2007@NLR:~$ gcc hello7.c -o h7
nlr2007@NLR:~$ ./h7
Hello World using 'VI'
nlr2007@NLR:~$ |
```

26.gcc

```
nlr2007@NLR:~$ vi hello7.c
nlr2007@NLR:~$ gcc hello7.c -o h7
nlr2007@NLR:~$ ./h7
Hello World using 'VI'
nlr2007@NLR:~$
```

27. ./hello

```
nlr2007@NLR:~$ vi hello7.c
nlr2007@NLR:~$ gcc hello7.c -o h7
nlr2007@NLR:~$ ./h7
Hello World using 'VI'
nlr2007@NLR:~$
```

28.which

```
nlr2007@NLR:~$ which gcc
/usr/bin/gcc
nlr2007@NLR:~$ which cmatrix
/usr/bin/cmatrix
nlr2007@NLR:~$ |
```

29.whereisgcc

```
127 nlr2007@NLR:~$ whereis gcc
gcc: /usr/bin/gcc /usr/lib/gcc /usr/libexec/gcc /usr/share/gcc /usr/share/man/man1/gcc.1.gz
nlr2007@NLR:~$ |
```

30.man

```

GCC(1)                                GNU                                GCC(1)

NAME
    gcc - GNU project C and C++ compiler

SYNOPSIS
    gcc [-c|-S|-E] [-std=standard]
        [-g] [-pg] [-Olevel]
        [-Wwarn...] [-Wpedantic]
        [-Idir...] [-Ldir...]
        [-Dmacro[=defn]...] [-Umacro]
        [-foption...] [-mmachine-option...]
        [-o outfile] [@file] infile...

    Only the most useful options are listed here; see below for the
    remainder.  g++ accepts mostly the same options as gcc.

DESCRIPTION
    When you invoke GCC, it normally does preprocessing, compilation,
    assembly and linking.  The "overall options" allow you to stop this
    process at an intermediate stage.  For example, the -c option says
    not to run the linker.  Then the output consists of object files
    output by the assembler.

    Other options are passed on to one or more stages of processing.
    Some options control the preprocessor and others the compiler
    itself.  Yet other options control the assembler and linker; most
    of these are not documented here, since you rarely need to use any
    of them.

    Most of the command-line options that you can use with GCC are
    useful for C programs; when an option is only useful with another
    language (usually C++), the explanation says so explicitly.  If the
    description for a particular option does not mention a source
    language, you can use that option with all supported languages.

    The usual way to run GCC is to run the executable called gcc, or
    machine-gcc when cross-compiling, or machine-gcc-version to run a
    specific version of GCC.  When you compile C++ programs, you should
    invoke GCC as g++ instead.

Manual page gcc(1) line 1 (press h for help or q to quit)

```

31.ps

```

nlr2007@NLR:~$ ps
  PID TTY          TIME CMD
  351 pts/0        00:00:00 bash
  881 pts/0        00:00:00 ps
nlr2007@NLR:~$ |

```

32.ps ef

```

nlr2007@NLR:~$ ps -ef
UID          PID    PPID  C  STIME TTY          TIME CMD
root           1        0  0  15:36 ?        00:00:00 /sbin/init
root           2          1  0  15:36 ?        00:00:00 /init
root           8          2  0  15:36 ?        00:00:00 plan9 --control-socket 7
root          57          1  0  15:36 ?        00:00:00 /usr/lib/systemd/systemd
root         106          1  0  15:36 ?        00:00:00 /usr/lib/systemd/systemd
systemd+     128          1  0  15:36 ?        00:00:00 /usr/lib/systemd/systemd
systemd+     129          1  0  15:36 ?        00:00:00 /usr/lib/systemd/systemd
root         190          1  0  15:36 ?        00:00:00 /usr/sbin/cron -f -P
message+     191          1  0  15:36 ?        00:00:00 @dbus-daemon --system --
root         199          1  0  15:36 ?        00:00:00 /usr/lib/systemd/systemd
root         210          1  0  15:36 hvc0     00:00:00 /sbin/agetty -o -p -- \u
syslog       218          1  0  15:36 ?        00:00:00 /usr/sbin/rsyslogd -n -i
root         227          1  0  15:36 tty1     00:00:00 /sbin/agetty -o -p -- \u
root         230          1  0  15:36 ?        00:00:00 /usr/sbin/atopacctd
root         238          1  0  15:36 ?        00:00:00 /usr/bin/atop -w /var/lo
root         253          1  0  15:36 ?        00:00:00 /usr/bin/python3 /usr/sh
root         349          2  0  15:36 ?        00:00:00 /init
root         350         349  0  15:36 ?        00:00:00 /init
nlr2007       351         350  0  15:36 pts/0    00:00:00 -bash
root          352          2  0  15:36 pts/1    00:00:00 /bin/login -f
nlr2007       399          1  0  15:36 ?        00:00:00 /usr/lib/systemd/systemd
nlr2007       400         399  0  15:36 ?        00:00:00 (sd-pam)
nlr2007       422         352  0  15:36 pts/1    00:00:00 -bash
root          859          1  0  16:07 ?        00:00:00 /usr/libexec/wsl-pro-ser
root          886         106  0  16:08 ?        00:00:00 (udev-worker)
root          887         106  0  16:08 ?        00:00:00 (udev-worker)
nlr2007       889         351  0  16:08 pts/0    00:00:00 ps -ef
nlr2007@NLR:~$

```

33.top

```

top - 16:09:32 up 32 min,  1 user,  load average: 0.00, 0.00, 0.00
Tasks:  25 total,   1 running,  24 sleeping,   0 stopped,   0 zombie
%Cpu(s):  0.0 us,   0.8 sy,   0.0 ni,  99.2 id,   0.0 wa,   0.0 hi,   0.0 si,   0.
MiB Mem :   7763.2 total,   7174.4 free,    515.9 used,    229.4 buff/cache
MiB Swap:   2048.0 total,   2048.0 free,     0.0 used.   7247.3 avail Mem

  PID USER      PR  NI  VIRT  RES  SHR  S  %CPU  %MEM   TIME+
    1 root        20   0   21772 12352  9280 S   0.0   0.2   0:00.90
    2 root        20   0    3120  2048  1920 S   0.0   0.0   0:00.01
    8 root        20   0    3136  1792  1792 S   0.0   0.0   0:00.00
   57 root        19  -1   50360 15616 14720 S   0.0   0.2   0:00.26
  106 root        20   0   25280  6272  4864 S   0.0   0.1   0:00.58
  128 systemd+    20   0   21336 12800 10752 S   0.0   0.2   0:00.18
  129 systemd+    20   0   91028  7552  6784 S   0.0   0.1   0:00.14
  190 root        20   0    4236  2432  2304 S   0.0   0.0   0:00.00
  191 message+    20   0    9640  4992  4480 S   0.0   0.1   0:00.05
  199 root        20   0   17968  8192  7296 S   0.0   0.1   0:00.11
  210 root        20   0    3160  2048  1920 S   0.0   0.0   0:00.01
  218 syslog     20   0  222508  5248  4096 S   0.0   0.1   0:00.09
  227 root        20   0    3116  1920  1792 S   0.0   0.0   0:00.00
  230 root         0 -20    2692  1280  1280 S   0.0   0.0   0:00.15
  238 root         0 -20   12608 12192  5888 S   0.0   0.2   0:00.11
  253 root        20   0  107028 22656 13568 S   0.0   0.3   0:00.14
  349 root        20   0    3136    900    768 S   0.0   0.0   0:00.00
  350 root        20   0    3136   1164   1024 S   0.0   0.0   0:00.35
  351 nlr2007      20   0    6200  5120  3584 S   0.0   0.1   0:00.41
  352 root        20   0    6696  4608  3840 S   0.0   0.1   0:00.01
  399 nlr2007      20   0   20120 11008  9216 S   0.0   0.1   0:00.11
  400 nlr2007      20   0   21156  3504  1792 S   0.0   0.0   0:00.00
  422 nlr2007      20   0    6072  4864  3456 S   0.0   0.1   0:00.03
  859 root        20   0 1756364 12928 10880 S   0.0   0.2   0:00.08
  909 nlr2007      20   0    9384  5376  3200 R   0.0   0.1   0:00.00

```

34. Sleep

```

130 nlr2007@NLR:~$ sleep 300 &
[1] 950
nlr2007@NLR:~$ |

```

35.kill -9

```

130 nlr2007@NLR:~$ sleep 300 &
[1] 950
nlr2007@NLR:~$ kill -9 950
[1]+  Killed                  sleep 300
nlr2007@NLR:~$ ps
      PID TTY          TIME CMD
      351 pts/0        00:00:00 bash
      964 pts/0        00:00:00 ps
nlr2007@NLR:~$ |

```

36.jobs

```
nlr2007@NLR:~$ jobs
nlr2007@NLR:~$ sleep 300&
[1] 979
nlr2007@NLR:~$ jobs
[1]+  Running                  sleep 300 &
nlr2007@NLR:~$ |
```

37. Bg

```
nlr2007@NLR:~$ sleep 300
^Z
[2]+  Stopped                  sleep 300
148 nlr2007@NLR:~$ bg %1
-bash: bg: job 1 already in background
nlr2007@NLR:~$ bg %2
[2]+  sleep 300 &
nlr2007@NLR:~$ |
```

38. Fg

```
nlr2007@NLR:~$ jobs
[1]-  Running                  sleep 300 &
[2]+  Running                  sleep 300 &
nlr2007@NLR:~$ fg %2
sleep 300
|
```

38. ./hello & 7

```
130 nlr2007@NLR:~$ ./h7 &
[2] 1027
Hello World using 'VI'
[2]+  Done                      ./h7
nlr2007@NLR:~$ |
```

39.chmod


```
chmod: cannot access 'script.sh': No such file or directory
1 nlr2007@NLR:~$ nano script.sh
nlr2007@NLR:~$ chmod +x script.sh
nlr2007@NLR:~$ ./script.sh
hello linux
nlr2007@NLR:~$ █
```

40.chmod 755

```
nlr2007@NLR:~$ chmod 755
chmod: missing operand after '755'
Try 'chmod --help' for more information.
1 nlr2007@NLR:~$ chmod 755 script.sh
nlr2007@NLR:~$ ls -l script.sh
-rwxr-xr-x 1 nlr2007 nlr2007 20 Aug  4 16:19 script.sh
nlr2007@NLR:~$ █
```

41. Ln

```
nlr2007@NLR:~$ echo "Hello Bro What Sapp" > greet.txt
nlr2007@NLR:~$ ln greet.txt grettings.txt
nlr2007@NLR:~$ ls
a.out          few            hello7.c
a.txt          fork_exec_wait.c newfile
b.txt          fork_wait.c    o
data.txt       frok.c         os_4.c
display_pc.c   fruits.txt     oslab
display_proccess_id.c greet.txt      parent_child.c
dp             grettings.txt  pc
dpc            h7             read_user_name.c
e              hello.c        run
exec.c         hello1         scrip.sh
f              hello1.c       script.sh
               test
nlr2007@NLR:~$ cat greetings.txt
cat: greetings.txt: No such file or directory
1 nlr2007@NLR:~$ cat grettings.txt
Hello Bro What Sapp
nlr2007@NLR:~$
```

42. Ln -s

```
lrwxrwxrwx 1 nlr2007 nlr2007 6 Aug 4 16:24 s -> sc.txt
-rw-r--r-- 1 nlr2007 nlr2007 20 Aug 4 16:24 sc.txt
-rw-r--r-- 1 nlr2007 nlr2007 19 Aug 4 16:18 scrip.sh
```

43. Df -h

```

nlr2007@NLR:~$ df -h
Filesystem      Size  Used Avail Use% Mounted on
none            3.8G   0    3.8G   0% /usr/lib/modules/6.6.87.2-micros
oft-standard-WSL2
none            3.8G  4.0K   3.8G   1% /mnt/wsl
drivers          331G  237G   95G   72% /usr/lib/wsl/drivers
/dev/sdd        1007G  2.4G  954G   1% /
none            3.8G   80K   3.8G   1% /mnt/wslg
none            3.8G   0    3.8G   0% /usr/lib/wsl/lib
rootfs          3.8G  2.7M   3.8G   1% /init
none            3.8G  696K   3.8G   1% /run
none            3.8G   0    3.8G   0% /run/lock
none            3.8G   8.0K   3.8G   1% /run/shm
none            3.8G   76K   3.8G   1% /mnt/wslg/versions.txt
none            3.8G   76K   3.8G   1% /mnt/wslg/doc
C:\              331G  237G   95G   72% /mnt/c
D:\              64G   51G   14G   80% /mnt/d
E:\              81G   35G   47G   44% /mnt/e
tmpfs            3.8G   0    3.8G   0% /run/qemu
tmpfs            777M  20K   777M   1% /run/user/1000
nlr2007@NLR:~$

```

44. Du -sh .

```

nlr2007@NLR:~$ du -sh .
404K  .
nlr2007@NLR:~$

```

45.free -h

```

nlr2007@NLR:~$ free -h
total        used        free        shared  buff/cache
available
Mem:    7.6Gi    522Mi    6.7Gi    3.7Mi    557Mi
Swap:   2.0Gi      0B    2.0Gi
nlr2007@NLR:~$

```

46. Id

```

nlr2007@NLR:~$ id
uid=1000(nlr2007) gid=1000(nlr2007) groups=1000(nlr2007),4(adm),20(dia
lout),24(cdrom),25(floppy),27(sudo),29(audio),30(dip),44(video),46(plu
gdev),100(users),107(netdev)
nlr2007@NLR:~$

```

47.env

```
nlr2007@NLR:~$ env
SHELL=/bin/bash
WSL2_GUI_APPS_ENABLED=1
WSL_DISTRO_NAME=Ubuntu
WT_SESSION=2d073559-6fcb-4b81-9538-3aa058897f84
BYOBU_CONFIG_DIR=/home/nlr2007/.config/byobu
NAME=NLR
PWD=/home/nlr2007
LOGNAME=nlr2007
HOME=/home/nlr2007
LANG=C.UTF-8
WSL_INTEROP=/run/WSL/1168_interop
LS_COLORS=rs=0:di=01;34:ln=01;36:mh=00:pi=40;33:so=01;35:do=01;35:bd=40;33;01:cd=40;33;01:or=40;31;01:mi=00:su=37;41:sg=30;43:ca=00:tw=30;42:ow=34;42:st=37;44:ex=01;32:*.tar=01;31:*.tgz=01;31:*.arc=01;31:*.arj=01;31:*.taz=01;31:*.lha=01;31:*.lz4=01;31:*.lzh=01;31:*.lzma=01;31:*.t
```

48.export

```
1 nlr2007@NLR:~$ export NAME="Lokesh"
nlr2007@NLR:~$ echo $NAME
Lokesh
nlr2007@NLR:~$
```

49.alias ll= 'ls -l'

```
nlr2007@NLR:~$ alias ll='ls -l'
nlr2007@NLR:~$ ll
total 304
-rwxr-xr-x 1 nlr2007 nlr2007 16048 Jul 31 12:02 -e
-rwxr-xr-x 1 nlr2007 nlr2007 16016 Jul 31 11:39 a.out
-rw-r--r-- 1 nlr2007 nlr2007 6 Aug 4 15:55 a.txt
-rw-r--r-- 1 nlr2007 nlr2007 7 Aug 4 15:55 b.txt
-rw-r--r-- 1 nlr2007 nlr2007 32 Aug 4 15:57 data.txt
-rw-r--r-- 1 nlr2007 nlr2007 296 Jul 31 11:53 display_pc.c
-rw-r--r-- 1 nlr2007 nlr2007 106 Jul 31 10:06 display_proccess_id.c
-rwxr-xr-x 1 nlr2007 nlr2007 16016 Jul 31 11:39 dp
-rwxr-xr-x 1 nlr2007 nlr2007 16096 Jul 31 11:53 dpc
-rwxr-xr-x 1 nlr2007 nlr2007 16048 Jul 31 12:02 e
```

Completed...

